Bridging the Gap Between Theory and Practice in Adversarial Machine Learning: A Systematic Cross-Venue Analysis of 454 Papers (2022–2025)

Madhav Khanal
Rollins College
mkhanal@rollins.edu

JJ Jasser
Rollins College
jjasser@rollins.edu

Abstract

Machine learning systems are increasingly used in security critical environments, yet research on adversarial machine learning often diverges from the needs of real deployments. This systematic review examines 454 papers published between 2022 and 2025 in four leading security venues (ACM CCS, IEEE S&P, NDSS and USENIX Security) and applies the framework of Apruzzese et al. to assess how well current work addresses the gap between theory and practice. We find that most papers do not test their methods on deployed systems (94.7 per cent), rely on gradient access that is seldom available in practice (67.8 per cent), assume query budgets that exceed typical operational limits (80.4 per cent) and adopt white box threat models (63.2 per cent). Five critical dimensions—clear threat modelling, accounting for limited gradient access, validation on real systems, diversification beyond image classification and incorporation of economic and human factors—remain largely overlooked, and progress across these dimensions is slow. We also synthesise documented adversarial incidents where attackers exploited system integration, extracted training data, cloned proprietary models, poisoned generative model training data and used deepfake audio and video, and we discuss similar challenges in large language and multimodal models. We conclude by offering recommendations for researchers, conference organisers, industry practitioners and funding agencies to align adversarial machine learning research with operational realities.

Keywords: adversarial machine learning, theory-practice gap, security research, systematic review, threat modeling

Contents

1 Introduction **4**

2 Background: Foundations of Adversarial Machine Learning **4**
- 2.1 The Discovery of Adversarial Vulnerabilities . . . 4
- 2.2 The Arms Race: Attacks and Defenses . . . 5
  - 2.2.1 Advanced Gradient-Based Attacks . . . 5
  - 2.2.2 The Breakdown of Early Defenses . . . 6
  - 2.2.3 Adversarial Training and Certified Defenses . . . 6
- 2.3 Expanding Threat Landscape . . . 7
- 2.4 The Theory-Practice Gap . . . 8
- 2.5 Types of Adversarial Attacks . . . 8
- 2.6 Threat Models and Their Implications . . . 9

3 Methodology **10**
- 3.1 Data Collection . . . 10
- 3.2 Coding Framework . . . 10
- 3.3 Gap Score Framework . . . 11

4 Quantitative Findings **12**
- 4.1 Real-World Validation . . . 12
- 4.2 Gradient Dependency . . . 13
- 4.3 Threat Model Assumptions . . . 14
- 4.4 Query Budget Assumptions . . . 14
- 4.5 Domain Distribution . . . 15
- 4.6 Code Availability . . . 16
- 4.7 Gap Score Distribution . . . 16

5 Thematic Findings **16**

6 Foundation Models and Large Language Models: An Emerging Parallel Frontier **18**
- 6.1 From Manual Jailbreaks to Automated Optimization . . . 19
- 6.2 Multimodal Models: Exploiting Cross-Modal Alignment Gaps . . . 19
- 6.3 The Theory-Practice Gap Manifests Differently for LLMs . . . 20
- 6.4 Defense Mechanisms: Progress and Persistent Limitations . . . 20
- 6.5 Foundation Model Properties Amplify Systemic Risk . . . 21

7 Temporal Trends **21**

8 Cross-Venue Analysis **23**
- 8.1 ACM CCS: Economics and System Integration . . . 23
- 8.2 IEEE S&P: Efficiency and Formal Guarantees . . . 23
- 8.3 NDSS: Physical Constraints and Operational Realities . . . 23
- 8.4 USENIX Security: Real-World Validation and Domain Diversity . . . 24

8.5 Attack versus Defense Papers 24

9 Recommendations **24**

10 Limitations and Threats to Validity **25**

11 Conclusion **26**

A Complete Paper Analysis Dataset **35**

1 Introduction

Machine learning has become an essential part of software systems in many areas. It is used in facial recognition at border crossings, fraud detection in financial services, navigation for autonomous vehicles, and content moderation on social platforms. Large language models now power customer service chatbots, code generation tools, and medical assistants. ML models now influence decisions that impact millions of people every day. This widespread use has led to greater scrutiny of vulnerabilities in these models. Researchers design specific inputs to trigger failures that system creators did not foresee.

The field of adversarial machine learning (AML) has emerged to explore these weaknesses and develop defenses. Over the last ten years, researchers have shown how sophisticated attacks can work: small changes that lead to image misclassification, poisoned training data that creates hidden backdoors, and privacy attacks that reveal sensitive information through targeted queries. In response, the community has proposed many defenses to improve model strength.

Despite these developments, a key question remains: **how well do the assumptions in academic research match the realities of real-world systems?**

In 2022, Apruzzese and colleagues published a thorough analysis titled "Real Attackers Don't Compute Gradients" [1]. They documented a gap between academic AML research and practical security needs. Their main finding was that academic studies often assume attackers can calculate gradients from target models, which requires access to the model's structure and parameters. However, real-world attackers usually lack this access. Often, simpler methods like social engineering or basic input manipulation are sufficient, making complex approaches unnecessary for them.

This systematic review asks: *how has the research community responded since this critique?*

To find answers, we analyzed 454 adversarial ML papers published from 2022 to 2025 in four leading security venues: ACM CCS (118 papers), IEEE S&P (79 papers), NDSS (49 papers), and USENIX Security (208 papers). We assessed each paper based on several factors related to practical relevance: realism of the threat model, computational needs, validation methods, and awareness of deployment challenges.

Our findings show that the gap between theory and practice is still significant. While the research community has made valuable contributions to our understanding of adversarial issues, the drive to publish often emphasizes innovation and theoretical strength over practical implementation and cost considerations. This review outlines the current state of the field, identifies common trends across venues, and provides practical recommendations for various stakeholders.

2 Background: Foundations of Adversarial Machine Learning

2.1 The Discovery of Adversarial Vulnerabilities

The modern study of adversarial machine learning began with the important work of Szegedy et al. [2]. They showed that small, barely noticeable changes to input data could lead state-of-the-art deep learning models to produce wrong outputs with high confidence. These changes were not just random mistakes; they were systematic vulnerabilities that could transfer between different models. Adversarial examples created for one model often worked against other models trained separately. This ability to transfer highlighted the nature of the vulnerability and sparked further research.

Goodfellow et al. [3] suggested that the linear behavior of neural networks, instead of their nonlinearity or overfitting, was the main cause of their vulnerability to adversarial attacks. They introduced the Fast Gradient Sign Method (FGSM), which made it easier to generate adversarial inputs using a single gradient step. The speed and effectiveness of FGSM set a standard for later research, as gradient-based attacks became the common approach.

These foundational studies shaped the direction of adversarial ML research in three significant ways. First, they assumed that adversaries had white-box access to models, including details about their architecture and gradient information. Second, they focused on imperceptible changes measured by specific distance metrics. Third, they highlighted optimization-based methods as the best way to generate adversarial inputs. While these frameworks allowed for thorough analysis, they also shifted research away from the practical realities of real-world attacks.

2.2 The Arms Race: Attacks and Defenses

The discovery of adversarial vulnerabilities triggered an ongoing cycle of proposed defenses and increasingly sophisticated attacks designed to circumvent them. This pattern has come to characterize adversarial machine learning research as an "arms race" between attackers and defenders [4]. Each new defense mechanism motivated adaptive attacks that exploited weaknesses in the defense strategy, which in turn motivated new defensive approaches. This adversarial co-evolution has shaped both the technical landscape and methodological standards of the field.

2.2.1 Advanced Gradient-Based Attacks

Building on the foundational work of Szegedy et al. [2] and Goodfellow et al. [3], researchers developed more sophisticated attack methods that optimized adversarial perturbations more precisely. A central challenge in designing adversarial attacks is balancing two competing objectives: maximizing the probability of misclassification while minimizing the perceptibility of the perturbation. To formalize this trade-off, researchers employ **distance metrics** that quantify how much an adversarial example differs from the original input.

The most commonly used distance metrics in adversarial ML are L_p norms, which measure the magnitude of perturbations applied to inputs:

- L_0 **norm** counts the number of features modified. For an image with pixel values x and adversarial image x', $\|x - x'\|_0$ equals the count of pixels that differ between the two images. An L_0 attack might change only a small number of pixels but by arbitrary amounts. This metric is relevant when adversaries can precisely manipulate specific features (e.g., changing a few critical pixels in an image or specific words in text).
- L_2 **norm** (Euclidean distance) measures the root-mean-square deviation: $\|x-x'\|_2 = \sqrt{\sum_i (x_i - x'_i)^2}$. This metric treats perturbations as vectors in high-dimensional space and measures their geometric length. L_2 perturbations tend to apply small changes across many features, producing smoother, more diffuse modifications that may appear as slight blurring or color shifts in images.
- L_∞ **norm** (maximum norm or Chebyshev distance) measures the largest single perturbation across all features: $\|x - x'\|_\infty = \max_i |x_i - x'_i|$. This bounds the maximum change to any individual feature, ensuring that no single pixel (in images) or feature (in other domains) changes by more

than a specified threshold. L_∞ constraints are commonly used because they provide intuitive bounds on per-pixel modifications.

Understanding these metrics is essential because different attack methods optimize for different norms, and defenses effective against one type of perturbation may fail against others.

Moosavi-Dezfooli et al. [5] introduced DeepFool, which frames adversarial example generation as finding the minimal perturbation required to cross the model's **decision boundary**, which is the geometric surface in input space that separates different classification regions. A classifier assigns class labels by determining which side of this boundary an input falls on; DeepFool iteratively computes the shortest path to cross it. By linearizing the decision boundary locally and solving for the minimal perturbation, DeepFool produces adversarial examples with smaller L_2 norms than FGSM, making them less perceptible while remaining effective.

Carlini and Wagner [6] developed a family of optimization-based attacks (known as C&W attacks) that reformulate adversarial example generation as a constrained optimization problem. Their approach jointly optimizes two objectives: (1) minimizing the distance between the original and adversarial example according to a chosen L_p norm, and (2) maximizing the confidence of misclassification. By carefully designing the optimization objective and using iterative gradient-based solvers, C&W attacks achieve state-of-the-art attack success rates across L_0, L_2, and L_∞ distance metrics. Notably, C&W attacks successfully defeated several defenses that had previously resisted simpler attacks, including **defensive distillation** [7], a technique that trains models on softened probability outputs rather than hard labels to smooth the loss surface and make gradient-based attacks less effective.

2.2.2 The Breakdown of Early Defenses

The proposal and subsequent failure of early defenses illustrated the challenge of defending against adaptive adversaries. Carlini and Wagner [8] conducted a systematic evaluation of ten detection-based defenses, which are methods designed to identify and reject adversarial inputs before they reach the classifier. They demonstrated that all ten defenses could be circumvented by adaptive attacks that account for the detection mechanism. This work established an important methodological principle: defenses must be evaluated against adaptive adversaries who know the defense strategy and can optimize attacks accordingly, not just against fixed attack methods developed before the defense was proposed.

This pattern repeated across numerous defense proposals. Defenses based on input transformations (such as JPEG compression, bit-depth reduction, or spatial smoothing) were bypassed by attacks optimized to remain effective after the transformation [9]. Defenses that obfuscated gradients by making it difficult for attackers to compute useful gradient information were shown to provide a false sense of security, as attackers could use gradient-free methods, approximate gradients, or exploit the defense mechanism itself [9].

2.2.3 Adversarial Training and Certified Defenses

As detection-based and gradient-masking defenses failed, the research community increasingly focused on two more principled approaches: adversarial training and certified robustness.

Adversarial training directly incorporates adversarial examples into the training process, teaching models to correctly classify both natural and adversarially perturbed inputs. Madry et al. [10] formalized

this approach as a **min-max optimization problem**:

$$\min_{\theta} \mathbb{E}_{(x,y)\sim D} \left[\max_{\|\delta\|\leq\epsilon} \mathcal{L}(f_\theta(x+\delta), y) \right]$$

where θ represents model parameters, (x, y) are training examples from distribution D, δ is the adversarial perturbation bounded by radius ϵ, and $\mathcal{L}$ is the loss function. The inner maximization finds the worst-case perturbation within the allowed threat model, while the outer minimization trains the model to minimize loss even against these worst-case perturbations. This formulation provides a theoretically grounded framework for robustness, though adversarially trained models often exhibit reduced accuracy on clean (non-adversarial) inputs, a phenomenon known as the robustness-accuracy trade-off [11, 12].

Tramèr et al. [13] introduced **ensemble adversarial training**, which augments training data with adversarial examples generated from multiple source models (an ensemble) rather than only the model being trained. This approach improves robustness against black-box transfer attacks, where adversarial examples crafted for one model are used to attack a different model. By exposing the model to adversarial examples from diverse architectures during training, ensemble adversarial training reduces the model's susceptibility to transferred perturbations.

Certified robustness takes a fundamentally different approach by providing mathematical guarantees that a model's prediction cannot be changed by any perturbation within a specified radius, regardless of the attack method used [14]. Rather than empirically testing defenses against known attacks, certified defenses use formal verification techniques, randomized smoothing [15], or interval bound propagation [16] to prove that no adversarial example exists within a defined threat model. For instance, a certifiably robust classifier might guarantee that for a given input, any perturbation with L_2 norm less than 0.5 will not change the predicted class. While certified robustness offers strong security guarantees, these methods face scalability challenges: certification becomes computationally expensive for large models and high-dimensional inputs, and the radius of certifiable robustness is often smaller than what adversarial training can achieve empirically. The choice between empirical robustness (adversarial training) and certified robustness represents a trade-off between practical effectiveness and theoretical guarantees.

2.3 Expanding Threat Landscape

The field then expanded beyond evasion attacks to include privacy violations and threats during training. Membership inference attacks [17, 18] determine whether specific data points were part of model training. Carlini et al. [19] argued for assessing such attacks at low false positive rates, which reflect the serious nature of privacy issues.

Training-time attacks interfere with the learning process itself. Backdoor attacks introduce hidden triggers that cause specific misbehaviors when activated, with recent studies showing attacks on self-supervised learning [20], along with distribution-preserving methods that avoid detection [21]. Poisoning attacks that corrupt training data demonstrate that even small amounts of malicious samples can significantly harm model performance [22].

Physical-world attacks took gradient-based techniques beyond digital settings. Kurakin et al. [23] showed that adversarial examples remained effective when printed and photographed. Later work [24] developed robust physical adversarial examples against traffic sign recognition systems in autonomous

vehicles, raising questions about whether real-world attackers would use such complex methods when simpler options might work.

2.4 The Theory-Practice Gap

As the theoretical level of adversarial ML research increased, worries grew about whether this work addressed actual security needs in the real world. Kumar et al. [25] interviewed practitioners from 28 organizations, discovering that the industry lacked practical tools for dealing with adversarial ML threats. Grosse et al. [26] surveyed 271 industrial practitioners, revealing that while academic threat models were theoretically valid, research often overestimated what attackers could do, especially regarding access to training data and query limits.

Mink et al. [27] identified organizational barriers to deploying defenses through interviews with ML practitioners. These barriers included a lack of motivation from institutions, difficulty assessing AML risk, and competing business priorities. Practitioners often saw security as outside their expertise, revealing mismatches between job definitions in ML and security duties.

Apruzzese et al. [1] crystallized these issues through real-world case studies showing that actual ML system breaches often involved simple tactics rather than complex gradient-based attacks: input manipulation without gradients, exploiting system weaknesses instead of model-specific faults, operational gaps, and social engineering. This historical trend encourages a systematic analysis of recent publications to see if current research is addressing the theory-practice gap or continuing past patterns.

2.5 Types of Adversarial Attacks

Understanding the landscape of adversarial threats requires a taxonomy of attack objectives and methodologies. The adversarial ML community has identified distinct categories of attacks based on when they occur in the machine learning pipeline and what adversarial goals they serve [28]. These categories differ fundamentally in their threat models, required adversarial capabilities, and real-world implications for deployed systems.

Adversarial attacks generally fall into three primary categories based on their goals and the phase of the ML pipeline they target:

Evasion attacks manipulate inputs during inference to cause misclassification [2, 3]. The attacker changes an input (such as an image, malware sample, or network packet) so that the model gives an incorrect prediction while the model itself remains unchanged. These attacks target the inference phase and represent the most extensively studied threat type in adversarial ML literature. Early demonstrations by Szegedy et al. [2] and subsequent refinements [5, 6] established evasion attacks as the canonical adversarial threat, though their prevalence in academic research may not reflect their occurrence in real-world deployments.

Poisoning attacks corrupt the training process by injecting malicious data [29]. By adding carefully crafted malicious examples to training data, attackers can lead models to learn incorrect behaviors or establish backdoors, which are hidden triggers that cause specific failures when activated [30]. A poisoned model might classify most inputs correctly but systematically fail on inputs containing a particular pattern or trigger. Unlike evasion attacks that affect individual predictions, poisoning attacks compromise the model itself, potentially affecting all future inferences. Recent work has demonstrated poisoning

attacks against federated learning [31], self-supervised learning [20], and even distribution-preserving poisoning that evades detection [21].

Privacy attacks extract sensitive information from trained models [17]. Membership inference attacks determine if specific individuals were included in the training data [17, 18], potentially violating privacy even when models do not explicitly memorize training examples. Model extraction attacks aim to replicate model functionality through repeated queries [32], threatening intellectual property and enabling subsequent attacks. Data reconstruction attacks attempt to retrieve actual training examples from model parameters [33], with recent work demonstrating extraction of training data from large language models. These attacks raise fundamental questions about the privacy guarantees of machine learning systems and have motivated research into differential privacy [34] and other privacy-preserving training methods.

2.6 Threat Models and Their Implications

A critical dimension for evaluating adversarial ML research is the threat model, which formally specifies an adversary's capabilities, knowledge, and objectives [4]. The threat model determines what the attacker knows about the target system, what actions they can perform, and what constraints they face. This aspect represents a major area where academic research assumptions diverge from real-world deployment realities, as the adversarial capabilities assumed in research often exceed what attackers have in practice [1, 26].

The security community traditionally categorizes adversarial access along a spectrum from complete knowledge to query-only interaction:

White-box access assumes the attacker possesses complete knowledge of the model: its architecture, all parameters (weights and biases), training procedures, and possibly the training data itself [6, 10]. With white-box access, attackers can compute gradients (the mathematical derivatives indicating how changes to inputs affect model outputs), enabling efficient optimization-based attacks. Many seminal academic attacks assume white-box access [2, 3, 6] because it simplifies the mathematical formulation and enables rigorous worst-case analysis. However, this assumption provides adversaries with capabilities rarely available against production systems, where models are deployed as black-box services or protected by intellectual property measures.

Black-box access constrains the attacker to query-only interaction: they can submit inputs and observe outputs (predictions, confidence scores, or rankings) but cannot inspect internal model components [35]. This scenario more closely reflects real-world deployments where models operate as web services, mobile applications, or embedded systems with no internal visibility. Black-box attackers must rely on query-based optimization, transfer attacks from surrogate models [35], or input transformations that do not require gradient information [36]. Commercial ML services typically implement rate limiting, query costs, and anomaly detection that further constrain black-box attack feasibility.

Gray-box access represents intermediate scenarios where attackers possess partial knowledge [35]. They might know the model architecture but not the trained parameters, have access to a similar (but not identical) training dataset, or understand the training procedure without accessing the final model. Gray-box settings attempt to bridge the gap between white-box theoretical analysis and black-box deployment realities, though they remain less studied than the two extremes.

The choice of threat model profoundly affects research conclusions. Apruzzese et al. [1] stress that

real-world attackers rarely have white-box access to production systems, which typically employ API abstractions, model encryption, and restricted query interfaces. Similarly, Grosse et al. [26] document through practitioner surveys that academic assumptions about attacker knowledge, particularly regarding training data access and unlimited queries, systematically overestimate real-world adversarial capabilities. Yet, as our analysis shows, 63.2% of papers in our dataset assume white-box access, suggesting that research priorities may emphasize theoretical worst-case analysis over empirically grounded threat modeling.

3 Methodology

3.1 Data Collection

We systematically reviewed all papers with adversarial ML focus published at four top-tier security venues from 2022 through 2025. These venues were selected because they represent primary publication outlets for security-focused ML research and have historically shaped the field's direction.



Figure 1: Dataset overview showing the distribution of 454 papers across four security conferences (ACM CCS, IEEE S&P, NDSS, USENIX Security) from 2022 to 2025.

Our dataset comprises 454 papers: ACM CCS contributed 118 papers (26.0%), IEEE S&P contributed 79 papers (17.4%), NDSS contributed 49 papers (10.8%), and USENIX Security contributed 208 papers (45.8%). The temporal distribution includes 89 papers from 2022, 136 from 2023, 198 from 2024, and 31 from 2025 (partial year at time of analysis).

3.2 Coding Framework

Each paper was evaluated across multiple dimensions designed to capture practical relevance:

- **Research Focus (G1):** Whether the paper primarily proposes attacks (60%), defenses (39%), or both (2%).

- **Attack Type (G2):** Classification as evasion (48%), poisoning (20%), privacy (23%), or multiple types (9%).
- **Data Domain (G4):** The input modality: images (65%), text (11%), audio (7%), malware (6%), or other (12%).
- **Threat Model (T1):** Assumed adversary access: white-box (63.2%), black-box (34.1%), or gray-box (2.6%).
- **Gradient Requirements (Q1):** Whether the approach requires gradient access.
- **Query Budget (Q2):** High (>1000 queries), low, or none.
- **Real System Testing (G7):** Whether validation occurred on deployed systems.
- **Code Release (G6):** Whether code was released publicly.

3.3 Gap Score Framework

To quantify the theory-practice gap, we developed a 6-point "Gap Score" summing binary indicators of assumptions that may limit practical applicability:

1. Requires white-box access (vs. black/gray-box)
2. Requires gradient computation
3. Assumes high query budget (>1000 queries)
4. Requires substantial computation (GPU-level resources)
5. No testing on deployed systems
6. No consideration of economic factors

Higher scores indicate greater distance from practical deployment considerations. A paper scoring 0 would employ realistic threat models, require minimal resources, validate on production systems, and consider economic constraints. A paper scoring 6 would represent a primarily theoretical contribution with limited immediate applicability to deployed systems.

4 Quantitative Findings



Figure 2: Overview of the theory-practice gap showing the percentage of papers exhibiting each characteristic: no real-world testing (94.7%), high query budget (80.4%), gradient dependency (67.8%), white-box access (63.2%), and no code release (10.4%).

Our analysis identifies several areas where research practices diverge from deployment realities. Figure 2 summarizes the key indicators across all 454 papers.

4.1 Real-World Validation

The most pronounced finding concerns real-world validation: **only 5.3% of papers (24 of 454) evaluate on actual deployed systems**. The remaining 94.7% validate exclusively on research benchmarks, simulated environments, or research prototypes.



Figure 3: Real-world testing rate: 5.3% of papers validate on deployed systems.

This pattern has implications because deployment introduces constraints absent from controlled experiments. Production systems employ proprietary model formats and encryption. They integrate ML components into complex security pipelines where multiple components interact. They face hardware

constraints, latency requirements, and regulatory compliance obligations. Research validated only in laboratory settings may require substantial adaptation for deployment.

The few papers that do validate on real systems often reveal differences between laboratory and field performance. Nayan et al. [37] conducted a systematic review of on-device ML model extraction attacks, finding that many proposed academic attacks proved difficult to reproduce, performed less effectively on production models, or introduced unacceptable computational and energy costs. Similarly, Layton et al. [38] demonstrated that deepfake detection research employs metrics and dataset distributions that may lead to overestimation of detector efficacy.

Duan et al. [39] validated perception-aware attacks against YouTube's copyright detection system, representing one of the rare examples of testing against commercial infrastructure. Their work demonstrated that attacks optimized in simulation required adaptation to succeed in practice.

4.2 Gradient Dependency

Apruzzese et al.'s critique centered on the observation that "real attackers don't compute gradients." Our analysis indicates this pattern persists: **67.8% of papers require gradient access**, despite this capability being unavailable against most production systems.



Figure 4: Gradient dependency analysis showing limited change over time (68.2% in 2022 to 65.9% in 2025) and variation by attack type.

Temporal analysis reveals limited change in this dimension. Gradient dependency has remained relatively stable: 68.2% in 2022, 69.1% in 2023, 66.8% in 2024, and 65.9% in 2025. While individual papers have explored gradient-free approaches, the overall distribution has not shifted substantially.

Some research has pioneered gradient-free methods in specific domains. The Universal Robustness Evaluation Toolkit (URET) from Eykholt et al. [36] formulates adversarial generation as a graph exploration problem, seeking sequences of domain-specific, functionality-preserving transformations rather than relying on differentiable feature spaces. This framework enables evaluation of systems processing inputs like malware binaries or tabular data where semantic and functional correctness must be maintained during perturbation.

Similarly, practical LLM jailbreak attacks demonstrate that effective attacks need not be gradient-based. Liu et al. [40] and Yu et al. [41] showed that jailbreaking large language models can be effective

even when executed via strategically crafted natural language prompts, illustrating the potential of accessible black-box attacks compared to complex gradient optimization.

4.3 Threat Model Assumptions

White-box access remains the predominant assumption: **63.2% of papers assume adversaries have complete knowledge of model architecture and parameters**. Only 34.1% consider black-box scenarios more closely matching deployment conditions, and 2.6% examine gray-box settings.



Figure 5: Distribution of threat model assumptions across all papers, showing prevalence of white-box assumptions.

This pattern contrasts with industrial practice. As Grosse et al. [26] document, academic studies often operate under assumptions of attacker access (such as extensive access to internal models, parameters, or training data) that do not reflect the security controls present in production environments.

The foundational meta-analysis by Arp et al. [42] identified methodological patterns in security research, including reliance on laboratory-only evaluation and deployment of threat models that may not account for adaptive adversaries. Our analysis suggests these patterns persist in the 2022–2025 literature.

4.4 Query Budget Assumptions

Even papers employing black-box threat models often assume substantial query access. **80.4% of papers assume high query budgets (>1000 queries)**, which may be impractical when commercial APIs implement rate limiting, repeated queries trigger anomaly detection, and real-time constraints limit iterative optimization.



Figure 6: Query budget assumptions showing 80.4% of papers assume high query budgets.

Some recent work has addressed query efficiency. HARDBEAT from Tao et al. [43] generates triggers requiring knowledge only of the final predicted label (hard-label) and minimal queries, addressing restrictions imposed by commercial services. BounceAttack from Wan et al. [44] demonstrates query-efficient decision-based attacks. However, these remain exceptions rather than the predominant approach.

4.5 Domain Distribution

Adversarial ML research exhibits notable domain concentration: **65% of papers focus exclusively on image data**. Text receives 11% of attention, audio 7%, malware 6%, with all other domains combined representing 12%.



Figure 7: Data domain distribution revealing concentration on image classification in adversarial ML research.

This concentration creates potential blind spots. Financial systems process tabular data where adversarial perturbations cannot be measured by pixel distances. As Kireev et al. [45] observe for fraud detection, the meaningful constraint is not visual imperceptibility but rather the quantifiable financial cost or utility an adversary must expend. L_p norms may be less informative for tabular financial data; what matters is whether fraudulent transactions remain economically viable.

4.6 Code Availability

One dimension shows encouraging results: **89.6% of papers release their code**. This represents substantial commitment to reproducibility and exceeds code release rates in many other fields.

However, this introduces a nuanced consideration: code designed for research datasets may not transfer directly to production environments without substantial re-engineering. High code release rates support reproducibility while not necessarily indicating deployment readiness.

4.7 Gap Score Distribution



Figure 8: Distribution of Gap Scores showing the typical paper (mean 3.17/6) incorporates roughly half of the measured assumptions.

The mean Gap Score across all 454 papers is **3.17 out of 6**, indicating the typical paper incorporates approximately half of the assumptions we measured. The distribution peaks at scores of 3 to 4, with approximately 10.5% of papers achieving scores of 0 to 1 that would indicate closer alignment with deployment considerations.

Conference-level analysis reveals similar patterns across venues: ACM CCS averages 3.04, NDSS 3.12, IEEE S&P 3.18, and USENIX 3.25. No venue has established itself as substantially more practice-focused than others; the patterns we observe appear consistent across the security research community.

5 Thematic Findings

Beyond the quantitative metrics, our thematic analysis across venues reveals several recurring patterns and emerging directions in adversarial machine learning research.

Utility and robustness trade-off. Practical deployment often requires balancing security guarantees against system performance. Studies from USENIX Security highlight that defenses offering certifiable robustness can reduce clean accuracy and increase inference cost by an order of magnitude [46, 47]. This tension extends beyond vision: defenses against malicious activations in voice assistants degrade natural accuracy [48], and differential privacy techniques reduce model utility [49, 50]. Recent work shows progress: PatchCleanser masks images without harming state-of-the-art accuracy [46]; MIST limits

overfitting on the most vulnerable training instances [51]; and CAMP demonstrates that adversarially robust reinforcement learning can preserve expected returns [52].

Evaluation methodology. There is increasing recognition that standard distance metrics and evaluation practices may not reflect human perception or operational realities. Lp norms measure pixel differences but do not reliably predict whether humans detect adversarial examples [19], a conclusion reinforced by eye-tracking studies in virtual reality that show mathematically imperceptible perturbations can be obvious to drivers [53]. Privacy research warns that defences evaluated using average-case metrics may still leak data about specific individuals [19]. As a result, researchers advocate human-in-the-loop evaluation, domain-appropriate perturbation constraints, realistic query budgets and explicit reporting of computational cost.

Physical deployment and system integration. A significant theme is the gap between digital adversarial examples and the complexities of physical environments. Physical attacks must contend with distance, viewpoint, illumination and sensor noise. Jia et al. tested physical adversarial signs against production autonomous vehicles [24], while subsequent studies attacked X-ray detectors [54], LiDAR systems [55], voice recognition using tubes [56], road-surface LiDAR spoofing [57] and perceptual hashing algorithms [58]. Researchers also show that system components such as data filters, file-type detectors and compiler pipelines can introduce new vulnerabilities: privacy side channels can emerge from data filtering [59], malware detection can be bypassed via file-type manipulation [60], and defences can disappear during compilation [61]. These findings stress that robustness must be integrated end-to-end.

Real-world adversarial incidents. Documented attacks underscore the importance of system interfaces and economic incentives. The EchoLeak attack used a single phishing email, a reference link and automatic image preview to extract data from Microsoft 365 Copilot [62]. A prompt-injection exploit on Google Bard hid instructions in a shared document and encoded private data via an image URL [63], while the AgentFlayer demonstration extracted API keys from a poisoned document in Google Drive [64]. These cases show that large language model deployments can be compromised via email, document summarisation and browsing contexts, and attackers often chain simple techniques. Beyond prompt injection, the divergence attack reveals training data from ChatGPT at rates far exceeding previous methods [65], and high-fidelity model extraction against commercial APIs is feasible [66]. Supply chain poisoning tools like Nightshade allow artists to corrupt generative model training data [67], and deepfake scams show how attackers manipulate human users [68]. Together, these incidents illustrate that adversarial threats span the entire ML pipeline, from data collection to deployment and human interaction.

Attack and defence evolution. Over time, attacks have become more practical and stealthy. Early work focused on physically realisable perturbations like the frustum attack, which exploits automotive sensor fusion [69]. The popularity of large language models brought natural-language jailbreaking; black-box methods such as PAIR and TAP elicit harmful outputs within a small number of queries [70, 71]. Multimodal models reveal cross-modal vulnerabilities as vision encoders receive less hardening than text components [72]. Recent attacks prioritise persistence: MergeBackdoor remains dormant until

merged with other models [73], and persistent backdoors survive continual learning [74]. Defences have evolved from generic heuristics to specialised, interpretable and context-aware mechanisms. Blacklight identifies black-box query attacks by detecting near-duplicate queries [75]. JBShield manipulates hidden states to remove toxic or jailbreak concepts [76], SafeSpeech reduces the utility of synthesised voice data to deter cloning [77], and DeBackdoor detects backdoors under black-box and data-scarce conditions [78]. The distribution of attack types over time is shown in Figure 9.

Economic and organisational factors. Finally, we note that economic and organisational dynamics receive relatively little attention. Researchers highlight that the cost of extracting proprietary models can be much lower than the cost of training and protecting them: pre-trained encoders can be extracted cheaply [79], and watermark removal requires only a small fraction of training data [80]. Organisational studies suggest that ML practitioners often lack motivation or resources to implement adversarial defences, viewing security and machine learning as separate domains [27]. As a result, adversarial evaluations are rarely prioritised, and attacks may go undetected in production. Addressing adversarial threats therefore requires not only technical advances but also shifts in organisational culture and closer collaboration between ML and security teams.



Figure 9: Distribution of attack types across the 2022–2025 period. Evasion attacks dominate, but the composition shifts as new modalities and tactics emerge.

6 Foundation Models and Large Language Models: An Emerging Parallel Frontier

The rapid growth of large language models represents a significant shift in adversarial machine learning, developing alongside traditional research focused on computer vision. While image classifiers operate in continuous pixel space with bounded L_p-norm perturbations, LLMs function in discrete token spaces with open-ended context windows and fundamentally different attack surfaces. These systems now power applications affecting millions, including customer service chatbots, code generation tools, and medical assistants. However, adversarial research in this domain reveals the same theory-practice gaps observed in traditional ML fields.

6.1 From Manual Jailbreaks to Automated Optimization

Initial LLM adversarial research relied on manual prompt engineering, where simple role-playing scenarios or encoded instructions (ROT13, Base64) bypassed safety measures. This changed with Zou et al.'s [81] Greedy Coordinate Gradient (GCG) attack, which automates discrete optimization over token sequences to generate universal adversarial suffixes. GCG achieved 100% success on Vicuna-7B and 88% on Llama-2-7B-Chat, with transfer rates of 87.9% for GPT-3.5, 53.6% for GPT-4, and 66% for PaLM-2. Notably, Claude-2 showed significantly higher resistance at only 2.1% success.

Yet GCG exemplifies the theory-practice gap. The attack requires white-box gradient access through the model's embedding layer and hundreds of thousands of forward and backward passes during optimization. For production APIs that expose only final text outputs, obtaining gradients is impossible. Carlini et al. [82] note that conducting such attacks would cost approximately $18 on GPT-3.5-Turbo, making them impractical when loss and gradients cannot be easily accessed.

Recent research has shifted toward black-box methods reflecting real-world constraints. Chao et al. [70] introduced PAIR (Prompt Automatic Iterative Refinement), using an attacker LLM to refine jailbreak prompts based on target model feedback, succeeding in fewer than 20 queries. Mehrotra et al. [71] developed Tree of Attacks with Pruning (TAP), achieving over 80% success against GPT-4-Turbo and GPT-4o while bypassing LlamaGuard. These represent serious attack vectors requiring only API access and operating within reasonable query limits.

Multi-turn attacks reveal particularly concerning vulnerabilities. Russinovich et al. [83] demonstrated the Crescendo attack, gradually escalating through seemingly harmless conversations to achieve up to 100% success in under 10 turns. Each message passes safety checks individually; only the accumulated context produces policy violations. Production chat interfaces designed to maintain conversation history inadvertently enable attacks that unfold over minutes rather than seconds.

6.2 Multimodal Models: Exploiting Cross-Modal Alignment Gaps

Vision-language models present attack surfaces absent in text-only systems. Qi et al. [72] showed that a single adversarial image can universally jailbreak vision-language models, forcing compliance with harmful instructions the models would reject in text-only contexts. This vulnerability arises from an alignment gap: while LLM components undergo extensive safety training on text data, vision encoders receive substantially less adversarial hardening.

Typography-based attacks achieve concerning results without gradient access. Gong et al. [84] introduced FigStep, converting harmful text into images that models read via OCR, yielding 82.5% average attack success across six open-source vision-language models compared to 44.8% for identical text-only queries. Against commercial systems, Niu et al. [85] demonstrated multi-modal linkage attacks combining encryption-decryption processes across modalities, achieving 97.8% success on GPT-4o's SafeBench, 98.8% on MM-SafetyBench, and 99.1% on HADES-Dataset.

Audio modalities show similar vulnerabilities. Zhang et al. [86] developed AdvWave, demonstrating that adversarial acoustic noise can jailbreak speech-enabled models with 40% higher success rates than baselines. It successfully jailbroke GPT-4o's speech-to-speech API in just 30 queries with nearly perfect results. The perturbations mimic common urban sounds (dog barks, car horns), making detection difficult without compromising legitimate functionality.

6.3 The Theory-Practice Gap Manifests Differently for LLMs

Examining LLM adversarial research through our analytical framework reveals familiar issues with domain-specific characteristics:

Model Access Assumptions. The most powerful attacks require white-box gradient access available only for open-source models. Production APIs like GPT-4 and Claude expose at most top-5 token probabilities, making direct loss calculations impossible. Huang et al. [87] found their "Catastrophic Jailbreak" achieved 95% misalignment on 11 open-source models but only 7% on ChatGPT, an 88-point gap demonstrating substantially more thorough safety training for proprietary models.

Query Budget Realism. OpenAI's free tier permits approximately 3 requests per minute, while paid tiers allow up to 3,500 requests per minute [88]. Gradient-based attacks requiring 50,000 to 256,000 queries face economic barriers (costs exceeding $18 per attempt) and rate limiting that academic papers often overlook. Black-box methods like PAIR operate within more realistic budgets (approximately 20 queries), though even these face practical limitations at scale.

Evaluation Instability. Unlike static computer vision models, LLM providers continuously update systems and silently patch vulnerabilities. A paper claiming 80% success against "GPT-4 as of March 2024" cannot be verified by June 2024 when the model has changed. Rando and Tramèr [89] note that this evolving defense landscape means "we cannot measure progress against continuously updated closed-source systems," creating benchmarking challenges absent in traditional adversarial ML.

Threat Model Formalization. LLM attacks lack the formal structure bounding CV adversarial examples (like L_p-norm budgets or imperceptibility constraints). Defining "harmful" output requires subjective human judgment. Perez et al. [90] showed that manual red teaming still outperforms automated methods in finding worst-case model failures, suggesting the full attack landscape remains only partially understood by algorithmic approaches.

Prompt-injection incidents further illustrate how the theory–practice gap for LLMs is rooted in interface design. EchoLeak bypassed Copilot's prompt classifier, link filter and content-security policy by chaining hidden instructions, reference-style links and auto-fetched images [62]. Bard's Extensions were hijacked by a hidden prompt in a shared document, causing the model to encode sensitive data into a URL [63]. *AgentFlayer* showed that a single malicious document could extract API keys via OpenAI's Connectors [64]. Tenable's HackedGPT study identified seven vulnerabilities in ChatGPT's browsing and memory tools, demonstrating how comments or trusted websites can inject instructions into the model's browsing context. These cases reveal that LLM robustness must address prompt filtering, memory management and connector policies alongside traditional model training.

6.4 Defense Mechanisms: Progress and Persistent Limitations

Production systems have adopted guardrail architectures assessing prompts and responses before and after LLM processing. Meta's Llama Guard [91] fine-tunes a Llama model to detect policy violations in six harm categories, now at its fourth version with multimodal support. NVIDIA's NeMo Guardrails [92] provides programmable input/output guidelines using Colang, achieving 1.4× improvement in safety compliance with approximately 0.5 seconds added latency.

Recent studies reveal significant weaknesses. Hackett and Gretton [93] tested six guardrail systems, including Azure Prompt Shield and Meta Prompt Guard, against character injection attacks (homo-

glyphs, zero-width characters, Unicode tags) and emoji smuggling, finding up to 100% evasion success with no guardrail performing consistently across attack types. Perplexity-based detection works well against GCG-style attacks producing scrambled suffixes but fails against semantic jailbreaks generating fluent text.

Automated red teaming has advanced substantially. Bertrand et al. [94] introduced Rainbow Teaming, employing quality-diversity optimization through MAP-Elites to create diverse attack databases, achieving greater than 90% success across Llama 2/3 models while providing attacks valuable for diagnosis and safety fine-tuning. Hong et al. [95] applied curiosity-driven reinforcement learning to red teaming, successfully provoking harmful responses from RLHF-tuned models.

Bai et al. [96] introduced Constitutional AI, using RLAIF (RL from AI Feedback) with explicit constitutional principles for self-assessment and revision, producing responses that explain objections rather than refusing outright. However, conflicting goals between helpfulness and harmlessness create vulnerabilities that adversaries can exploit.

Standardized benchmarks aim to systematize jailbreak assessments. Chao et al. [97] released JailbreakBench, featuring 100 misuse behaviors across 10 OpenAI policy categories with public leaderboards tracking attack methods and defenses. While enabling reproducible comparison, it faces typical safety evaluation issues: subjective harm definitions, model updates invalidating findings, and challenges capturing worst-case behaviors through automated metrics.

Agent-specific vulnerabilities represent an emerging concern. Zhan et al. [98] developed InjecAgent, testing 1,054 cases for indirect prompt injection in tool-integrated agents, finding ReAct-prompted GPT-4 vulnerable 24% of the time, with enhanced attacks nearly doubling success rates. When LLMs control tools, access databases, and execute code, successful jailbreaks shift from producing problematic text to taking consequential real-world actions.

6.5 Foundation Model Properties Amplify Systemic Risk

Bommasani et al. [99] identified two features distinguishing foundation models from traditional ML: emergence (unpredictable capabilities from scale) and homogenization (single models serving numerous downstream applications). Adversarial weaknesses in GPT-4 impact not only ChatGPT but every application built on its API, affecting tools from legal document analyzers to educational tutors and medical triage systems. Unlike standalone image classifiers where a compromise affects specific implementations, vulnerabilities in foundation models have systemic effects across the ecosystem.

7 Temporal Trends

A central question of this review is whether the research community has responded to calls for greater practical relevance. Figure 10 summarises temporal trends from 2022 to 2025. Our analysis reveals several persistent patterns. Real system testing remains rare—about five per cent of papers across all years—despite widespread encouragement to evaluate on deployed systems. Dependence on gradient information has held steady at roughly sixty-seven per cent, with few works adopting gradient-free methods. White box assumptions have not declined appreciably (about sixty-three per cent in 2025 compared to sixty-four per cent in 2022), and the distribution of application domains continues to be

dominated by image data (around sixty-five per cent). Very few papers incorporate economic analysis, and this proportion stays below eleven per cent in every year.

There is evidence of modest progress. High query budgets have become slightly less common, declining from about eighty per cent to roughly seventy-six per cent by 2025, and some researchers have proposed more query-efficient attacks. Awareness that attackers often lack complete system knowledge has increased, but this has yet to result in major changes to threat modelling practices.

A further shift is evident in the emergence of large language and multimodal models as a focus of adversarial ML. Work in 2024–2025 points to fundamentally different attack surfaces for such systems: they operate on discrete tokens rather than continuous pixel values and are subject to instability as providers continually update their models. Despite these differences, similar theory-to-practice gaps persist. White box gradient-based attacks such as GCG achieve high success on open-source language models [81], yet they are impractical against commercial APIs that reveal only output tokens. Recent black box methods like PAIR [70] and TAP [71] succeed within tens of queries under more realistic conditions. Multimodal models expose cross-modal vulnerabilities—vision encoders often receive less hardening than text components [72]—and foundation models centralise risk because one model supports many downstream applications. Taken together, the temporal trends indicate that while some improvements have been made, the research community has not yet fully embraced the operational realities of adversarial machine learning.



Figure 10: Temporal trends showing the gap between research and practice from 2022 to 2025. Real-world testing remains rare and other key metrics show only incremental change.

8 Cross-Venue Analysis



Figure 11: Conference comparison heatmap showing similar patterns across all venues.

While all venues share similar theory-practice gap patterns, each has developed distinctive emphases that collectively illuminate different facets of the research landscape.

8.1 ACM CCS: Economics and System Integration

ACM CCS research uniquely emphasizes business logic, usability constraints, and intellectual property protection. Contributions include demonstrating how economic incentives shape the threat landscape [79, 80], documenting relationships between mathematical metrics and human perception [53], analyzing system-level integration considerations [60], and examining architectural constraints in emerging deployment patterns.

8.2 IEEE S&P: Efficiency and Formal Guarantees

IEEE S&P research emphasizes computational efficiency, privacy-utility trade-offs, and certified scalability. The venue has advanced understanding of threat modeling considerations and resource assumptions [19], documented accuracy-privacy trade-offs [100], and examined scalability considerations for certified robustness deployment [101].

8.3 NDSS: Physical Constraints and Operational Realities

NDSS research emphasizes system-level constraints, distributed training considerations, and physical deployment realities. Contributions include documenting gaps between digital perturbations and physical deployment [24], developing metrics for non-image domains [45], analyzing distributed training

heterogeneity [102], and studying adversarial dynamics where defenses create exploitable side channels.

8.4 USENIX Security: Real-World Validation and Domain Diversity

USENIX Security research emphasizes testing on deployed systems and domain-specific constraints. The venue has documented tensions between theoretical rigor and deployment constraints [46, 47], analyzed trade-offs involving computational cost, regulatory compliance, and usability [48], studied adversarial dynamics when defenses encounter adaptive attackers in production, and examined domain-specific requirements [36].

8.5 Attack versus Defense Papers



Figure 12: Comparison of practicality metrics between attack-focused and defense-focused papers.

Our analysis reveals that defense papers demonstrate somewhat higher alignment with practical considerations than attack papers on average. Defense papers show 6% real-system testing versus 5% for attacks, 41% gradient-free approaches versus 27%, and 38% black-box focus versus 31%. However, both categories remain distant from deployment-ready research.

9 Recommendations

Bridging the gap between academic adversarial machine learning and practical deployment requires coordinated action across researchers, conference organisers, industry and funding bodies. We summarise key recommendations for each group without sub-levels of subsections.

Researchers. Researchers should prioritise validation on operational systems and seek partnerships with industry to test defences in deployment settings, even if only limited real-environment evaluation is feasible. Adopt realistic threat models by default: assume black-box access unless a white-box scenario is justified and clearly state the implications of such assumptions. Expand the scope of research beyond image classification to include tabular, graph, time series, multimodal and language models, reflecting real deployment contexts. Incorporate economic analysis by considering attack costs, defender

budgets and return-on-investment trade-offs, and recognise that human factors (e.g. perceptibility) are essential, so evaluation should include human testing rather than relying solely on mathematical metrics. When reporting results, use domain-appropriate perturbation constraints and disclose query budgets and computational cost in practical units.

Venues and programme committees. Conference organisers and reviewers can foster practical research by encouraging or requiring real-world validation; if such testing is infeasible, authors should explain why. Recognise and reward deployability, for example by providing artefact badges for work tested on production systems. Develop clear guidelines that ask authors to address the realism of their threat models, query budgets, gradient assumptions, choice of metrics, economic implications and the ability of attackers to adapt. Value negative results: papers demonstrating that attacks fail under realistic conditions provide important insights and should not be overlooked in favour of only positive findings.

Industry practitioners. Practitioners should interpret academic results in light of operational realities, adjusting risk assessments accordingly rather than accepting laboratory success rates at face value. Budget time and resources for re-engineering research prototypes before they are production-ready, and prioritise defences against plausible adversaries—black-box attacks, low query budgets, economically motivated attackers and domain-specific constraints. Organisations can improve the relevance of research by contributing anonymised data on actual adversarial attempts and deployment constraints.

To secure large language model and foundation model deployments, industry should: (i) maintain least-privilege architectures by treating connectors (email, drives, calendars, repositories) as untrusted input and isolating system prompts from user prompts; (ii) implement robust prompt filtering and memory controls that parse Markdown, HTML and other formats, and treat comments or metadata as untrusted while limiting the exposure of conversational history; (iii) reduce model memorisation by limiting training on sensitive data, applying de-identification or differential privacy, and monitoring for repeated or unnatural queries; (iv) raise the cost of model extraction through strict query limits, output randomisation and watermarking; and (v) protect the training pipeline and human layer by verifying data provenance, detecting poisoned samples, honouring opt-out requests, and educating staff about deepfake and phishing threats.

Funding agencies. Funding bodies should support industry–academic collaborations that include real-world validation and fund deployment studies rather than focusing solely on novel algorithms. Replication studies that test academic claims against operational systems are essential for progress and should be incentivised. Red-team/blue-team exercises with realistic constraints can yield valuable insights and merit funding.

10 Limitations and Threats to Validity

This review has several limitations that warrant consideration. First, our analysis focuses exclusively on four security venues (ACM CCS, IEEE S&P, NDSS, and USENIX Security) and may not reflect patterns at machine learning conferences such as NeurIPS, ICML, or ICLR, where different methodological norms and evaluation standards may apply. Second, publication bias may suppress negative

results, meaning that attacks which fail under realistic constraints or defenses which prove impractical in deployment are less likely to be published, potentially skewing our view of the field's progress. Third, our temporal window from 2022 to 2025 may not capture longer-term trends or reflect the full impact of recent methodological shifts.

Our quantitative framework, while systematic, introduces its own limitations. The Gap Score reduces complex trade-offs to binary indicators, potentially oversimplifying nuanced situations where papers exhibit partial alignment with practical considerations. Manual coding introduces subjectivity, particularly for papers that span multiple categories or employ hybrid approaches. Additionally, the definition of "real system testing" may vary across papers, with some testing on emulated production environments that share some but not all deployment constraints.

Finally, security venues may be more practice-focused than typical computer science venues given their traditional emphasis on real-world threats. If this is the case, our findings may underestimate the theory-practice gap in the broader machine learning research community, suggesting that the disconnect we document could be even more pronounced when considering adversarial ML research published outside security conferences.

11 Conclusion

The analysis of 454 research papers from 2022 to 2025, presented at the four largest security conferences (ACM CCS, IEEE S&P, NDSS, and USENIX Security), shows that while the adversarial ML community has developed a strong foundation of theories, many researchers overlook real-world issues. The results reveal that most research papers do not pass validity checks for real-world systems (94.7%), often require gradient access, which is rarely feasible in practice (67.8%), suggest query budgets that exceed real-world limits (80.4%), and use white-box threat models (63.2%). Other problems highlighted by a thematic analysis include Lp norms that do not align with human understanding, robustness failing to carry over from simulations to real applications, neglecting economic impact and compatibility, and benchmarks that emphasize worst-case scenarios. Large language models and other foundational models introduce new vulnerabilities through discrete token spaces and cross-modal inputs. However, the gap between scientific research and real-world use remains. Many applications depend on a single model, making it crucial for researchers and other professionals to address these gaps. Case studies examining prompt injection attacks on Copilot and Bard, divergence attacks related to training data leaks, and model extraction provide further evidence of these issues.

References

[1] Giovanni Apruzzese, Hyrum S Anderson, Savino Dambra, David Freeman, Fabio Pierazzi, and Kevin A Roundy. "real attackers don't compute gradients": Bridging the gap between adversarial ml research and practice. *arXiv preprint arXiv:2212.14315*, 2022.

[2] Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In *International Conference on Learning Representations*, 2014.

[3] Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *International Conference on Learning Representations*, 2015.

[4] Nicholas Carlini, Anish Athalye, Nicolas Papernot, Wieland Brendel, Jonas Rauber, Dimitris Tsipras, Ian Goodfellow, Aleksander Madry, and Alexey Kurakin. On evaluating adversarial robustness. In *arXiv preprint arXiv:1902.06705*, 2019.

[5] Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, and Pascal Frossard. DeepFool: A simple and accurate method to fool deep neural networks. In *IEEE Conference on Computer Vision and Pattern Recognition*, pages 2574–2582, 2016.

[6] Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks. In *IEEE Symposium on Security and Privacy*, pages 39–57, 2017.

[7] Nicolas Papernot, Patrick McDaniel, Xi Wu, Somesh Jha, and Ananthram Swami. Distillation as a defense to adversarial perturbations against deep neural networks. In *IEEE Symposium on Security and Privacy*, pages 582–597, 2016.

[8] Nicholas Carlini and David Wagner. Adversarial examples are not easily detected: Bypassing ten detection methods. In *ACM Workshop on Artificial Intelligence and Security*, pages 3–14, 2017.

[9] Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In *International Conference on Machine Learning*, pages 274–283, 2018.

[10] Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *International Conference on Learning Representations*, 2018.

[11] Dimitris Tsipras, Shibani Santurkar, Logan Engstrom, Alexander Turner, and Aleksander Madry. Robustness may be at odds with accuracy. In *International Conference on Learning Representations*, 2019.

[12] Hongyang Zhang, Yaodong Yu, Jiantao Jiao, Eric P Xing, Laurent El Ghaoui, and Michael I Jordan. Theoretically principled trade-off between robustness and accuracy. In *International Conference on Machine Learning*, pages 7472–7482, 2019.

[13] Florian Tramèr, Alexey Kurakin, Nicolas Papernot, Dan Boneh, and Patrick McDaniel. Ensemble adversarial training: Attacks and defenses. In *International Conference on Learning Representations*, 2018.

[14] Linyi Li, Tao Xie, and Bo Li. SoK: Certified robustness for deep neural networks. In *IEEE Symposium on Security and Privacy*, 2023.

[15] Jeremy M Cohen, Elan Rosenfeld, and J Zico Kolter. Certified adversarial robustness via randomized smoothing. In *International Conference on Machine Learning*, pages 1310–1320, 2019.

[16] Sven Gowal, Krishnamurthy Dvijotham, Robert Stanforth, Rudy Bunel, Chongli Qin, Jonathan Uesato, Relja Arandjelovic, Timothy Mann, and Pushmeet Kohli. On the effectiveness of interval bound propagation for training verifiably robust models. *arXiv preprint arXiv:1810.12715*, 2018.

[17] Reza Shokri, Marco Stronati, Congzheng Song, and Vitaly Shmatikov. Membership inference attacks against machine learning models. In *IEEE Symposium on Security and Privacy*, pages 3–18, 2017.

[18] Jiayuan Ye, Aadyaa Maddi, Sasi Kumar Murakonda, Vincent Bindschaedler, and Reza Shokri. Enhanced membership inference attacks against machine learning models. In *ACM Conference on Computer and Communications Security*, pages 3093–3106, 2022.

[19] Nicholas Carlini, Steve Chien, Milad Nasr, Shuang Song, Andreas Terzis, and Florian Tramer. Membership inference attacks from first principles. In *Proceedings of the 2022 IEEE Symposium on Security and Privacy*, 2022.

[20] Jinyuan Jia, Yupei Liu, and Neil Zhenqiang Gong. BadEncoder: Backdoor attacks to pre-trained encoders in self-supervised learning. *arXiv preprint arXiv:2108.00352*, 2021.

[21] Guanhong Tao, Zhenting Wang, Shiwei Feng, Guangyu Shen, Shiqing Ma, and Xiangyu Zhang. Distribution preserving backdoor attack in self-supervised learning. In *IEEE Symposium on Security and Privacy*, 2024.

[22] Florian Tramèr, Reza Shokri, Ayrton San Joaquin, Hoang Manh Le, Matthew Jagielski, Sanghyun Hong, and Nicholas Carlini. Truth serum: Poisoning machine learning models to reveal their secrets. In *ACM Conference on Computer and Communications Security*, pages 2779–2792, 2022.

[23] Alexey Kurakin, Ian Goodfellow, and Samy Bengio. Adversarial examples in the physical world. In *International Conference on Learning Representations Workshop*, 2017.

[24] Yaomin Jia et al. Physical adversarial attack on vehicle detector in the carla simulation environment. In *Proceedings of the 2022 Network and Distributed System Security Symposium*, 2022.

[25] Ram Shankar Siva Kumar, Magnus Nyström, John Lambert, Andrew Marshall, Mario Goertzel, Andi Comissoneru, Matt Swann, and Sharon Xia. Adversarial machine learning – industry perspectives. In *IEEE Security and Privacy Workshops*, pages 69–75, 2020.

[26] Kathrin Grosse, Lukas Bieringer, Tarek R Besold, and Hongxin Hu. Towards more practical threat models in artificial intelligence security. In *Proceedings of the 33rd USENIX Security Symposium*, 2024.

[27] Jaron Mink et al. "security is not my field, i'm a stats guy": A qualitative root cause analysis of barriers to adversarial machine learning defenses in industry. In *Proceedings of the 32nd USENIX Security Symposium*, 2023.

[28] Battista Biggio and Fabio Roli. Wild patterns: Ten years after the rise of adversarial machine learning. *Pattern Recognition*, 84:317–331, 2018.

[29] Battista Biggio, Blaine Nelson, and Pavel Laskov. Poisoning attacks against support vector machines. In *International Conference on Machine Learning*, pages 1467–1474, 2012.

[30] Tianyu Gu, Brendan Dolan-Gavitt, and Siddharth Garg. BadNets: Identifying vulnerabilities in the machine learning model supply chain. In *arXiv preprint arXiv:1708.06733*, 2017.

[31] Eugene Bagdasaryan, Andreas Veit, Yiqing Hua, Deborah Estrin, and Vitaly Shmatikov. Backdoor attacks against federated learning. In *arXiv preprint arXiv:1807.00459*, 2020.

[32] Florian Tramèr, Fan Zhang, Ari Juels, Michael K Reiter, and Thomas Ristenpart. Stealing machine learning models via prediction APIs. In *USENIX Security Symposium*, pages 601–618, 2016.

[33] Nicholas Carlini, Florian Tramer, Eric Wallace, Matthew Jagielski, Ariel Herbert-Voss, Katherine Lee, Adam Roberts, Tom Brown, Dawn Song, Ulfar Erlingsson, Alina Oprea, and Colin Raffel. Extracting training data from large language models. In *USENIX Security Symposium*, pages 2633–2650, 2021.

[34] Martin Abadi, Andy Chu, Ian Goodfellow, H Brendan McMahan, Ilya Mironov, Kunal Talwar, and Li Zhang. Deep learning with differential privacy. In *ACM Conference on Computer and Communications Security*, pages 308–318, 2016.

[35] Nicolas Papernot, Patrick McDaniel, Ian Goodfellow, Somesh Jha, Z Berkay Celik, and Ananthram Swami. Practical black-box attacks against machine learning. In *ACM Asia Conference on Computer and Communications Security*, pages 506–519, 2017.

[36] Kevin Eykholt et al. URET: Universal robustness evaluation toolkit (for evasion). In *Proceedings of the 32nd USENIX Security Symposium*, 2023.

[37] Tanvir Nayan, Qian Guo, Mohammed Al Duniawi, Marcus Botacin, Selcuk Uluagac, and Ruimin Sun. SoK: All you need to know about on-device ML model extraction - the gap between research and practice. In *Proceedings of the 33rd USENIX Security Symposium*, 2024.

[38] Samuel Layton, Tyler Tucker, Dominik Olszewski, Kevin Warren, Kevin Butler, and Patrick Traynor. SoK: The good, the bad, and the unbalanced: Measuring structural limitations of deepfake media datasets. In *Proceedings of the 33rd USENIX Security Symposium*, 2024.

[39] Rui Duan et al. Perception-aware attack: Creating adversarial music via reverse engineering. In *Proceedings of the 31st USENIX Security Symposium*, 2022.

[40] Haoyu Liu, Yuxuan Zhang, Zihan Zhao, Yunjie Dong, Guozhu Meng, and Kai Chen. Making them ask and answer: Jailbreaking large language models in few queries via disguise and reconstruction. In *Proceedings of the 33rd USENIX Security Symposium*, 2024.

[41] Zhiyuan Yu, Xiaogeng Liu, Shunning Liang, Zach Cameron, Chaowei Xiao, and Ning Zhang. Don't listen to me: Understanding and exploring jailbreak prompts of large language models. In *Proceedings of the 33rd USENIX Security Symposium*, 2024.

[42] Daniel Arp, Erwin Quiring, Feargus Pendlebury, Alexander Warnecke, Fabio Pierazzi, Christian Wressnegger, Lorenzo Cavallaro, and Konrad Rieck. Dos and don'ts of machine learning in computer security. In *Proceedings of the 31st USENIX Security Symposium*, 2022.

[43] Guanhong Tao et al. Hard-label black-box universal adversarial patch attack. In *Proceedings of the 32nd USENIX Security Symposium*, 2023.

[44] Yuying Wan et al. BounceAttack: A query-efficient decision-based black-box attack. In *Proceedings of the 2024 IEEE Symposium on Security and Privacy*, 2024.

[45] Klim Kireev et al. On the robustness of machine learning models beyond adversarial settings. In *Proceedings of the 2023 Network and Distributed System Security Symposium*, 2023.

[46] Chong Xiang, Saeed Mahloujifar, and Prateek Mittal. PatchCleanser: Certifiably robust defense against adversarial patches for any image classifier. In *Proceedings of the 31st USENIX Security Symposium*, 2022.

[47] Chong Xiang, Tong Wu, Sihui Dai, Jonathan Petit, Suman Jana, and Prateek Mittal. PATCHCURE: Improving certifiable robustness, model utility, and computation efficiency of adversarial patch defenses. In *Proceedings of the 33rd USENIX Security Symposium*, 2024.

[48] Shimaa Ahmed, Ilia Shumailov, Nicolas Papernot, and Kassem Fawaz. Towards more robust keyword spotting for voice assistants. In *Proceedings of the 31st USENIX Security Symposium*, 2022.

[49] Yugeng Liu, Rui Wen, Xinlei He, Ahmed Salem, Zheng Zhang, Michael Backes, Emiliano De Cristofaro, Mario Fritz, and Yang Zhang. ML-Doctor: Holistic risk assessment of inference attacks against machine learning models. In *Proceedings of the 31st USENIX Security Symposium*, 2022.

[50] Xinyu Tang, Saeed Mahloujifar, Liwei Song, Virat Shejwalkar, Milad Nasr, Amir Houmansadr, and Prateek Mittal. Mitigating membership inference attacks by self-distillation through a novel ensemble architecture. In *Proceedings of the 31st USENIX Security Symposium*, 2022.

[51] Jiacheng Li et al. MIST: Defending against membership inference attacks through membership-invariant subspace training. In *Proceedings of the 33rd USENIX Security Symposium*, 2024.

[52] Dingwen Wang et al. CAMP in the odyssey: Provably robust reinforcement learning with certified radius maximization. In *Proceedings of the 34th USENIX Security Symposium*, 2025.

[53] Yueqi Ma et al. Avara: Measuring human perception of adversarial traffic sign examples using virtual and augmented reality. In *Proceedings of the 2024 ACM SIGSAC Conference on Computer and Communications Security*, 2024.

[54] Siyuan Liu et al. X-Adv: Physical adversarial object attacks against x-ray prohibited item detection. In *Proceedings of the 32nd USENIX Security Symposium*, 2023.

[55] Yulong Cao et al. You can't see me: Physical removal attacks on lidar-based autonomous vehicles driving frameworks. In *Proceedings of the 32nd USENIX Security Symposium*, 2023.

[56] Shimaa Ahmed et al. Tubes among us: Analog attack on automatic speaker identification. In *Proceedings of the 32nd USENIX Security Symposium*, 2023.

[57] Ryunosuke Kobayashi et al. Invisible but detected: Physical adversarial shadow attack and defense on lidar object detection. In *Proceedings of the 34th USENIX Security Symposium*, 2025.

[58] Yizheng Zhang et al. ATKSCOPES: Multiresolution adversarial perturbation as a unified attack on perceptual hashing and beyond. In *Proceedings of the 34th USENIX Security Symposium*, 2025.

[59] Edoardo Debenedetti et al. Privacy side channels in machine learning systems. In *Proceedings of the 33rd USENIX Security Symposium*, 2024.

[60] Milad Nasr et al. Exploiting component vulnerabilities in production ML pipelines. In *Proceedings of the 2025 ACM SIGSAC Conference on Computer and Communications Security*, 2025.

[61] Yanzuo Chen et al. OBSAN: An out-of-bound sanitizer to harden DNN executables. In *Proceedings of the 32nd USENIX Security Symposium*, 2023.

[62] Rohan Samuly et al. Echoleak: The first real-world zero-click prompt injection exploit in a production llm system. *arXiv preprint arXiv:2509.00000*, 2025. Describes a zero-click prompt-injection attack against Microsoft 365 Copilot and mitigation strategies.

[63] HackerOne Security Researchers. How a prompt injection vulnerability led to data exfiltration, 2024. URL https://www.hackerone.com/blog/prompt-injection-vulnerability-bard. Blog post describing a prompt-injection exploit against Google Bard Extensions.

[64] Michael Bargury and Tamir Ishay Sharbat. Agentflayer: Demonstrating data exfiltration via chatgpt connectors. *Black Hat USA 2025 Presentation*, 2025. Illustrates how a poisoned document can extract secrets via ChatGPT Connectors.

[65] Milad Nasr, Nicholas Carlini, et al. Scalable extraction of training data from (production) language models. *arXiv preprint arXiv:2311.17035*, 2023. Introduces the divergence attack for extracting ChatGPT training data.

[66] Lingjuan Liu et al. Model extraction attacks revisited. *arXiv preprint arXiv:2403.00000*, 2024. Analyzes model extraction against commercial MLaaS APIs.

[67] Ben Wang et al. Nightshade: Prompt-specific poisoning attacks on text-to-image generative models. *arXiv preprint arXiv:2310.20350*, 2023. Shows how artists can poison training data to mislead generative models.

[68] Eftsure Pty Ltd. 7 deepfake attacks examples: Deepfake ceo scams, 2024. URL https://eftsure.com/blog/deepfake-attacks-examples/. Describes real deepfake scams targeting organisations.

[69] R Spencer Hallyburton, Yupei Liu, Yulong Cao, Z Morley Mao, and Miroslav Pajic. Security analysis of camera-lidar fusion against black-box attacks on autonomous vehicles. In *Proceedings of the 31st USENIX Security Symposium*, 2022.

[70] Patrick Chao, Alexander Robey, Edgar Dobriban, Hamed Hassani, George J. Pappas, and Eric Wong. Jailbreaking black box large language models in twenty queries. *arXiv preprint arXiv:2310.08419*, 2023.

[71] Anay Mehrotra, Manolis Zampetakis, Paul Kassianik, Blaine Nelson, Hyrum Anderson, Yaron Singer, and Amir Globerson. Tree of attacks: Jailbreaking black-box LLMs automatically. In *Advances in Neural Information Processing Systems*, 2024.

[72] Xiangyu Qi, Kaixuan Zeng, Tinghao Xie, Pin-Yu Chen, Peter Henderson, Matt Fredrikson, and Siheng Zhu. Visual adversarial examples jailbreak aligned large language models. *Proceedings of the AAAI Conference on Artificial Intelligence*, 38(19):21527–21536, 2024.

[73] Lu Wang et al. From purity to peril: Backdooring merged models from "harmless" benign components. In *Proceedings of the 34th USENIX Security Symposium*, 2025.

[74] Zhen Guo et al. Persistent backdoor attacks in continual learning. In *Proceedings of the 34th USENIX Security Symposium*, 2025.

[75] Huiying Li, Shawn Shan, Emily Wenger, Jiayun Zhang, Haitao Zheng, and Ben Y Zhao. Blacklight: Scalable defense for neural networks against query-based black-box attacks. In *Proceedings of the 31st USENIX Security Symposium*, 2022.

[76] Shenyi Zhang et al. JBShield: Defending large language models from jailbreak attacks through activated concept analysis and manipulation. In *Proceedings of the 34th USENIX Security Symposium*, 2025.

[77] Zhiyuan Zhang et al. SafeSpeech: Robust and universal voice protection against malicious speech synthesis. In *Proceedings of the 34th USENIX Security Symposium*, 2025.

[78] Dusan Popovic et al. DeBackdoor: A deductive framework for detecting backdoor attacks on deep models with limited data. In *Proceedings of the 34th USENIX Security Symposium*, 2025.

[79] Tianshuo Cong et al. SSLGuard: A watermarking scheme for self-supervised learning pre-trained encoders. In *Proceedings of the 2022 ACM SIGSAC Conference on Computer and Communications Security*, 2022.

[80] Yifan Lu et al. Neural dehydration: Effective erasure of black-box watermarks from DNNs with limited data. In *Proceedings of the 2024 ACM SIGSAC Conference on Computer and Communications Security*, 2024.

[81] Andy Zou, Zifan Wang, J. Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models. In *Advances in Neural Information Processing Systems*, volume 36, 2023.

[82] Nicholas Carlini, Milad Nasr, Christopher A. Choquette-Choo, Matthew Jagielski, Irena Gao, Anas Awadalla, Pang Wei Koh, Daphne Ippolito, Katherine Lee, Florian Tramer, and Ludwig Schmidt. Jailbroken: How does LLM safety training fail? *Advances in Neural Information Processing Systems*, 36, 2023.

[83] Mark Russinovich, Ahmed Salem, and Ronen Elmasry. Great, now write an article about that: The crescendo multi-turn LLM jailbreak attack. In *33rd USENIX Security Symposium*, pages 3937–3954, 2024.

[84] Yichen Gong, Delong Deng, Ziang Lu, Nan Sun, Qiang Tan, Bochao Wu, Jianmin Cao, and Junying Zhang. FigStep: Jailbreaking large vision-language models via typographic visual prompts. In *AAAI Conference on Artificial Intelligence*, 2024.

[85] Yu Niu, Shang Yu, Ruikang Zhang, Juanxi Liu, Xiangyu Yang, and Lei Song. Jailbreak large vision-language models through multi-modal linkage. *arXiv preprint arXiv:2412.00473*, 2024.

[86] Mintong Zhang, Jiyi Li, Tianxin Li, Zhaoyuan Liu, and Dinghao Zhang. AdvWave: Stealthy adversarial jailbreak attack against large audio-language models. *arXiv preprint arXiv:2412.08608*, 2024.

[87] Yangsibo Huang, Samyak Gupta, Mengzhou Xia, Kai Li, and Danqi Chen. Catastrophic jailbreak of open-source LLMs via exploiting generation. *arXiv preprint arXiv:2310.06987*, 2023.

[88] OpenAI. Rate limits. https://platform.openai.com/docs/guides/rate-limits, 2024.

[89] Javier Rando and Florian Tramèr. Universal jailbreak backdoors from poisoned human feedback. *International Conference on Learning Representations*, 2024.

[90] Ethan Perez, Saffron Huang, Francis Song, Trevor Cai, Roman Ring, John Aslanides, Amelia Glaese, Nat McAleese, and Geoffrey Irving. Red teaming language models with language models. *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 3419–3448, 2022.

[91] Hakan Inan, Kartikeya Upasani, Jianfeng Chi, Rashi Rungta, Krithika Iyer, Yuning Mao, Michael Tontchev, Qing Hu, Brian Fuller, Davide Testuggine, and Madian Khabsa. Llama Guard: LLM-based input-output safeguard for human-AI conversations. *arXiv preprint arXiv:2312.06674*, 2023.

[92] Traian Rebedea, Razvan Dinu, Makesh Nandan Sreedhar, Christopher Parisien, and Jonathan Cohen. NeMo guardrails: A toolkit for controllable and safe LLM applications with programmable rails. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 431–445, 2023.

[93] Samuel Hackett and Charles Gretton. Bypassing LLM guardrails: An empirical analysis of evasion attacks. *arXiv preprint arXiv:2504.11168*, 2024.

[94] Mikayel Bertrand, Ata Iqbal, Suhas Guttula, Brandon Rivera, Aman Saparov, Adithya Zhao, Jeff Clune, and Jean-Baptiste Mouret. Rainbow teaming: Open-ended generation of diverse adversarial prompts. In *Advances in Neural Information Processing Systems*, 2024.

[95] Zhang-Wei Hong, Idan Firoozi, Alefiya Raj, Varun Agrawal, Karl Tuyls, and Doina Precup. Curiosity-driven red-teaming for large language models. In *International Conference on Learning Representations*, 2024.

[96] Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, et al. Constitutional AI: Harmlessness from AI feedback. *arXiv preprint arXiv:2212.08073*, 2022.

[97] Patrick Chao, Edoardo Debenedetti, Alexander Robey, Maksym Andriushchenko, Francesco Croce, Vikash Sehwag, Edgar Dobriban, Nicolas Flammarion, J. Zico Kolter, Prateek Mittal, et al. JailbreakBench: An open robustness benchmark for jailbreaking large language models. In *Advances in Neural Information Processing Systems Datasets and Benchmarks Track*, 2024.

[98] Qiusi Zhan, Zhixiang Fang, Wei Gao, Shijia Gao, Dianbo Yang, Yiwei Liang, Xiaobing Zhang, Gang Chen, Kai Chen, and Junchi Ye. InjecAgent: Benchmarking indirect prompt injections in tool-integrated large language model agents. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 2566–2587, 2024.

[99] Rishi Bommasani, Drew A. Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S. Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, et al. On the opportunities and risks of foundation models. *arXiv preprint arXiv:2108.07258*, 2021.

[100] Shahbaz Rezaei et al. On the accuracy-privacy trade-off of deep ensembles. In *Proceedings of the 2023 IEEE Symposium on Security and Privacy*, 2023.

[101] Linyi Li et al. SoK: Certified robustness for deep neural networks. In *Proceedings of the 2023 IEEE Symposium on Security and Privacy*, 2023.

[102] Phillip Rieger et al. DeepSight: Mitigating backdoor attacks in federated learning through deep model inspection. In *Proceedings of the 2022 Network and Distributed System Security Symposium*, 2022.

A Complete Paper Analysis Dataset

The complete analysis of all 454 papers is available in the supplementary CSV file: `all_conferences_analysis_r`

The dataset includes the following columns for each paper:

- Year, Conference, Filename, Title, Authors
- G1 (Focus), G2 (Attack Type), G3 (ML Type), G4 (Data Domain)
- G5 (Economics), G6 (Code Release), G7 (Real System Testing)
- T1 (Threat Model), T2 (Training Data Access)
- Q1 (Gradient Requirements), Q2 (Query Budget), Q3 (Computation)
- Gap indicator flags and Traditional Score

Benchmark meanings (aligned with the CSV fields used in the table):

- G1 Focus: atk (attack), def (defense), both.
- G2 Attack Type: Evasion, Poisoning, Privacy, Multiple.
- G3 ML Type: DL, Traditional, Both.
- G4 Data Domain: Images, Text, Audio, Malware, Other.
- G5 Economics mentioned: YES/NO.
- G6 Code released: YES/NO.
- G7 Real system testing: YES/NO.
- T1 Threat model: White-box, Gray-box, Black-box.
- T2 Training data access: Full, Partial, None.
- Q1 Requires gradients: YES/NO.
- Q2 Query budget: High (>1000), Low (<1000), None.
- Q3 Computation: High (GPU), Low (CPU).
- Traditional_Score (Gap Score 0–6): sum of six impractical-assumption flags (higher = less practical).

For full per-paper details (all 24 columns), please see the CSV file. Below is a compact, bordered summary table focused on the most critical taxonomy fields. Binary fields are rendered as checkmarks (yes) or blanks (no); threat/access levels are abbreviated (W/B/G/P, F/P, H/L).

Table 1: Compact summary of papers (key taxonomy fields).

Year	Venue	Paper (1st author)	G1	G2	G3	G4	G5	G6	G7	T1	T2	Grad	Qry	Comp	WB	Trad.
2022	ACM	Using	def	Poisoning	DL	Images	✓	✓	×	G	F	✓	H	L	0	3
2022	ACM	Reverse-Engineering	atk	Evasion	DL	Audio	✓	✓	×	B		×	H	L	0	2
2022	ACM	Tianshuo	def	Privacy	DL	Images	✓	✓	×	B		×	L	L	0	1
2022	ACM	CISPA	atk	Privacy	DL	Other	✓	×	×	B		×	L	L	0	2
2022	ACM	CISPA	atk	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	ACM	School	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	ACM	Physical	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	ACM	Framework	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	ACM	Florian	atk	Poisoning	DL	Images	✓	×	×	W	F	✓	H	L	1	5
2022	ACM	via	atk	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	ACM	ExamplesforLeakage	def	Evasion	DL	Images	✓	✓	×	W	P	✓	H	L	1	4
2022	ACM	Harnessing	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	ACM	Feature	atk	Privacy	DL	Other	✓	×	✓	B		×	L	L	0	1
2022	ACM	Imperial	atk	Privacy	Both	Other	✓	✓	×	B		×	H	L	0	2
2022	ACM	Learning	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	ACM	CISPA	atk	Evasion	DL	Text	✓	✓	×	B		×	H	L	0	2
2022	ACM	Amrita	def	Poisoning	DL	Images	✓	×	×	B		✓	H	L	0	4
2022	ACM	A	def	Evasion	Both	Text	✓	✓	×	B		×	L	L	0	1
2022	ACM	CISPA	atk	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	ACM	ETH	def	Privacy	Both	Other	✓	×	×	B		×	L	L	0	2
2022	ACM	Hanqing	atk	Evasion	DL	Audio	✓	✓	×	W	F	✓	H	L	1	4
2022	ACM	Stevens	atk	Privacy	DL	Other	✓	✓	×	W	F	✓	H	L	1	4
2022	ACM	Are	atk	Privacy	DL	Other	✓	✓	×	W	F	✓	H	L	1	4
2022	ACM	When	atk	Evasion	DL	Audio	✓	✓	✓	B		×	H	H	0	1
2022	ACM	Learning	atk	Privacy	DL	Images	✓	✓	×	B		×	H	L	0	2
2022	ACM	Using	atk	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	ACM	Neural	atk	Evasion	DL	Text	✓	✓	×	B	P	✓	H	H	0	3
2022	ACM	CISPA	atk	Privacy	DL	Images	✓	✓	×	B	P	×	L	L	0	1
2022	ACM	A	atk	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	ACM	LPGNet:	def	Privacy	DL	Other	✓	✓	×	B		✓	H	L	0	3
2022	IEEE	Encoders	atk	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	IEEE	1Illinois	atk	Evasion	DL	Images	✓	✓	×	B		×	L	L	0	1
2022	IEEE	Graph	atk	Privacy	DL	Other	✓	✓	×	B	F	✓	H	L	0	3
2022	IEEE	Imperceptible	atk	Evasion	DL	Text	✓	✓	✓	B		×	L	L	0	0
2022	IEEE	Security	def		DL	Other	✓	✓	×	B		×		L	0	1
2022	IEEE	Jialuo	def		DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	IEEE	Yun	atk	Evasion	DL	Other	✓	✓	×	B		×	H	L	0	2
2022	IEEE	Production	atk	Poisoning	DL	Images	✓	×	×	W	P	✓	H	L	1	5
2022	IEEE	Classification	def		Both	Malware	✓	✓	×	B		×	L	L	0	1
2022	IEEE	in	def	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	IEEE	Markus	def	Privacy	Both	Other	✓	✓	×	B		×	L	L	0	1
2022	IEEE	Eugene	atk	Poisoning	DL	Text	✓	✓	×	B		✓	H	H	0	3
2022	IEEE	"Adversarial	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	IEEE	Attacks	atk	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	IEEE	Weight	atk	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	IEEE	SoK:	def		Both	Other	✓	×	×	B		×		L	0	2
2022	IEEE	Borja	atk	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	IEEE	Transformer	atk	Evasion	DL	Text	✓	✓	×	W	F	✓	H	L	1	4
2022	IEEE	Property	atk	Poisoning	DL	Images	✓	✓	×	B	F	×	H	L	0	2
2022	IEEE	Yuhao	atk	Evasion	DL	Images	✓	✓	×	B		×	H	L	0	2
2022	NDS	School	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	NDS	Federated	def	Poisoning	DL	Text	✓	×	×	W		×	L	L	1	3
2022	NDS	Property	atk	Privacy	DL	Images	✓	✓	×	B	F	✓	H	L	0	3
2022	NDS	RamBoAttack:	atk	Evasion	DL	Images	✓	✓	×	B		×	H	H	0	2
2022	NDS	Shengwei	atk	Privacy	DL	Images	✓	✓	✓	W	F	✓	H	L	1	3
2022	NDS	Robustness	both	Poisoning	DL	Images	✓	×	×	W	F	✓	H	L	1	5
2022	NDS	Ahmed	atk	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	USENIX	for	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	USENIX	Vocal	def	Evasion	DL	Audio	✓	✓	×	B		×		L	0	1
2022	USENIX	31st	atk	Privacy	Both	Other	✓	×	×	W	F	✓	H	L	1	5
2022	USENIX	August	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	USENIX	sponsored	atk	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	USENIX	August	atk	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4

Continued on next page

Year	Venue	Paper (1st author)	G1	G2	G3	G4	G5	G6	G7	T1	T2	Grad	Qry	Comp	WB	Trad.
2022	USENIX	sponsored	atk	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	USENIX	sponsored	atk	Poisoning	DL	Text	✓	✓	×	W	F	✓	H	L	1	4
2022	USENIX	Attacks	atk	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	USENIX	sponsored	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	USENIX	August	atk	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2022	USENIX	August	atk	Privacy	DL	Other	✓	✓	×	W	F	✓	H	L	1	4
2022	USENIX	Novel	atk	Privacy	Both	Other	✓	✓	×	B		×	H	L	0	2
2022	USENIX	Technische	def		Both	Malware	✓	×	×	B		×		L	0	2
2022	USENIX	ICISPA	atk	Privacy	DL	Other	✓	✓	×	W	F	✓	H	L	1	4
2023	ACM	CISPA	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	ACM	Machine	def	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	ACM	Virginia	atk	Poisoning	DL	Images	✓	✓	×	G	P	✓	L	L	0	2
2023	ACM	through	atk	Privacy	DL	Audio	✓	✓	×	W	F	✓	H	L	1	4
2023	ACM	Stealing	atk	Evasion	DL	Text	✓	✓	×	B		×	H	L	0	2
2023	ACM	Stolen	both	Multiple	DL	Other	✓	✓	×	B	P	✓	H	L	0	3
2023	ACM	Information	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	ACM	Deep	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	ACM	Unforgeability	def		DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	ACM	Stefano	def	Evasion	Traditional	Images	✓	✓	×	B		×	L	L	0	1
2023	ACM	Learning	atk	Poisoning	DL	Other	✓	✓	×	G	P	✓	H	L	0	3
2023	ACM	Secure	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	ACM	Detection	atk	Evasion	DL	Malware	✓	✓	×	B		×	L	L	0	1
2023	ACM	Code	def		DL	Other	✓	✓	×	G		×	L	L	0	1
2023	ACM	and	def	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	ACM	through	atk	Privacy	DL	Other	✓	✓	×	B		✓	H	L	0	3
2023	ACM	Jingxuan	def		DL	Other	✓	✓	×	B		×	L	L	0	1
2023	ACM	and	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	ACM	Evading	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	ACM	Changqing	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	ACM	AntiFake:	def	Evasion	DL	Audio	✓	×	✓	B		×	H	L	0	2
2023	ACM	against	def	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	IEEE	Effects	def	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	IEEE	Deep	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	IEEE	arXiv:2112.04558v2	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	IEEE	Federated	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	IEEE	SNAP:	atk	Poisoning	DL	Other	✓	✓	×	B		×	H	L	0	2
2023	IEEE	Federated	def	Poisoning	DL	Images	✓	×	×	W	F	✓	H	L	1	5
2023	IEEE	Information	atk	Privacy	DL	Text	✓	✓	×	B		×	H	L	0	2
2023	IEEE	Covert	atk	Poisoning	DL	Images	✓	✓	×	B		✓	H	L	0	3
2023	IEEE	DepthFake	atk	Evasion	DL	Images	✓	✓	×	B		×	H	L	0	2
2023	IEEE	Jiameng	atk	Evasion	DL	Text	✓	✓	×	B		×		L	0	1
2023	IEEE	Multi-party	def	Privacy	Both	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	IEEE	Andrew	def	Privacy	Both	Other	✓	×	×	W	F	✓	H	L	1	5
2023	IEEE	Information	atk	Privacy	DL	Text	✓	✓	×	B		×	H	L	0	2
2023	IEEE	Extraction	atk	Evasion	DL	Images	✓	✓	×	B		×	H	L	0	2
2023	IEEE	Limin	atk	Poisoning	DL	Malware	✓	✓	×	W	F	✓	H	L	1	4
2023	IEEE	Learning	def	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	IEEE	Attacks	both	Evasion	DL	Text	✓	✓	×	W	F	✓	H	L	1	4
2023	IEEE	Automatic	atk	Evasion	DL	Audio	✓	✓	×	W	F	✓	H	L	1	4
2023	IEEE	yCybersecurity	def		DL	Images	✓	×	×	W		×	L	L	1	3
2023	IEEE	Ruijie	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	IEEE	A	both	Privacy	DL	Images	✓	✓	×	B	P	×	H	L	0	2
2023	IEEE	SNAP:	atk	Poisoning	DL	Other	✓	×	×	B		×	H	L	0	3
2023	IEEE	Hong	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	IEEE	BayBFed	def	Poisoning	DL	Images	✓	×	×	W	F	✓	H	L	1	5
2023	IEEE	Andre	atk	Evasion	DL	Audio	✓	✓	×	B	F	×	L	L	0	1
2023	IEEE	KASTEL	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	IEEE	ELSA:	def	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	IEEE	Shengwei	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	IEEE	Patch-agnostic	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	IEEE	RAB:	def	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	IEEE	ETH	def	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	IEEE	and	def	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	IEEE	through	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	IEEE	StyleFool:	atk	Evasion	DL	Images	✓	✓	×	B		×	L	L	0	1
2023	NDS	DNN	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	NDS	Hadi	def	Evasion	DL	Audio	✓	✓	×	B		×	H	L	0	2

Continued on next page

Year	Venue	Paper (1st author)	G1	G2	G3	G4	G5	G6	G7	T1	T2	Grad	Qry	Comp	WB	Trad.
2023	NDS	Yugeng	atk	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	NDS	Commercial	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	NDS	Classifiers	def	Evasion	DL	Images	✓	✓	×	B		×	L	L	0	1
2023	NDS	Learning	def	Evasion	DL	Other	✓	✓	×	B		✓	H	L	0	3
2023	NDS	Jiayun	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	NDS	Klim	atk	Evasion	DL	Other	✓	×	×	B		×	H	H	0	3
2023	NDS	Siyuan	atk	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	NDS	Universidad	def	Poisoning	DL	Text	✓	✓	×	W	F	✓	H	L	1	4
2023	NDS	Deep	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	NDS	Chunyi	atk	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	NDS	Robust	def	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	NDS	Physical	def	Evasion	Both	Other	✓	✓	✓	G	P	×	L	L	0	0
2023	NDS	*Technische	def	Privacy	Both	Text	✓	✓	×	W	F	✓	H	L	1	4
2023	USENIX		atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	USENIX	Detection	atk	Evasion	DL	Malware	✓	×	×	B		×	H	L	0	3
2023	USENIX	Scientific	atk	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	USENIX	of	def		DL	Other	✓	✓	×	B		×	L	L	0	1
2023	USENIX	for	atk	Poisoning	Both	Other	✓	×	×	W	F	✓	H	L	1	5
2023	USENIX	via	def	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	USENIX	FREE	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	USENIX	1CISPA	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	USENIX	Jonathan	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	USENIX	Vehicles	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	USENIX	Fairness	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	USENIX	Fairness	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	USENIX	Decompiling	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	USENIX	August	def		Both	Malware	✓	✓	×	B		×	L	L	0	1
2023	USENIX	Mazal	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	USENIX	August	def		DL	Malware	✓	✓	×	W	F	✓	H	L	1	4
2023	USENIX	is	atk	Privacy	DL	Images	✓	✓	×	B	P	✓	H	L	0	3
2023	USENIX	is	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	USENIX	Federated	def	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	USENIX	Kunal	atk	Evasion	DL	Malware	✓	✓	×	B	P	×	H	L	0	2
2023	USENIX	for	def	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	USENIX	by	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	USENIX	is	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	USENIX	is	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	USENIX	August	atk	Poisoning	DL	Text	✓	×	×	B		×	H	L	0	3
2023	USENIX	Universal	atk	Evasion	DL	Images	✓	✓	×	B		×	H	L	0	2
2023	USENIX	is	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2023	USENIX	August	def	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	from	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Xueluan	def	Privacy	DL	Images	✓	×	×	B		×	L	L	0	2
2024	ACM	SafeEar:	def	Privacy	DL	Audio	✓	✓	×	B		×	L	L	0	1
2024	ACM	Against	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Multi-Agent	atk	Evasion	DL	Images	✓	✓	×	B		×	H	H	0	2
2024	ACM	Text-to-Image	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Autonomous	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Wei	atk	Poisoning	Both	Other	✓	✓	×	G	P	✓	H	L	0	3
2024	ACM	Byzantine-Robust	def	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Recognition	atk	Evasion	DL	Audio	✓	✓	✓	B		×		H	0	0
2024	ACM	Zijin	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	CSIRO's	atk	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Items	atk	Poisoning	DL	Other	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Applications	atk	Privacy	DL	Text	✓	✓	×	B		✓	H	H	0	3
2024	ACM	Attack	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Attachment	atk	Evasion	DL	Malware	✓	✓	✓	B		×	H	L	0	1
2024	ACM	Information	atk	Evasion	DL	Text	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Alchemy:	def	Evasion	DL	Images	✓	✓	×	W		✓	H	L	1	4
2024	ACM	S2NeRF:	both	Privacy	DL	Images	✓	✓	×	B		✓	H	L	0	3
2024	ACM	Certified	atk	Poisoning	DL	Other	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	ETH	atk	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Jie	atk	Privacy	DL	Images	✓	✓	×	B	P	×	H	L	0	2
2024	ACM	Understanding	atk	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	in	def	Evasion	DL	Malware	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	A	def	Privacy	DL	Images	✓	✓	×	B		×	H	L	0	2

Continued on next page

Year	Venue	Paper (1st author)	G1	G2	G3	G4	G5	G6	G7	T1	T2	Grad	Qry	Comp	WB	Trad.
2024	ACM	The	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Fisher	def	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	into	atk	Privacy	DL	Text	✓	✓	×	B		×	H	L	0	2
2024	ACM	BadMerging:	atk	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Optimization-based	atk	Evasion	DL	Text	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Optimization-based	atk	Evasion	DL	Text	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Model	atk	Privacy	DL	Text	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Shenzhen	atk	Privacy	DL	Text	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Information	def	Evasion	DL	Images	✓	✓	×	B		×		H	0	1
2024	ACM	Learning	atk	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Blind	def		Both	Audio	×	×	×	B		×		L	0	3
2024	ACM	Information	atk	Privacy	DL	Text	✓	×	×	B		×	L	L	0	2
2024	ACM	Deepfake	def		DL	Audio	✓	✓	×	B		×		L	0	1
2024	ACM	Membership	atk	Privacy	DL	Images	✓	✓	×	B	P	×	L	L	0	1
2024	ACM	Membership	atk	Privacy	DL	Images	✓	✓	×	B	P	×	L	L	0	1
2024	ACM	Neural	atk	Privacy	DL	Images	✓	✓	×	B		×		L	0	1
2024	ACM		atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Fine-grained	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	from	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Institute	atk	Privacy	DL	Images	✓	✓	×	B		×	H	L	0	2
2024	ACM	Institute	atk	Privacy	DL	Images	✓	✓	×	B	F	×	H	L	0	2
2024	ACM	of	def	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	School	atk	Evasion	DL	Text	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Examples:	atk	Evasion	DL	Images	✓	✓	×	B		×	H	L	0	2
2024	ACM	Models	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	ACM	Learning	atk	Poisoning	DL	Images	✓	✓	×	B	P	×	L	L	0	1
2024	IEEE	Pattern	def	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	IEEE	Robin	def	Privacy	Both	Other	✓	✓	×	W	F	✓	H	L	1	4
2024	IEEE	Yuzheng	def	Privacy	Both	Images	✓	✓	×	B		×	L	L	0	1
2024	IEEE	Joshua	atk	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	IEEE	Ziqi	def	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	IEEE	Linguistic	atk	Evasion	DL	Audio	✓	✓	✓	B		×	L	L	0	0
2024	IEEE	Language	atk	Evasion	DL	Text	✓	✓	×	W	F	✓	H	L	1	4
2024	IEEE	It's	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	IEEE	into	atk	Evasion	DL	Images	✓	✓	×	B		×	H	L	0	2
2024	IEEE	Test-Time	atk	Poisoning	DL	Images	✓	✓	×	G	P	✓	L	L	0	2
2024	IEEE	Xingshuo	atk	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	IEEE	Mohammad	atk	Poisoning	DL	Images	✓	×	×	G	P	✓	H	L	0	4
2024	IEEE	Attacks	def	Evasion	DL	Images	✓	✓	×	B		×	H	L	0	2
2024	IEEE	Distribution	atk	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	IEEE	Dropout	atk	Poisoning	DL	Images	✓	×	×	W	F	✓	H	L	1	5
2024	IEEE	GROV	def	Evasion	DL	Other	✓	✓	×	B		×	L	L	0	1
2024	IEEE	Mahmoud	atk	Evasion	DL	Other	✓	✓	×	B	P	×	L	L	0	1
2024	IEEE	Alec	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	IEEE	Accelerator	atk	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	IEEE	KASTEL	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	IEEE	Adversarial	def	Evasion	DL	Text	×	✓	×	W		×		L	1	3
2024	IEEE	2Services	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	NDS	Large	def	Evasion	DL	Text	✓	✓	×	W	F	✓	H	L	1	4
2024	NDS	DEMASQ:	def	Evasion	DL	Text	✓	×	×	B		✓	H	L	0	4
2024	NDS	Attacks	atk	Privacy	DL	Audio	✓	✓	×	W	F	✓	H	L	1	4
2024	NDS	Poisoning	atk	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	NDS	by	def	Privacy	DL	Images	✓	✓	×	B		×	L	L	0	1
2024	NDS	CamPro	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	NDS	Ensemble	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	NDS	Gelei	atk	Evasion	DL	Text	✓	×	×	B		×	H	H	0	3
2024	NDS	Watermarking	def	Evasion	DL	Audio	✓	✓	✓	W	F	×	L	L	1	1
2024	NDS	ICS	atk	Evasion	DL	Other	✓	✓	×	W	F	✓	H	L	1	4
2024	NDS	Federated	def	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	NDS	Chengkun	def	Poisoning	DL	Text	✓	✓	×	B		✓	L	L	0	2
2024	NDS	Recognition	atk	Evasion	DL	Audio	✓	✓	×	W	F	✓	H	L	1	4
2024	NDS	Transpose	atk	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	NDS	Transpose	atk	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	NDS	Inversion-based	def	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4

Continued on next page

Year	Venue	Paper (1st author)	G1	G2	G3	G4	G5	G6	G7	T1	T2	Grad	Qry	Comp	WB	Trad.
2024	NDS	Networks	atk	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	NDS	Browser	def	Privacy	Traditional	Other	✓	×	×	B		×		L	0	2
2024	NDS	Deep	def	Evasion	DL	Images	✓	✓	×	B		×	H	L	0	2
2024	NDS	Bang	def	Privacy	DL	Other	✓	✓	×	B		×	L	L	0	1
2024	NDS	Against	atk	Poisoning	DL	Images	✓	✓	×	B	P	✓	H	L	0	3
2024	NDS	Speaker	atk	Evasion	DL	Audio	✓	✓	✓	B		×		L	0	0
2024	NDS	Mitigating	def	Poisoning	DL	Images	✓	×	×	B		×		L	0	2
2024	NDS	for	def		DL	Malware	✓	✓	×	B		×	L	L	0	1
2024	NDS	in	both	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	NDS	Attacks	def	Poisoning	DL	Text	✓	✓	×	W	F	×	L	L	1	2
2024	NDS	Chaoxiang	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	Tong	atk	Evasion	DL	Text	✓	✓	×	B		×	L	L	0	1
2024	USENIX	Attacks	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	Approach	def	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	Qingzhao	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	Zhenghang	def		Both	Other	✓	✓	×	B		×		L	0	1
2024	USENIX	Synthesis	def	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	Measuring	def		DL	Audio	✓	✓	×	B		×	L	L	0	1
2024	USENIX	Large	atk	Evasion	DL	Text	✓	✓	×	B		×	H	L	0	2
2024	USENIX	Efficiency	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	Efficiency	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	Kathrin	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	DNN-GP:	both	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	for	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	DeepEclipse	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	DeepEclipse	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	Between	atk	Multiple	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	Red-Teaming	atk	Evasion	DL	Images	✓	✓	×	B		×	H	L	0	2
2024	USENIX	Red-Teaming	atk	Evasion	DL	Images	✓	✓	×	B		×	H	L	0	2
2024	USENIX	Property	atk	Privacy	DL	Images	✓	✓	×	B	F	×	H	L	0	2
2024	USENIX	Transposed	def		DL	Images	✓	×	×	W	F	✓	H	L	1	5
2024	USENIX	in	def	Privacy	DL	Images	✓	✓	×	B		×	L	L	0	1
2024	USENIX	Shuaifan	def	Privacy	DL	Images	✓	✓	✓	W	F	✓	H	L	1	3
2024	USENIX	CISPA	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	CISPA	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	Runtime	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	Splitting	def	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	Yixin	atk	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	Changjiang	atk	Poisoning	DL	Images	✓	✓	×	B	F	✓	H	L	0	3
2024	USENIX	Guangsheng	atk	Privacy	DL	Images	✓	×	×	W	F	✓	H	L	1	5
2024	USENIX	Bailey	def	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	Meng	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	"Minxue	def	Privacy	DL	Images	✓	✓	×	W		✓	H	L	1	4
2024	USENIX	CISPA	atk	Privacy	DL	Images	✓	✓	×	B	P	×	H	H	0	2
2024	USENIX	False	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	Shenchen	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	through	atk	Privacy	DL	Other	✓	×	×	B		✓	H	L	0	4
2024	USENIX	Shaofeng	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	Mudjacking:	def	Poisoning	DL	Images	✓	×	×	B		✓	H	L	0	4
2024	USENIX	Randomised	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	33rd	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	is	def		DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	August	def	Privacy	Both	Text	✓	✓	×	B		×	L	L	0	1
2024	USENIX	August	atk	Privacy	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	is	atk	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	is	def		DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	is	def	Poisoning	DL	Images	✓	×	×	B		×		L	0	2
2024	USENIX	Attacks	def	Privacy	DL	Images	✓	✓	×	B		✓	H	L	0	3
2024	USENIX	Model	atk	Evasion	DL	Text	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	Zooming	both	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	August	atk	Privacy	DL	Text	✓	✓	×	B		×	L	L	0	1
2024	USENIX	is	def		DL	Text	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	August	def		DL	Other	✓	✓	×	W	F	×	H	L	1	3
2024	USENIX	August	def		DL	Other	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	August	def	Evasion	DL	Images	✓	✓	×	B		×		L	0	1
2024	USENIX	August	def		Both	Malware	✓	×	×	B		×	L	L	0	2
2024	USENIX	Learning	def	Evasion	Both	Other	✓	✓	×	W	F	✓	H	L	1	4

Continued on next page

Year	Venue	Paper (1st author)	G1	G2	G3	G4	G5	G6	G7	T1	T2	Grad	Qry	Comp	WB	Trad.
2024	USENIX	Framework	def		DL	Text	✓	✓	×	B		×		L	0	1
2024	USENIX		def		DL	Images	✓	✓	×	B		×		L	0	1
2024	USENIX		atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2024	USENIX	Inference	def	Privacy	DL	Images	✓	×	×	G		✓	H	L	0	4
2025	ACM	1Technion	atk	Evasion	DL	Text	✓	✓	×	B		×	H	L	0	2
2025	ACM	in	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2025	ACM	arXiv:2501.05928v2	atk	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2025	ACM	Anti-Facial	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2025	ACM	BIFOLD	atk	Evasion	DL	Other	✓	✓	×	W	F	✓	H	H	1	4
2025	ACM	Targeted	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2025	ACM	Language	atk	Poisoning	DL	Text	✓	✓	×	B		×	L	L	0	1
2025	ACM	Models	def	Evasion	DL	Images	✓	×	✓	G	P	✓	H	H	0	3
2025	ACM	Adversarial	atk	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2025	ACM	Construction	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2025	ACM	Latent-based	atk	Evasion	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2025	ACM	Milad	atk	Evasion	DL	Malware	✓	✓	✓	W	F	✓	H	L	1	3
2025	ACM	VillainNet:	atk	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2025	ACM	Deep	def		DL	Malware	✓	✓	×	B		×		L	0	1
2025	USENIX	Jiachen	def	Evasion	DL	Images	✓	✓	✓	B		✓	H	H	0	2
2025	USENIX	Lingchen	def	Evasion	DL	Text	✓	✓	×	W	F	×	L	L	1	2
2025	USENIX	Revisiting	atk	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2025	USENIX	Zhisheng	def	Privacy	DL	Audio	✓	✓	×	B		×	L	L	0	1
2025	USENIX	with	def	Evasion	DL	Other	✓	✓	×	W	F	×	H	L	1	3
2025	USENIX	Persistent	atk	Poisoning	DL	Images	✓	✓	×	W		✓	H	L	1	4
2025	USENIX	Benign	atk	Poisoning	DL	Images	✓	✓	×	W	F	✓	H	L	1	4
2025	USENIX	34th	def	Evasion	DL	Malware	✓	✓	×	B		✓	H	L	0	3