



SDS

Request for Analysis

A26-12570

Lab Use Only
Work Order #:

Date Received:

Submitted to: Ancaster, Canada

Email completed form to: sample@actlabs.com

SUBMISSION DETAILS

Company Name: GIP Construction Engineering

Submitted By: Jessica Yao

Phone: 647-227-6112

Email: jyao@gipi.com

Address: 10 Perdue Court, Units 2-3, Caledon, ON L7C 3M6

Project Name: 17507.001

PO #: 1351043

Quote/Proforma #:

of Packages: 1 # of Samples: 8

INVOICING DETAILS

METHOD OF PAYMENT

- ☐ Payment is included (make cheque/bank draft payable to Activation Laboratories Ltd.)
☒ Credit has been established with Actlabs (refer to Credit Application Form)
☐ Charge to Credit Card on file with Actlabs
☐ Charge to NEW Credit Card (details are provided below)

☐ VISA Number: _____
☐ MasterCard Name: _____
☐ AMEX Expiry Date: _____ CVV: _____
Signature: _____

☐ Retain credit card information to charge this work order and all future work orders.

REPORTING AND INVOICING DETAILS

Name	Email	Confirmation Receipt	Report	Invoice
Jessica Yao	<u>jyao@gipi.com</u>	☒	☒	☒
Sohail Hassanzada	<u>shassanzada@gipi.com</u>	☒	☒	☒
Nirmala Gracias	<u>AP-GCE@gipi.com</u>	☐	☐	☒

SAMPLE AND ANALYSIS DETAILS

SAMPLE TYPE

- ☐ DC - Core ☐ S - Soil
☒ R - Rock ☐ LS - Lake Sediment
☐ P - Pulp ☐ Others

GRADE TYPE

- ☐ Exploration ☐ Control
☐ Ore ☐ Umpire
☐ Concentrate ☒ Others

RUSH

- ☐ Request RUSH - Date Required By _____
Subject to surcharge and availability
Contact lab to confirm requirements

SAMPLE PREPARATION

- ☐ Contact me if sample preparation is required
☒ I authorize any required sample preparation charges

SPECIAL INSTRUCTION

Cement

☐ Hazardous Materials Included

# of Samples	Sample Numbers (list or range)	Sample Type (DC, R, etc.)	Preparation Code	Analysis code	Overlimit Analysis Code
8	DNNP26-0125, DNNP26-0126, DNNP26-0136, DNNP26-0137		Cement + Slag	4F - Sulphur Trioxide (SO3)	
	DNNP26-0170, DNNP26-0171, DNNP26-0173, DNNP26-0175		Cement + Slag	4F - Sulphur Trioxide (SO3)	
4	DNNP26-0170, DNNP26-0173, DNNP26-0125, DNNP26-0136		Cement	4C - Magnesium Oxide (MgO)	
4	DNNP26-0171, DNNP26-0175, DNNP26-0126, DNNP26-0137		Slag	4F - Sulphide Sulphur(S2)	

SAMPLE DISPOSITION

Sample Return	Pulps	Rejects	Sieve
IMMEDIATELY Return	☐	☐	☐
AFTER FREE STORAGE Return	☐	☐	☐
Dispose	☒	☒	☒
Paid Storage	☐	☐	☐

Return Samples To:

Address: _____
Attention: _____
Carrier: _____ ☐ At Cost +15%
Account#: _____

Free Storage Period
90 days for Pulps
60 days for Rejects
90 days for Sieve

Failure to indicate
sample disposition will
result in sample disposal

Authorized By:

Print Name: Sohail Hassanzada

Signature: _____

Date: 7/14/26

SAFETY DATA SHEET

Revision date: August 1, 2023

Section 1: Identification**1.1 Product identifier:**

St Marys Masonry Cement
St Marys Mortar Cement

Alternate names:

- Masonry Cement
- CSA and ASTM Types N, S and M

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Identified uses:

Industrial uses in manufacture of concrete for building materials and pavement.

Uses advised against:

Keep out of reach of children.

1.3 Details of the supplier of the Safety Data Sheet:

St. Marys Cement
55 Industrial Street
Toronto, ON
M4G 3W9

Information Telephone Numbers

In Canada: 1-800-268-6148

In USA: 1-800-462-9157 ext. 537

1.4 Emergency telephone number:

In Canada: 1-613-996-6666 CANUTEC (Call Collect or *666 Cellular)

In USA: 1-800-462-9157

Section 2: Hazards Identification**2.1 Classification of the substance or mixture:**

Skin Irritation Cat. 2; H315

Eye Damage Cat. 1; H318

Specific Target Organ Toxicity, Single Exposure, Cat. 3; H335

Carcinogenicity Cat. 1; H350 (inhalation)

Specific Target Organ Toxicity, Repeated Exposure, Cat. 1; H372 (inhalation)

2.2 Label elements:

Danger.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H335: May cause respiratory irritation.

H350: May cause cancer by inhalation.

H372: Causes damage to lungs through prolonged or repeated exposure by inhalation.

Prevention

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P260: Do not breathe dusts.

P264: Wash hands and exposed skin thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/ protective clothing and eye protection/face protection.

Response

P302+ P352: IF ON SKIN: Wash with plenty of water.

P321: Specific treatment: Caustic burns must be treated promptly by a doctor.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

SAFETY DATA SHEET

Revision date: August 1, 2023

Section 2: Hazards Identification

2.2 Label elements: (continued)

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310: Immediately call a POISON CENTER or doctor.
 P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P313: If exposed or concerned: Get medical advice/attention.
 P314: Get medical advice/attention if you feel unwell.

Storage

P403+P233: Store in well-ventilated place. Keep container tightly closed.
 P405: Store locked up.

Disposal

P501: Recycle and or dispose of contents/containers in accordance with local/regional/national/ international regulations

2.3 Other hazards

Dusts from this product, when combined with water or sweat, produce a corrosive alkaline solution. The potential exists for static build-up and static discharge when moving cement powders through a plastic, nonconductive, or non-grounded pneumatic conveyance system. Static discharge may result in damage to equipment and injury to workers.

Section 3: Composition/Information on Ingredients

Chemical Name	CAS No.	Wt. %	Classification according to GHS
Portland Cement	65997-15-1	40 - 70	Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1, H317. STOT SE 3, H335
Calcium hydroxide	1305-62-0	0.1 - 3	Skin Irrit. 2; H315 Eye Dam. 1; H318
Crystalline silica	14808-60-7	0.5 - 3	Carc. 1; H350 STOT RE1; H372
Calcium oxide	1305-78-8	0 - 3	Skin Irrit. 2; H315 Eye Dam. 1; H318
Chromate compounds	Not available	<0.1	Not available
Nickel compounds	Not available	<0.1	Not available

Section 4: First Aid Measures

4.1 Description of first aid measures:

Precautions: First aid providers should avoid direct contact with this chemical. Wear chemical protective gloves, if necessary. Take precautions to ensure your own safety before attempting rescue, (e.g. wear appropriate protective equipment).

Inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek medical help if coughing or other symptoms persist. Inhalation of large amounts of Cement requires immediate medical attention. Call a poison center or doctor. If the individual is not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.