



Omc Classic User Manual

Project BMW AUTOSAR 4 Core Rel. 3

Author BMW AG
Release Date 2017-12-14

Version 5.2.0

Status Release

Hotline +49 89 382 - 32233

contact bac@bmw.de

https://asc.bmw.com/jira/browse/BSUP (extern) https://asc.bmwgroup.net/jira/browse/BSUP (intern)

Revision History

Version	Date	Description
5.2.0	2017-12-14	Version Update
5.1.1	2017-10-12	Version Update
5.1.0	2017-08-10	Version Update
5.0.0	2017-06-29	Initial version for SP2021

Company Bayerische Motoren Werke

Motoren Werke Aktiengesellschaft

Postal address BMW AG 80788 München

Office address Forschungs- und Innovationszentrum (FIZ) Hufelandstr. 1

Hufelandstr. 1 80937 München

Telephone Switchboard +49 89 382-0

Internet www.bmwgroup.com

BMW GROUP



Table of Contents

1	Overv 1.1	iew Purpose	. 3
2	Relate	ed documentation	4
3	API		5
	3.1	Datatypes	5
	3.1.1	Omc_OperatingModeType	5
	3.1.2	Omc_ExtendedOperatingModeType	5
	3.2	Interfaces	6
	3.2.1	Provided	6
	3.2.1.	1 OmcOperatingMode	6
	3.2.1.	2 OmcExtendedOperatingMode	6





1 Overview

This User Manual describes the basis functionality, API and the configuration and integration of the BMW System Function Omc.

Purpose

The main objective of the Omc functionality is to maintain the current Operating Mode of an ECU.

This means:

- Allowing the change of the current Operating Mode via diagnostic request
- Saving the current Operating Mode to Non Volatile RAM (NVRAM)
- Enabling/disabling Dem (more concrete: Setting/Unsetting a enable condition)
- Providing the current Operating Mode to other software components.

The Omc module distinguishes the following vehicle operating modes:

- NORMAL
- ASSEMBLY
- TRANSPORT
- FLASH

Note that in different documents these modes are sometimes called "energy modes" sometimes called "operating modes". Although both terms are equivalent, we strictly use the term operating mode.

BMW GROUP



2 Related documentation

References

BMW GROUP



3 API

Datatypes

${\bf Omc_OperatingModeType}$

This type is used to represent the Operating Mode.

Type name	Omc_OperatingModeType				
Туре	uint8	uint8			
Values	0x00	OMC_MODE_NORMAL	Normal Mode		
	0x01	OMC_MODE_ASSEMBLY	Assembly Mode		
	0x02	OMC_MODE_TRANSPORT	Transport Mode		
	0x03	OMC_MODE_FLASH	Flash Mode		
Description	Represents the operation mode.				

$Omc_ExtendedOperatingModeType$

This type is used to represent the Extended Operating Mode.

Type name	Omc_ExtendedOperatingModeType			
Туре	uint8			
Values	0x00	OMC_MODE_EXTENSION_NORMAL	Normal Extended Mode	
	0x01	OMC_MODE_EXTENSION_1	Extended Mode 1	
	0x02	OMC_MODE_EXTENSION_2	Extended Mode 2	
	0x03	OMC_MODE_EXTENSION_3	Extended Mode 3	
	0x04	OMC_MODE_EXTENSION_4	Extended Mode 4	
	0x05	OMC_MODE_EXTENSION_5	Extended Mode 5	
	0x06	OMC_MODE_EXTENSION_6	Extended Mode 6	
	0x07	OMC_MODE_EXTENSION_7	Extended Mode 7	
	0x08	OMC_MODE_EXTENSION_8	Extended Mode 8	
	0x09	OMC_MODE_EXTENSION_9	Extended Mode 9	
	0x0A	OMC_MODE_EXTENSION_10	Extended Mode 10	
	0x0B	OMC_MODE_EXTENSION_11	Extended Mode 11	
	0x0C	OMC_MODE_EXTENSION_12	Extended Mode 12	
	0x0D	OMC_MODE_EXTENSION_13	Extended Mode 13	
	0x0E	OMC_MODE_EXTENSION_14	Extended Mode 14	
	0x0F	OMC_MODE_EXTENSION_15	Extended Mode 15	
	0xFF	OMC_MODE_EXTENSION_INVALID	Invalid Extended Mode	
Description	Represents the extended operation mode.			





Interfaces

Provided

Omc provides two Mode interfaces to the user to be able to detect the current Operating Mode and Extended Operating Mode. The interface Mode interface, so the user can also trigger able runnable on-entry, on-change or on-exit of a mode.

OmcOperatingMode

OmcExtendedOperatingMode

```
ModeDeclarationGroup OmcExtendedOperatingMode {
      OMC_MODE_EXTENSION_1,
      OMC_MODE_EXTENSION_10,
      OMC_MODE_EXTENSION_11,
      OMC_MODE_EXTENSION_12,
      OMC_MODE_EXTENSION_13,
      OMC_MODE_EXTENSION_14,
      OMC_MODE_EXTENSION_2,
      OMC_MODE_EXTENSION_3,
      OMC_MODE_EXTENSION_4,
      OMC_MODE_EXTENSION_5,
      OMC_MODE_EXTENSION_6,
      OMC_MODE_EXTENSION_7,
      OMC_MODE_EXTENSION_8,
      OMC_MODE_EXTENSION_9,
      OMC_MODE_EXTENSION_INVALID,
      OMC_MODE_EXTENSION_NORMAL,
      OMC_MODE_EXTENSION_SAVE_ENERGY
   initialMode = OMC_MODE_EXTENSION_NORMAL
```