



Forecasting

Jeffrey Leek, Assistant Professor of Biostatistics
Johns Hopkins Bloomberg School of Public Health

Time series data

Finance

Google Inc (NASDAQ:GOOG)

Add to portfolio

More results

Company

Summary

News

Option chain

Related companies

Historical prices

Financials

Markets

News

Portfolios

Stock screener

Google Domestic Trends

Recent Quotes (Turn on)

You have no recent quotes

1,120.71
+11.25 (1.01%)

Dec 31 - Close

NASDAQ real-time data - Disclaimer
Currency in USD

Range 1,106.26 - 1,121.00
52 week 695.52 - 1,121.00
Open 1,112.24
Vol / Avg. 1.36M/1.54M
Mkt cap 374.42B
P/E 32.19
Div/yield -
EPS 34.81
Shares 334.09M
Beta 0.87
Inst. own 72%

g+ 9.4k

Dow Jones	16,576.66	0.44%	
Nasdaq	4,176.59	0.00%	
Technology		0.70%	
GOOG	1,120.71	1.01%	

Compare: ☐ Dow Jones ☐ Nasdaq ☐ BIDU ☐ YNDX ☐ MSFT ☐ YHOO ☐ BCOR ☐ IACI ☐ AAPL

Zoom: [1d](#) [5d](#) [1m](#) [3m](#) [6m](#) [YTD](#) [1y](#) [5y](#) [10y](#) [All](#)

Dec 27, 2013 - Dec 31, 2013 **+2.83 (0.25%)**




2012 2013
Settings | Technical | [Link to this view](#) Values delayed by 45 min

<https://www.google.com/finance>

What is different?

- Data are dependent over time
- Specific pattern types
 - Trends - long term increase or decrease
 - Seasonal patterns - patterns related to time of week, month, year, etc.
 - Cycles - patterns that rise and fall periodically
- Subsampling into training/test is more complicated
- Similar issues arise in spatial data
 - Dependency between nearby observations
 - Location specific effects
- Typically goal is to predict one or more observations into the future.
- All standard predictions can be used (with caution!)


Beware spurious correlations!



<http://www.google.com/trends/correlate>

<http://www.newscientist.com/blogs/onepercent/2011/05/google-correlate-passes-our-we.html>


Also common in geographic analyses



PET PEEVE #208:
GEOGRAPHIC PROFILE MAPS WHICH ARE
BASICALLY JUST POPULATION MAPS

<http://xkcd.com/1138/>

Beware extrapolation!



<http://www.nature.com/nature/journal/v431/n7008/full/431525a.html>

Google data

```
library(quantmod)
from.dat <- as.Date("01/01/08", format="%m/%d/%y")
to.dat <- as.Date("12/31/13", format="%m/%d/%y")
getSymbols("GOOG", src="google", from = from.dat, to = to.dat)
```


```
[1] "GOOG"
```

```
head(GOOG)
```

	GOOG.Open	GOOG.High	GOOG.Low	GOOG.Close	GOOG.Volume
2008-01-02	692.9	697.4	677.7	685.2	4306848
2008-01-03	685.3	686.9	676.5	685.3	3252846
2008-01-04	679.7	681.0	655.0	657.0	5359834
2008-01-07	653.9	662.3	637.4	649.2	6404945
2008-01-08	653.0	660.0	631.0	631.7	5341949
2008-01-09	630.0	653.3	622.5	653.2	6744242

Summarize monthly and store as time series

```
mGoog <- to.monthly(GOOG)
googOpen <- Op(mGoog)
ts1 <- ts(googOpen,frequency=12)
plot(ts1,xlab="Years+1", ylab="GOOG")
```




Example time series decomposition

- **Trend** - Consistently increasing pattern over time
- **Seasonal** - When there is a pattern over a fixed period of time that recurs.
- **Cyclic** - When data rises and falls over non fixed periods

<https://www.otexts.org/fpp/6/1>

Decompose a time series into parts

```
plot(decompose(ts1), xlab="Years+1")
```



Training and test sets

```
ts1Train <- window(ts1,start=1,end=5)
ts1Test <- window(ts1,start=5,end=(7-0.01))
ts1Train
```

	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1	692.9	528.7	471.5	447.7	578.3	582.5	519.6	472.5	476.8	412.1	357.6	286.7
2	308.6	334.3	333.3	343.8	395.0	418.7	424.2	448.7	459.7	493.0	537.1	588.1
3	627.0	534.6	529.2	571.4	526.5	480.4	445.3	489.0	455.0	530.0	615.7	563.0
4	596.5	604.5	617.8	588.8	545.7	528.0	506.7	611.2	540.8	509.9	580.1	600.0
5	652.9											

Simple moving average

$$Y_t = \frac{1}{2 * k + 1} \sum_{j=-k}^k y_{t+j}$$

```
plot(ts1Train)
lines(ma(ts1Train,order=3),col="red")
```

Exponential smoothing

Example - simple exponential smoothing


$$\hat{y}_{t+1} = \alpha y_t + (1 - \alpha)\hat{y}_{t-1}$$

	Seasonal Component		
Trend	N	A	M
Component	(None)	(Additive)	(Multiplicative)
N (None)	(N,N)	(N,A)	(N,M)
A (Additive)	(A,N)	(A,A)	(A,M)
A _d (Additive damped)	(A _d ,N)	(A _d ,A)	(A _d ,M)
M (Multiplicative)	(M,N)	(M,A)	(M,M)
M _d (Multiplicative damped)	(M _d ,N)	(M _d ,A)	(M _d ,M)

<https://www.otexts.org/fpp/7/6>

Exponential smoothing

```
ets1 <- ets(ts1Train,model="MMM")  
fcast <- forecast(ets1)  
plot(fcast); lines(ts1Test,col="red")
```



Get the accuracy

```
accuracy(fcast,ts1Test)
```

	ME	RMSE	MAE	MPE	MAPE	MASE	ACF1	Theil's U
Training set	0.9464	48.78	39.35	-0.3297	7.932	0.3733	0.07298	NA
Test set	156.1890	205.76	160.78	18.1819	18.971	1.5254	0.77025	3.745

Notes and further resources

- [Forecasting and timeseries prediction](#) is an entire field
- Rob Hyndman's [Forecasting: principles and practice](#) is a good place to start
- Cautions
 - Be wary of spurious correlations
 - Be careful how far you predict (extrapolation)
 - Be wary of dependencies over time
- See [quantmod](#) or [quandl](#) packages for finance-related problems.