



In sample and out of sample error

Jeffrey Leek
Johns Hopkins Bloomberg School of Public Health

In sample versus out of sample

In Sample Error: The error rate you get on the same data set you used to build your predictor. Sometimes called resubstitution error.


Out of Sample Error: The error rate you get on a new data set. Sometimes called generalization error.

Key ideas

1. Out of sample error is what you care about
2. In sample error $<$ out of sample error
3. The reason is overfitting
 - Matching your algorithm to the data you have

In sample versus out of sample errors

```
library(kernlab); data(spam); set.seed(333)
smallSpam <- spam[sample(dim(spam)[1],size=10),]
spamLabel <- (smallSpam$type=="spam")*1 + 1
plot(smallSpam$capitalAve,col=spamLabel)
```



Prediction rule 1

- $\text{capitalAve} > 2.7 = \text{"spam"}$
- $\text{capitalAve} < 2.40 = \text{"nonspam"}$
- $\text{capitalAve} \text{ between } 2.40 \text{ and } 2.45 = \text{"spam"}$
- $\text{capitalAve} \text{ between } 2.45 \text{ and } 2.7 = \text{"nonspam"}$

Apply Rule 1 to smallSpam

```
rule1 <- function(x){  
  prediction <- rep(NA,length(x))  
  prediction[x > 2.7] <- "spam"  
  prediction[x < 2.40] <- "nonspam"  
  prediction[(x >= 2.40 & x <= 2.45)] <- "spam"  
  prediction[(x > 2.45 & x <= 2.70)] <- "nonspam"  
  return(prediction)  
}  
table(rule1(smallSpam$capitalAve),smallSpam$type)
```

	nonspam	spam
nonspam	5	0
spam	0	5

Prediction rule 2

- $\text{capitalAve} > 2.40 = \text{"spam"}$
- $\text{capitalAve} \leq 2.40 = \text{"nonspam"}$

Apply Rule 2 to smallSpam

```
rule2 <- function(x){  
  prediction <- rep(NA,length(x))  
  prediction[x > 2.8] <- "spam"  
  prediction[x <= 2.8] <- "nonspam"  
  return(prediction)  
}  
table(rule2(smallSpam$capitalAve),smallSpam$type)
```

	nonspam	spam
nonspam	5	1
spam	0	4

Apply to complete spam data

```
table(rule1(spam$capitalAve),spam$type)
```

	nonspam	spam
nonspam	2141	588
spam	647	1225

```
table(rule2(spam$capitalAve),spam$type)
```

	nonspam	spam
nonspam	2224	642
spam	564	1171

```
mean(rule1(spam$capitalAve)==spam$type)
```


Look at accuracy

```
sum(rule1(spam$capitalAve)==spam$type)
```

```
[1] 3366
```

```
sum(rule2(spam$capitalAve)==spam$type)
```

```
[1] 3395
```

What's going on?

Overfitting

- Data have two parts
 - Signal
 - Noise
- The goal of a predictor is to find signal
- You can always design a perfect in-sample predictor
- You capture both signal + noise when you do that
- Predictor won't perform as well on new samples

<http://en.wikipedia.org/wiki/Overfitting>