

Regular Expressions

Chapter 11



Python for Everybody
www.py4e.com



Regular Expressions

In computing, a regular expression, also referred to as “regex” or “regexp”, provides a concise and flexible means for matching strings of text, such as particular characters, words, or patterns of characters. A regular expression is written in a formal language that can be interpreted by a regular expression processor.

http://en.wikipedia.org/wiki/Regular_expression

Regular Expressions

Really clever “wild card” expressions for matching
and parsing strings

http://en.wikipedia.org/wiki/Regular_expression



Really smart “Find” or “Search”

Understanding Regular Expressions

- Very powerful and quite cryptic
- Fun once you understand them
- Regular expressions are a language unto themselves
- A language of “marker characters” - programming with characters
- It is kind of an “old school” language - compact



<http://xkcd.com/208/>

Regular Expression Quick Guide

<code>^</code>	Matches the beginning of a line
<code>\$</code>	Matches the end of the line
<code>.</code>	Matches any character
<code>\s</code>	Matches whitespace
<code>\S</code>	Matches any non-whitespace character
<code>*</code>	Repeats a character zero or more times
<code>*?</code>	Repeats a character zero or more times (non-greedy)
<code>+</code>	Repeats a character one or more times
<code>+?</code>	Repeats a character one or more times (non-greedy)
<code>[aeiou]</code>	Matches a single character in the listed set
<code>[^XYZ]</code>	Matches a single character not in the listed set
<code>[a-z0-9]</code>	The set of characters can include a range
<code>(</code>	Indicates where string extraction is to start
<code>)</code>	Indicates where string extraction is to end

<https://www.py4e.com/lectures3/Pythonlearn-11-Regex-Handout.txt>

The Regular Expression Module

- Before you can use regular expressions in your program, you must import the library using “`import re`”
- You can use `re.search()` to see if a string matches a regular expression, similar to using the `find()` method for strings
- You can use `re.findall()` to extract portions of a string that match your regular expression, similar to a combination of `find()` and slicing: `var[5:10]`

Using `re.search()` Like `find()`

```
hand = open('mbox-short.txt')
for line in hand:
    line = line.rstrip()
    if line.find('From:') >= 0:
        print(line)
```

```
import re

hand = open('mbox-short.txt')
for line in hand:
    line = line.rstrip()
    if re.search('From:', line) :
        print(line)
```

Using `re.search()` Like `startswith()`

```
hand = open('mbox-short.txt')
for line in hand:
    line = line.rstrip()
    if line.startswith('From:') :
        print(line)
```

```
import re

hand = open('mbox-short.txt')
for line in hand:
    line = line.rstrip()
    if re.search('^From:', line) :
        print(line)
```

We fine-tune what is matched by adding special characters to the string

Wild-Card Characters


- The **dot** character matches any character
- If you add the **asterisk** character, the character is “any number of times”

```
X-Sieve: CMU Sieve 2.3
X-DSPAM-Result: Innocent
X-DSPAM-Confidence: 0.8475
X-Content-Type-Message-Body: text/plain
```

Match the start of the
line

Many
times

Match any character



Fine-Tuning Your Match

Depending on how “clean” your data is and the purpose of your application, you may want to narrow your match down a bit

```
X-Sieve: CMU Sieve 2.3
X-DSPAM-Result: Innocent
X-Plane is behind schedule: two weeks
X-: Very short
```

Match the start of
the line

Many
times

Match any character

^ X . * :

Fine-Tuning Your Match

Depending on how “clean” your data is and the purpose of your application, you may want to narrow your match down a bit

```
X-Sieve: CMU Sieve 2.3
X-DSPAM-Result: Innocent
X-: Very Short
X-Plane is behind schedule: two weeks
```

Match the start of
the line

One or more
times

[^]X-\S+:

Match any non-whitespace character

Matching and Extracting Data

- `re.search()` returns a True/False depending on whether the string matches the regular expression
- If we actually want the matching strings to be extracted, we use `re.findall()`

`[0-9]+`



One or more digits

```
>>> import re
>>> x = 'My 2 favorite numbers are 19 and 42'
>>> y = re.findall('[0-9]+',x)
>>> print(y)
['2', '19', '42']
```

Matching and Extracting Data

When we use `re.findall()`, it returns a list of zero or more sub-strings that match the regular expression

```
>>> import re
>>> x = 'My 2 favorite numbers are 19 and 42'
>>> y = re.findall('[0-9]+',x)
>>> print(y)
['2', '19', '42']
>>> y = re.findall('[AEIOU]+',x)
>>> print(y)
[]
```

Warning: Greedy Matching


The **repeat** characters (***** and **+**) push **outward** in both directions (greedy) to match the largest possible string

```
>>> import re
>>> x = 'From: Using the : character'
>>> y = re.findall('^F.+:', x)
>>> print(y)
['From: Using the :']
```

Why not 'From:' ?

First character in the match is an F

Last character in the match is a :



Non-Greedy Matching

Not all regular expression repeat codes are greedy!
If you add a `?` character, the `+` and `*` chill out a bit...

```
>>> import re
>>> x = 'From: Using the : character'
>>> y = re.findall('^F.+?:', x)
>>> print(y)
['From:']
```

First character in
the match is an F

Last character in the
match is a :

One or more
characters but
not greedy

`^F.+?:`


Fine-Tuning String Extraction

You can refine the match for `re.findall()` and separately determine which portion of the match is to be extracted by using parentheses

From `stephen.marquard@uct.ac.za` Sat Jan 5 09:14:16 2008

```
>>> y = re.findall('\S+@\S+', x)
>>> print(y)
['stephen.marquard@uct.ac.za']
```

`\S+@\S+`



At least one
non-whitespace
character


Fine-Tuning String Extraction

Parentheses are not part of the match - but they tell where to **start** and **stop** what string to extract

From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008

```
>>> y = re.findall('\S+@\S+',x)
>>> print(y)
['stephen.marquard@uct.ac.za']
>>> y = re.findall('^From (\S+@\S+)',x)
>>> print(y)
['stephen.marquard@uct.ac.za']
```

^From (\S+@\S+)



String Parsing Examples...

From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008

21 ↓ 31 ↓

@uct.ac.za

```
>>> data = 'From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008'
>>> atpos = data.find('@')
>>> print(atpos)
21
>>> sppos = data.find(' ', atpos)
>>> print(sppos)
31
>>> host = data[atpos+1 : sppos]
>>> print(host)
uct.ac.za
```

Extracting a host
name - using find
and string slicing

The Double Split Pattern

Sometimes we split a line one way, and then grab one of the pieces of the line and split that piece again

```
From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008
```

```
words = line.split()  
email = words[1]  
pieces = email.split('@')  
print(pieces[1])
```

```
stephen.marquard@uct.ac.za  
['stephen.marquard', 'uct.ac.za']  
'uct.ac.za'
```

The Regex Version

```
From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008

import re
lin = 'From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008'
y = re.findall('@([ ^ ]*)', lin)
print(y)

['uct.ac.za']
```

'@([^]*)'



Look through the string until you find an at sign

The Regex Version

```
From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008
```

```
import re
lin = 'From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008'
y = re.findall('@([ ^ ]*)', lin)
print(y)
```

```
['uct.ac.za']
```

' @ ([^] *) '

Match non-blank character

Match many of them

The Regex Version

```
From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008
```

```
import re
lin = 'From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008'
y = re.findall('@([ ^ ]*)', lin)
print(y)
```

```
['uct.ac.za']
```

'@([^]*)'

Extract the non-blank characters


Even Cooler Regex Version

```
From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008
```

```
import re
lin = 'From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008'
y = re.findall('^From .*@([ ^]*)', lin)
print(y)
```

```
['uct.ac.za']
```

'^From .*@([^]*)'



Starting at the beginning of the line, look for the string 'From'

Even Cooler Regex Version

```
From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008
```

```
import re
lin = 'From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008'
y = re.findall('^From .*@([ ^]*)', lin)
print(y)
```

```
['uct.ac.za']
```

'^From . * @ ([^] *) '

Skip a bunch of characters, looking for an at sign

Even Cooler Regex Version

```
From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008
```

```
import re
lin = 'From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008'
y = re.findall('^From .*@([ ^]*)', lin)
print(y)
```

```
['uct.ac.za']
```

'^From .*@([^]*)'



Start extracting

Even Cooler Regex Version

From **stephen.marquard@uct.ac.za** **Sat Jan 5 09:14:16 2008**

```
import re
lin = 'From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008'
y = re.findall('^From .*@([ ^]*)', lin)
print(y)
```

['uct.ac.za']

' ^From .*@ ([^] +) '

Match non-blank character Match many of them

Even Cooler Regex Version

```
From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008
```

```
import re
lin = 'From stephen.marquard@uct.ac.za Sat Jan 5 09:14:16 2008'
y = re.findall('^From .*@([ ^]*)', lin)
print(y)
```

```
['uct.ac.za']
```

```
'^From .*@([ ^]+)'
```



Stop extracting

Spam Confidence

```
import re
hand = open('mbox-short.txt')
numlist = list()
for line in hand:
    line = line.rstrip()
    stuff = re.findall('^X-DSPAM-Confidence: ([0-9.]+)', line)
    if len(stuff) != 1 : continue
    num = float(stuff[0])
    numlist.append(num)
print('Maximum:', max(numlist))
```

X-DSPAM-Confidence: 0.8475

python ds.py
Maximum: 0.9907

Escape Character

If you want a special regular expression character to just behave **normally** (most of the time) you prefix it with `'\'`

```
>>> import re
>>> x = 'We just received $10.00 for cookies.'
>>> y = re.findall('\$[0-9.]+', x)
>>> print(y)
['$10.00']
```

At least one
or more

\ \$ [0 - 9 .] +

A real dollar sign

A digit or period

Summary

- Regular expressions are a cryptic but powerful language for matching strings and extracting elements from those strings
- Regular expressions have special characters that indicate intent



Acknowledgements / Contributions



These slides are Copyright 2010- Charles R. Severance (www.dr-chuck.com) of the University of Michigan School of Information and open.umich.edu and made available under a Creative Commons Attribution 4.0 License. Please maintain this last slide in all copies of the document to comply with the attribution requirements of the license. If you make a change, feel free to add your name and organization to the list of contributors on this page as you republish the materials.

Initial Development: Charles Severance, University of Michigan School of Information

... Insert new Contributors and Translations here