

## DSA Project

Clique of people

Group: G612277

Brajan Miśkowicz

Adam Szałański

Łucja Pałkus



<b>1 User Documentation</b>	<b>1</b>
<b>2 UML Diagram</b>	<b>3</b>
<b>3 Namespace Index</b>	<b>5</b>
3.1 Package List . . . . .	5
<b>4 Class Index</b>	<b>7</b>
4.1 Class List . . . . .	7
<b>5 File Index</b>	<b>9</b>
5.1 File List . . . . .	9
<b>6 Namespace Documentation</b>	<b>11</b>
6.1 Package fileHandling . . . . .	11
6.2 Package people . . . . .	11
6.3 Package relationships . . . . .	11
<b>7 Class Documentation</b>	<b>13</b>
7.1 fileHandling.FileHandling Class Reference . . . . .	13
7.1.1 Detailed Description . . . . .	13
7.1.2 Member Function Documentation . . . . .	13
7.1.2.1 readFile() . . . . .	13
7.1.2.2 writeToFile() . . . . .	14
7.2 Menu Class Reference . . . . .	15
7.2.1 Detailed Description . . . . .	15
7.2.2 Member Function Documentation . . . . .	15
7.2.2.1 main() . . . . .	15
7.2.2.2 menu() . . . . .	16
7.3 people.People Class Reference . . . . .	17
7.3.1 Constructor & Destructor Documentation . . . . .	18
7.3.1.1 People() . . . . .	18
7.3.2 Member Function Documentation . . . . .	18
7.3.2.1 addPersonFromString() . . . . .	18
7.3.2.2 anySymbolLineFormatter() . . . . .	19
7.3.2.3 dashLineFormatter() . . . . .	19
7.3.2.4 fillTheClasses() . . . . .	20
7.3.2.5 findMatchesByFile() . . . . .	20
7.3.2.6 findPeopleBornBetween() . . . . .	21
7.3.2.7 findPeopleByBirthplace() . . . . .	22
7.3.2.8 findPeopleByHome() . . . . .	22
7.3.2.9 findPersonById() . . . . .	23
7.3.2.10 findPersonBySurname() . . . . .	24
7.3.2.11 getPeople() . . . . .	24

7.3.2.12 printAllClasses()	25
7.3.2.13 printAllPeople()	25
7.3.2.14 printPeopleBornBetween()	25
7.3.2.15 printPeopleByBirthplace()	26
7.3.2.16 printPeopleByHome()	27
7.3.2.17 printRelationshipsByLastname()	28
7.3.2.18 quicksortByBirthplaceSurnameAndName()	29
7.3.2.19 removePersonById()	29
7.3.2.20 setPeople()	30
7.3.2.21 sortByBirthplaceSurnameAndName()	30
7.3.2.22 sortBySurnameAndName()	31
7.3.2.23 sortClasses()	32
7.3.2.24 sortPeopleByMovies()	32
7.3.2.25 writeToFile()	33
7.3.3 Member Data Documentation	34
7.3.3.1 FIRST_LINE_PEOPLE	34
7.3.3.2 profiles	34
7.4 people.Person Class Reference	34
7.4.1 Constructor & Destructor Documentation	35
7.4.1.1 Person()	35
7.4.2 Member Function Documentation	35
7.4.2.1 equals()	35
7.4.2.2 getBirthdate()	36
7.4.2.3 getBirthplace()	37
7.4.2.4 getFilms()	37
7.4.2.5 getGender()	37
7.4.2.6 getGroupCode()	38
7.4.2.7 getHome()	38
7.4.2.8 getIdPerson()	38
7.4.2.9 getLastname()	39
7.4.2.10 getName()	39
7.4.2.11 getStudiedAt()	40
7.4.2.12 getWorkplaces()	40
7.4.2.13 hashCode()	40
7.4.2.14 setBirthdate()	40
7.4.2.15 setBirthplace()	41
7.4.2.16 setFilms()	41
7.4.2.17 setGender()	41
7.4.2.18 setGroupCode()	42
7.4.2.19 setHome()	42
7.4.2.20 setIdPerson()	42
7.4.2.21 setLastname()	42

7.4.2.22 setName()	43
7.4.2.23 setStudiedAt()	43
7.4.2.24 setWorkplaces()	43
7.4.2.25 toString()	44
7.5 people.Quicksort Class Reference	44
7.5.1 Member Function Documentation	44
7.5.1.1 sort()	44
7.6 relationships.Relationship Class Reference	44
7.6.1 Detailed Description	45
7.6.2 Constructor & Destructor Documentation	45
7.6.2.1 Relationship()	45
7.6.3 Member Function Documentation	45
7.6.3.1 equals()	45
7.6.3.2 getFriend1()	46
7.6.3.3 getFriend2()	47
7.6.3.4 hashCode()	47
7.6.3.5 setFriend1()	47
7.6.3.6 setFriend2()	48
7.6.3.7 toString()	48
7.7 relationships.Relationships Class Reference	49
7.7.1 Constructor & Destructor Documentation	49
7.7.1.1 Relationships()	49
7.7.2 Member Function Documentation	49
7.7.2.1 addRelationship()	49
7.7.2.2 deleteRelationship()	50
7.7.2.3 findRelationshipsById()	51
7.7.2.4 findRelationshipsByIds()	51
7.7.2.5 getRelations()	52
7.7.2.6 printAllRelationships()	52
7.7.2.7 toString()	53
7.7.2.8 writeToFile()	53
7.7.3 Member Data Documentation	54
7.7.3.1 FIRST_LINE_RELATIONSHIPS	54
7.8 UnitTests Class Reference	54
7.8.1 Member Function Documentation	55
7.8.1.1 done()	55
<b>8 File Documentation</b>	<b>57</b>
8.1 D:/Projekty/DSA_ehu_JavaProject/src/fileHandling/FileHandling.java File Reference	57
8.2 D:/Projekty/DSA_ehu_JavaProject/src/Menu.java File Reference	57
8.3 D:/Projekty/DSA_ehu_JavaProject/src/people/People.java File Reference	57
8.4 D:/Projekty/DSA_ehu_JavaProject/src/people/Person.java File Reference	58

8.5 D:/Projekty/DSA_ehu_JavaProject/src/people/Quicksort.java File Reference . . . . .	58
8.6 D:/Projekty/DSA_ehu_JavaProject/src/relationships/Relationship.java File Reference . . . . .	58
8.7 D:/Projekty/DSA_ehu_JavaProject/src/relationships/Relationships.java File Reference . . . . .	58
8.8 D:/Projekty/DSA_ehu_JavaProject/src/UnitTests.java File Reference . . . . .	59
<b>Index</b>	<b>61</b>

# Chapter 1

## User Documentation

The aim of this programming project is to manage a social network. This social network is formed by people that may be linked among each other if there is a friendship relationship between them.

If one runs program, menu options are displayed, where one can choose loading data from file with people, file with relationships between people, displaying loaded data, saving current data to new files, deleting people (including all of their relationships) and deleting particular relationship.

One has to type file name without '.txt' extension if decides to load data from file with people or from file with relationships.

If one decides to display data from people or relationships files, data will be listed on screen.

One has to type file name without '.txt' extension when decides to save current data. If file has already existed, it will be overwritten.

One has to type person's ID if decides to delete person from data. All relationships that include this ID will be removed.

Deleting relationship between two people from data requires typing their IDs.

This program is protected from invalid input:

One cannot input string in menu options. Exception with message "Bad input" will appear on screen, but menu will reload.

Unexisting files cannot be loaded. Error "Such file does not exist" will be displayed, but program will not crash.

Unexisting person cannot be deleted. Exception "Person with that id does not exist" is thrown, but it doesn't interrupt the program.

Program doesn't crash if one tries to delete unexisting relationship.

Second version of the program allows users to retrieve friends of a person (given surname). If there are several people with the same surname then there is printed out a list of friends for each of those people. Moreover given a city once can retrieve all people born there, returning id and surname for each person. Having two dates program can return people born between them, sorted by birthplace, surname, name. This part retrieves people's IDs from the provided file and finds them in the people net. Next takes their hometown and creates a list of people which birthplace matches that hometown. One of the possibilities in the menu is to build a list of classes, where classes contains users who likes the same collection of movies.





## Chapter 2

## UML Diagram




Figure 2.1 UML diagram of the classes



## Chapter 3

# Namespace Index

### 3.1 Package List

Here are the packages with brief descriptions (if available):

<a href="#">fileHandling</a>	.....	<a href="#">11</a>
<a href="#">people</a>	.....	<a href="#">11</a>
<a href="#">relationships</a>	.....	<a href="#">11</a>



## Chapter 4

# Class Index

### 4.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

<a href="#">fileHandling.FileHandling</a>	13
<a href="#">Menu</a>	15
<a href="#">people.People</a>	17
<a href="#">people.Person</a>	34
<a href="#">people.Quicksort</a>	44
<a href="#">relationships.Relationship</a>	44
<a href="#">relationships.Relationships</a>	49
<a href="#">UnitTests</a>	54



## Chapter 5

# File Index

### 5.1 File List

Here is a list of all files with brief descriptions:

D:/Projekty/DSA_ehu_JavaProject/src/ <a href="#">Menu.java</a> . . . . .	57
D:/Projekty/DSA_ehu_JavaProject/src/ <a href="#">UnitTests.java</a> . . . . .	59
D:/Projekty/DSA_ehu_JavaProject/src/fileHandling/ <a href="#">FileHandling.java</a> . . . . .	57
D:/Projekty/DSA_ehu_JavaProject/src/people/ <a href="#">People.java</a> . . . . .	57
D:/Projekty/DSA_ehu_JavaProject/src/people/ <a href="#">Person.java</a> . . . . .	58
D:/Projekty/DSA_ehu_JavaProject/src/people/ <a href="#">Quicksort.java</a> . . . . .	58
D:/Projekty/DSA_ehu_JavaProject/src/relationships/ <a href="#">Relationship.java</a> . . . . .	58
D:/Projekty/DSA_ehu_JavaProject/src/relationships/ <a href="#">Relationships.java</a> . . . . .	58





## Chapter 6

# Namespace Documentation

### 6.1 Package fileHandling

#### Classes

- class [FileHandling](#)

### 6.2 Package people

#### Classes

- class [People](#)
- class [Person](#)
- class [Quicksort](#)

### 6.3 Package relationships

#### Classes

- class [Relationship](#)
- class [Relationships](#)



## Chapter 7

# Class Documentation

### 7.1 fileHandling.FileHandling Class Reference

#### Static Public Member Functions

- static List< String > [readFile](#) (String fileName) throws FileNotFoundException
- static void [writeToFile](#) (String output, String fileName) throws IOException

#### 7.1.1 Detailed Description

This class responsible for handling operations related to files It has classes which writes and rides text from/to files

#### 7.1.2 Member Function Documentation

##### 7.1.2.1 [readFile\(\)](#)

```
static List< String > fileHandling.FileHandling.readFile (  
    String fileName ) throws FileNotFoundException [static]
```

This method read lines from the whole file.

#### Parameters

<i>fileName</i>	is String parameter with a file name
-----------------	--------------------------------------

**Returns**

list of Strings

Here is the caller graph for this function:

**7.1.2.2 writeToFile()**

```
static void fileHandling.FileHandling.writeToFile (
    String output,
    String fileName ) throws IOException [static]
```

This method write String to the file.


**Parameters**

<i>output</i>	String which will be written to file
<i>fileName</i>	String contains name of file where output will be written

**Exceptions**

<i>IOException</i>	This throws could occur when an I/O exception of some sort has occurred.
--------------------	--

Here is the caller graph for this function:



The documentation for this class was generated from the following file:

- D:/Projekty/DSA\_ehu\_JavaProject/src/fileHandling/[FileHandling.java](#)

## 7.2 Menu Class Reference

### Static Public Member Functions

- static void `main` (String[] args)
- static int `menu` ()

#### 7.2.1 Detailed Description

This class is currently the main class of the projects. It creates the menu that allows user to insert People and Relationships and view them.

#### 7.2.2 Member Function Documentation

##### 7.2.2.1 `main()`


```
static void Menu.main (  
    String[] args ) [static]
```

This method consist of calls to all functions related to the options presented in menu.

##### Parameters

<i>args</i>	
-------------	--

Here is the call graph for this function:



### 7.2.2.2 menu()

```
static int Menu.menu ( ) [static]
```

This method prints menu options of our programming project and reads input from the user.

## Returns

integer

Here is the caller graph for this function:



The documentation for this class was generated from the following file:

- D:/Projekty/DSA\_ehu\_JavaProject/src/[Menu.java](#)

## 7.3 people.People Class Reference

### Public Member Functions

- [People](#) ()
- List< [Person](#) > [getPeople](#) ()
- void [setPeople](#) (List< [Person](#) > people)
- void [printAllPeople](#) ()
- void [addPersonFromString](#) (String data) throws ParseException
- [Person](#) [findPersonById](#) (String id)
- List< [Person](#) > [findPersonBySurname](#) (String surname)
- void [printRelationshipsByLastname](#) (String lastname, [Relationships](#) relationships)
- List< [Person](#) > [findPeopleByHome](#) (String home)
- void [printPeopleByHome](#) (String home)
- List< [Person](#) > [findPeopleByBirthplace](#) (String birthplace)
- void [printPeopleByBirthplace](#) (String birthplace)
- List< [Person](#) > [findPeopleBornBetween](#) (int yearMin, int yearMax)
- void [printPeopleBornBetween](#) (int yearMin, int yearMax)
- void [writeToFile](#) (String filename) throws IOException
- void [removePersonById](#) (String id)
- void [findMatchesByFile](#) (String filename) throws IOException
- void [sortBySurnameAndName](#) ()
- void [sortByBirthplaceSurnameAndName](#) ()
- void [quicksortByBirthplaceSurnameAndName](#) ()
- void [fillTheClasses](#) ()
- void [printAllClasses](#) ()
- void [sortClasses](#) ()
- void [sortPeopleByMovies](#) ()

### Static Public Member Functions

- static String [dashLineFormatter](#) (String line)
- static String [anySymbolLineFormatter](#) (String line, String symbol)

## Public Attributes

- `HashMap< List< String >, List< Person > > profiles = new HashMap<>()`

## Static Public Attributes

- `static final String FIRST_LINE_PEOPLE = "idperson,name,lastname,birthdate,gender,birthplace,home,studiedat,workplaces,fil`

## 7.3.1 Constructor & Destructor Documentation

### 7.3.1.1 [People](#)()

```
people.People.People ( )
```

Constructor for a [People](#) class.

## 7.3.2 Member Function Documentation

### 7.3.2.1 `addPersonFromString()`

```
void people.People.addPersonFromString (
    String data ) throws ParseException
```

This method check if the user ID is already in list of people, if not - add person from string to list of people

#### Parameters

<i>data</i>	is string containing data for creating a new object of <a href="#">Person</a> class.
-------------	--

#### Exceptions

<i>ParseException</i>	Signals that an error has been reached unexpectedly while parsing.
-----------------------	--



Here is the caller graph for this function:



### 7.3.2.2 anySymbolLineFormatter()

```
static String people.People.anySymbolLineFormatter (  
    String line,  
    String symbol ) [static]
```

A little function that takes a line containing column names and returns a line of dashes adjusted to the length of passed line

#### Parameters

<i>line</i>	String with column names
<i>symbol</i>	String to be used as a delimiter line

#### Returns

String of passed symbol

### 7.3.2.3 dashLineFormatter()

```
static String people.People.dashLineFormatter (  
    String line ) [static]
```

A little function that takes a line containing column names and returns a line of dashes adjusted to the length of passed line


#### Parameters

<i>line</i>	String with column names
-------------	--------------------------

**Returns**


String of dashes

Here is the caller graph for this function:

**7.3.2.4 fillTheClasses()**

```
void people.People.fillTheClasses ( )
```

This function builds a classes of movies containing peoples who likes the same sets of movies Here is the caller graph for this function:

**7.3.2.5 findMatchesByFile()**

```
void people.People.findMatchesByFile (
    String filename ) throws IOException
```

The function takes the name of the .txt file, reads the contents of the file being the ID's of people and prints the lists of people whose birthplace is equal to hometown of people from file


## Parameters

<i>filename</i>	String - name of the file without extension
-----------------	---

## Exceptions

<i>IOException</i>	in case the file causes issues
--------------------	--------------------------------

Here is the call graph for this function:



Here is the caller graph for this function:



### 7.3.2.6 findPeopleBornBetween()

```
List< Person > people.People.findPeopleBornBetween (
    int yearMin,
    int yearMax )
```

This method finds a list of people born between passed years


## Parameters

<i>yearMin</i>	int
<i>yearMax</i>	int

**Returns**

List<Person> list of found people

Here is the caller graph for this function:

**7.3.2.7 findPeopleByBirthplace()**

```
List< Person > people.People.findPeopleByBirthplace (
    String birthplace )
```

This method finds a list of people with the passed birthplace


**Parameters**

<i>birthplace</i>	String
-------------------	--------

**Returns**

List<Person> list of found people

Here is the caller graph for this function:

**7.3.2.8 findPeopleByHome()**

```
List< Person > people.People.findPeopleByHome (
    String home )
```

This method finds a list of people with the passed hometown


## Parameters

<i>home</i>	String
-------------	--------

## Returns

List<Person> list of found people

Here is the caller graph for this function:



## 7.3.2.9 findPersonById()

```
Person people.People.findPersonById (  
    String id )
```

This method finds `Person` object with corresponding ID in people list.


## Parameters

<i>id</i>	string
-----------	--------

## Returns

`Person` object

Here is the caller graph for this function:



### 7.3.2.10 findPersonBySurname()

```
List< Person > people.People.findPersonBySurname (
    String surname )
```

This method finds List of [Person](#) objects with corresponding surname in people list.


#### Parameters

<i>surname</i>	string
----------------	--------

#### Returns

List<Person> object

Here is the caller graph for this function:



### 7.3.2.11 getPeople()

```
List< Person > people.People.getPeople ( )
```

Getter for a people field.

#### Returns

list of [Person](#) type objects.

#### 7.3.2.12 printAllClasses()

```
void people.People.printAllClasses ( )
```

This function prints all movies classes and all the people who like them Here is the caller graph for this function:




#### 7.3.2.13 printAllPeople()

```
void people.People.printAllPeople ( )
```

This method prints out the list of all the people loaded to the program. Here is the call graph for this function:



Here is the caller graph for this function:



#### 7.3.2.14 printPeopleBornBetween()


```
void people.People.printPeopleBornBetween (
    int yearMin,
    int yearMax )
```

This method prints people born between passed years

## Parameters

<i>yearMin</i>	int
<i>yearMax</i>	int

Here is the call graph for this function:



Here is the caller graph for this function:



### 7.3.2.15 printPeopleByBirthplace()

```
void people.People.printPeopleByBirthplace (
    String birthplace )
```


This method prints people with a given birthplace

## Parameters

<i>birthplace</i>	String
-------------------	--------



Here is the call graph for this function:



Here is the caller graph for this function:



#### 7.3.2.16 printPeopleByHome()


```
void people.People.printPeopleByHome (
    String home )
```

This method prints people with a given hometown

##### Parameters

<i>home</i>	String
-------------	--------

Here is the call graph for this function:



### 7.3.2.17 printRelationshipsByLastname()


```
void people.People.printRelationshipsByLastname (
    String lastname,
    Relationships relationships )
```

This method prints relationships of people with a given lastname


#### Parameters

<i>lastname</i>	String
<i>relationships</i>	Relationships

Here is the call graph for this function:



Here is the caller graph for this function:



#### 7.3.2.18 quicksortByBirthplaceSurnameAndName()

```
void people.People.quicksortByBirthplaceSurnameAndName ( )
```

This function sorts people by birthplace surname and name with QuickSort Here is the caller graph for this function:



#### 7.3.2.19 removePersonById()

```
void people.People.removePersonById (
    String id )
```

This method removes person with a certain id from the list of people If person with that id does not exist, prints out a message


##### Parameters

<i>id</i>	String
-----------	--------

Here is the call graph for this function:



Here is the caller graph for this function:



#### 7.3.2.20 setPeople()

```
void people.People.setPeople (
    List< Person > people )
```

Setter for a people field.


##### Parameters

<i>people</i>	is list of <code>Person</code> type objects.
---------------	--


#### 7.3.2.21 sortByBirthplaceSurnameAndName()

```
void people.People.sortByBirthplaceSurnameAndName ( )
```

This function sorts people by birthplace surname and name with build-in sort Here is the call graph for this function:




Here is the caller graph for this function:




#### 7.3.2.22 sortBySurnameAndName()

```
void people.People.sortBySurnameAndName ( )
```

This function sorts people by surname and name with build-in sort Here is the call graph for this function:



Here is the caller graph for this function:



#### 7.3.2.23 sortClasses()

```
void people.People.sortClasses ( )
```


This function sorts the classes of movies by number of people who likes them Here is the caller graph for this function:



#### 7.3.2.24 sortPeopleByMovies()

```
void people.People.sortPeopleByMovies ( )
```

This function sorts people by most common movies sets it creates the classes, sort them and then get sorted people from hashmap Here is the call graph for this function:



Here is the caller graph for this function:



#### 7.3.2.25 writeToFile()

```
void people.People.writeToFile (
    String filename ) throws IOException
```

This method writes string to given file name.


##### Parameters

<i>filename</i>	string
-----------------	--------

##### Exceptions

<i>IOException</i>	This throws could occur when writing to a file
--------------------	--

Here is the call graph for this function:



Here is the caller graph for this function:



### 7.3.3 Member Data Documentation

#### 7.3.3.1 FIRST\_LINE\_PEOPLE

```
final String people.People.FIRST_LINE_PEOPLE = "idperson,name,lastname,birthdate,gender,birthplace,home,studiedAt,workplaces,films,groupCode";  
[static]
```

#### 7.3.3.2 profiles

```
HashMap<List<String>, List<Person> > people.People.profiles = new HashMap<>();
```

The documentation for this class was generated from the following file:

- D:/Projekty/DSA\_ehu\_JavaProject/src/people/[People.java](#)

## 7.4 people.Person Class Reference

### Public Member Functions

- boolean [equals](#) (Object o)
- int [hashCode](#) ()
- [Person](#) (String idPerson, String name, String lastname, Date birthdate, char gender, String birthplace, String home, List< String > studiedAt, List< String > workplaces, List< String > films, String groupCode)
- String [getIdPerson](#) ()
- void [setIdPerson](#) (String idPerson)
- String [getName](#) ()
- void [setName](#) (String name)
- String [getLastname](#) ()
- void [setLastname](#) (String lastname)
- Date [getBirthdate](#) ()
- void [setBirthdate](#) (Date birthdate)
- char [getGender](#) ()
- void [setGender](#) (char gender)
- String [getBirthplace](#) ()
- void [setBirthplace](#) (String birthplace)
- String [getHome](#) ()
- void [setHome](#) (String home)
- List< String > [getStudiedAt](#) ()
- void [setStudiedAt](#) (List< String > studiedAt)
- List< String > [getWorkplaces](#) ()
- void [setWorkplaces](#) (List< String > workplaces)
- List< String > [getFilms](#) ()
- void [setFilms](#) (List< String > films)
- String [getGroupCode](#) ()
- void [setGroupCode](#) (String groupCode)
- String [toString](#) ()



## 7.4.1 Constructor & Destructor Documentation

### 7.4.1.1 Person()

```
people.Person.Person (
    String idPerson,
    String name,
    String lastname,
    Date birthdate,
    char gender,
    String birthplace,
    String home,
    List< String > studiedAt,
    List< String > workplaces,
    List< String > films,
    String groupCode )
```

All-argument constructor for a [Person](#) class.

#### Parameters

<i>idPerson</i>	String contains user ID
<i>name</i>	String contains username
<i>lastname</i>	String contains lastname
<i>birthdate</i>	Date contains birthdate
<i>gender</i>	char contains 'M' as 'male' / 'F' as 'female'
<i>birthplace</i>	String contains birthplace
<i>home</i>	String contains name of hometown
<i>studiedAt</i>	list of Strings contains name of university
<i>workplaces</i>	list of Strings contains workplaces
<i>films</i>	list of Strings contains favourites movie titles
<i>groupCode</i>	String contains group code

## 7.4.2 Member Function Documentation

### 7.4.2.1 equals()

```
boolean people.Person.equals (
    Object o )
```

This method compares this object with object given in parameter. It overrides default method and allows us to use '==' operator.

**Parameters**

<i>o</i>	is an object of undefined type
----------	--------------------------------

**Returns**

boolean

Here is the call graph for this function:



Here is the caller graph for this function:

**7.4.2.2 getBirthdate()**

```
Date people.Person.getBirthdate ( )
```

Getter for a birthdate field.

**Returns**

Date type object.

### 7.4.2.3 getBirthplace()


```
String people.Person.getBirthplace ( )
```

Getter for a birthplace field.

#### Returns

String type object.

Here is the caller graph for this function:



### 7.4.2.4 getFilms()

```
List< String > people.Person.getFilms ( )
```

Getter for a films field.

#### Returns

List of String type objects.

### 7.4.2.5 getGender()

```
char people.Person.getGender ( )
```

Getter for a gender field.

#### Returns

char type object.

#### 7.4.2.6 getGroupCode()

```
String people.Person.getGroupCode ( )
```

Getter for a groupCode field.

##### Returns

String type object.

#### 7.4.2.7 getHome()

```
String people.Person.getHome ( )
```

Getter for a getHome field.

##### Returns

String type object.

#### 7.4.2.8 getIdPerson()


```
String people.Person.getIdPerson ( )
```

Getter for a idPerson field.

##### Returns

String type object.

Here is the caller graph for this function:



#### 7.4.2.9 getLastname()


```
String people.Person.getLastname ( )
```

Getter for a lastname field.

##### Returns

String type object.

Here is the caller graph for this function:



#### 7.4.2.10 getName()


```
String people.Person.getName ( )
```

Getter for a name field.

##### Returns

String type object.

Here is the caller graph for this function:



#### 7.4.2.11 `getStudiedAt()`

```
List< String > people.Person.getStudiedAt ( )
```

Getter for a studiedAt field.

##### Returns

List of String type objects.

#### 7.4.2.12 `getWorkplaces()`

```
List< String > people.Person.getWorkplaces ( )
```

Getter for a workplaces field.

##### Returns

List of String type objects.

#### 7.4.2.13 `hashCode()`

```
int people.Person.hashCode ( )
```

This method overrides default method and returns the integer hash code value of the object.

##### Returns

integer

Here is the call graph for this function:



#### 7.4.2.14 `setBirthdate()`

```
void people.Person.setBirthdate (
    Date birthdate )
```

Setter for a birthdate field.

## Parameters

<i>birthdate</i>	is a Date type object.
------------------	------------------------

**7.4.2.15 setBirthplace()**

```
void people.Person.setBirthplace (
    String birthplace )
```

Setter for a birthplace field.

## Parameters

<i>birthplace</i>	is a String type object.
-------------------	--------------------------

**7.4.2.16 setFilms()**

```
void people.Person.setFilms (
    List< String > films )
```

Setter for a films field.

## Parameters

<i>films</i>	is a list of String type object.
--------------	----------------------------------

**7.4.2.17 setGender()**

```
void people.Person.setGender (
    char gender )
```

Setter for a gender field.

## Parameters

<i>gender</i>	is a char type object.
---------------	------------------------

#### 7.4.2.18 setGroupCode()

```
void people.Person.setGroupCode (
    String groupCode )
```

Setter for a groupCode field.

##### Parameters

<i>groupCode</i>	is a String type object.
------------------	--------------------------

#### 7.4.2.19 setHome()

```
void people.Person.setHome (
    String home )
```

Setter for a home field.

##### Parameters

<i>home</i>	is a String type object.
-------------	--------------------------

#### 7.4.2.20 setIdPerson()

```
void people.Person.setIdPerson (
    String idPerson )
```

Setter for a idPerson field.

##### Parameters

<i>idPerson</i>	is a String type object.
-----------------	--------------------------

#### 7.4.2.21 setLastname()

```
void people.Person.setLastname (
    String lastname )
```

Setter for a lastname field.



## Parameters

<i>lastname</i>	is a String type object.
-----------------	--------------------------

**7.4.2.22 setName()**

```
void people.Person.setName (  
    String name )
```

Setter for a name field.

## Parameters

<i>name</i>	is a String type object.
-------------	--------------------------

**7.4.2.23 setStudiedAt()**

```
void people.Person.setStudiedAt (  
    List< String > studiedAt )
```

Setter for a studiedAt field.

## Parameters

<i>studied↔ At</i>	is a list of String type object.
------------------------	----------------------------------

**7.4.2.24 setWorkplaces()**

```
void people.Person.setWorkplaces (  
    List< String > workplaces )
```

Setter for a workplaces field.

## Parameters

<i>workplaces</i>	is a list of String type object.
-------------------	----------------------------------

#### 7.4.2.25 toString()

```
String people.Person.toString ( )
```

This method overrides default method and returns a string representation of this object.

##### Returns

string

The documentation for this class was generated from the following file:

- D:/Projekty/DSA\_ehu\_JavaProject/src/people/[Person.java](#)

## 7.5 people.Quicksort Class Reference

### Static Public Member Functions

- static< T extends Comparable< T > void [sort](#) (List< [Person](#) > list)

#### 7.5.1 Member Function Documentation

##### 7.5.1.1 sort()

```
static< T extends Comparable< T > void people.Quicksort.sort (
    List< Person > list ) [static]
```

first method of sorting

The documentation for this class was generated from the following file:

- D:/Projekty/DSA\_ehu\_JavaProject/src/people/[Quicksort.java](#)

## 7.6 relationships.Relationship Class Reference

### Public Member Functions

- String [toString](#) ()
- boolean [equals](#) (Object o)
- int [hashCode](#) ()
- [Relationship](#) ([Person](#) friend1, [Person](#) friend2)
- [Person](#) [getFriend1](#) ()
- void [setFriend1](#) ([Person](#) friend1)
- [Person](#) [getFriend2](#) ()
- void [setFriend2](#) ([Person](#) friend2)

## 7.6.1 Detailed Description

This class represents a single relationship between two people. Consists of two objects of type Person. @field friend1 an absolute URL giving the base location of the image @field friend2 the location of the image, relative to the url argument

## 7.6.2 Constructor & Destructor Documentation

### 7.6.2.1 Relationship()

```
relationships.Relationship.Relationship (
    Person friend1,
    Person friend2 )
```

Constructor for a [Relationships](#) class.

#### Parameters

<i>friend1</i>	is parameter of Person type.
<i>friend2</i>	is parameter of Person type.

## 7.6.3 Member Function Documentation

### 7.6.3.1 equals()

```
boolean relationships.Relationship.equals (
    Object o )
```

This method compares this object with object given in parameter. It overrides default method and allows us to use '=' operator.


#### Parameters

<i>o</i>	is an object of undefined type
----------	--------------------------------

**Returns**

boolean

Here is the call graph for this function:

**7.6.3.2 getFriend1()**


```
Person relationships.Relationship.getFriend1 ( )
```

Getter for a friend1 field.

**Returns**

object of Person type.

Here is the caller graph for this function:



### 7.6.3.3 getFriend2()


```
Person relationships.Relationship.getFriend2 ( )
```

Getter for a friend2 field.

#### Returns

object of Person type.

Here is the caller graph for this function:



### 7.6.3.4 hashCode()


```
int relationships.Relationship.hashCode ( )
```

This method overrides default method and returns the integer hash code value of the object.

#### Returns

integer

Here is the call graph for this function:



### 7.6.3.5 setFriend1()

```
void relationships.Relationship.setFriend1 (
    Person friend1 )
```

Setter for a friend1 field.

## Parameters

<i>friend1</i>	is parameter of Person type.
----------------	------------------------------

**7.6.3.6 setFriend2()**

```
void relationships.Relationship.setFriend2 (
    Person friend2 )
```

Setter for a friend2 field.

## Parameters

<i>friend2</i>	is parameter of Person type.
----------------	------------------------------

**7.6.3.7 toString()**

```
String relationships.Relationship.toString ( )
```

This method returns a string representation of this object.

## Returns

string

Here is the call graph for this function:



The documentation for this class was generated from the following file:

- `D:/Projekty/DSA_ehu_JavaProject/src/relationships/Relationship.java`

## 7.7 relationships.Relationships Class Reference

### Public Member Functions

- [Relationships](#) ()
- List< [Relationship](#) > [getRelations](#) ()
- void [addRelationship](#) (String list, [People](#) ppl)
- String [toString](#) ()
- void [writeToFile](#) (String filename) throws IOException
- List< [Relationship](#) > [findRelationshipsById](#) (String id)
- void [deleteRelationship](#) ([Relationship](#) r)
- [Relationship](#) [findRelationshipsByIds](#) (String id1, String id2)
- void [printAllRelationships](#) ()

### Static Public Attributes

- static final String [FIRST\\_LINE\\_RELATIONSHIPS](#) = "friend1,friend2\n"

### 7.7.1 Constructor & Destructor Documentation

#### 7.7.1.1 Relationships()

```
relationships.Relationships.Relationships ( )
```

Constructor for a [Relationships](#) class.

### 7.7.2 Member Function Documentation

#### 7.7.2.1 addRelationship()


```
void relationships.Relationships.addRelationship (
    String list,
    People ppl )
```

This method check if relationship for two people exists. If not - create relationship between two people and add this relationship to list of relationships.


#### Parameters

<i>list</i>	This parameter is string list which consists two user IDs.
<i>ppl</i>	This parameter is People type object which have list of all users

Here is the call graph for this function:



Here is the caller graph for this function:



### 7.7.2.2 deleteRelationship()

```
void relationships.Relationships.deleteRelationship (
    Relationship r )
```


Removes passed relationship from the list of relationships

#### Parameters

<i>r</i>	Relation
----------	----------



Here is the caller graph for this function:



### 7.7.2.3 findRelationshipsById()

```
List< Relationship > relationships.Relationships.findRelationshipsById (
    String id )
```

This method finds every relationship containing passed id


#### Parameters

<i>id</i>	String
-----------	--------

#### Returns

List<Relationship> List of relationships containing that id

Here is the caller graph for this function:



### 7.7.2.4 findRelationshipsByIds()

```
Relationship relationships.Relationships.findRelationshipsByIds (
    String id1,
    String id2 )
```

This method finds relationship containing passed IDs


**Parameters**

<i>id1</i>	String
<i>id2</i>	String

**Returns**

[Relationship](#) containing passed IDs

Here is the caller graph for this function:

**7.7.2.5 getRelations()**

```
List< Relationship > relationships.Relationships.getRelations ( )
```

Getter for a relations field.


**Returns**

list of [Relationship](#) objects


**7.7.2.6 printAllRelationships()**

```
void relationships.Relationships.printAllRelationships ( )
```

This method prints out every relationship stored in the program Here is the call graph for this function:



Here is the caller graph for this function:



### 7.7.2.7 toString()


```
String relationships.Relationships.toString ( )
```

This method overrides default method and returns a string representation of this object.

#### Returns

string

Here is the caller graph for this function:



### 7.7.2.8 writeToFile()

```
void relationships.Relationships.writeToFile (
    String filename ) throws IOException
```

This method writes string to given file name.


#### Parameters

<i>filename</i>	string
-----------------	--------


**Exceptions**

<i>IOException</i>	This throws could occur when writing to a file
--------------------	--

Here is the call graph for this function:



Here is the caller graph for this function:

**7.7.3 Member Data Documentation****7.7.3.1 FIRST\_LINE\_RELATIONSHIPS**

```
final String relationships.Relationships.FIRST_LINE_RELATIONSHIPS = "friend1,friend2\n" [static]
```

The documentation for this class was generated from the following file:

- [D:/Projekty/DSA\\_ehu\\_JavaProject/src/relationships/Relationships.java](#)

**7.8 UnitTests Class Reference****Classes**

- class **FileHandlingTest**
- class **MenuTests**
- class **MilestoneTest**
- class **PeopleTest**
- class **PersonTest**
- class **RelationshipsTest**

## Public Member Functions

- void [done](#) ()

### 7.8.1 Member Function Documentation

#### 7.8.1.1 done()

```
void UnitTests.done ( )
```

The documentation for this class was generated from the following file:

- D:/Projekty/DSA\_ehu\_JavaProject/src/[UnitTests.java](#)



## Chapter 8

# File Documentation

### 8.1 D:/Projekty/DSA\_ehu\_JavaProject/src/fileHandling/FileHandling.java File Reference

#### Classes

- class [fileHandling.FileHandling](#)

#### Packages

- package [fileHandling](#)

### 8.2 D:/Projekty/DSA\_ehu\_JavaProject/src/Menu.java File Reference

#### Classes

- class [Menu](#)

### 8.3 D:/Projekty/DSA\_ehu\_JavaProject/src/people/People.java File Reference

#### Classes

- class [people.People](#)

#### Packages

- package [people](#)

## 8.4 D:/Projekty/DSA\_ehu\_JavaProject/src/people/Person.java File Reference

### Classes

- class [people.Person](#)

### Packages

- package [people](#)

## 8.5 D:/Projekty/DSA\_ehu\_JavaProject/src/people/Quicksort.java File Reference

### Classes

- class [people.Quicksort](#)

### Packages

- package [people](#)

## 8.6 D:/Projekty/DSA\_ehu\_JavaProject/src/relationships/↔ Relationship.java File Reference

### Classes

- class [relationships.Relationship](#)

### Packages

- package [relationships](#)

## 8.7 D:/Projekty/DSA\_ehu\_JavaProject/src/relationships/↔ Relationships.java File Reference

### Classes

- class [relationships.Relationships](#)



## Packages

- package [relationships](#)

## 8.8 D:/Projekty/DSA\_ehu\_JavaProject/src/UnitTests.java File Reference

### Classes

- class [UnitTests](#)
- class **UnitTests.MenuTests**
- class **UnitTests.FileHandlingTest**
- class **UnitTests.PeopleTest**
- class **UnitTests.PersonTest**
- class **UnitTests.RelationshipsTest**
- class **UnitTests.RelationshipsTest.RelationTest**
- class **UnitTests.MilestoneTest**



# Index

addPersonFromString  
    people.People, 18  
addRelationship  
    relationships.Relationships, 49  
anySymbolLineFormatter  
    people.People, 19  
D:/Projekty/Dsa\_ehu\_JavaProject/src/fileHandling/FileHandling.java, 57  
D:/Projekty/Dsa\_ehu\_JavaProject/src/Menu.java, 57  
D:/Projekty/Dsa\_ehu\_JavaProject/src/people/People.java, getBirthdate 57  
D:/Projekty/Dsa\_ehu\_JavaProject/src/people/Person.java, getBirthplace 58  
D:/Projekty/Dsa\_ehu\_JavaProject/src/people/Quicksort.java, getFilms 58  
D:/Projekty/Dsa\_ehu\_JavaProject/src/relationships/Relationships.java, getFriends 58  
D:/Projekty/Dsa\_ehu\_JavaProject/src/relationships/Relationships.java, getFriends 58  
D:/Projekty/Dsa\_ehu\_JavaProject/src/UnitTests.java, 59  
dashLineFormatter  
    people.People, 19  
deleteRelationship  
    relationships.Relationships, 50  
done  
    UnitTests, 55  
equals  
    people.Person, 35  
    relationships.Relationship, 45  
fileHandling, 11  
fileHandling.FileHandling, 13  
    readFile, 13  
    writeToFile, 14  
fillTheClasses  
    people.People, 20  
findMatchesByFile  
    people.People, 20  
findPeopleBornBetween  
    people.People, 21  
findPeopleByBirthplace  
    people.People, 22  
findPeopleByHome  
    people.People, 22  
findPersonById  
    people.People, 23  
findPersonBySurname  
    people.People, 24  
findRelationshipsById  
    relationships.Relationships, 51  
findRelationshipsByIds  
    relationships.Relationships, 51  
FIRST\_LINE\_PEOPLE  
    people.People, 34  
FIRST\_LINE\_RELATIONSHIPS  
    relationships.Relationships, 54  
getGender  
    people.Person, 36  
getGroupCode  
    people.Person, 36  
getHome  
    people.Person, 37  
getIdPerson  
    people.Person, 37  
getLastName  
    people.Person, 38  
getName  
    people.Person, 39  
getPeople  
    people.People, 24  
getRelations  
    relationships.Relationships, 52  
getStudiedAt  
    people.Person, 39  
getWorkplaces  
    people.Person, 40  
hashCode  
    people.Person, 40  
    relationships.Relationship, 47  
main  
    Menu, 15  
Menu, 15  
    main, 15  
    menu, 16

- menu
  - Menu, 16
- People
  - people.People, 18
- people, 11
- people.People, 17
  - addPersonFromString, 18
  - anySymbolLineFormatter, 19
  - dashLineFormatter, 19
  - fillTheClasses, 20
  - findMatchesByFile, 20
  - findPeopleBornBetween, 21
  - findPeopleByBirthplace, 22
  - findPeopleByHome, 22
  - findPersonById, 23
  - findPersonBySurname, 24
  - FIRST\_LINE\_PEOPLE, 34
  - getPeople, 24
  - People, 18
  - printAllClasses, 24
  - printAllPeople, 25
  - printPeopleBornBetween, 25
  - printPeopleByBirthplace, 26
  - printPeopleByHome, 27
  - printRelationshipsByLastname, 28
  - profiles, 34
  - quicksortByBirthplaceSurnameAndName, 29
  - removePersonById, 29
  - setPeople, 30
  - sortByBirthplaceSurnameAndName, 30
  - sortBySurnameAndName, 31
  - sortClasses, 32
  - sortPeopleByMovies, 32
  - writeToFile, 33
- people.Person, 34
  - equals, 35
  - getBirthdate, 36
  - getBirthplace, 36
  - getFilms, 37
  - getGender, 37
  - getGroupCode, 37
  - getHome, 38
  - getIdPerson, 38
  - getLastname, 38
  - getName, 39
  - getStudiedAt, 39
  - getWorkplaces, 40
  - hashCode, 40
  - Person, 35
  - setBirthdate, 40
  - setBirthplace, 41
  - setFilms, 41
  - setGender, 41
  - setGroupCode, 41
  - setHome, 42
  - setIdPerson, 42
  - setLastname, 42
  - setName, 43
  - setStudiedAt, 43
  - setWorkplaces, 43
  - toString, 43
- people.Quicksort, 44
  - sort, 44
- Person
  - people.Person, 35
- printAllClasses
  - people.People, 24
- printAllPeople
  - people.People, 25
- printAllRelationships
  - relationships.Relationships, 52
- printPeopleBornBetween
  - people.People, 25
- printPeopleByBirthplace
  - people.People, 26
- printPeopleByHome
  - people.People, 27
- printRelationshipsByLastname
  - people.People, 28
- profiles
  - people.People, 34
- quicksortByBirthplaceSurnameAndName
  - people.People, 29
- readFile
  - fileHandling.FileHandling, 13
- Relationship
  - relationships.Relationship, 45
- Relationships
  - relationships.Relationships, 49
- relationships, 11
- relationships.Relationship, 44
  - equals, 45
  - getFriend1, 46
  - getFriend2, 46
  - hashCode, 47
  - Relationship, 45
  - setFriend1, 47
  - setFriend2, 48
  - toString, 48
- relationships.Relationships, 49
  - addRelationship, 49
  - deleteRelationship, 50
  - findRelationshipsById, 51
  - findRelationshipsByIds, 51
  - FIRST\_LINE\_RELATIONSHIPS, 54
  - getRelations, 52
  - printAllRelationships, 52
  - Relationships, 49
  - toString, 53
  - writeToFile, 53
- removePersonById
  - people.People, 29
- setBirthdate
  - people.Person, 40

- setBirthplace
  - people.Person, [41](#)
- setFilms
  - people.Person, [41](#)
- setFriend1
  - relationships.Relationship, [47](#)
- setFriend2
  - relationships.Relationship, [48](#)
- setGender
  - people.Person, [41](#)
- setGroupCode
  - people.Person, [41](#)
- setHome
  - people.Person, [42](#)
- setIdPerson
  - people.Person, [42](#)
- setLastname
  - people.Person, [42](#)
- setName
  - people.Person, [43](#)
- setPeople
  - people.People, [30](#)
- setStudiedAt
  - people.Person, [43](#)
- setWorkplaces
  - people.Person, [43](#)
- sort
  - people.Quicksort, [44](#)
- sortByBirthplaceSurnameAndName
  - people.People, [30](#)
- sortBySurnameAndName
  - people.People, [31](#)
- sortClasses
  - people.People, [32](#)
- sortPeopleByMovies
  - people.People, [32](#)
- toString
  - people.Person, [43](#)
  - relationships.Relationship, [48](#)
  - relationships.Relationships, [53](#)
- UnitTests, [54](#)
  - done, [55](#)
- writeToFile
  - fileHandling.FileHandling, [14](#)
  - people.People, [33](#)
  - relationships.Relationships, [53](#)