Runtime - IDE

Task Status

Task Code

Task Runner

Task Return (HTML View)

Task Output (Log)

Task View

```
task uid = 4f1e3536939e1e1f (28776 | demo/demo_5_1_formatter) [Fork]
task status = close
task schedule_at =
task last_run = 2022-06-06T07:17:43.856Z
task last_save = 2022-06-06T07:17:42.618Z
task last_update = 2022-06-06T07:17:45.152Z


cmd: [Save] [Run]
```

Task Code

```
 1   __TASK_NAME__ = "demo/demo_5_1_formatter"
 2   __ENV__ = 'ruby3'
 3
 4
 5   def main()
 6       return [1,2,3,4]
 7   end
 8
 9   def render_html()
10   '''<h1>output</h1>
11   <% @raw_ret.each do |item| %>
12       <li><%= item %></li>
13   <% end %>
14
15   <h1>counter</h1>
16   <div id="counter"></div>
17   '''
18   end
19
20   def render_js_rb()
21   '''
22   counter = 0
23
24   $$[:setInterval].call(->{ $document.at_css("#counter").inner_html="tick #{counter}"; counter=counter+1 },1000)
25   '''
26   end
27
28
```

Task Runner

```
ruby3.panworker-2_7ebf
```

Task Return

[view]

output

- 1
- 2
- 3
- 4

counter

tick 6

Task Output

```
2022-06-06 07:17:43 +0000 runner ruby3.panworker-2_7ebf take task 28776 : demo/demo_5_1_formatter
2022-06-06 07:17:44 +0000 == begin run ==
2022-06-06 07:17:45 +0000 == end run ==
```

Runtime - Task Cluster

| Docker | Docker | Docker |
| Docker | Docker | Docker |

| Docker | Docker | Docker |
| Docker | Docker | Docker |

| Docker | Docker | Docker |
| Docker | Docker | Docker |

任务队列   任务持久化层

业务

任务的存储信息

| ID | Code 代码 | Status 状态 | Output 日志 | Runner 运行节点 | Params 输入参数 |