Latex Symbols Template

Short symbol commands for \LaTeX

version: 2.0.13

Arindam Bose

March 12, 2020

Contents

1	Installation and usage:	3									
2	Packages used:										
3	Available environments:										
4	Extras in algorithms:	3									
5	Tables of usage:	4									
	5.1 Lower case bold English alphabets	4									
	5.2 Upper case bold English alphabets	4									
	5.3 Bold Greek alphabets	4									
	5.4 Mathbf lower case English alphabets	4									
	5.5 Mathbf upper case English alphabets	5									
	5.6 Caligraphy upper case English alphabets	5									
	5.7 Numbers	5									
	5.8 Sets and notations	5									
	5.9 Matrix terms	5									
	5.10 Misc	6									
	5.11 Basic text colors	6									
	5.12 Special colors that comes with [dvipsnames] option in xcolor package	7									
6	Theorem-like environments	8									
	6.1 Theorems	8									
	6.2 Definitions	8									
	6.3 Propositions	8									
	6.4 Lemmas	8									
	6.5 Corollaries	8									
	6.6 Examples	8									
	6.7 Remarks	9									
7	Algorithm	10									
8	Underbrace inside a matrix environment	12									

1 Installation and usage:

- 1. Download the symbols.tex file and put is in the same folder as that of the main .tex file.
- 2. Add \input{symbols.tex} after all \usepackage{} headers in the main .tex file.
- 3. Refer to test.tex and test.pdf for further help.
- 4. Note that $[\cdot]$: Optional argument and $\{\cdot\}$: Mandatory argument

2 Packages used:

Thanks to these packages. They are all included and no need to include them manually. Other packages might have issues with it.

- 1. algorithm
- 2. amsmath
- 3. amsthm
- 4. amssymb
- 5. dsfont
- 6. algpseudocode
- 7. thmtools
- 8. xcolor

3 Available environments:

- 1. Theorem
- 2. Definition
- 3. Proposition
- 4. Lemma
- 5. Corollary
- 6. Example
- 7. Remark

See Section 6 for usage information.

4 Extras in algorithms:

If you use algorithmic inside algorithm environment,

- 1. All the following introductory commands are valid
 - using \Require will result into Require:
 - using \Ensure will result into Ensure:
 - using \Input will result into Input:
 - using \Init will result into Initialize:
 - using \Output will result into Output:
- 2. \Print and \To commands are compatible with required packages

See Section 7 for usage information.

5 Tables of usage:

5.1 Lower case bold English alphabets

Syntax	Description	Syntax	Description	Syntax	Description	Syntax	Description
\ba	a	\bb	b	\bc	c	\bd	d
\be	e	\bdf	f	\bg	g	\bh	h
\bi	i	\bj	j	\bk	k	\bl	l
\bm	m	\bn	n	\bo	o	\bp	p
\bq	$oldsymbol{q}$	\br	r	\bs	s	\bt	t
\bu	u	\bv	\boldsymbol{v}	\bw	w	\bx	\boldsymbol{x}
\by	\boldsymbol{y}	\bz	z				

5.2 Upper case bold English alphabets

Syntax	Description	Syntax	Description	Syntax	Description	Syntax	Description
\bA	\boldsymbol{A}	\bB	B	\bC	C	\bD	D
\bE	$oldsymbol{E}$	\bF	$oldsymbol{F}$	\bG	G	\bH	H
\bI	I	\bJ	J	\bK	K	\bL	L
\bM	M	\bN	N	\b0	0	\bP	P
\bQ	$oldsymbol{Q}$	\bR	R	\bS	S	\bT	T
\bU	$oldsymbol{U}$	\bV	V	/bW	W	\bX	X
\bY	Y	\bZ	Z				

5.3 Bold Greek alphabets

Syntax	Description	Syntax	Description	Syntax	Description
\balpha	α	\bbeta	β	\bgamma	γ
\bGamma	Γ	\bdelta	δ	\bDelta	Δ
\bepsilon	ϵ	\bvarepsilon	ε	\bzeta	ζ
\bdeta	η	\btheta	θ	\bvartheta	ϑ
\bTheta	Θ	\biota	ι	\bkappa	κ
\blambda	λ	\bLambda	Λ	\bmu	μ
\bnu	ν	\bxi	ξ	\bXi	Ξ
\bpi	π	\bPi	П	\brho	ρ
\bvarrho	ϱ	\bsigma	σ	\bSigma	Σ
\btau	au	\bupsilon	$oldsymbol{v}$	\bUpsilon	Υ
\bphi	ϕ	\bvarphi	φ	\bPhi	Φ
\bchi	χ	\bpsi	$ \psi $	\bPsi	Ψ
\bomega	ω	\b0mega	Ω		

5.4 Mathbf lower case English alphabets

Syntax	Description	Syntax	Description	Syntax	Description	Syntax	Description
\mba	a	\mbb	b	\mbc	c	\mbd	d
\mbe	\mathbf{e}	\mbf	f	\mbg	g	\mbh	h
\mbi	i	\mbj	j	\mbk	k	\mbl	1
\mbm	\mathbf{m}	\mbn	n	\mbo	o	\mbp	p
\mbq	${f q}$	\mbr	r	\mbs	s	\mbt	t
\mbu	u	\mbv	\mathbf{v}	\mbw	w	\mbx	x
\mby	\mathbf{y}	\mbz	\mathbf{z}				

5.5 Mathbf upper case English alphabets

Syntax	Description	Syntax	Description	Syntax	Description	Syntax	Description
\mbA	A	\mbB	В	\mbC	C	\mbD	D
\mbE	${f E}$	\mbF	\mathbf{F}	\mbG	G	\mbH	H
\mbI	I	\mbJ	J	\mbK	K	\mbL	\mathbf{L}
\mbM	\mathbf{M}	\mbN	\mathbf{N}	\mb0	О	\mbP	P
\mbQ	${f Q}$	\mbR	\mathbf{R}	\mbS	\mathbf{S}	\mbT	\mathbf{T}
\mbU	\mathbf{U}	\mbV	\mathbf{V}	\mbW	\mathbf{W}	\mbX	X
\mbY	\mathbf{Y}	\mbZ	${f Z}$				

5.6 Caligraphy upper case English alphabets

Syntax	Description	Syntax	Description	Syntax	Description	Syntax	Description
\calA	\mathcal{A}	\calB	\mathcal{B}	\calC	\mathcal{C}	\calD	\mathcal{D}
\calE	\mathcal{E}	\calF	\mathcal{F}	\calG	\mathcal{G}	\calH	\mathcal{H}
\calI	\mathcal{I}	\calJ	$\mathcal J$	\calK	\mathcal{K}	\calL	\mathcal{L}
\calM	\mathcal{M}	\calN	\mathcal{N}	\cal0	O	\calP	\mathcal{P}
\calQ	Q	\calR	\mathcal{R}	\calS	\mathcal{S}	\calT	$\mid \mathcal{T} \mid$
\calU	\mathcal{U}	\calV	\mathcal{V}	\calW	\mathcal{W}	\calX	\mathcal{X}
\calY	\mathcal{Y}	\calZ	\mathcal{Z}				

5.7 Numbers

Syntax	Description	Syntax	Description
\bzero	0	\bone	1

5.8 Sets and notations

Syntax	Description	Syntax	Description	Syntax	Description
\binaryB[N]	\mathbb{B}^N	\complexC[N]	\mathbb{C}^N	\expecE{\bx}	$\mathbb{E}\left\{ oldsymbol{x} ight\}$
\naturalN[N]	\mathbb{N}^N	\probP{\bx}	$\mathbb{P}\mathrm{r}\left\{oldsymbol{x} ight\}$	\rationalQ[N]	\mathbb{Q}^N
\realR[N]	\mathbb{R}^N	\realRp[N]	\mathbb{R}^N_+	\realRn[N]	\mathbb{R}^N
\integerZ[N]	\mathbb{Z}^N		'		

5.9 Matrix terms

Syntax	Description	Syntax	Description	Syntax	Description
\tr{X}	$\operatorname{Tr}\left(X\right)$	\vec{X}	$\operatorname{vec}(X)$	\diag{X}	$\operatorname{diag}\left(X\right)$
\Diag{\bx}	$\mathrm{Diag}\left(oldsymbol{x} ight)$	\bdiag{X}	$\mathbf{diag}\left(X\right)$	\cov{\bx}	$\operatorname{cov}\left(oldsymbol{x} ight)$
\Cov{X}	Cov(X)	\bcov{\bx}	$\mathbf{cov}\left(oldsymbol{x} ight)$		

5.10 Misc.

Syntax	Description	Syntax	Description	Syntax	Description
\asin{x}	$\sin^{-1}(x)$	\acos{x}	$\cos^{-1}(x)$	\atan{x}	$\tan^{-1}(x)$
\acsc{x}	$\csc^{-1}(x)$	\asec{x}	$\sec^{-1}(x)$	\acot{x}	$\cot^{-1}(x)$
\implies	\Rightarrow	\half	$\frac{1}{2}$	\roothalf	$\frac{1}{\sqrt{2}}$
\third	$\frac{1}{3}$	\quarter	$\frac{1}{4}$	\fourth	$\frac{1}{4}$
\fifth	$\frac{1}{5}$	\threequarter	$\frac{3}{4}$	\ejomg[k]	$e^{jk\omega}$
\ejnomg[k]	$e^{-jk\omega}$	\zinv[k]	z^{-k}	\sgn{x}	$\operatorname{sgn}(x)$
\sign{x}	sign(x)	\csign{x}	csign (x)	X\deg	X°
\Oh{N}	$\mathcal{O}\left(N ight)$	\oh{N}	o(N)	\st	s.t.
/ow	otherwise	\ew	elsewhere	\eg	e.g.
\ie	i.e.	\etal	et al.	\etc	etc.
\viz	viz.	\d{y}	dy	\conv	*
\wrt	w.r.t.	\deriv[k]{\xi}{x}	$\frac{d^k \xi}{dx^k}$	\parderiv[k]{\xi}{x}	$\frac{\partial^k \xi}{\partial x^k}$

5.11 Basic text colors

Syntax	Description	Syntax	Description	Syntax	Description
\white{text}		\black{text}	text	\red{text}	text
\green{text}	text	\blue{text}	text	\cyan{text}	text
\magenta{text}	text	\yellow{text}	text		

5.12 Special colors that comes with [dvipsnames] option in xcolor package

Syntax	Description	Syntax	Description	Syntax	Description
\Apricot{text}	text	\Aquamarine{text}	text	\Bittersweet{text}	text
\Black{text}	text	\Blue{text}	text	\BlueGreen{text}	text
\BlueViolet{text}	text	\BrickRed{text}	text	\Brown{text}	text
\BurntOrange{text}	text	\CadetBlue{text}	text	\CarnationPink{text}	text
\Cerulean{text}	text	\CornflowerBlue{text}	text	\Cyan{text}	text
\Dandelion{text}	text	\DarkOrchid{text}	text	\Emerald{text}	text
\ForestGreen{text}	text	\Fuchsia{text}	text	\Goldenrod{text}	text
\Gray{text}	text	\Green{text}	text	\GreenYellow{text}	text
\JungleGreen{text}	text	\Lavender{text}	text	\LimeGreen{text}	text
\Magenta{text}	text	\Mahogany{text}	text	\Maroon{text}	text
\Melon{text}	text	\MidnightBlue{text}	text	\Mulberry{text}	text
\NavyBlue{text}	text	\OliveGreen{text}	text	\Orange{text}	text
\OrangeRed{text}	text	\Orchid{text}	text	\Peach{text}	text
\Periwinkle{text}	text	\PineGreen{text}	text	\Plum{text}	text
\ProcessBlue{text}	text	\Purple{text}	text	\RawSienna{text}	text
\Red{text}	text	\RedOrange{text}	text	\RedViolet{text}	text
\Rhodamine{text}	text	\RoyalBlue{text}	text	\RoyalPurple{text}	text
\RubineRed{text}	text	\Salmon{text}	text	\SeaGreen{text}	text
\Sepia{text}	text	\SkyBlue{text}	text	\SpringGreen{text}	text
\Tan{text}	text	\TealBlue{text}	text	\Thistle{text}	text
\Turquoise{text}	text	\Violet{text}	text	\VioletRed{text}	text
\White{text}		\WildStrawberry{text}	text	\Yellow{text}	text
\YellowGreen{text}	text	\YellowOrange{text}	text		

6 Theorem-like environments

6.1 Theorems

```
\begin{theorem}\label{thm:1}
    \mylipsum
\end{theorem}
```

Theorem 1. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Praesent luctus sem nibh, et venenatis mauris aliquet et. Sed velit nisl.

6.2 Definitions

```
\begin{definition}\label{def:1}
   \mylipsum
\end{definition}
```

Definition 1. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Praesent luctus sem nibh, et venenatis mauris aliquet et. Sed velit nisl.

6.3 Propositions

```
\begin{proposition}\label{prop:1}
    \mylipsum
\end{proposition}
```

Proposition 1. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Praesent luctus sem nibh, et venenatis mauris aliquet et. Sed velit nisl.

6.4 Lemmas

```
\begin{lemma}\label{lem:1}
    \mylipsum
\end{lemma}
```

Lemma 1. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Praesent luctus sem nibh, et venenatis mauris aliquet et. Sed velit nisl.

6.5 Corollaries

```
\begin{corollary}\label{cor:1}
    \mylipsum
\end{corollary}
```

Corollary 1. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Praesent luctus sem nibh, et venenatis mauris aliquet et. Sed velit nisl.

6.6 Examples

```
\begin{example}\label{exm:1}
    \mylipsum
\end{example}
```

Example 1. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Praesent luctus sem nibh, et venenatis mauris aliquet et. Sed velit nisl.

6.7 Remarks

\begin{remark}\label{rem:1}
 \mylipsum
\end{remark}

Remark 1. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Praesent luctus sem nibh, et venenatis mauris aliquet et. Sed velit nisl.

Referencing

Lorem ipsum dolor sit amet \underline{Theorem \ref{thm:1}}, consectetur adipiscing

elit. In vel orci id est porta laoreet at non nisl. Pellentesque habitant morbi

tristique senectus et netus et malesuada fames ac turpis egestas

\underline{Definition \ref{def:1}}. Maecenas posuere augue nec turpis pretium

faucibus \underline{Proposition \ref{prop:1}}. Pellentesque dui massa, facilisis

eu placerat sit amet, tincidunt sit amet nisl. In pellentesque molestie ipsum at

dictum \underline{Lemma \ref{lem:1}}. Curabitur libero metus, eleifend porta

finibus eu, sagittis nec lorem. Maecenas ante quam, faucibus cursus erat vel,

accumsan dictum eros \underline{Corollary \ref{cor:1}}. Quisque commodo libero

quis enim laoreet congue. Quisque sed egestas quam. In posuere malesuada mollis

\underline{Example \ref{exm:1}}.

Lorem ipsum dolor sit amet <u>Theorem 1</u>, consectetur adipiscing elit. In vel orci id est porta laoreet at non nisl. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas <u>Definition 1</u>. Maecenas posuere augue nec turpis pretium faucibus <u>Proposition 1</u>. Pellentesque dui massa, facilisis eu placerat sit amet, tincidunt sit amet nisl. In pellentesque molestie ipsum at dictum <u>Lemma 1</u>. Curabitur libero metus, eleifend porta finibus eu, sagittis nec lorem. Maecenas ante quam, faucibus cursus erat vel, accumsan dictum eros <u>Corollary 1</u>. Quisque commodo libero quis enim laoreet congue. Quisque sed egestas quam <u>Remark 1</u>. In posuere malesuada mollis Example 1.

7 Algorithm

```
\begin{algorithm}[H]
    \caption{\textsc{ExampleAlgorithm}}\label{alg:1}
    \begin{algorithmic}[1]
        \Require \texttt{var1}, \texttt{var2}, $N$
        \Ensure \texttt{var1} $\gets$ 1, \texttt{var2} $\gets$ 1, \texttt{flag} $\gets$ 0
        \Input \texttt{var1}, \texttt{var2}, $N$
        \Init \texttt{var1} $\gets$ 1, \texttt{var2} $\gets$ 1, \texttt{flag} $\gets$ 0
        \Output \texttt{var3}
        \Comment All five commands are equally valid
        \Repeat \Comment{Example: \texttt{repeat}}
            \State \textsc{SomeSteps}
        \Until \textsc{SomeConditionIsMet}
        \For{\$i=0\$ \To \$10\$} \Comment{Example: \texttt{for} loop}
            \State \textsc{SomeStepsForLoop}
        \EndFor
        \While{\texttt{flag}} \Comment{Example: \texttt{while} loop}
            \State \texttt{var1} $\gets$ \textsc{DoSomeShit}
            \State \texttt{var2} $\gets$ \textsc{DoSomeMoreShit}
        \EndWhile
        \Loop \Comment{Example: \texttt{loop}}
            \State \textsc{SomeInfiniteLoopStuff}
        \EndLoop
        \If{\texttt{var1} $< N$}\Comment{Example: \texttt{if-else if- else}}
            \State \texttt{flag} $\gets 1$
        \ElsIf{\texttt{var1} $= N$}
            \State \texttt{flag} $\gets 0$
        \Else
            \State \texttt{var3} $\gets$ \texttt{var1} $+$ \texttt{var2}
        \EndIf
        \State \Print{some results}
        \State \Return \texttt{var3}
    \end{algorithmic}
\end{algorithm}
```

Algorithm 1 ExampleAlgorithm

```
Require: var1, var2, N
Ensure: var1 \leftarrow 1, var2 \leftarrow 1, flag \leftarrow 0
Input: var1, var2, N
Initialize: var1 \leftarrow 1, var2 \leftarrow 1, flag \leftarrow 0
Output: var3
                                                                                         \triangleright All five commands are equally valid
 1: repeat
                                                                                                              \triangleright Example: repeat
        SOMESTEPS
 3: until SomeConditionIsMet
 4: for i = 0 to 10 do
                                                                                                            ▷ Example: for loop
        SOMESTEPSFORLOOP
 6: end for
 7: while flag do

ightharpoonup Example: while loop
        \mathtt{var1} \leftarrow \mathrm{DoSomeShit}
        var2 \leftarrow DoSomeMoreShit
10: end while
11: loop
                                                                                                                 ▷ Example: loop
        {\bf Some Infinite Loop Stuff}
12:
13: end loop
14: if var1 < N then
                                                                                                ▷ Example: if-else if- else
        flag \leftarrow 1
15:
16: else if var1 = N then
        \texttt{flag} \leftarrow 0
17:
18: else
19:
        \mathtt{var3} \leftarrow \mathtt{var1} + \mathtt{var2}
20: end if
21: print some results
22: return var3
```

8 Underbrace inside a matrix environment

Short usage: $\mbox{undermat{arg1}{arg2}}$ For example:

$$oldsymbol{J}_k = egin{bmatrix} 0 & \dots & 0 & 1 & \dots & 0 \ dots & & & \ddots & & \ 0 & \dots & 0 & \dots & & \ \end{pmatrix}$$

Code:

```
\begin{align*}
\bJ_k =
   \begin{bmatrix}
                   & \dots & 0
                                 & 1
                                       & \dots & 0 \\
                                       & \ddots & \\
      \vdots
                   & &
                                 &
                                          & 1 \\
                                 &
      \undermat{0
                   & \dots & 0}{k} & \dots &
                                               & \\
   \end{bmatrix}
\end{align*}
```