

## **Technical operators**

Vinga Ship Management AB Donsö Hamnväg 45 430 82 Donsö | Sweden

Phone: +46 31-97 33 92 | Fax: +46 31-97 33 99

Mail: technical@vingaship.se

## **Commercial Operators**

Swedia Tankerfrakt AB Donsö Hamnväg 45 430 82 Donsö | Sweden

Phone: +46 31-97 33 92 | Fax: +46 31-97 33 99

Mail: chartering@swedia.se

70.00	D-16
L.O.A	Delivered
<b>L.P.P.</b>	<b>Machinery</b>
<b>Beam</b> 12,75 m	AuxiliariesMAN 2x D2866E/LXE (243kW)
<b>Draft</b> 5,19 m (in ballast 4,00 m)	Bowthruster Jastram BU40F (250kW)
Moulded depth6,20 m	
<b>SDWT</b> 2 653	Speed & Consumption
<b>WDWT</b> 2 560	Ballast/Laden 11,5/10,5 kn 4,2/5,2 t/d MDO/MGO
<b>TPCM</b> 8,48	Idle/Working 0,8/1,5 t/d MGO.
<b>Gross</b>	Boiler abt. 1,0 t/d MDO to maintain cargo temp.
Net	
<b>SBT</b>	Cargo tank capacity 2 670 m³ (2618 m³ 98%)
Keel to top of mast26,60 m	Cargo arrangement 10 WT Jotun Tankguard
Bow to cent of manifold(load/disch)35,5 m/43,0 m	CoatingSpecial Epoxy
	HeatingHot water in steel coils
TypeOil/Product tanker (double hull)	Max loadtemp/Maintain
<b>IMO No.</b>	Cargo pumps1 X Screw (200 m³/h) + 2 Centrifugal
FlagFaroe Island	pumps (2x325 m³/h)
<b>Call Sign</b> OZ2136	Ballast pumps2 X Centrifugal pump (2x100 m³/h)
HomeportTorshavn	Ballast tanks coating Jotamastic Epoxy coated
	Ballast tank capacity1 060 m <sup>3</sup>
ClassGL 100 A5 ESP T3D10 Product Tanker, Machinery	Ballast arrangement
MC Aut.	Cargo control Autronica Tank Radar, high level alarm
Ice-classII (Ice D)	, ,
(	<b>Phone</b> +46 73-371 30 41 or +46 73-371 30 91
BuildersTorlak Shipyard, Tuzla, Turkey	E-mailmaster@vingasafir.swedia.se

Delivered	2000/06
Machinery	MAK 8M20 (1 499kW)
Auxiliaries	MAN 2x D2866E/LXE (243kW)
Bowthruster	Jastram BU40F (250kW)

## **Speed & Consumption**

Cargo tank capacity	2 670 m³ (2618 m³ 98%)
Cargo arrangement	10 WT Jotun Tankguard
Coating	Special Epoxy
Heating	Hot water in steel coils
Max loadtemp/Maintain	
Cargo pumps1 X Sci	rew (200 m <sup>3</sup> /h) + 2 Centrifugal
pumps (2x325 m³/h)	
Ballast pumps2 X C	Centrifugal pump (2x100 m <sup>3</sup> /h)
Ballast tanks coating	Jotamastic Epoxy coated
Ballast tank capacity	1 060 m <sup>3</sup>
Ballast arrangement	10 L-shaped WT
	a Tank Radar, high level alarm
Phone+46 73-3	371 30 41 or +46 73-371 30 91
	. 6 . 6 . 1