CreateActivity

Overview

The **CreateActivity** API uses an HTTP **POST** request to create a new activity based on the provided request body. This API can also be used to create a new activity by copying an existing one.

If the **SourceActivity** attributes (such as jurisdiction and product code) match the values in the request—or if they are not specified—the system uses Copy As-Is logic and permissions. If different values are provided, the system applies **Copy With Changes** logic.

A valid user session is required to call this API.

API Endpoints

To use this API, send a POST request to one of the following endpoints, depending on the API version:

- **Version 1**

  {root}URL/Activity/CreateActivity

- **Version 2**

  {root}URL/Activity/v2/CreateActivity?activityID=XXX

  Note: XXX is a placeholder for the identifier of the activity being created.

Request Body (Required)

The **CreateActivityRequestModel** is the request body that's required to create a new activity.

Example

```
{
  "Id": "123e4567-e89b-12d3-a456-426614174000",
  "SourceActivityId": "987e6543-e21b-45d3-b654-123456789abc",
  "ActivityName": "Sample Activity Name",
  "Jurisdiction": 1,
  "ProductCode": "PROD001",
  "ProviderCode": "PRV01",
  "FormTypeCode": 100,
  "FormSubTypeCode": 10,
  "EffectiveDate": "2026-01-01",
  "ExpirationDate": "2027-01-01",
  "DataItems": [
    {
      "DataItemId": "PrimaryContactName",
      "Value": "Jane Doe"
    },
```

2026 Generic Company, Inc. All rights reserved.

```
      {
        "DataItemId": "Channel",
        "Value": "API"
      }
    ],
    "CopyMode": "CopyWithChanges"
  }
  ``
```

Common Fields Explained

Field	Description
Id	Unique identifier for the new activity.
SourceActivityId (optional)	Identifier of an existing activity to copy from.
ActivityName	Display name for the new activity
Jurisdiction	Numeric or coded value representing a regional or regulatory context.
ProductCode	Code identifying the product or offering associated with the activity.
ProviderCode	Identifier for the organization or provider related to the activity.
FormTypeCode / FormSubTypeCode	Codes defining the type and subtype of the activity.
EffectiveDate / ExpirationDate	Date range during which the activity is valid.
DataItems	Key/value pairs used to populate configurable or dynamic fields.
CopyMode (optional)	Indicates how the activity should be copied: • `CopyAsIs` • `CopyWithChanges`

Response

The **CreateActivityResponseModel** is returned upon successful processing of the request.

2026 Generic Company, Inc. All rights reserved.

Example

```
{
  "ActivityId": "123e4567-e89b-12d3-a456-426614174000",
  "Status": "Success",
  "Message": "Activity created successfully.",
  "Warnings": [],
  "Errors": [],
  "CreatedDateUtc": "2026-04-15T05:42:31Z",
  "Activity": {
    "ActivityName": "Sample Activity Name",
    "Jurisdiction": 1,
    "ProductCode": "PROD001",
    "FormTypeCode": 100,
    "CurrentState": "Draft"
  }
}
```

Common Fields Explained

Field	Description
ActivityId	Unique identifier of the newly created activity.
Status	Overall result of the operation (for example, `Success`, `Failure`, `PartialSuccess`).
Message	Human-readable summary of the outcome.
Warnings	Non-fatal issues encountered during processing.
Errors	Error details if the request failed.
CreatedDateUtc	Timestamp indicating whent the activity was created.
Activity (optional summary object)	Snapshot of key attributes of the created activity: • Name • Jurisdiction • Product • Type • Current lifecycle state (for example, `Draft`, `Active`, `Submitted`)

Application Origin Data Item

A system-defined data item called "**APP_ORIGIN**" records how an activity was created.

2026 Generic Company, Inc. All rights reserved.

Creating an Application in the Product's UI

When you create a new application in Generic Product's platform, the APP_ORIGIN data item will have the value of “**Generic Product UI**”.

REST API

When you create an application using REST API, the APP_ORIGIN data item will have the value of "**API**".

SSO/103

When you create a new application with the 103/1228, the APP_ORIGIN data item will have the value of "**Unknown**".

Copying the Activity Through the SourceActivityId Parameter

When you copy an activity by using the SourceActivityId parameter, the APP_ORIGIN data item will have a value of "**API**".

The SourceActivityId identifies the original (source) activity from which a new activity is to be created. It enables the system to reference and pull data from an existing activity when creating a new one. You can use this parameter to copy an activity as-is or copy it with changes applied.

- Copy As-Is:
  - The new activity is created as an exact copy of the source activity.
  - All fields default to the values from the source activity unless explicitly overridden in the request.
  - If the **Name** field is not supplied, it defaults to "**Copy Of [Source Activity Name]**".
- Copy With Changes:
  - The new activity is based on the source activity, but you can override specific fields in the request.
  - Any field not supplied in the request will default to the value from the source activity.

Other App Origins

All other App creation methods displays a value of "**Unknown**".

Errors and Exceptions

Version 1 - Error Conditions

Criteria	Error Message	Status Code
Organization not found in token	Invalid organization	500
Missing or invalid user	No associated user	500

2026 Generic Company, Inc. All rights reserved.

Criteria	Error Message	Status Code
Incomplete user data	User information invalid	500
Null request	Malformed request	500
Missing jurisdiction	Invalid or missing jurisdiction	500
Missing product code	Product code required	500
Insufficient permissions	No permission to copy activity	500
Unsupported form type	Copy not permitted	500

Version 2 - Error Conditions

Criteria	Error Message	Status Code
Organization not found in token	Invalid organization	400
Missing or invalid user	No associated user	400
Incomplete user data	User information invalid	400
Missing jurisdiction	Invalid or missing jurisdiction	500
Missing product code	Product code required	400
Insufficient permissions	Unauthorized	401
Copy As-Is disabled	Operation not allowed	401
Copy With Changes disabled	Operation not allowed	401
Unsupported form type	Copy not permitted	500
Invalid activity type	Activity type not available	400
Attempted form type change during copy	Not allowed	500

2026 Generic Company, Inc. All rights reserved.