



NC SANDING SEALER

4L

PEACOCK PAINTS LIMITED

📍 Plot 56, Sixth street, Industrial Area

✉ P.O Box 9549 Kampala, Uganda.

☎ +256 414 256 518 / 231 721

🕒 +256 700 159 368

@ sales@peacock.co.ug

💻 www.peacock.co.ug

📷 @peacockpaints_ug

📘 Peacock Paints Ltd

✂ @peacockpaintsug

in peacock-paints-ltd



CERTIFIED COMPANY
ISO 9001: 2015
ISO 45001: 2018
ISO 14001: 2015



PRODUCT DESCRIPTION

An Nc, wood care product, formulated to seal off all the pores in the surface. A very quick drying product with special polishing agents that facilitate the filling of the pores whilst sanding, generating a smooth and even surface.

SURFACE PREPARATION

Clean the timber, sand the wood, using a hand or oscillating sander to smoothen the surface.

Remove the dust with Vaccum equipment. Stain the timber if necessary. Mix the sealer with a sync thinner and apply the sealer in 2-3 coats allowing for 20-30 mins between coats. Sand down the first coat before the second is applied with 240 grit abrasive pad or paper.

DILUTION

4 Litres of Paint: 2 Litres of Sync Thinner

COVERAGE

1L/4-6 Sqm

APPLICATION

Brush ,Spray & Immersion.

DRYING TIME

15 Mins (Touch Dry)
30 Mins (Recoatable)

PACK SIZE

1 Litre, 4 Litres

STORAGE

Store this product in a cool dry place, out of reach of children.

DISPOSAL

Dispose of paint at designated waste facilities or community collection events.

FOR PROFESSIONAL USE ONLY.

