



STANDARD EMULSION

20 L

PEACOCK PAINTS LIMITED

📍 Plot 56, Sixth street, Industrial Area

✉ P.O Box 9549 Kampala, Uganda.

☎ +256 414 256 518 / 231 721

📞 +256 700 159 368

@ sales@peacock.co.ug

🌐 www.peacock.co.ug

📷 @peacockpaints_ug

📘 Peacock Paints Ltd

✂ @peacockpaintsug

in peacock-paints-ltd



PRODUCT DESCRIPTION

An acrylic emulsion designed to withstand interior conditions and moderate harsh exterior environments. Suitable for application on both wood and concrete surfaces.

SURFACE PREPARATION

Sand to remove dirt and grease, scrape loose paint, fill cracks with Peacock Undercoat Putty, and sand smoothly once dry.

DILUTION

4 Litres of paint: 1 Litre of Water

COVERAGE

12-15sqm/4Litres

APPLICATION

Brush, roller.

DRYING TIME

Touch Dry: 20-30 Mins

Through Dry: 5 Hrs

PACK SIZE

4 Litres, 20 Litres

STORAGE

Store this product in a cool dry place out of reach of children.

DISPOSAL

Dispose of paint at designated waste facilities or community collection events.

FOR PROFESSIONAL USE ONLY.



WEAR GLOVES



WEAR MASK



EYE PROTECTION



RECYCLABLE