



SUPERMATT EMULSION

MATT EMULSION PAINT

20 L

PEACOCK PAINTS LIMITED

📍 Plot 56, Sixth street, Industrial Area
✉ P.O Box 9549 Kampala, Uganda.
☎ +256 414 256 518 / 231 721
📞 +256 700 159 368
@ sales@peacock.co.ug
💻 www.peacock.co.ug
📱 @peacockpaints_ug
🏢 Peacock Paints Ltd
✖ @peacockpaintsug
🌐 peacock-paints-ltd



PRODUCT DESCRIPTION

An acrylic emulsion with a matt finish, formulated for application on interior and exterior ceiling areas. It can be used on surfaces of wood and cement plaster.

SURFACE PREPARATION

Clean all surfaces, sand them, and prime with Peacock Plaster Primer or Latex Primer Sealer. Fill dents and imperfections with Peacock Undercoat Putty.

DILUTION

4 Litres of Paint: 1 Litre of water

COVERAGE

1L/8-10sqm

APPLICATION

Apply one coat of Peacock Super Matt, allowing one hour of drying time between coats using a paint roller or brush.

DRYING TIME

15-30 mins Touch dry

PACK SIZE

1 Litres, 4 Litres, 20 Litres

STORAGE

Store this product in a cool dry place, out of reach of children.

DISPOSAL

Dispose of paint at designated waste facilities or community collection events.

FOR PROFESSIONAL USE ONLY.



WEAR GLOVES



WEAR MASK



EYE PROTECTION



RECYCLABLE