

Node: synthetic < Primordial, Lcom/ibm/wala/FakeRootClass, fakeRootMethod()V > Context: Everywhere

Node: synthetic < Primordial, Lcom/ibm/wala/FakeRootClass, fakeWorldClinit()V > Context: Everywhere Node: < Application, Lorg/paninij/soter/tests/LeakyServerTemplate, <init>()V > Context: ReceiverInstanceContext<SITE_IN_NODE{synthetic < Primordial, Lcom/ibm/wala/FakeRootClass, fakeRootMethod()V >:NEW <Application,Lorg/paninij/soter/tests/LeakyServerTemplate>@1 in Everywhere}>

Node: < Application, Lorg/paninij/soter/tests/Secret, <init>()V > Context: ReceiverInstanceContext<[<Application,Lorg/paninij/soter/tests/Secret>]>

Node: < Application, Lorg/paninij/soter/tests/LeakyServerTemplate, <init>()V > Context: ReceiverInstanceContext<SITE_IN_NODE{synthetic < Primordial, Lcom/ibm/wala/FakeRootClass, fakeRootMethod()V >:NEW <Application,Lorg/paninij/soter/tests/LeakyServerTemplate>@7 in Everywhere}> Node: < Application, Lorg/paninij/soter/tests/LeakyServerTemplate, <init>()V > Context: ReceiverInstanceContext<SITE_IN_NODE{synthetic < Primordial, Lcom/ibm/wala/FakeRootClass, fakeRootMethod()V >:NEW <Application,Lorg/paninij/soter/tests/LeakyServerTemplate>@13 in Everywhere}> Node: < Application, Lorg/paninij/soter/tests/LeakyServerTemplate, getInteger()Ljava/lang/Integer; > Context: ReceiverInstanceContext<SITE_IN_NODE{synthetic < Primordial, Lcom/ibm/wala/FakeRootClass, fakeRootMethod()V >:NEW <Application,Lorg/paninij/soter/tests/LeakyServerTemplate>@7 in Everywhere}>

Node: < Primordial, Ljava/lang/Number, <init>()V > Context: ReceiverInstanceContext<[<Primordial,Ljava/lang/Integer>]>

Node: < Application, Lorg/paninij/soter/tests/LeakyServerTemplate, <init>()V > Context: ReceiverInstanceContext<SITE_IN_NODE{synthetic < Primordial, Lcom/ibm/wala/FakeRootClass, fakeRootMethod()V >:NEW <Application,Lorg/paninij/soter/tests/LeakyServerTemplate>@21 in Everywhere}> Node: < Application, Lorg/paninij/soter/tests/LeakyServerTemplate, <init>()V > Context: ReceiverInstanceContext<SITE_IN_NODE{synthetic < Primordial, Lcom/ibm/wala/FakeRootClass, fakeRootMethod()V >:NEW <Application,Lorg/paninij/soter/tests/LeakyServerTemplate>@29 in Everywhere}> Node: < Application, Lorg/paninij/soter/tests/LeakyServerTemplate, <init>()V > Context: ReceiverInstanceContext<SITE_IN_NODE{synthetic < Primordial, Lcom/ibm/wala/FakeRootClass, fakeRootMethod()V >:NEW <Application,Lorg/paninij/soter/tests/LeakyServerTemplate>@35 in Everywhere}> Node: < Application, Lorg/paninij/soter/tests/LeakyServerTemplate, giveInteger(Ljava/lang/Integer;)V > Context: ReceiverInstanceContext<SITE_IN_NODE{synthetic < Primordial, Lcom/ibm/wala/FakeRootClass, fakeRootMethod()V >:NEW <Application,Lorg/paninij/soter/tests/LeakyServerTemplate>@13 in Everywhere}> Node: < Application, Lorg/paninij/soter/tests/LeakyServerTemplate, giveSecret(Lorg/paninij/soter/tests/Secret;)V > Context: ReceiverInstanceContext<SITE_IN_NODE{synthetic < Primordial, Lcom/ibm/wala/FakeRootClass, fakeRootMethod()V >:NEW <Application,Lorg/paninij/soter/tests/LeakyServerTemplate>@21 in Everywhere}> Node: < Application, Lorg/paninij/soter/tests/LeakyServerTemplate, getSecret()Lorg/paninij/soter/tests/Secret; > Context: ReceiverInstanceContext<SITE_IN_NODE{synthetic < Primordial, Lcom/ibm/wala/FakeRootClass, fakeRootMethod()V >:NEW <Application,Lorg/paninij/soter/tests/LeakyServerTemplate>@29 in Everywhere}> Node: < Application, Lorg/paninij/soter/tests/LeakyServerTemplate, getTemplateReference()Lorg/paninij/soter/tests/LeakyServerTemplate; > Context: ReceiverInstanceContext<SITE_IN_NODE{synthetic < Primordial, Lcom/ibm/wala/FakeRootClass, fakeRootMethod()V >:NEW <Application,Lorg/paninij/soter/tests/LeakyServerTemplate>@35 in Everywhere}>

Node: < Primordial, Ljava/lang/Object, <clinit>()V > Context: Everywhere Node: < Primordial, Ljava/lang/Integer, <clinit>()V > Context: Everywhere Node: < Primordial, Ljava/lang/Class, <clinit>()V > Context: Everywhere

Node: < Primordial, Ljava/lang/Object, registerNatives()V > Context: Everywhere

Node: < Primordial, Ljava/lang/Object, <init>()V > Context: ReceiverInstanceContext<SITE_IN_NODE{synthetic < Primordial, Lcom/ibm/wala/FakeRootClass, fakeRootMethod()V >:NEW <Application,Lorg/paninij/soter/tests/LeakyServerTemplate>@1 in Everywhere}>

Node: < Primordial, Ljava/lang/Object, <init>()V > Context: ReceiverInstanceContext<[<Application,Lorg/paninij/soter/tests/Secret>]>

Node: < Primordial, Ljava/lang/Object, <init>()V > Context: ReceiverInstanceContext<SITE_IN_NODE{synthetic < Primordial, Lcom/ibm/wala/FakeRootClass, fakeRootMethod()V >:NEW <Application,Lorg/paninij/soter/tests/LeakyServerTemplate>@7 in Everywhere}> Node: < Primordial, Ljava/lang/Object, <init>()V > Context: ReceiverInstanceContext<SITE_IN_NODE{synthetic < Primordial, Lcom/ibm/wala/FakeRootClass, fakeRootMethod()V >:NEW <Application,Lorg/paninij/soter/tests/LeakyServerTemplate>@13 in Everywhere}> Node: < Primordial, Ljava/lang/Integer, <init>(I)V > Context: ReceiverInstanceContext<[<Primordial,Ljava/lang/Integer>]>

Node: synthetic < Primordial, Ljava/lang/Class, getPrimitiveClass(Ljava/lang/String;)Ljava/lang/Class; > Context: Everywhere

Node: < Primordial, Ljava/lang/Object, <init>()V > Context: ReceiverInstanceContext<[<Primordial,Ljava/lang/Integer>]>

Node: < Primordial, Ljava/lang/Object, <init>()V > Context: ReceiverInstanceContext<SITE_IN_NODE{synthetic < Primordial, Lcom/ibm/wala/FakeRootClass, fakeRootMethod()V >:NEW <Application,Lorg/paninij/soter/tests/LeakyServerTemplate>@21 in Everywhere}> Node: < Primordial, Ljava/lang/Object, <init>()V > Context: ReceiverInstanceContext<SITE_IN_NODE{synthetic < Primordial, Lcom/ibm/wala/FakeRootClass, fakeRootMethod()V >:NEW <Application,Lorg/paninij/soter/tests/LeakyServerTemplate>@29 in Everywhere}> Node: < Primordial, Ljava/lang/Object, <init>()V > Context: ReceiverInstanceContext<SITE_IN_NODE{synthetic < Primordial, Lcom/ibm/wala/FakeRootClass, fakeRootMethod()V >:NEW <Application,Lorg/paninij/soter/tests/LeakyServerTemplate>@35 in Everywhere}>

Node: < Primordial, Ljava/lang/Class, registerNatives()V > Context: Everywhere