

Programmering og Problemløsning

16 December 2016

Christina Lioma

c.lioma@di.ku.dk

Today's lecture

UML diagrams

- What they are
- UML diagrams of classes
- UML diagrams of class relations

Today's lecture

UML diagrams

- What they are
- UML diagrams of classes
- UML diagrams of class relations

Beginning Java Objects, Jacquie Barker pp. 355 – 407

(non profit, educational use in classroom, do not disseminate or reproduce)

UML: Unified Modeling Language

UML: Unified Modeling Language

Graphical language for communicating system design

UML: Unified Modeling Language

Graphical language for communicating system design

Industry standard for OO design notation

UML: Unified Modeling Language

Graphical language for communicating system design

Industry standard for OO design notation

<http://www.umlet.com>

UML in latex (labs)

UML diagram of a class

Class: rectangle split into 3 horizontal parts



UML diagram of a class

Class: rectangle split into 3 horizontal parts

- Class name
- Attributes (one per row)
- Methods (one per row)

Class Name
Attribute1
Attribute2
Attribute3
Method1()

UML diagram of a class

Class: rectangle split into 3 horizontal parts

- Class name
- Attributes (one per row)
- Methods (one per row)

Class Name
Attribute1
Attribute2
Attribute3
Method1()

(Methods are also referred to as *operations* in UML)

UML diagram of a class

Class: rectangle split into 3 horizontal parts

- Class name
- Attributes (one per row)
 - Optional: data type
- Methods (one per row)

Class Name
Attribute1: string
Attribute2
Attribute3 : float
Method1()

(Methods are also referred to as *operations* in UML)

UML diagram of a class

Class: rectangle split into 3 horizontal parts

- Class name
- Attributes (one per row)
 - Optional: data type
 - Optional: initial value
- Methods (one per row)

Class Name
Attribute1: string
Attribute2
Attribute3 : float = 100.0
Method1()

(Methods are also referred to as *operations* in UML)

UML diagram of a class

Class: rectangle split into 3 horizontal parts

- Class name
- Attributes (one per row)
 - Optional: data type
 - Optional: initial value
- Methods (one per row)
 - Optional: parameter list

Class Name
Attribute1: string
Attribute2
Attribute3 : float = 100.0
Method1(y)

(Methods are also referred to as *operations* in UML)

UML diagram of a class

Class: rectangle split into 3 horizontal parts

- Class name
- Attributes (one per row)
 - Optional: data type
 - Optional: initial value
- Methods (one per row)
 - Optional: parameter list

Class Name
Attribute1: string
<u>Attribute2</u>
Attribute3 : float = 100.0
Method1(y)

Static members are underlined

(Methods are also referred to as *operations* in UML)

UML diagram of a class

Class: rectangle split into 3 horizontal parts

- Class name
- Attributes (one per row)
 - Optional: data type
 - Optional: initial value
- Methods (one per row)
 - Optional: parameter list

Class Name
Attribute1: string
<u>Attribute2</u>
Attribute3 : float = 100.0
Method1(y)

Static members are underlined

Include *only important* attributes and methods, e.g. not get() set()
(Methods are also referred to as *operations* in UML)

UML diagrams of a class relations

- What are class relations
- How to draw their UML diagrams

Example (p. 369)

We have been asked to develop an automated Student Registration System (SRS) for the university. This system will **enable students to register online for courses** each semester, as well as **track their progress toward completion of their degree**.

When a student first **enrolls at the university**, he/she uses the SRS to **set forth a plan of study** as to which **courses he/she plans on taking to satisfy a particular degree program**, and **chooses a faculty advisor**. The SRS will **verify whether or not the proposed plan of study satisfies the requirements of the degree that the student is seeking**.

Once a **plan of study has been established**, then, during the registration period preceding each semester, a student is able to **view the schedule of classes** online, and **choose whichever classes he/she wishes to attend, indicating the preferred section** (day of the week and time of day) if the **class is offered by more than one professor**. The SRS will **verify whether or not the student has satisfied the necessary prerequisites** for each requested course by **referring to the student's online transcript** of courses completed and grades received (the **student may review his/her transcript** online at any time).

Program to process university records

Abstract object classes

University

School

Course

Plan of study

Student

Professor

Transcript

Program to process university records

Abstract object classes

University: consists of Schools (of Science, Humanities, ...)

School: belongs to the university; employs people...

Course: taught by professors; belongs to plan of study...

Plan of study: consists of courses; followed by students...

Student: studies at the university; follows courses...

Professor: teaches students; works at the university...

Transcript: record of all courses and grades per student

Program to process university records

Abstract object classes are often related

University: consists of **Schools** (of Science, Humanities, ...)

School: belongs to the **university**; employs people...

Course: taught by **professors**; belongs to **plan of study**...

Plan of study: consists of **courses**; followed by **students**...

Student: studies at the **university**; follows **courses**...

Professor: teaches **students**; works at the **university**...

Transcript: record of all **courses** and grades per **student**

Program to process university records

Abstract object classes are often related

University: consists of **Schools** (of Science, Humanities, ...)

School: belongs to the **university**; employs **people**...

Course: taught by **professors**; belongs to **plan of study**...

Plan of study: consists of **courses**; followed by **students**...

Student: studies at the **university**; follows **courses**...

Professor: teaches **students**; works at the **university**...

Transcript: record of all **courses** and grades per **student**

People: **students**; **professors**...

Inheritance

Relations between classes (e.g. inheritance) are called
Associations


Relations between classes (e.g. inheritance) are called *Associations*

We use UML diagrams to represent the associations between our classes


Class A

Class B

Solid line: relationship between classes






Solid line: relationship between classes (can be named)




Solid line: relationship between classes (can be named)


Within the association classes may have roles








Small arrowhead reflects the direction of the association



Solid line: relationship between classes

Within the association classes may have roles

Association name & roles are optional in UML
(use only when needed to clarify abstraction)




Three main types of associations (relations between classes):

Inheritance



Aggregation

Composition

1. Inheritance (class B **is a type of** class A)
UML: *white arrow* points to the Base class



Equivalent UML representations of inheritance



2. Aggregation (class A **contains** class B):

A university contains faculties, schools, departments

2. Aggregation (class A **contains** class B):

A university contains faculties, schools, departments

Difference between inheritance and aggregation:

2. Aggregation (class A **contains** class B):

A university contains faculties, schools, departments

Difference between inheritance and aggregation:

*A university **contains** a department* *AGGREG*

A department is not a type of university ~~*INHERIT*~~

2. Aggregation (class A **contains** class B):

A university contains faculties, schools, departments

Difference between inheritance and aggregation:

*A university **contains** a department* *AGGREG*


A department is not a type of university ~~*INHERIT*~~

*A student **is a type of** person* *INHERIT*


A person does not contain students ~~*AGGREG*~~

2. Aggregation (class A **contains** class B)



UML: *diamond* points to the containing class





Any orientation



Equivalent



Equivalent UML representations for aggregation



3. Composition (strong case of aggregation)

3. Composition (strong case of aggregation):
class A **contains** class B **and**
class B **cannot exist without** class A

3. Composition (strong case of aggregation):
class A **contains** class B **and**
class B **cannot exist without** class A

A book contains chapters
(chapters cannot exist without books)

3. Composition (strong case of aggregation):

class A **contains** class B **and**

class B **cannot exist without** class A

A book contains chapters

(chapters cannot exist without books)

A car contains wheels

(wheels exist without cars)

3. Composition (strong case of aggregation):

class A **contains** class B **and**

class B **cannot exist without** class A

A book contains chapters

COMPOS

(chapters cannot exist without books)

~~*AGGREG*~~

A car contains wheels

AGGREG

(wheels exist without cars)

~~*COMPOS*~~

3. Composition (strong case of aggregation):

class A **contains** class B **and**

class B **cannot exist without** class A

A book contains chapters

(chapters cannot exist without books)

(chapter is not a type of book)

COMPOS

~~*AGGREG*~~

~~*INHERIT*~~

A car contains wheels

(wheels exist without cars)


(wheels are not a type of car)

AGGREG

~~*COMPOS*~~

~~*INHERIT*~~

3. Composition in UML: black diamond points to the containing class



Class associations in UML

Inheritance:

white arrow

class B is a type of class A

Aggregation:

diamond

class A contains class B

Composition:

black diamond

class A contains class B

and

class B cannot exist without class A

Class associations in UML

Inheritance:

class B is a type of class A

white arrow

is-a

Aggregation:

class A contains class B

diamond

has-a

Composition:

class A contains class B

and

class B cannot exist without class A

black diamond

has-a

Class associations in UML

Inheritance

Aggregation

Composition

→ **how** classes are related

Class associations in UML

Inheritance

Aggregation

Composition

→ **how** classes are related

Binary

Unary

Multiplicity

→ **how many** classes/instances are related

Binary versus unary class associations

Binary versus unary class associations:

- Binary: between two classes (what we have seen so far)

Binary versus unary class associations:

- Binary: between two classes (what we have seen so far)
- Unary: between instances of the *same class*

Binary versus unary class associations:

- Binary: between two classes (what we have seen so far)
- Unary: between instances of the *same class*

Course “Math” is a prerequisite of course “CompSci”

(Math and CompSci are *different instances of the class* Course)

Binary versus unary class associations:

- Binary: between two classes (what we have seen so far)
- Unary: between instances of the *same class*

Course “Math” is a prerequisite of course “CompSci”
(Math and CompSci are *different instances of the class* Course)

Student X represents student Y in the council
(X and Y are *different instances of the class* Student)

Binary versus unary class associations:

- Binary: between two classes (what we have seen so far)
- Unary: between instances of the *same class*

Course “Math” is a prerequisite of course “CompSci”
(Math and CompSci are *different instances of the class* Course)

Student X represents student Y in the council
(X and Y are *different instances of the class* Student)

But student X represents also himself in the council
(X-representative and X-student are the *same instance of the class* Student)

Binary versus unary class associations:

- Binary: between two classes (what we have seen so far)
- Unary: between **(different or the same)** instances of the *same class*

Course “Math” is a prerequisite of course “CompSci”

(Math and CompSci are *different instances of the class* Course)

Student X represents student Y in the council

(X and Y are *different instances of the class* Student)

But student X represents also himself in the council

(X-representative and X-student are the *same instance of the class* Student)

Binary versus unary class associations:

- Binary: between two classes (what we have seen so far)
- Unary: between **(different or the same)** instances of the *same class*

Course “Math” is a prerequisite of course “CompSci”

(Math and CompSci are *different instances of the class* Course)

Student X represents student Y in the council

(X and Y are *different instances of the class* Student)


But student X represents also himself in the council

(X-representative and X-student are the *same instance of the class* Student)

How to represent unary associations in UML?

Unary associations in UML

(between instances of the *same* class)




Association multiplicity

How many instances of class A can be associated with an instance of class B


Association multiplicity

How many instances of class A can be associated with an instance of class B



Association multiplicity

How many instances of class A can be associated with an instance of class B




Exactly one: 1

Several: *

Association multiplicity

How many instances of class A can be associated with an instance of class B




Exactly one: 1

From e.g. 3 to 7: 3..7

Several: *

Association multiplicity

How many instances of class A can be associated with an instance of class B



Exactly one: 1


From e.g. 3 to 7: 3..7

Several: *

Zero or more: 0..*

Association multiplicity

How many instances of class A can be associated with an instance of class B



Exactly one: 1


From e.g. 3 to 7: 3..7

One or more: 1..*


Several: *

Zero or more: 0..*


At most one: 0..1




A student has **one** transcript and a transcript belongs to **one** student



A student has **one** transcript and a transcript belongs to **one** student



A professor works for **one** department but a department has **many** professors



A course can be a prerequisite for **zero or more** courses and a course can have **zero or more** prerequisites



A study plan is composed of **several** courses
and
a course can be included in **several** study plans


(Aggregation & multiplicity)



A study plan is composed of **several** courses
and
a course can be included in **several** study plans

(Aggregation & multiplicity)

Why not composition?



UML best practice

- Less is more (legible when printed on A4)

UML best practice

- Less is more (legible when printed on A4)
- Orthogonality (right angles)

UML best practice

- Less is more (legible when printed on A4)
- Orthogonality (right angles)
- Parents up

UML best practice

- Less is more (legible when printed on A4)
- Orthogonality (right angles)
- Parents up
- Align elements when possible
- Make elements the same size when possible

Recap today's lecture

- Unified Modeling Language (UML)
 - Classes
 - Class relations
 - Instance relations