

Local faithfulness constraints over correspondence structures

Adam Jardine, University of Delaware


ajardine@udel.edu




Overview

- The computationally local nature of phonological generalizations (Chandlee, 2014; Chandlee et al., 2014) can be captured through *banned substructure constraints over correspondence graphs* (Potts and Pullum, 2002)

E.g. intervocalic voicing




- We can constrain correspondence through *concatenation* of primitives (Jardine and Heinz, 2015)



- We can describe patterns without powerful LINEARITY constraints or 'counting' overgeneralization predicted by optimization
- Opens up possibilities for learning transformations

Computational locality

- Patterns describable by banning substructures that are **connected** and **bounded in size** are **computationally local**



- Locality in strings: **substrings** are substructures (Rogers and Pullum 2011; Rogers et al., 2013)
- For non-linear structures, we can extend this notion to **subgraphs** (Jardine, 2016)

The nature of correspondence

- Languages use a subset of logically possible **individual correspondences** (e.g., no $a \rightarrow b$)

Inventory = $\{a, p, b\}$

$$C_{Sym} = \left\{ \begin{array}{c} \emptyset \\ \downarrow \\ a \end{array}, \begin{array}{c} \emptyset \\ \downarrow \\ b \end{array}, \begin{array}{c} \emptyset \\ \downarrow \\ p \end{array}, \begin{array}{c} a \\ \downarrow \\ \emptyset \end{array}, \begin{array}{c} a \\ \downarrow \\ b \end{array}, \begin{array}{c} p \\ \downarrow \\ \emptyset \end{array}, \begin{array}{c} p \\ \downarrow \\ p \end{array}, \begin{array}{c} b \\ \downarrow \\ \emptyset \end{array}, \begin{array}{c} b \\ \downarrow \\ p \end{array} \right\}$$

- Graph concatenation** (Engelfriet and Vereijken, 1997; Jardine and Heinz, 2015) can generate **string correspondences** from C_{Sym}

$$C_{Str} = \left\{ \dots, \begin{array}{c} \# a p a \# \\ \downarrow \downarrow \downarrow \downarrow \\ \# a p a \# \end{array}, \begin{array}{c} \# a p a \# \\ \downarrow \downarrow \downarrow \downarrow \\ \# a b a \# \end{array}, \begin{array}{c} \# a p a \# \\ \downarrow \downarrow \downarrow \downarrow \\ \# \emptyset \emptyset \emptyset \emptyset \# \end{array}, \begin{array}{c} \# a p a p \# \\ \downarrow \downarrow \downarrow \downarrow \\ \# a p a p \# \end{array}, \dots \right\}$$

- Similar to, but different from; OT's GEN
- All inputs are considered; input-output correspondence constrained by concatenation

Language-specific constraints

- Form of constraints: $\neg s_1 \wedge \neg s_2 \wedge \neg s_3 \wedge \dots \wedge \neg s_n$

$$\neg a \wedge \neg p \wedge \neg b \quad (=MAX) \quad \begin{array}{c} \# a p a \# \\ \downarrow \downarrow \downarrow \downarrow \\ \emptyset \emptyset \emptyset \emptyset \end{array} \quad \begin{array}{c} \# a p a \# \\ \downarrow \downarrow \downarrow \downarrow \\ \# a \emptyset a \# \end{array} \quad \begin{array}{c} \# a p a \# \\ \downarrow \downarrow \downarrow \downarrow \\ \# a p a \# \end{array}$$

$$*apa = \neg p \quad \begin{array}{c} \# a p a p \# \\ \downarrow \downarrow \downarrow \downarrow \\ a p a \# \end{array} \quad \begin{array}{c} \# a p a p \# \\ \downarrow \downarrow \downarrow \downarrow \\ \# a b a p \# \end{array} \quad \begin{array}{c} \# a p a p \# \\ \downarrow \downarrow \downarrow \downarrow \\ \# a p a p \# \end{array}$$

- Constraints interact through *conjunction* (\wedge):

$$*apa \wedge MAX \wedge DEP$$

- Surface $*apa$ sequences repaired through voicing

Constraints (cont'd)

- We also need to forbid *over-repairing*

$$\begin{array}{c} \# a p a p \# \\ \downarrow \downarrow \downarrow \downarrow \\ \# b a b \# \end{array} \quad \begin{array}{c} \# a p a p a \# \\ \downarrow \downarrow \downarrow \downarrow \downarrow \\ \# p a b p a \# \end{array} \quad \begin{array}{c} \# a p a b p a \# \\ \downarrow \downarrow \downarrow \downarrow \downarrow \\ \# p a b b a \# \end{array}$$


$$NoCCVOI = \neg p \wedge \neg p \wedge \neg p \wedge \neg p$$

$$\begin{array}{c} \downarrow \downarrow \downarrow \downarrow \\ p b \quad b p \quad b b \quad b b \end{array}$$

Final grammar: $*apa \wedge MAX \wedge DEP \wedge NoCCVOI \wedge NoINITVOI \wedge NoFINVOI$

Discussion/Conclusions

- Captures the **local** nature of correspondence and faithfulness
- Cannot capture 'counting' patterns overgenerated by optimization (Gerdemann and Hulden, 2012, Lombardi 1999; Baković 2000;)
- A local learning model can 'scan' through input



Acknowledgements & Select References

Acknowledgements

Thanks to Jeff Heinz and the audience at the 2016 UD CSGSC.

References

- Chandlee, J., Eyraud, R., and Heinz, J. (2014). Learning Strictly Local subsequential functions. *Transactions of the Association for Computational Linguistics*, 2:491–503.
- Engelfriet, J. and Vereijken, J. J. (1997). Context-free graph grammars and concatenation of graphs. *Acta Informatica*, 34:773–803.
- Gerdemann, D. and Hulden, M. (2012). Practical finite state optimality theory. In *Proceedings of the 10th International Workshop on FSMNLP*, pages 10–19. ACL.
- Jardine, A. and Heinz, J. (2015). A concatenation operation to derive autosegmental graphs. In *Proceedings of the 14th Meeting on the Mathematics of Language (MoL 2015)*, pages 139–151. Chicago, USA. Association for Computational Linguistics.
- Potts, C. and Pullum, G. K. (2002). Model theory and the content of OT constraints. *Phonology*, 19:361–393.
- Rogers, J. and Pullum, G. (2011). Aural pattern recognition experiments and the subregular hierarchy. *Journal of Logic, Language and Information*, 20:329–342.