

TFP3 production CRISPR pipeline parameters by dataset

	Hon CM (2026_04_19_no_spacer)	Huangfu DE (muddy_penguin)	Huangfu ESC (sceptre_v1)	Gersbach Hep (sara_synapse_syn74842722)
Operator / platform	Weizhou Qian, UMich	Adam, GCP	Gary Yang, GCP	Sara Geraghty, Duke HPC
ENABLE_DATA_HASHING	true	false	false	false
use_igvf_reference	false	true	true	true
is_10x3v3	false	true	true	false
reverse_complement_guides	true	false	false	true
spacer_tag	""	GAGTACATGGGGG	GAGTACATGGGGG	TAGCTCTTAAAC
QC_min_genes_per_cell	500	500	500	2500
QC_min_cells_per_gene	0.05	0.05	0.05	0.05
QC_pct_mito	15	20	20	15
QC_barcode_filter	knee2	knee2	knee2	none
Multiplicity_of_infection	high	high	high	high
GUIDE_ASSIGNMENT_method	sceptre	sceptre	sceptre	cleanser
GUIDE_ASSIGNMENT_capture_method	CR0P-seq	CR0P-seq	CR0P-seq	direct-capture
INFERENCE_SCEPTRE_control_group	default	default	default	complement
INFERENCE_SCEPTRE_GENE_CHUNK_SIZE	1000	1000	1000	1000
Base container	pinellolab/crispr_pipeline conda-docker:latest	sjiang9/conda-docker:0.3	sjiang9/conda-docker:0.3	pinellolab/crispr_pipeline conda-docker:latest (sif)
max_cpus / max_memory	16 / 1500 GB	128 / 256 GB	128 / 256 GB	12 / 600 GB

Highlighted cells differ from the majority of datasets for that parameter. Source: docs/jamborees/2026_UTSW/working_groups/wg1_data_qc/pipeline_qc/manifests/production_pipeline_params.tsv