

# Reinforcement learning

## Lecture 1: Introduction

Hado van Hasselt  
hado@google.com

Advanced deep learning and reinforcement learning, UCL  
January 18, 2018

## 加入知识星球资源管理库，每日免费获取报告


- 1、每天分享30+最新行业报告（涵盖科技、金融、教育、互联网、房地产、生物制药、医疗健康等最新行业）
- 2、每天分享10+企业咨询管理文件（涵盖国内外著名咨询公司相关管理方案，企业运营制度等）
- 3、每天分享10+科技类论文或者大师课件、笔记。
- 4、每天更新企业运营管理中遇到的问题及解决方案
- 5、高端人才管理与行业交流

更多文件请点击链接， <https://t.zsxq.com/2nElq7a>

微信扫码进微信群，每日获取资料（微信号：Teamkon）



微信二维码



管理资源库

# Admin

- ▶ RL lectures: mostly Thursday 9-11am, some exceptions
- ▶ Check Moodle for updates
- ▶ Use Moodle for questions
- ▶ Grading: assignments
- ▶ Background material:  
Reinforcement Learning: An Introduction, Sutton & Barto 2018  
<http://incompleteideas.net/book/the-book-2nd.html>  
Background for this lecture: chapters 1 and 3

# Outline

What is reinforcement learning?

Core concepts

Agent components

Challenges in reinforcement learning

What is reinforcement learning?


# Motivation

- ▶ First, automation of repeated physical solutions
  - ▶ **Industrial revolution** (1750 - 1850) and Machine Age (1870 - 1940)
- ▶ Second, automation of repeated mental solutions
  - ▶ **Digital revolution** (1960 - now) and Information Age
- ▶ Next step: allow machines to find solutions themselves
  - ▶ **AI revolution** (now - ????)
- ▶ This requires learning autonomously how to make decisions

# What is Reinforcement Learning?

- ▶ We, and other intelligent beings, learn by **interacting with our environment**
- ▶ This differs from certain other types of learning
  - ▶ It is **active** rather than passive
  - ▶ Interactions are often **sequential** — future interactions can depend on earlier ones
- ▶ We are **goal-directed**
- ▶ We can learn **without examples** of optimal behaviour

## The Interaction Loop





# What is Reinforcement Learning?

There are (at least) two distinct reasons to learn:


1. Find previously unknown solutions  
E.g., a program that can play Go better than any human, ever
  2. Find solutions online, for unforeseen circumstances  
E.g., a robot that can navigate terrains that differ greatly from any expected terrain
- ▶ Reinforcement learning seeks to provide algorithms for both cases
  - ▶ Note that the second point is not (just) about generalization — it is about learning efficiently **online**, during operation

# What is Reinforcement Learning?


- ▶ Science of **learning to make decisions** from **interaction**
- ▶ This requires us to think about
  - ▶ ...time
  - ▶ ...(long-term) consequences of actions
  - ▶ ...actively gathering experience
  - ▶ ...predicting the future
  - ▶ ...dealing with uncertainty
- ▶ Huge potential scope

RL = AI?

## Related Disciplines



# Branches of Machine Learning



# Characteristics of Reinforcement Learning

How does reinforcement learning differ from other machine learning paradigms?

- ▶ No supervision, only a **reward** signal
- ▶ Feedback can be delayed, not instantaneous
- ▶ Time matters
- ▶ Earlier decisions affect later interactions

# Examples of decision problems

- ▶ Examples:
  - ▶ Fly a helicopter
  - ▶ Manage an investment portfolio
  - ▶ Control a power station
  - ▶ Make a robot walk
  - ▶ Play video or board games
- ▶ These are all reinforcement learning problems  
(no matter which solution method you use)

Video

Atari


# Core concepts

Core concepts of a reinforcement learning system are:

- ▶ **Environment**
- ▶ **Reward** signal
- ▶ **Agent**, containing:
  - ▶ Agent state
  - ▶ Policy
  - ▶ Value function (probably)
  - ▶ Model (optionally)



# Agent and Environment



- ▶ At each step  $t$  the agent:
  - ▶ Receives observation  $O_t$  (and reward  $R_t$ )
  - ▶ Executes action  $A_t$
- ▶ The environment:
  - ▶ Receives action  $A_t$
  - ▶ Emits observation  $O_{t+1}$  (and reward  $R_{t+1}$ )

# Rewards

- ▶ A **reward**  $R_t$  is a scalar feedback signal
- ▶ Indicates how well agent is doing at step  $t$  — defines the goal
- ▶ The agent's job is to maximize cumulative reward

$$G_t = R_{t+1} + R_{t+2} + R_{t+3} + \dots$$

- ▶ We call this the **return**

Reinforcement learning is based on the **reward hypothesis**

## Definition (Reward Hypothesis)

*Any goal can be formalized as the outcome of maximizing a cumulative reward*

Do you agree?

# Values

- ▶ We call the expected cumulative reward, from a state  $s$ , the **value**

$$\begin{aligned}v(s) &= \mathbb{E}[G_t \mid S_t = s] \\ &= \mathbb{E}[R_{t+1} + R_{t+2} + R_{t+3} + \dots \mid S_t = s]\end{aligned}$$

- ▶ Goal is then to **maximize value**, by picking suitable actions
- ▶ Rewards and values define **desirability** of a state or action (no supervised feedback)
- ▶ Note that returns and values can be defined recursively

$$G_t = R_{t+1} + G_{t+1}$$

# Actions in sequential problems

- ▶ Goal: **select actions to maximise value**
- ▶ Actions may have long term consequences
- ▶ Reward may be delayed
- ▶ It may be better to sacrifice immediate reward to gain more long-term reward
- ▶ Examples:
  - ▶ A financial investment (may take months to mature)
  - ▶ Refueling a helicopter (might prevent a crash in several hours)
  - ▶ Blocking opponent moves (might help winning chances many moves from now)
- ▶ A mapping from states to actions is called a **policy**

## Action values

- ▶ It is possible to condition the value on **actions**:

$$\begin{aligned}q(s, a) &= \mathbb{E}[G_t \mid S_t = s, A_t = a] \\&= \mathbb{E}[R_{t+1} + R_{t+2} + R_{t+3} + \dots \mid S_t = s, A_t = a]\end{aligned}$$

- ▶ We will talk in depth about state and action values later

# Agent components


## Agent components

- ▶ Agent state
- ▶ Policy
- ▶ Value function
- ▶ Model

# State

- ▶ Actions depend on the **state** of the agent
- ▶ Both agent and environment may have an internal state
- ▶ In the simplest case, there is only one state (next lecture)
- ▶ Often, there are many different states — sometimes infinitely many
- ▶ The state of the agent generally differs from the state of the environment
- ▶ The agent may not even know the full state of the environment

# Environment State



- ▶ The **environment state** is the environment's internal state
- ▶ It is not usually visible to the agent
- ▶ Even if it is visible, it may contain lots of irrelevant information




# Agent State

- ▶ A **history** is a sequence of observations, actions, rewards

$$\mathcal{H}_t = O_0, A_0, R_1, O_1, \dots, O_{t-1}, A_{t-1}, R_t, O_t$$

- ▶ For instance, the sensorimotor stream of a robot
- ▶ This history can be used to construct an **agent state**  $S_t$
- ▶ Actions depend on this state

# Fully Observable Environments



## Full observability:

Suppose the agent sees the full environment state

- ▶ observation = environment state
- ▶ The agent state could just be this observation:

$$S_t = O_t = \text{environment state}$$

- ▶ Then the agent is in a **Markov decision process**

# Markov decision processes

Markov decision processes (MDPs) provide a useful mathematical framework

## Definition

A decision process is Markov if

$$p(r, s \mid S_t, A_t) = p(r, s \mid \mathcal{H}_t, A_t)$$

- ▶ “The future is independent of the past given the present”


$$\mathcal{H}_t \rightarrow S_t \rightarrow \mathcal{H}_{t+1}$$

- ▶ Once the state is known, the history may be thrown away
- ▶ The environment state is typically Markov
- ▶ The history  $\mathcal{H}_t$  is Markov

# Partially Observable Environments

- ▶ **Partial observability**: The agent gets partial information
  - ▶ A robot with camera vision isn't told its absolute location
  - ▶ A poker playing agent only observes public cards
- ▶ Now the observation is not Markov
- ▶ Formally this is a **partially observable Markov decision process** (POMDP)
- ▶ The **environment state** can still be Markov, but the agent does not know it

# Agent State



- ▶ The **agent state** is a function of the history
- ▶ The agent's action depends on its state
- ▶ For instance,  $S_t = O_t$
- ▶ More generally:

$$S_{t+1} = f(S_t, A_t, R_{t+1}, O_{t+1})$$

where  $f$  is a 'state update function'

- ▶ The agent state is typically much smaller than the environment state

## Agent State

The full environment state of a maze



## Agent State

A potential observation



## Agent State


An observation in a different location






## Agent State

The two observations are indistinguishable



## Agent State

These two states are not Markov



How could you construct a Markov agent state in this maze (for any reward signal)?

# Partially Observable Environments

- ▶ To deal with partial observability, agent can construct suitable state representations
- ▶ Examples of agent states:
  - ▶ Last observation:  $S_t = O_t$  (might not be enough)
  - ▶ Complete history:  $S_t = \mathcal{H}_t$  (might be too large)
  - ▶ Some incrementally updated state:  $S_t = f(S_{t-1}, O_t)$   
(E.g., implemented with a recurrent neural network.)  
(Sometimes called 'memory'.)
- ▶ Constructing a Markov agent state may not be feasible; this is common!
- ▶ More importantly, the should state be contain enough informative for good policies, and/or good value predictions

# Agent components

## Agent components

- ▶ Agent state
- ▶ Policy
- ▶ Value function
- ▶ Model

# Policy

- ▶ A **policy** defines the agent's behaviour
- ▶ It is a map from agent state to action
- ▶ Deterministic policy:  $A = \pi(S)$
- ▶ Stochastic policy:  $\pi(A|S) = p(A|S)$

# Agent components

## Agent components

- ▶ Agent state
- ▶ Policy
- ▶ Value function
- ▶ Model

# Value Function

- ▶ The actual value function is the expected return

$$\begin{aligned}v_{\pi}(s) &= \mathbb{E}[G_t \mid S_t = s, \pi] \\&= \mathbb{E}[R_{t+1} + \gamma R_{t+2} + \gamma^2 R_{t+3} + \dots \mid S_t = s, \pi]\end{aligned}$$

- ▶ We introduced a **discount factor**  $\gamma \in [0, 1]$ 
  - ▶ Trades off importance of immediate vs long-term rewards
- ▶ The value depends on a policy
- ▶ Can be used to evaluate the desirability of states
- ▶ Can be used to select between actions

# Value Functions

- ▶ The return has a recursive form  $G_t = R_{t+1} + \gamma G_{t+1}$
- ▶ Therefore, the value has as well

$$\begin{aligned}v_{\pi}(s) &= \mathbb{E}[R_{t+1} + \gamma G_{t+1} \mid S_t = s, A_t \sim \pi(s)] \\&= \mathbb{E}[R_{t+1} + \gamma v_{\pi}(S_{t+1}) \mid S_t = s, A_t \sim \pi(s)]\end{aligned}$$

Here  $a \sim \pi(s)$  means  $a$  is chosen by policy  $\pi$  in state  $s$  (even if  $\pi$  is deterministic)

- ▶ This is known as a **Bellman equation** (Bellman 1957)
- ▶ A similar equation holds for the optimal (=highest possible) value:

$$v_*(s) = \max_a \mathbb{E}[R_{t+1} + \gamma v_*(S_{t+1}) \mid S_t = s, A_t = a]$$

This does **not** depend on a policy

- ▶ We heavily exploit such equalities, and use them to create algorithms



# Value Function approximations

- ▶ Agents often approximate value functions
- ▶ We will discuss algorithms to learn these efficiently
- ▶ With an accurate value function, we can behave optimally
- ▶ With suitable approximations, we can behave well, even in intractably big domains

# Agent components

## Agent components

- ▶ Agent state
- ▶ Policy
- ▶ Value function
- ▶ Model

# Model

- ▶ A **model** predicts what the environment will do next
- ▶ E.g.,  $\mathcal{P}$  predicts the next state


$$\mathcal{P}(s, a, s') \approx p(S_{t+1} = s' \mid S_t = s, A_t = a)$$

- ▶ E.g.,  $\mathcal{R}$  predicts the next (immediate) reward

$$\mathcal{R}(s, a) \approx \mathbb{E}[R_{t+1} \mid S_t = s, A_t = a]$$


- ▶ A model does not immediately give us a good policy - we would still need to plan
- ▶ We could also consider **stochastic** (**generative**) models

## Maze Example




- ▶ Rewards: -1 per time-step
- ▶ Actions: N, E, S, W
- ▶ States: Agent's location

## Maze Example: Policy




- ▶ Arrows represent policy  $\pi(s)$  for each state  $s$

## Maze Example: Value Function



- Numbers represent value  $v_{\pi}(s)$  of each state  $s$

## Maze Example: Model



- ▶ Grid layout represents partial transition model  $\mathcal{P}_{ss'}^a$
- ▶ Numbers represent immediate reward  $\mathcal{R}_{ss'}^a$  from each state  $s$  (same for all  $a$  and  $s'$  in this case)

# Categorizing agents


- ▶ Value Based
  - ▶ No Policy (Implicit)
  - ▶ Value Function
- ▶ Policy Based
  - ▶ Policy
  - ▶ No Value Function
- ▶ Actor Critic
  - ▶ Policy
  - ▶ Value Function



# Categorizing agents

- ▶ Model Free
  - ▶ Policy and/or Value Function
  - ▶ No Model
- ▶ Model Based
  - ▶ Optionally Policy and/or Value Function
  - ▶ Model

# Agent Taxonomy



# Challenges in reinforcement learning

# Learning and Planning

Two fundamental problems in reinforcement learning

- ▶ Learning:
  - ▶ The environment is initially unknown
  - ▶ The agent interacts with the environment
- ▶ Planning:
  - ▶ A model of the environment is given
  - ▶ The agent plans in this model (without external interaction)
  - ▶ a.k.a. reasoning, pondering, thought, search, planning

# Prediction and Control

- ▶ Prediction: evaluate the future (for a given policy)
- ▶ Control: optimize the future (find the best policy)
- ▶ These are strongly related:


$$\pi_*(s) = \operatorname{argmax}_{\pi} v_{\pi}(s)$$

- ▶ If we could predict **everything** do we need anything else?

# Learning the components of an agent

- ▶ All components are functions
  - ▶ Policies map states to actions
  - ▶ Value functions map states to values
  - ▶ Models map states to states and/or rewards
  - ▶ State updates map states and observations to new states
- ▶ We could represent these functions as neural networks, then use deep learning methods to optimize these
- ▶ Take care: we often violate assumptions from supervised learning (iid, stationarity)
- ▶ Deep reinforcement learning is a rich and active research field
- ▶ (Current) neural networks are not always the best tool (but they often work well)


# Atari Example: Reinforcement Learning



- ▶ Rules of the game are unknown
- ▶ Learn directly from interactive game-play
- ▶ Pick actions on joystick, see pixels and scores

# Atari Example: Planning

- ▶ Rules of the game are known
- ▶ Can query emulator: perfect model
- ▶ If I take action  $a$  from state  $s$ :
  - ▶ what would the next state be?
  - ▶ what would the score be?
- ▶ Plan ahead to find optimal policy
- ▶ Later versions add noise, to break algorithms that rely on determinism





# Exploration and Exploitation

- ▶ We learn by trial and error
- ▶ The agent should discover a good policy
- ▶ ...from new experiences
- ▶ ...without sacrificing too much reward along the way

# Exploration and Exploitation

- ▶ **Exploration** finds more information
- ▶ **Exploitation** exploits known information to maximise reward
- ▶ It is important to explore as well as exploit
- ▶ This is a fundamental problem that does not occur in supervised learning

# Examples

- ▶ Restaurant Selection

Exploitation Go to your favourite restaurant

Exploration Try a new restaurant

- ▶ Oil Drilling

Exploitation Drill at the best known location


Exploration Drill at a new location

- ▶ Game Playing


Exploitation Play the move you currently believe is best

Exploration Try a new strategy

## Gridworld Example: Prediction



(a)




3.3	8.8	4.4	5.3	1.5
1.5	3.0	2.3	1.9	0.5
0.1	0.7	0.7	0.4	-0.4
-1.0	-0.4	-0.4	-0.6	-1.2
-1.9	-1.3	-1.2	-1.4	-2.0

(b)

Reward is  $-1$  when bumping into a wall,  $\gamma = 0.9$

What is the value function for the uniform random policy?


## Gridworld Example: Control



a) gridworld

22.0	24.4	22.0	19.4	17.5
19.8	22.0	19.8	17.8	16.0
17.8	19.8	17.8	16.0	14.4
16.0	17.8	16.0	14.4	13.0
14.4	16.0	14.4	13.0	11.7

b)  $V^*$



c)  $\pi^*$

What is the optimal value function over all possible policies?

What is the optimal policy?

# Course

- ▶ In this course, we discuss how to learn by interaction
- ▶ The focus is on understanding core principles and learning algorithms

Topics include

- ▶ Exploration, in bandits and in sequential problems
- ▶ Markov decision processes, and planning by dynamic programming
- ▶ Model-free prediction and control (e.g., Q-learning)
- ▶ Policy-gradient methods
- ▶ Challenges in deep reinforcement learning
- ▶ Integrating learning and planning
- ▶ Guest lectures by Vlad Mnih and David Silver

Video

Locomotion