

# Presentation Studio

## Source Installation Guide

Set up the Electron desktop app, connect any standard MCP client, and understand the project and export security boundaries.

| INSTALLATION                           | PROJECTS                              | AI CONTROL                      |
|----------------------------------------|---------------------------------------|---------------------------------|
| Source setup only<br>macOS and Windows | Self-contained<br>optional encryption | Local MCP<br>human review gates |

**Important**

There is no DMG, PKG, MSI, EXE, app-store package, or other application installer in this release. The setup scripts install and verify the source checkout without disabling operating-system protections.

# Before you begin

Presentation Studio is designed for local presentation review and redesign. Imported PowerPoint files are copied into a self-contained project, audited without changing the originals, and exported only as new files through a human-controlled save or export action.

## Requirements

|                  |                                                                                                                               |
|------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Operating system | macOS or Windows                                                                                                              |
| Runtime          | Node.js 22.13 or newer with npm                                                                                               |
| Disk space       | Enough local space for source decks, packaged Resources, recovery files, and exported copies                                  |
| Network          | Needed only to obtain source dependencies when they are not already cached; the running app blocks non-local network requests |

## Install or update Version 0.2

Version 0.2 is delivered from the isolated codex/web-slide-design-engine branch. A fresh checkout and an existing-checkout update are shown below.

```
git clone --branch codex/web-slide-design-engine --single-branch
https://github.com/adammalin/Presentation-Studio.git
cd Presentation-Studio

git fetch origin codex/web-slide-design-engine
git switch codex/web-slide-design-engine
git pull --ff-only origin codex/web-slide-design-engine
```

**Update safety**

Close Presentation Studio before updating. The fast-forward-only pull stops instead of overwriting local development changes. Run the platform setup script after cloning or updating so dependencies and the production renderer match the checked-out version.

## What setup verifies

The setup scripts run the locked dependency install, automated tests, repository data-safety scan, and production renderer build. A successful setup proves the current checkout can run; it does not approve any presentation for distribution.

**Data boundary**

Do not place client decks, manuscripts, project packages, extracted text, previews, or exports in the repository. Synthetic fixtures are generated locally and ignored by Git.

# Install on macOS

Use the included source setup script. It checks the installed Node.js version and stops with a clear message if the requirement is not met.

- 1 Get or update the Version 0.2 release branch using the commands on the previous page.
- 2 Double-click scripts/setup-macos.command, or run it from Terminal.
- 3 Wait for dependency installation, tests, data-safety checks, and the production build to pass.
- 4 Start the app with scripts/start-macos.command.

## Terminal commands

```
./scripts/setup-macos.command  
./scripts/start-macos.command
```

### macOS security

The script does not change Gatekeeper, quarantine attributes, or other operating-system protections. Follow your organization's approved software process if local policy blocks source execution.

# Install on Windows

- 1 Get or update the Version 0.2 release branch and open PowerShell in that folder.
- 2 Run the setup script shown below. It performs the same checks as macOS.
- 3 Start the app with the separate start script after setup passes.

```
& .\scripts\setup-windows.ps1  
& .\scripts\start-windows.ps1
```

### Windows security

The script does not change PowerShell execution policy, SmartScreen, or other protections. Use an approved policy exception or source-install process instead of disabling controls.

# Connect an MCP client

Presentation Studio exposes a standard STDIO MCP server. It can be used by any compatible AI client; the app does not contain a provider-specific model or API-key workflow.

- 1

Open Presentation Studio and keep the desktop app running.
- 2

Print the standard configuration snippet with the command below.
- 3

Add the presentation-studio entry to your MCP client's normal mcpServers configuration, then restart that client if required.
- 4

Turn on the visible AI session switch in Presentation Studio only when you want the current project and deck context available.

```
node scripts/configure-mcp.mjs
```

To merge the entry into an explicitly selected JSON file:

```
node scripts/configure-mcp.mjs --write /absolute/path/to/mcp-config.json
```

## MCP safety model

| Allowed                                                                                                                                                                                         | Human only                                                                                                                                                                         |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <div>Check app status</div> <div>Read authorized deck context</div> <div>Stage semantic design changes</div> <div>Build private local candidates</div> <div>Record qualification evidence</div> | <div>Confirm a template exception</div> <div>Apply or reject a legacy proposal</div> <div>Save a project</div> <div>Export a PowerPoint copy</div> <div>Distribute an output</div> |

- Current MCP boundary

Authorized MCP models can inspect, stage semantic design changes, build private local candidates, and record qualification evidence. They cannot overwrite an original, save the project, export to a user destination, or distribute an output.
- Local connection

The STDIO server reaches the active app through a per-session token on a loopback-only bridge. The token descriptor is written with private local permissions and removed when the app closes.

# Projects, encryption, and verification

## Project formats

| .pstudio                                                                                                                          | .pstudio-secure                                                                                                                 |
|-----------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| ZIP-based self-contained package<br>Canonical project JSON<br>Immutable-by-hash Resources<br>Portable without original file paths | Encrypts the complete .pstudio payload<br>AES-256-GCM<br>PBKDF2-SHA-256 with 250,000 iterations<br>Password cannot be recovered |

Encryption boundary

Encrypted project files protect packaged JSON and Resources. They do not encrypt the external originals or separately exported PowerPoint, PDF, SVG, or PNG files.

## Verify the checkout

```
npm run quality
npm run desktop:smoke
```

## Expected result

Tests should pass, the repository scan should report no tracked client artifacts, Vite should produce a production bundle, and the Electron smoke check should save a valid renderer capture before exiting.

## Troubleshooting

App reports that setup is missing

Run the platform setup script from the repository root so that node\_modules and the production bundle are created.

MCP says the app is unavailable

Open Presentation Studio first. Restart the desktop app if the local runtime descriptor is stale, then retry the MCP tool.

A deck needs manual review

Macros, embedded OLE objects, external relationships, uncertain templates, and ambiguous formatting intentionally stop automated cleanup. Preserve the source and resolve the finding in the app.