What's new in NetApp HCI

HCI

Michael Wallis, Ann-Marie Grissino, amitha July 08, 2020

This PDF was generated from https://docs.netapp.com/us-en/hci/docs/rn_whatsnew.html on July 17, 2020. Always check docs.netapp.com for the latest.



Table of Contents

V	Vhat's new in NetApp HCI	1
	NetApp HCI 1.8	1
	Element 12.0	2

What's new in NetApp HCI

NetApp periodically updates NetApp HCI to bring you new features, enhancements, and bug fixes. NetApp HCI 1.8 includes Element 12.0 for storage clusters.

- The NetApp HCI 1.8 section describes new features and updates in NetApp HCI version 1.8.
- The Element 12.0 section describes new features and updates in NetApp Element 12.0.

NetApp HCI 1.8

NetApp HCI 1.8 introduces two-node and three-node storage cluster capability, multi-factor authentication, and NetApp Hybrid Cloud Control enhancements.

Active IQ Config Advisor

Active IQ Config Advisor is a tool that helps streamline the installation experience and reduce networking failures during deployment. It validates that the configuration is ready for deployment and generates a report that you can use to resolve issues and send to NetApp Professional Services before hardware installation. See the Deployment Guide for details.

NetApp HCI documentation enhancements

You can now access NetApp HCI upgrading, expansion, monitoring, and concepts information in an easy-to-navigate format here.

NetApp Element Plug-in for vCenter Server 4.4 availability

The NetApp Element Plug-in for vCenter Server 4.4 is available outside of the management node 12.0 and NetApp HCI 1.8 releases. To upgrade the plug-in, follow the instructions in the NetApp HCI Upgrades documentation.

NetApp Hybrid Cloud Control enhancements

NetApp Hybrid Cloud Control is enhanced for version 1.8. Learn more.

Support for two-node and three-node storage clusters

With version 1.8, you can set up NetApp HCI to use a storage cluster with two or three storage nodes. When you deploy with a two-node or three-node storage cluster, the deployment process automatically configures two NetApp Witness Nodes as virtual machines. Witness Nodes are virtual nodes that enable storage node redundancy in the event of a storage node failure. NetApp HCI supports the H410S-0, H410S-1, and H610S-1 storage nodes in two-node or three-node storage clusters. Learn more.

Element 12.0

NetApp HCI 1.8 includes Element 12.0 for storage clusters. Element 12.0 introduces multi-factor authentication, session-based web UI logins, external key management (EKM) enhancements, faster upgrades, customizable protection domains, and contains stability and functionality improvements.

Element 12.0 firmware updates

The following firmware updates for H610S storage node hardware components are included with this release:

Component	Firmware version
BIOS	3B03
NVDIMM Gen1	3.1
NVDIMM BPM	2.16
CPLD	v122
BMC	3.78.07
YafuFlash2	4.16.21

Multiple vCenter VASA support

VASA support for up to 10 vCenters is available as an upgrade patch if you have already registered a VASA provider with your vCenter. To install, follow the directions in the VASA39 manifest and download the .tar.gz file from the NetApp Software Downloads site.

NOTE: The NetApp Element VASA provider uses a NetApp certificate. With this patch, the certificate is used unmodified by vCenter to support multiple vCenters for VASA and VVols use. Do not modify the certificate. Custom SSL certificates are not supported by VASA.

Customizable Protection Domains

Beginning with Element 12.0, you can customize protection domain layouts to cover zones of storage nodes within a rack, or between multiple racks. This enables you to have more flexibility in data resiliency and to improve storage availability, especially in large scale installations. When you enable the feature, you must have at least 3 domains, and at least 2 storage nodes per domain.

The following are Element API methods related to Protection Domains (the Element API Reference Guide has more information):

- SetProtectionDomainLayout
- GetProtectionDomainLayout
- ListAllNodes

- ListActiveNodes
- ListPendingNodes
- AddDrives
- ListProtectionDomainLevels
- CheckProposedNodeAdditions
- CheckProposedCluster

Faster upgrades

Element 12.0 brings decreases in upgrade times. Upgrades from Element 12.0 to future Element releases are significantly faster than upgrades from previous versions.

Enhanced external key management

Element 12.0 external key management (EKM) now supports the following key management services:

- Gemalto SafeNet KeySecure
- SafeNet AT KeySecure
- HyTrust KeyControl
- Vormetric Data Security Manager (new in Element 12.0)
- IBM Security Key Lifecycle Manager (new in Element 12.0)
 Learn more.

Multi-factor authentication

With multi-factor authentication (MFA) support, you can now integrate the Element web UI and the storage per-node web UI with your single sign-on (SSO) infrastructure.

MFA supports the following SAML 2.0-based identity providers (IdPs):

- Microsoft Active Directory Federation Services (ADFS) 2016
- Shibboleth 3.4.4

The following are Element API methods related to MFA (the Element API Reference Guide has more information):

- CreateIdpConfiguration
- UpdateIdpConfiguration
- DeleteIdpConfiguration
- ListIdpConfigurations

- EnableIdpAuthentication
- DisableIdpAuthentication
- ListProtectionDomainLevels
- GetIdpAuthenticationState
- ListCurrentClusterAdmins
- DeleteAuthSession
- DeleteAuthSessionsByClusterAdmin
- DeleteAuthSessionsByUsername
- ListActiveAuthSessions
- ListAuthSessionsByClusterAdmin
- ListAuthSessionsByUsername

New storage node terminal user interface (TUI)

The Element TUI is now restructured and features easier to use navigation and input fields.

New storage per-node web UI

The Element 12.0 storage per-node web UI now uses the look and feel of NetApp Hybrid Cloud Control. You can access this UI at https://<Node IP address>:442/hcc.

Security enhancements

Element 12.0 resolves many security vulnerabilities for storage nodes and the management node. Learn more about these security enhancements.

Session-based authentication

The Element API now supports token authentication and authorization, enabling you to log on to the Element web UI or individual storage per-node web UIs with either the local cluster admin credentials or LDAP-based cluster admin credentials. One browser login session token covers multiple web UI logins, so you can log in to the Element web UI and then log in to all individual storage per-node web UIs in that storage cluster and not have to re-authenticate with each one.

The following are Element API methods related to session-based authentication (the Element API Reference Guide has more information):

- ListAuthSessionsByClusterAdmin
- ListActiveAuthSessions
- ListAuthSessionsByUsername

Find more information

- NetApp HCI Documentation Center
- SolidFire and Element Software Documentation Center
- Firmware and driver versions for NetApp HCI and NetApp Element software

Copyright Information

Copyright © 2020 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval systemwithout prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at http://www.netapp.com/TM are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.