



# Validation Results: NetApp HCI for Red Hat OpenShift on RHV

## HCI

Dorian Henderson  
July 08, 2020

This PDF was generated from [https://docs.netapp.com/us-en/hci-solutions/redhat\\_openshift\\_validation\\_results\\_\\_netapp\\_hci\\_for\\_red\\_hat\\_openshift\\_on\\_rhv.html](https://docs.netapp.com/us-en/hci-solutions/redhat_openshift_validation_results__netapp_hci_for_red_hat_openshift_on_rhv.html) on July 31, 2020. Always check docs.netapp.com for the latest.



# Table of Contents

Validation Results: NetApp HCI for Red Hat OpenShift on RHV ..... 1

# Validation Results: NetApp HCI for Red Hat OpenShift on RHV

This section provides the steps to deploy a continuous integration/continuous delivery or deployment (CI/CD) pipeline with Jenkins in order to validate the operation of the solution.

## Create the Resources Required for Jenkins Deployment

To create the resources required for deploying the Jenkins application, complete the following steps:

1. Create a new project named Jenkins.

### Create Project

Name \*

Display Name

Description

Cancel

Create

2. In this example, we deployed Jenkins with persistent storage. To support the Jenkins build, create the PVC. Navigate to Storage > Persistent Volume Claims and click Create Persistent Volume Claim. Select the storage class that was created, make sure that the Persistent Volume Claim Name is jenkins, select the appropriate size and access mode, and then click Create.

## Create Persistent Volume Claim

[Edit YAML](#)

### Storage Class

SC basic ▼

Storage class for the new claim.

### Persistent Volume Claim Name \*

jenkins

A unique name for the storage claim within the project.

### Access Mode \*

☒ Single User (RWO) ☐ Shared Access (RWX) ☐ Read Only (ROX)

Permissions to the mounted drive.

### Size \*

100 GiB ▼

Desired storage capacity.

☐ Use label selectors to request storage

Use label selectors to define how storage is created.

Create

Cancel

## Deploy Jenkins with Persistent Storage

To deploy Jenkins with persistent storage, complete the following steps:

1. In the upper left corner, change the role from Administrator to Developer. Click +Add and select From Catalog. In the Filter by Keyword bar, search jenkins. Select Jenkins Service, with Persistent Storage.

## Developer Catalog

Add shared apps, services, or source-to-image builders to your project from the Developer Catalog. Cluster admins can install additional apps which will show up here automatical

All Items

Languages

Databases

Middleware

CI/CD

Other

Type

☒ Operator Backed (0)

☐ Helm Charts (0)

☒ Builder Image (0)


☒ Template (4)

☐ Service Class (0)

All Items


jenkins

Group By: None ▾

Template


Jenkins  
provided by Red Hat, Inc.

Jenkins service, with persistent storage. NOTE: You must have persistent volumes available in...

Template


Jenkins  
provided by Red Hat, Inc.

Jenkins service, with persistent storage. NOTE: You must have persistent volumes available in...

Template

Jenkins (Ephemeral)  
provided by Red Hat, Inc.

Jenkins service, without persistent storage. WARNING: Any data stored will be lost upon...

Template

Jenkins (Ephemeral)  
provided by Red Hat, Inc.

Jenkins service, without persistent storage. WARNING:

### 2. Click Instantiate Template.



## Jenkins

Provided by Red Hat, Inc.



Instantiate Template

### Provider

Red Hat, Inc.

### Support

[Get support](#)

### Created At

 May 26, 3:58 am

### Description

Jenkins service, with persistent storage.

NOTE: You must have persistent volumes available in your cluster to use this template.

### Documentation

[https://docs.okd.io/latest/using\\_images/other\\_images/jenkins.html](https://docs.okd.io/latest/using_images/other_images/jenkins.html)

### 3. By default, the details for the Jenkins application are populated. Based on your requirements, modify the parameters, and click Create. This process creates all the required resources for

supporting Jenkins on OpenShift.

## Instantiate Template

**Namespace \***  

PR jenkins

**Jenkins Service Name**  

jenkins

The name of the OpenShift Service exposed for the Jenkins container.

**Jenkins JNLP Service Name**  

jenkins-jnlp

The name of the service used for master/slave communication.

**Enable OAuth in Jenkins**  

true

Whether to enable OAuth OpenShift integration. If false, the static account 'admin' will be initialized with the password 'password'.

**Memory Limit**  

1Gi

Maximum amount of memory the container can use.

**Volume Capacity \***  

50Gi

Volume space available for data, e.g. 512Mi, 2Gi.

**Jenkins ImageStream Namespace**  

openshift

The OpenShift Namespace where the Jenkins ImageStream resides.

**Disable memory intensive administrative monitors**  

false

Whether to perform memory intensive, possibly slow, synchronization with the Jenkins Update Center on start. If true, the Jenkins core update monitor and site warnings monitor are disabled.

**Jenkins ImageStreamTag**  

jenkins:2

Name of the ImageStreamTag to be used for the Jenkins image.

**Fatal Error Log File**  

false

When a fatal error occurs, an error log is created with information and the state obtained at the time of the fatal error.


**Allows use of Jenkins Update Center repository with invalid SSL certificate**  

false

Whether to allow use of a Jenkins Update Center that uses invalid certificate (self-signed, unknown CA). If any value other than 'false', certificate check is bypassed. By default, certificate check is enforced.

Create

Cancel



**Jenkins**  
INSTANT-APP JENKINS  
[View documentation](#) [Get support](#)

Jenkins service, with persistent storage.

NOTE: You must have persistent volumes available in your cluster to use this template.

---

The following resources will be created:

- DeploymentConfig
- PersistentVolumeClaim
- RoleBinding
- Route
- Service
- ServiceAccount





4. The Jenkins pods take approximately 10–12 minutes to enter the Ready state.

## Pods

[Create Pod](#)

<div>1</div> Running	<div>0</div> Pending	<div>0</div> Terminating	<div>0</div> CrashLoopBackOff	<div>1</div> Completed	<div>0</div> Failed	<div>0</div> Unknown
<div>Select all filters</div>						

1 of 2 Items





Name ↑	Namespace ↑	Status ↑	Ready ↑	Owner ↑	Memory ↑	CPU ↑	
 jenkins-1-c77n9	 jenkins	 Running	1/1	 jenkins-1	-	0.004 cores	⋮

5. After the pods are instantiated, navigate to Networking > Routes. To open the Jenkins webpage, click the URL provided for the jenkins route.


## Routes

[Create Route](#)

1 Accepted	0 Rejected	0 Pending	<a href="#">Select all filters</a>	1 Item	
------------	------------	-----------	------------------------------------	--------	--

Name ↓	Namespace ↑	Status	Location ↑	Service ↑	
 jenkins	 jenkins	 Accepted	<a href="https://jenkins-jenkins.apps.rhv-ocp-cluster.cie.netapp.com">https://jenkins-jenkins.apps.rhv-ocp-cluster.cie.netapp.com</a>	 jenkins	⋮

6. Because the OpenShift OAuth was used while creating the Jenkins app, click Log in with OpenShift.



7. Authorize jenkins service-account to access the OpenShift users.

## Authorize Access

Service account `jenkins` in project `jenkins` is requesting permission to access your account (`kube:admin`)

### Requested permissions

- ☒ **user:info**  
Read-only access to your user information (including username, identities, and group membership)
- ☒ **user:check-access**  
Read-only access to view your privileges (for example, "can I create builds?")

You will be redirected to <https://jenkins-jenkins.apps.rhv-ocp-cluster.cie.netapp.com/securityRealm/finishLogin>

Allow selected permissions

Deny

8. The Jenkins welcome page is displayed. Because we are using a Maven build, complete the Maven installation first. Navigate to Manage Jenkins > Global Tool Configuration, then in the Maven subhead, click Add Maven. Enter the name of your choice and make sure that the Install Automatically option is selected. Click Save.



**Maven**

Maven installations

**Add Maven**

Maven

Name

☒ Install automatically

**Install from Apache**

Version

**Add Installer**

**Add Maven**

**Delete Installer**

**Delete Maven**

List of Maven installations on this system

9. You can now create a pipeline to demonstrate the CI/CD workflow. On the home page, click Create New Jobs or New Item from the left- hand menu.

**Jenkins** 3  kube:admin | log out

Jenkins

[ENABLE AUTO REFRESH](#)

[add description](#)

- New Item
- People
- Build History
- Manage Jenkins
- My Views
- Open Blue Ocean
- Lockable Resources
- Credentials
- New View

**Welcome to Jenkins!**

Please [create new jobs](#) to get started.

**Build Queue**

No builds in the queue.

**Build Executor Status**

- 1 Idle
- 2 Idle

10. On the Create Item page, enter the name of your choice, select Pipeline, and click Ok.

## Enter an item name

sample-demo

» Required field



### Freestyle project

This is the central feature of Jenkins. Jenkins will build your project, combining any SCM with any build system, and this can be even used for something other than software build.



### Pipeline

Orchestrates long-running activities that can span multiple build agents. Suitable for building pipelines (formerly known as workflows) and/or organizing complex activities that do not easily fit in free-style job type.



### Multi-configuration project

Suitable for projects that need a large number of different configurations, such as testing on multiple environments, platform-specific builds, etc.



### Bitbucket Team/Project

Scans a Bitbucket Cloud Team (or Bitbucket Server Project) for all repositories matching some defined markers.



### Folder

Creates a container that stores nested items in it. Useful for grouping things together. Unlike view, which is just a filter, a folder creates a separate namespace, so you can have multiple things of the same name as long as they are in different folders.



### GitHub Organization

Scans a GitHub organization (or user account) for all repositories matching some defined markers.



### Multibranch Pipeline

Creates a set of Pipeline projects according to detected branches in one SCM repository.

11. Select the Pipeline tab. From the Try Sample Pipeline drop- down menu, select Github + Maven. The code is automatically populated. Click Save.

GeneralBuild TriggersAdvanced Project OptionsPipeline

Advanced...

## Pipeline

DefinitionPipeline script

Script

```
1 node {
2   def mvnHome
3   stage('Preparation') { // for display purposes
4     // Get some code from a GitHub repository
5     git 'https://github.com/jglick/simple-maven-project-with-tests.git'
6     // Get the Maven tool.
7     // ** NOTE: This 'M3' Maven tool must be configured
8     // **       in the global configuration.
9     mvnHome = tool 'M3'
10  }
11  stage('Build') {
12    // Run the maven build
13    withEnv(["MVN_HOME=$mvnHome"]) {
14      if (isUnix()) {
15        sh "$MVN_HOME/bin/mvn" -Dmaven.test.failure.ignore clean package
16      } else {
17        bat("%MVN_HOME%\bin\mvn" -Dmaven.test.failure.ignore clean package/)
18      }
19    }
20  }
21 }
```


GitHub + Maven

☒ Use Groovy Sandbox

[Pipeline Syntax](#)

SaveApply

12. Click Build Now to trigger the development through the preparation, build, and testing phase. It can take several minutes to complete the whole build process and display the results of the build.

Jenkins

Jenkins > sample-demo >

Back to Dashboard

Status

Changes

Build Now

Delete Pipeline

Configure

Full Stage View

Open Blue Ocean

Rename

Pipeline Syntax

Build History

trend

find

#1

May 27, 2020 3:53 PM

Atom feed for all

Atom feed for failures

# Pipeline sample-demo

Last Successful Artifacts

Recent Changes

simple-maven-project-with-tests-1.0-SNAPSHOT.jar

1.71 KB

view

Stage View

Average stage times:  
(Average full run time: ~7s)

#1

May 27 08:53

No Changes

Preparation	Build	Results
2s	4s	69ms
2s	4s	69ms

Latest Test Result (no failures)

Permalinks











Last build (#1), 1 min 23 sec ago


Last stable build (#1), 1 min 23 sec ago

Last successful build (#1), 1 min 23 sec ago

Last completed build (#1), 1 min 23 sec ago

13. Whenever there are any code changes, the pipeline can be rebuilt to patch the new version of software enabling continuous integration and continuous delivery. Click Recent Changes to track the changes from the previous version.

-  [Back to Dashboard](#)
-  [Status](#)
-  [Changes](#)
-  [Build Now](#)
-  [Delete Pipeline](#)
-  [Configure](#)
-  [Full Stage View](#)
-  [Open Blue Ocean](#)
-  [Rename](#)
-  [Pipeline Syntax](#)



**Build History**
[trend](#)


#2 May 27, 2020 3:56 PM


#1 May 27, 2020 3:53 PM

[Atom feed for all](#)
[Atom feed for failures](#)


## Pipeline sample-demo



[Last Successful Artifacts](#)


[Recent Changes](#)


[simple-maven-project-with-tests-1.0-SNAPSHOT.jar](#)
1.71 KB [view](#)

### Stage View




[Latest Test Result](#) (no failures)

### Permalinks

- [Last build \(#2\), 19 sec ago](#)
- [Last stable build \(#2\), 19 sec ago](#)
- [Last successful build \(#2\), 19 sec ago](#)
- [Last completed build \(#2\), 19 sec ago](#)

## Copyright Information

Copyright © 2020 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP “AS IS” AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.