DEMONSTRATION ONLY — NOT A QUALIFIED PROCEDURE; THE FACILITY OWNER'S QUALIFIED PROCEDURES AND APPLICABLE CODES GOVERN.

WO-300-04 — Bench test relief valve 3"-P300-RV-4001/2 on D-101-N3

Area	A300 Exchangers and drum	**Task**	PR Relief valve bench test and reinstatement
Priority	1 (safety)	**Issued by**	Facility owner (demonstration)
Primary asset	D-101 — D-101 horizontal vessel 60" ID × 180" — E 84'-0" N -25'-0" EL 107'-6"		
Equipment	D-101	**Lines**	3"-P300-RV-4001, 4"-P150-FL-4004
Isometrics	ISO-3"-P300-RV-4001, ISO-4"-P150-FL-4004 (generated); owner's drawings ISO-RV-4001, ISO-FL-4004		
Permits	General work permit, Lifting plan		

Reason

Relief valve due for its periodic bench test.

Scope of work

1. Confirm D-101 depressured and isolated.
2. Unbolt and remove VALVE, PRESSURE SAFETY VALVE 3" P300 INLET × 4" P150 OUTLET (3"-P300-RV-4001/2); blind the nozzle and the outlet line.
3. Bench test: set pressure 300 psi and seat tightness (SW-TEST-3); service the valve as found.
4. Reinstall with new gaskets and studs, tightened per SW-WO-5; remove blinds.

Affected items: 3"-P300-RV-4001/2, 3"-P300-RV-4001/1, 4"-P150-FL-4004/A1

Rules: SW-ITP-1, SW-ITP-2, SW-ITP-3, SW-NDE-5, SW-TEST-3, SW-WO-1, SW-WO-2, SW-WO-5, SW-WO-7

Owner's isometric drawings (SW-IMP-6)

Drawing	Line drawn	Work line	Sheets	Match to the plant model
ISO-RV-4001	3"-P300-RV-4001	3"-P300-RV-4001	1	0 error(s), 1 warning(s) — see below
ISO-FL-4004	4"-P150-FL-4004	4"-P150-FL-4004	1	0 error(s), 1 warning(s) — see below

ISO-RV-4001 (PDF): ../isometrics-imported/ISO-RV-4001.pdf · ISO-FL-4004 (PDF): ../isometrics-imported/ISO-FL-4004.pdf — the generated isometrics follow the ITP.

Drawing	Sheet	Level	Finding
ISO-RV-4001	1	warning	TO label 'PSV' is not on the drawing
ISO-FL-4004	1	warning	FROM label 'PSV ON D-101 NOZ. N3' is not on the drawing

Assets in the plant model (SW-WO-7)

Tag	Kind	Description	Line	Location
D-101	equipment	D-101 horizontal vessel 60" ID × 180"		E 84'-0" N -25'-0" EL 107'-6"
3"-P300-RV-4001/2	item	VALVE, PRESSURE SAFETY VALVE 3" P300 INLET × 4" P150 OUTLET	3"-P300-RV-4001	E 94'-0" N -25'-0" EL 111'-6"
3"-P300-RV-4001/1	item	GASKET 3" P300 COMPRESSED SHEET	3"-P300-RV-4001	E 94'-0" N -25'-0" EL 110'-10-3/8"
4"-P150-FL-4004/A1	item	GASKET 4" P150 COMPRESSED SHEET	4"-P150-FL-4004	E 94'-0" N -24'-4-1/16" EL 111'-6"

Isolation list (SW-WO-3)

#	Kind	Tag	Line	Action	Location	Fitted ✓	Removed ✓
1	equipment	D-101	3"-P300-RV-4001	D-101 depressured, drained and isolated under the shutdown isolation (no inlet valve)			
2	blind	3"-P300-RV-4001/1	3"-P300-RV-4001	Blind the nozzle D-101-N3 once the valve is removed	E 94'-0" N -25'-0" EL 110'-10-5/16"		
3	blind	4"-P150-FL-4004/A1	4"-P150-FL-4004	Blind the outlet line 4"-P150-FL-4004 at its first flange	E 94'-0" N -24'-4-1/8" EL 111'-6"		

Parts

Description	Qty	Replaces
GASKET 3" P300 COMPRESSED SHEET	1	3"-P300-RV-4001/1
STUD SET 4 × 0.875" × 5-3/4" WITH 2 NUTS, FOR 3" P300	1	3"-P300-RV-4001/3
GASKET 4" P150 COMPRESSED SHEET	1	4"-P150-FL-4004/A1
STUD SET 4 × 1" × 6-1/4" WITH 2 NUTS, FOR 4" P150	1	4"-P150-FL-4004/A3

Bolt-up (SW-WO-5)

Joint	Studs	Preload per stud (lbf)	Passes	Done ✓
3"-P300-RV-4001/1	4 × 0.875" studs (3"-P300-RV-4001/3)	27,059	3	
4"-P150-FL-4004/A1	4 × 1" studs (4"-P150-FL-4004/A3)	35,343	3	

Test — Relief valve bench test

Description	Set pressure 300 psi (class design pressure, PSV-1) and seat tightness
Pressure	300 psi
Basis	SW-TEST-3

Inspection and test plan (SW-ITP-1..3)

H hold · W witness · R review · S surveillance. Status: accepted / rejected / not applicable.

#	Activity	Reference	Acceptance	Record	Contr.	Owner	3rd party	Status	Signed (contr. / owner / 3rd)	Date	Remark
1	Work permit issued; isolation list (valves locked, blinds fitted) verified at zero pressure and drained	SW-WO-3, isolation list	Every isolation in place and tagged; zero pressure at the vent	Signed isolation certificate	H	H	—				
2	Relief valve removed; nozzle and outlet blinded	SW-WO-3	Both openings blinded and tagged	Isolation certificate	W	W	—				
3	As-found bench test (pop pressure recorded before any service)	SW-TEST-3	Recorded	Bench test record	W	W	W				
4	Set pressure and seat tightness after service	SW-TEST-3, PSV-1	Set at 300 psi; seat tight	Bench test record, seal tag	H	H	W				
5	Valve reinstalled; new gaskets; studs to preload	SW-WO-5	Preload as stated	Bolt-up record	W	W	—				
6	Blinds removed, isolations returned to normal line-up per the isolation list	SW-WO-3	Every blind removed and accounted for	Isolation certificate closed	H	H	—				
7	Records complete; work order handed back to operations	SW-ITP-3	All ITP activities accepted or not applicable	Signed ITP and completion record	H	H	R				

ISOMETRIC — 3"-P300-RV-4001 — Bench test relief valve 3"-P300-RV-4001/2 on D-101-N3

N



BILL OF MATERIALS

1	GASKET 3" P300 COMPRESSED SHEET	1
2	VALVE, PRESSURE SAFETY VALVE 3" P300 INLET × 4" P150 OU…	1
3	STUD SET 4 × 0.875" × 5-3/4" WITH 2 NUTS, FOR 3" P300	1

WELDS 0 (0 FIELD) · SUPPORTS 0 · SPOOLS 0

3"-P300-RV-4001

CLASS H300 — Hydrocarbon process
SERVICE RV · 3" · P300 · DESIGN 300 psi
D-101-N3 → PSV
PIPE 0.000" · WEIGHT 133 lb

DWG ISO-3"-P300-RV-4001 REV 0 WO-300-04

SmartWeld AI · not to scale · E lower right, N upper right, EL up (SW-ISO-1)

DEMONSTRATION ONLY — NOT A QUALIFIED PROCEDURE

ISOMETRIC — 4"-P150-FL-4004 — Bench test relief valve 3"-P300-RV-4001/2 on D-101-N3



BILL OF MATERIALS

1	GASKET 4" P150 COMPRESSED SHEET	1
2	FLANGE WELD-NECK 4" P150 RAISED FACE	1
3	STUD SET 4 × 1" × 6-1/4" WITH 2 NUTS, FOR 4" P150	1
4	PIPE 4" P150 BEVELLED ENDS	38'-11-15/16"
5	ELBOW 90° R = 5/3 OD 4" P150	3

WELDS 8 (2 FIELD) · SUPPORTS 0 · SPOOLS 2

W1F W2F W3 W4 W5 W6 W7 W8

4"-P150-FL-4004

CLASS F150 — Flare and relief outlets
SERVICE FL · 4" · P150 · DESIGN 150 psi
PSV on D-101-N3 → tap 8"-P150-FL-2009
PIPE 38'-11-15/16" · WEIGHT 355 lb

DWG ISO-4"-P150-FL-4004 REV 0 WO-300-04

SmartWeld AI · not to scale · E lower right, N upper right, EL up (SW-ISO-1)

DEMONSTRATION ONLY — NOT A QUALIFIED PROCEDURE

Notices

DEMONSTRATION ONLY — NOT A QUALIFIED PROCEDURE; THE FACILITY OWNER'S QUALIFIED PROCEDURES AND APPLICABLE CODES GOVERN.

This document embeds a subset of the DejaVu Sans font (SW-LIC-3), renamed under its licence. DejaVu Sans (assets/fonts/DejaVuSans.ttf), from the DejaVu fonts 2.37 as packaged in the build environment.

Copyright (c) 2003 by Bitstream, Inc. All Rights Reserved. Bitstream Vera is a trademark of Bitstream, Inc.
DejaVu changes are in public domain.

Permission is hereby granted, free of charge, to any person obtaining a copy
of the fonts accompanying this license ("Fonts") and associated
documentation files (the "Font Software"), to reproduce and distribute the
Font Software, including without limitation the rights to use, copy, merge,
publish, distribute, and/or sell copies of the Font Software, and to permit
persons to whom the Font Software is furnished to do so, subject to the
following conditions:

The above copyright and trademark notices and this permission notice shall
be included in all copies of one or more of the Font Software typefaces.

The Font Software may be modified, altered, or added to, and in particular
the designs of glyphs or characters in the Fonts may be modified and
additional glyphs or characters may be added to the Fonts, only if the fonts
are renamed to names not containing either the words "Bitstream" or the word
"Vera".

This License becomes null and void to the extent applicable to Fonts or Font
Software that has been modified and is distributed under the "Bitstream
Vera" names.

The Font Software may be sold as part of a larger software package but no
copy of one or more of the Font Software typefaces may be sold by itself.

THE FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS
OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY,
FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF COPYRIGHT, PATENT,
TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL BITSTREAM OR THE GNOME
FOUNDATION BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, INCLUDING
ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES,
WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF
THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE
FONT SOFTWARE.

Except as contained in this notice, the names of Gnome, the Gnome
Foundation, and Bitstream Inc., shall not be used in advertising or
otherwise to promote the sale, use or other dealings in this Font Software
without prior written authorization from the Gnome Foundation or Bitstream
Inc., respectively. For further information, contact: fonts at gnome dot
org.