DOWNLOAD PDF

Authentication

- HTTP Authentication, scheme: bearer

Market Data

Asset Directory

Code samples

```
const headers = {
  'Authorization':'Bearer {access-token}'
};

fetch('/api/assets/{id}/',
{
  method: 'DELETE',

  headers: headers
})
.then(function(res) {
    return res.json();
}).then(function(body) {
    console.log(body);
});
```

```
import requests
headers = {
  'Authorization': 'Bearer {access-token}'
}

r = requests.delete('/api/assets/{id}/', headers = headers)

print(r.json())
```

`DELETE /api/assets/{id}/`

Standard CRUD interface for all assets in the system. Use for admin-level management or full list retrieval.

Parameters

Name	In	Type	Required	Description
id	path	integer	true	A unique integer value identifying this asset.

Responses

Status	Meaning	Description	Schema
204	No Content	No response body	None

To perform this operation, you must be authenticated by means of one of the following methods: jwtAuth

Search Assets

Code samples

```
const headers = {
  'Accept':'application/json',
  'Authorization':'Bearer {access-token}'
};

fetch('/api/assets/search/?q=string',
{
  method: 'GET',

  headers: headers
})
.then(function(res) {
    return res.json();
}).then(function(body) {
    console.log(body);
});
```

```
import requests
headers = {
  'Accept': 'application/json',
  'Authorization': 'Bearer {access-token}'
}

r = requests.get('/api/assets/search/', params={
  'q': 'string'
}, headers = headers)

print(r.json())
```

`GET /api/assets/search/`

Search for stocks or assets by ticker symbol or full company name. Returns up to 20 matches.

Parameters

Name	In	Type	Required	Description
q	query	string	true	Search query (e.g., "AAPL" or "Apple")

> Example responses

```
{
  "results": [
    {
      "id": 1,
      "ticker": "AAPL",
      "name": "Apple Inc.",
      "type": "STOCK"
    }
  ]
}
```

Responses

Status	Meaning	Description	Schema
200	OK	none	Inline

Response Schema

Status Code **200**

Name	Type	Required	Restrictions	Description
» **additionalProperties**	any	false	none	none

To perform this operation, you must be authenticated by means of one of the following methods: jwtAuth

Get All Live Prices

> Code samples

```
const headers = {
  'Accept':'application/json',
  'Authorization':'Bearer {access-token}'
};

fetch('/api/market/prices/',
{
  method: 'GET',
```

```
  headers: headers
})
.then(function(res) {
    return res.json();
}).then(function(body) {
    console.log(body);
});
```

```
import requests
headers = {
  'Accept': 'application/json',
  'Authorization': 'Bearer {access-token}'
}

r = requests.get('/api/market/prices/', headers = headers)

print(r.json())
```

`GET /api/market/prices/`

Fetches real-time price data from Redis for all tracked assets in the simulation engine.

> Example responses

```
[
  {
    "ticker": "AAPL",
    "price": 150.25
  },
  {
    "ticker": "TSLA",
    "price": 675.1
  },
  {
    "ticker": "BTC",
    "price": 48000.5
  }
]
```

Responses

Status	Meaning	Description	Schema
200	OK	none	Inline

Response Schema

Status Code **200**

Name	Type	Required	Restrictions	Description
» **additionalProperties**	any	false	none	none

To perform this operation, you must be authenticated by means of one of the following methods: jwtAuth

Financial Operations

Deposit Funds

> Code samples

```
const inputBody = '{
  "amount": 1000
}';
const headers = {
  'Content-Type':'application/json',
  'Accept':'application/json',
  'Authorization':'Bearer {access-token}'
};

fetch('/api/deposit/',
{
  method: 'POST',
  body: inputBody,
  headers: headers
})
.then(function(res) {
    return res.json();
}).then(function(body) {
    console.log(body);
});
```

```
import requests
headers = {
  'Content-Type': 'application/json',
  'Accept': 'application/json',
  'Authorization': 'Bearer {access-token}'
}

r = requests.post('/api/deposit/', headers = headers)

print(r.json())
```

`POST /api/deposit/`

Adds a specified amount to the authenticated user's balance and logs a Transaction record.

> Body parameter

```
{
  "amount": 1000
}
```

```
amount: 1000
```

Parameters

Name	In	Type	Required	Description
body	body	Deposit	true	none
» amount	body	string(decimal)	true	none

> Example responses

```
{
  "amount": 1000
}
```

Responses

Status	Meaning	Description	Schema
200	OK	none	Inline

Response Schema

Status Code **200**

Name	Type	Required	Restrictions	Description
» **additionalProperties**	any	false	none	none

To perform this operation, you must be authenticated by means of one of the following methods: jwtAuth

Withdraw Funds

> Code samples

```
const inputBody = '{
  "amount": 500
}';
const headers = {
  'Content-Type':'application/json',
  'Accept':'application/json',
  'Authorization':'Bearer {access-token}'
};

fetch('/api/withdraw/',
{
  method: 'POST',
  body: inputBody,
  headers: headers
})
.then(function(res) {
    return res.json();
}).then(function(body) {
    console.log(body);
});
```

```
import requests
headers = {
  'Content-Type': 'application/json',
  'Accept': 'application/json',
  'Authorization': 'Bearer {access-token}'
}

r = requests.post('/api/withdraw/', headers = headers)

print(r.json())
```

`POST /api/withdraw/`

Deducts funds from the user's balance. Includes an atomic check to prevent overdrafts.

> Body parameter

```
{
  "amount": 500
}
```

```
amount: 500
```

Parameters

Name	In	Type	Required	Description
body	body	Deposit	true	none
» amount	body	string(decimal)	true	none

> Example responses

```
{
  "amount": 500
}
```

```
{
  "error": "Insufficient funds for this withdrawal."
}
```

Responses

Status	Meaning	Description	Schema
200	OK	none	Inline
400	Bad Request	none	Inline

Response Schema

Status Code **200**

Name	Type	Required	Restrictions	Description
» **additionalProperties**	any	false	none	none

Status Code **400**

Name	Type	Required	Restrictions	Description
» **additionalProperties**	any	false	none	none

To perform this operation, you must be authenticated by means of one of the following methods: jwtAuth

Trading

Cancel Pending Order

Code samples

```
const headers = {
  'Accept':'application/json',
  'Authorization':'Bearer {access-token}'
};

fetch('/api/orders/{id}/cancel/',
{
  method: 'DELETE',

  headers: headers
})
.then(function(res) {
    return res.json();
}).then(function(body) {
    console.log(body);
});
```

```
import requests
headers = {
  'Accept': 'application/json',
  'Authorization': 'Bearer {access-token}'
}

r = requests.delete('/api/orders/{id}/cancel/', headers = headers)

print(r.json())
```

`DELETE /api/orders/{id}/cancel/`

Updates order status to CANCELLED. Only works for orders that are not yet finalized.

Parameters

Name	In	Type	Required	Description
id	path	integer	true	none

Example responses

204 Response

```
{
  "property1": null,
```

```
  "property2": null
}
```

Responses

Status	Meaning	Description	Schema
204	No Content	none	Inline
400	Bad Request	none	Inline

Response Schema

Status Code **204**

Name	Type	Required	Restrictions	Description
» **additionalProperties**	any	false	none	none

Status Code **400**

Name	Type	Required	Restrictions	Description
» **additionalProperties**	any	false	none	none

To perform this operation, you must be authenticated by means of one of the following methods: jwtAuth

List Active Orders

> Code samples

```
const headers = {
  'Accept':'application/json',
  'Authorization':'Bearer {access-token}'
};

fetch('/api/orders/active/',
{
  method: 'GET',

  headers: headers
})
.then(function(res) {
    return res.json();
}).then(function(body) {
    console.log(body);
});
```

```
import requests
headers = {
  'Accept': 'application/json',
  'Authorization': 'Bearer {access-token}'
}

r = requests.get('/api/orders/active/', headers = headers)

print(r.json())
```

`GET /api/orders/active/`

Returns all orders currently in PENDING or PARTIAL status.

> Example responses

> 200 Response

```
[
  {
    "id": 0,
    "asset": "string",
    "side": "BUY",
    "type": "MARKET",
    "quantity": 2147483647,
    "limit_price": "string",
    "status": "PENDING",
    "timestamp": "2019-08-24T14:15:22Z"
  }
]
```

Responses

Status	Meaning	Description	Schema
200	OK	none	Inline

Response Schema

Status Code **200**

Name	Type	Required	Restrictions	Description
anonymous	[Order]	false	none	none
» id	integer	true	read-only	none
» asset	string	true	read-only	none

Name	Type	Required	Restrictions	Description
» side	SideEnum	true	none	* BUY - Buy * SELL - Sell
» type	OrderTypeEnum	true	none	* MARKET - Market * LIMIT - Limit
» quantity	integer	true	none	none
» limit_price	string(decimal)¦null	false	none	none
» status	StatusEnum	true	read-only	* PENDING - Pending * FILLED - Filled * CANCELLED - Cancelled * PARTIAL - Partially Filled
» timestamp	string(date-time)	true	read-only	none

Enumerated Values

Property	Value
side	BUY
side	SELL
type	MARKET
type	LIMIT
status	PENDING
status	FILLED
status	CANCELLED
status	PARTIAL

To perform this operation, you must be authenticated by means of one of the following methods: jwtAuth

Execute Market Buy

> Code samples

```
const inputBody = '{
  "ticker": "AAPL",
  "quantity": 10
}';
const headers = {
  'Content-Type':'application/json',
  'Accept':'application/json',
  'Authorization':'Bearer {access-token}'
};
```

```
fetch('/api/orders/market-buy/',
{
  method: 'POST',
  body: inputBody,
  headers: headers
})
.then(function(res) {
    return res.json();
}).then(function(body) {
    console.log(body);
});
```

```
import requests
headers = {
  'Content-Type': 'application/json',
  'Accept': 'application/json',
  'Authorization': 'Bearer {access-token}'
}

r = requests.post('/api/orders/market-buy/', headers = headers)

print(r.json())
```

`POST /api/orders/market-buy/`

Submits a buy order. Validation checks funds, balance is deducted immediately, and holdings are updated using weighted average cost.

> Body parameter

```
{
  "ticker": "AAPL",
  "quantity": 10
}
```

```
ticker: AAPL
quantity: 10
```

Parameters

Name	In	Type	Required	Description

Name	In	Type	Required	Description
body	body	PlaceMarketBuy	true	none
» asset_id	body	integer	true	none
» quantity	body	integer	true	none

> Example responses

```
{
  "ticker": "AAPL",
  "quantity": 10
}
```

```
{
  "detail": "Insufficient balance to cover order cost (including fees)."
}
```

Responses

Status	Meaning	Description	Schema
201	Created	none	Inline
400	Bad Request	none	Inline

Response Schema

Status Code **201**

Name	Type	Required	Restrictions	Description
» **additionalProperties**	any	false	none	none

Status Code **400**

Name	Type	Required	Restrictions	Description
» **additionalProperties**	any	false	none	none

To perform this operation, you must be authenticated by means of one of the following methods: jwtAuth

Execute Market Sell

> Code samples

```
const inputBody = '{
  "ticker": "TSLA",
```

```
  "quantity": 5
}';
const headers = {
  'Content-Type':'application/json',
  'Accept':'application/json',
  'Authorization':'Bearer {access-token}'
};

fetch('/api/orders/market-sell/',
{
  method: 'POST',
  body: inputBody,
  headers: headers
})
.then(function(res) {
    return res.json();
}).then(function(body) {
    console.log(body);
});
```

```
import requests
headers = {
  'Content-Type': 'application/json',
  'Accept': 'application/json',
  'Authorization': 'Bearer {access-token}'
}

r = requests.post('/api/orders/market-sell/', headers = headers)

print(r.json())
```

`POST /api/orders/market-sell/`

Submits a sell order. Checks if user owns the asset quantity, removes from holdings, and credits cash balance.

> Body parameter

```
{
  "ticker": "TSLA",
  "quantity": 5
}
```

```
ticker: TSLA
quantity: 5
```

Parameters

Name	In	Type	Required	Description
body	body	PlaceMarketSell	true	none
» asset_id	body	integer	true	none
» quantity	body	integer	true	none

Example responses

```
{
  "ticker": "TSLA",
  "quantity": 5
}
```

400 Response

```
{
  "property1": null,
  "property2": null
}
```

Responses

Status	Meaning	Description	Schema
201	Created	none	Inline
400	Bad Request	none	Inline

Response Schema

Status Code **201**

Name	Type	Required	Restrictions	Description
» **additionalProperties**	any	false	none	none

Status Code **400**

Name	Type	Required	Restrictions	Description
» **additionalProperties**	any	false	none	none

To perform this operation, you must be authenticated by means of one of the following methods: jwtAuth

Portfolio

Get Order History

> Code samples

```
const headers = {
  'Accept':'application/json',
  'Authorization':'Bearer {access-token}'
};

fetch('/api/orders/history/',
{
  method: 'GET',

  headers: headers
})
.then(function(res) {
    return res.json();
}).then(function(body) {
    console.log(body);
});
```

```
import requests
headers = {
  'Accept': 'application/json',
  'Authorization': 'Bearer {access-token}'
}

r = requests.get('/api/orders/history/', headers = headers)

print(r.json())
```

`GET /api/orders/history/`

Returns paginated list of finalized orders (FILLED, CANCELLED). Uses limit and offset query parameters.

Parameters

Name	In	Type	Required	Description
limit	query	integer	false	Number of results to return per page.
offset	query	integer	false	The initial index from which to return the results.

> Example responses

> 200 Response

```
{
  "count": 123,
  "next": "http://api.example.org/accounts/?offset=400&limit=100",
  "previous": "http://api.example.org/accounts/?offset=200&limit=100",
  "results": [
    {
      "id": 0,
      "asset": "string",
      "side": "BUY",
      "type": "MARKET",
      "quantity": 2147483647,
      "limit_price": "string",
      "status": "PENDING",
      "timestamp": "2019-08-24T14:15:22Z"
    }
  ]
}
```

Responses

Status	Meaning	Description	Schema
200	OK	none	PaginatedOrderList

To perform this operation, you must be authenticated by means of one of the following methods: jwtAuth

Portfolio Management

Get Portfolio

> Code samples

```
const headers = {
  'Accept':'application/json',
  'Authorization':'Bearer {access-token}'
};

fetch('/api/portfolio/',
{
  method: 'GET',

  headers: headers
})
.then(function(res) {
```

```
    return res.json();
}).then(function(body) {
    console.log(body);
});
```

```
import requests
headers = {
  'Accept': 'application/json',
  'Authorization': 'Bearer {access-token}'
}

r = requests.get('/api/portfolio/', headers = headers)

print(r.json())
```

`GET /api/portfolio/`

Calculates total net worth by combining cash balance and live asset valuations. Pricing uses order book mid-prices with a $100.00 fallback for simulation stability.

> Example responses

```
{
  "balance": 1250.5,
  "holdings": [
    {
      "asset": {
        "ticker": "AAPL",
        "name": "Apple Inc.",
        "type": "STOCK"
      },
      "quantity": 10,
      "current_price": 175.25,
      "current_value": 1752.5,
      "price_source": "order book mid-price"
    }
  ],
  "total_portfolio_value": 3003,
  "holdings_count": 1,
  "note": "Prices are derived from order book mid-price where available"
}
```

Responses

Status	Meaning	Description	Schema

Status	Meaning	Description	Schema
200	OK	none	Inline

Response Schema

Status Code **200**

Name	Type	Required	Restrictions	Description
» **additionalProperties**	any	false	none	none

To perform this operation, you must be authenticated by means of one of the following methods: jwtAuth

Authentication

User Registration

Code samples

```
const inputBody = '{
  "email": "user@example.com",
  "password": "string"
}';
const headers = {
  'Content-Type':'application/json',
  'Accept':'application/json',
  'Authorization':'Bearer {access-token}'
};

fetch('/api/register/',
{
  method: 'POST',
  body: inputBody,
  headers: headers
})
.then(function(res) {
    return res.json();
}).then(function(body) {
    console.log(body);
});
```

```
import requests
headers = {
  'Content-Type': 'application/json',
  'Accept': 'application/json',
  'Authorization': 'Bearer {access-token}'
}
```

```
r = requests.post('/api/register/', headers = headers)

print(r.json())
```

`POST /api/register/`

Creates a new user account in the system. New users typically start with a default balance of 0.00.

> Body parameter

```
{
  "email": "user@example.com",
  "password": "string"
}
```

```
email: user@example.com
password: string
```

Parameters

Name	In	Type	Required	Description
body	body	Register	true	none
» email	body	string(email)	true	none
» password	body	string	true	none

> Example responses

> 201 Response

```
{
  "email": "user@example.com"
}
```

Responses

Status	Meaning	Description	Schema
201	Created	none	Register

To perform this operation, you must be authenticated by means of one of the following methods: jwtAuth, None

schema

schema_retrieve

> Code samples

```
const headers = {
  'Accept':'application/vnd.oai.openapi',
  'Authorization':'Bearer {access-token}'
};

fetch('/api/schema/',
{
  method: 'GET',

  headers: headers
})
.then(function(res) {
    return res.json();
}).then(function(body) {
    console.log(body);
});
```

```
import requests
headers = {
  'Accept': 'application/vnd.oai.openapi',
  'Authorization': 'Bearer {access-token}'
}

r = requests.get('/api/schema/', headers = headers)

print(r.json())
```

`GET /api/schema/`

OpenApi3 schema for this API. Format can be selected via content negotiation.

- YAML: application/vnd.oai.openapi
- JSON: application/vnd.oai.openapi+json

Parameters

Name	In	Type	Required	Description
format	query	string	false	none

Name	In	Type	Required	Description
lang	query	string	false	none

Enumerated Values

Parameter	Value
format	json
format	yaml
lang	af
lang	ar
lang	ar-dz
lang	ast
lang	az
lang	be
lang	bg
lang	bn
lang	br
lang	bs
lang	ca
lang	ckb
lang	cs
lang	cy
lang	da
lang	de
lang	dsb
lang	el
lang	en
lang	en-au
lang	en-gb
lang	eo
lang	es
lang	es-ar

Parameter	Value
lang	es-co
lang	es-mx
lang	es-ni
lang	es-ve
lang	et
lang	eu
lang	fa
lang	fi
lang	fr
lang	fy
lang	ga
lang	gd
lang	gl
lang	he
lang	hi
lang	hr
lang	hsb
lang	ht
lang	hu
lang	hy
lang	ia
lang	id
lang	ig
lang	io
lang	is
lang	it
lang	ja
lang	ka
lang	kab
lang	kk

Parameter	Value
lang	km
lang	kn
lang	ko
lang	ky
lang	lb
lang	lt
lang	lv
lang	mk
lang	ml
lang	mn
lang	mr
lang	ms
lang	my
lang	nb
lang	ne
lang	nl
lang	nn
lang	os
lang	pa
lang	pl
lang	pt
lang	pt-br
lang	ro
lang	ru
lang	sk
lang	sl
lang	sq
lang	sr
lang	sr-latn
lang	sv

Parameter	Value
lang	sw
lang	ta
lang	te
lang	tg
lang	th
lang	tk
lang	tr
lang	tt
lang	udm
lang	ug
lang	uk
lang	ur
lang	uz
lang	vi
lang	zh-hans
lang	zh-hant

> Example responses

> 200 Response

```
{
  "property1": null,
  "property2": null
}
```

Responses

Status	Meaning	Description	Schema
200	OK	none	Inline

Response Schema

Status Code **200**

Name	Type	Required	Restrictions	Description

Name	Type	Required	Restrictions	Description
» **additionalProperties**	any	false	none	none

To perform this operation, you must be authenticated by means of one of the following methods: jwtAuth, None

token

token_create

Code samples

```
const inputBody = '{
  "email": "string",
  "password": "string"
}';
const headers = {
  'Content-Type':'application/json',
  'Accept':'application/json'
};

fetch('/api/token/',
{
  method: 'POST',
  body: inputBody,
  headers: headers
})
.then(function(res) {
    return res.json();
}).then(function(body) {
    console.log(body);
});
```

```
import requests
headers = {
  'Content-Type': 'application/json',
  'Accept': 'application/json'
}

r = requests.post('/api/token/', headers = headers)

print(r.json())
```

`POST /api/token/`

Takes a set of user credentials and returns an access and refresh JSON web token pair to prove the authentication of those credentials.

> Body parameter

```
{
  "email": "string",
  "password": "string"
}
```

```
email: string
password: string
```

Parameters

Name	In	Type	Required	Description
body	body	TokenObtainPair	true	none
» email	body	string	true	none
» password	body	string	true	none
» access	body	string	true	none
» refresh	body	string	true	none

> Example responses

> 200 Response

```
{
  "access": "string",
  "refresh": "string"
}
```

Responses

Status	Meaning	Description	Schema
200	OK	none	TokenObtainPair

This operation does not require authentication

token_refresh_create

> Code samples

```
const inputBody = '{
  "refresh": "string"
}';
const headers = {
  'Content-Type':'application/json',
  'Accept':'application/json'
};

fetch('/api/token/refresh/',
{
  method: 'POST',
  body: inputBody,
  headers: headers
})
.then(function(res) {
    return res.json();
}).then(function(body) {
    console.log(body);
});
```

```
import requests
headers = {
  'Content-Type': 'application/json',
  'Accept': 'application/json'
}

r = requests.post('/api/token/refresh/', headers = headers)

print(r.json())
```

`POST /api/token/refresh/`

Takes a refresh type JSON web token and returns an access type JSON web token if the refresh token is valid.

> Body parameter

```
{
  "refresh": "string"
}
```

```
refresh: string
```

Parameters

Name	In	Type	Required	Description
body	body	TokenRefresh	true	none
» access	body	string	true	none
» refresh	body	string	true	none

> Example responses

> 200 Response

```
{
  "access": "string"
}
```

Responses

Status	Meaning	Description	Schema
200	OK	none	TokenRefresh

This operation does not require authentication

Watchlists

List or Create Watchlists

> Code samples

```
const inputBody = '{
  "name": "string"
}';
const headers = {
  'Content-Type':'application/json',
  'Accept':'application/json',
  'Authorization':'Bearer {access-token}'
};

fetch('/api/watchlists/',
{
  method: 'POST',
  body: inputBody,
  headers: headers
})
.then(function(res) {
    return res.json();
}).then(function(body) {
```

```
    console.log(body);
});
```

```
import requests
headers = {
  'Content-Type': 'application/json',
  'Accept': 'application/json',
  'Authorization': 'Bearer {access-token}'
}

r = requests.post('/api/watchlists/', headers = headers)

print(r.json())
```

`POST /api/watchlists/`

Returns all watchlists belonging to the authenticated user or creates a new empty watchlist.

> Body parameter

```
{
  "name": "string"
}
```

```
name: string
```

Parameters

Name	In	Type	Required	Description
body	body	Watchlist	true	none
» id	body	integer	true	none
» name	body	string	true	none
» created_at	body	string(date-time)	true	none
» items	body	[WatchlistItem]	true	none
»» id	body	integer	true	none
»» asset	body	Asset	true	none

Name	In	Type	Required	Description
»»» id	body	integer	true	none
»»» ticker	body	string	true	none
»»» name	body	string	true	none
»»» type	body	AssetTypeEnum	false	* `STOCK` - Stock
»»» description	body	string	false	none
»» added_at	body	string(date-time)	true	none

Detailed descriptions

»»» type: * `STOCK` - Stock

- `ETF` - ETF

Enumerated Values

Parameter	Value
»»» type	STOCK
»»» type	ETF

> Example responses

> 201 Response

```
{
  "id": 0,
  "name": "string",
  "created_at": "2019-08-24T14:15:22Z",
  "items": [
    {
      "id": 0,
      "asset": {
        "id": 0,
        "ticker": "string",
        "name": "string",
        "type": "STOCK",
        "description": "string"
      },
      "added_at": "2019-08-24T14:15:22Z"
    }
  ]
}
```

Responses

Status	Meaning	Description	Schema
201	Created	none	Watchlist

To perform this operation, you must be authenticated by means of one of the following methods: jwtAuth

Watchlist Details

> Code samples

```
const headers = {
  'Authorization':'Bearer {access-token}'
};

fetch('/api/watchlists/{id}/',
{
  method: 'DELETE',

  headers: headers
})
.then(function(res) {
    return res.json();
}).then(function(body) {
    console.log(body);
});
```

```
import requests
headers = {
  'Authorization': 'Bearer {access-token}'
}

r = requests.delete('/api/watchlists/{id}/', headers = headers)

print(r.json())
```

`DELETE /api/watchlists/{id}/`

Retrieves, updates the name of, or deletes an entire watchlist container by ID.

Parameters

Name	In	Type	Required	Description
id	path	integer	true	none

Responses

Status	Meaning	Description	Schema
204	No Content	No response body	None

To perform this operation, you must be authenticated by means of one of the following methods: jwtAuth

Add Asset to Watchlist

> Code samples

```
const inputBody = '{
  "asset_id": 1
}';
const headers = {
  'Content-Type':'application/json',
  'Accept':'application/json',
  'Authorization':'Bearer {access-token}'
};

fetch('/api/watchlists/{watchlist_id}/items/',
{
  method: 'POST',
  body: inputBody,
  headers: headers
})
.then(function(res) {
    return res.json();
}).then(function(body) {
    console.log(body);
});
```

```
import requests
headers = {
  'Content-Type': 'application/json',
  'Accept': 'application/json',
  'Authorization': 'Bearer {access-token}'
}

r = requests.post('/api/watchlists/{watchlist_id}/items/', headers =
headers)

print(r.json())
```

`POST /api/watchlists/{watchlist_id}/items/`

Adds a specific asset to a chosen watchlist. Body requires asset_id. URL requires watchlist_id.

> Body parameter

```
{
  "asset_id": 1
}
```

```
asset_id: 1
```

Parameters

Name	In	Type	Required	Description
watchlist_id	path	integer	true	none
body	body	WatchlistItem	false	none
» id	body	integer	true	none
» asset	body	Asset	true	none
»» id	body	integer	true	none
»» ticker	body	string	true	none
»» name	body	string	true	none
»» type	body	AssetTypeEnum	false	* `STOCK` - Stock
»» description	body	string	false	none
» added_at	body	string(date-time)	true	none

Detailed descriptions

»» type: * `STOCK` - Stock

- `ETF` - ETF

Enumerated Values

Parameter	Value
»» type	STOCK
»» type	ETF

> Example responses

```
{
  "asset_id": 1
}
```

Responses

Status	Meaning	Description	Schema
201	Created	none	WatchlistItem

To perform this operation, you must be authenticated by means of one of the following methods: jwtAuth

Remove Asset from Watchlist

> Code samples

```
const headers = {
  'Authorization':'Bearer {access-token}'
};

fetch('/api/watchlists/{watchlist_id}/items/{asset_id}/',
{
  method: 'DELETE',

  headers: headers
})
.then(function(res) {
    return res.json();
}).then(function(body) {
    console.log(body);
});
```

```
import requests
headers = {
  'Authorization': 'Bearer {access-token}'
}

r = requests.delete('/api/watchlists/{watchlist_id}/items/{asset_id}/',
headers = headers)

print(r.json())
```

`DELETE /api/watchlists/{watchlist_id}/items/{asset_id}/`

Deletes a specific asset from a watchlist using the watchlist_id and asset_id provided in the URL.

Parameters

Name	In	Type	Required	Description
asset_id	path	integer	true	none
watchlist_id	path	integer	true	none

Responses

Status	Meaning	Description	Schema
204	No Content	No response body	None

To perform this operation, you must be authenticated by means of one of the following methods: jwtAuth

Schemas

Asset

```
{
  "id": 0,
  "ticker": "string",
  "name": "string",
  "type": "STOCK",
  "description": "string"
}
```

Properties

Name	Type	Required	Restrictions	Description
id	integer	true	read-only	none
ticker	string	true	none	none
name	string	true	none	none
type	AssetTypeEnum	false	none	* `STOCK` - Stock * `ETF` - ETF
description	string	false	none	none

AssetTypeEnum

```
"STOCK"
```

- `STOCK` - Stock

- `ETF` - ETF

Properties

Name	Type	Required	Restrictions	Description
anonymous	string	false	none	* `STOCK` - Stock * `ETF` - ETF

Enumerated Values

Property	Value
anonymous	STOCK
anonymous	ETF

Deposit

```
{
  "amount": "string"
}
```

Properties

Name	Type	Required	Restrictions	Description
amount	string(decimal)	true	none	none

Order

```
{
  "id": 0,
  "asset": "string",
  "side": "BUY",
  "type": "MARKET",
  "quantity": 2147483647,
  "limit_price": "string",
  "status": "PENDING",
  "timestamp": "2019-08-24T14:15:22Z"
}
```

Properties

Name	Type	Required	Restrictions	Description

Name	Type	Required	Restrictions	Description
id	integer	true	read-only	none
asset	string	true	read-only	none
side	SideEnum	true	none	* `BUY` - Buy * `SELL` - Sell
type	OrderTypeEnum	true	none	* `MARKET` - Market * `LIMIT` - Limit
quantity	integer	true	none	none
limit_price	string(decimal)¦null	false	none	none
status	StatusEnum	true	read-only	* `PENDING` - Pending * `FILLED` - Filled * `CANCELLED` - Cancelled * `PARTIAL` - Partially Filled
timestamp	string(date-time)	true	read-only	none

OrderTypeEnum

```
"MARKET"
```

- `MARKET` - Market
- `LIMIT` - Limit

Properties

Name	Type	Required	Restrictions	Description
anonymous	string	false	none	* `MARKET` - Market * `LIMIT` - Limit

Enumerated Values

Property	Value
anonymous	MARKET
anonymous	LIMIT

PaginatedOrderList

```
{
  "count": 123,
```

```
    "next": "http://api.example.org/accounts/?offset=400&limit=100",
    "previous": "http://api.example.org/accounts/?offset=200&limit=100",
    "results": [
      {
        "id": 0,
        "asset": "string",
        "side": "BUY",
        "type": "MARKET",
        "quantity": 2147483647,
        "limit_price": "string",
        "status": "PENDING",
        "timestamp": "2019-08-24T14:15:22Z"
      }
    ]
  }
```

Properties

Name	Type	Required	Restrictions	Description
count	integer	true	none	none
next	string(uri)¦null	false	none	none
previous	string(uri)¦null	false	none	none
results	[Order]	true	none	none

PatchedAsset

```
  {
    "id": 0,
    "ticker": "string",
    "name": "string",
    "type": "STOCK",
    "description": "string"
  }
```

Properties

Name	Type	Required	Restrictions	Description
id	integer	false	read-only	none
ticker	string	false	none	none
name	string	false	none	none

Name	Type	Required	Restrictions	Description
type	AssetTypeEnum	false	none	* STOCK - Stock * ETF - ETF
description	string	false	none	none

PatchedWatchlist

```
{
  "id": 0,
  "name": "string",
  "created_at": "2019-08-24T14:15:22Z",
  "items": [
    {
      "id": 0,
      "asset": {
        "id": 0,
        "ticker": "string",
        "name": "string",
        "type": "STOCK",
        "description": "string"
      },
      "added_at": "2019-08-24T14:15:22Z"
    }
  ]
}
```

Properties

Name	Type	Required	Restrictions	Description
id	integer	false	read-only	none
name	string	false	none	none
created_at	string(date-time)	false	read-only	none
items	[WatchlistItem]	false	read-only	none

PlaceMarketBuy

```
{
  "asset_id": 0,
  "quantity": 1
}
```

Properties

Name	Type	Required	Restrictions	Description
asset_id	integer	true	none	none
quantity	integer	true	none	none

PlaceMarketSell

```
{
  "asset_id": 0,
  "quantity": 1
}
```

Properties

Name	Type	Required	Restrictions	Description
asset_id	integer	true	none	none
quantity	integer	true	none	none

Register

```
{
  "email": "user@example.com",
  "password": "string"
}
```

Properties

Name	Type	Required	Restrictions	Description
email	string(email)	true	none	none
password	string	true	write-only	none

SideEnum

```
"BUY"
```

- BUY - Buy

- `SELL` - Sell

Properties

Name	Type	Required	Restrictions	Description
anonymous	string	false	none	* `BUY` - Buy * `SELL` - Sell

Enumerated Values

Property	Value
anonymous	BUY
anonymous	SELL

StatusEnum

```
"PENDING"
```

- `PENDING` - Pending
- `FILLED` - Filled
- `CANCELLED` - Cancelled
- `PARTIAL` - Partially Filled

Properties

Name	Type	Required	Restrictions	Description
anonymous	string	false	none	* `PENDING` - Pending * `FILLED` - Filled * `CANCELLED` - Cancelled * `PARTIAL` - Partially Filled

Enumerated Values

Property	Value
anonymous	PENDING
anonymous	FILLED
anonymous	CANCELLED
anonymous	PARTIAL

TokenObtainPair

```
{
  "email": "string",
  "password": "string",
  "access": "string",
  "refresh": "string"
}
```

Properties

Name	Type	Required	Restrictions	Description
email	string	true	write-only	none
password	string	true	write-only	none
access	string	true	read-only	none
refresh	string	true	read-only	none

TokenRefresh

```
{
  "access": "string",
  "refresh": "string"
}
```

Properties

Name	Type	Required	Restrictions	Description
access	string	true	read-only	none
refresh	string	true	write-only	none

Watchlist

```
{
  "id": 0,
  "name": "string",
  "created_at": "2019-08-24T14:15:22Z",
  "items": [
    {
      "id": 0,
      "asset": {
        "id": 0,
        "ticker": "string",
```

```
          "name": "string",
          "type": "STOCK",
          "description": "string"
        },
        "added_at": "2019-08-24T14:15:22Z"
      }
    ]
  }
```

Properties

Name	Type	Required	Restrictions	Description
id	integer	true	read-only	none
name	string	true	none	none
created_at	string(date-time)	true	read-only	none
items	[WatchlistItem]	true	read-only	none

WatchlistItem

```
{
  "id": 0,
  "asset": {
    "id": 0,
    "ticker": "string",
    "name": "string",
    "type": "STOCK",
    "description": "string"
  },
  "added_at": "2019-08-24T14:15:22Z"
}
```

Properties

Name	Type	Required	Restrictions	Description
id	integer	true	read-only	none
asset	Asset	true	read-only	none
added_at	string(date-time)	true	read-only	none