

# **Energy-Optimal Coverage Planning and Scheduling for Autonomous Aerial Robots**



University of Southern Denmark

# **Energy-Optimal Coverage Planning and Scheduling for Autonomous Aerial Robots**

A Dissertation submitted in partial satisfaction of the  
requirements for the degree of Doctor of Philosophy  
in Robotics

*by*

*Adam Seewald*

*Approved by:*

Prof. Ulrik Pagh Schultz, Advisor  
Unmanned Aerial Systems Center  
University of Southern Denmark

*Approved on:*

<https://doi.org/10.>

The typesetting is done using L<sup>A</sup>T<sub>E</sub>X. Figures are generated with PGF/TikZ. Fonts are EB Garamond, Helvetica, and Iwona for body, headers, and equations respectively.

Copyright © 2021 by Adam Seewald. Some rights reserved.

This work is subject to CC BY-NC-SA license, which means that you can copy, redistribute, remix, transform, and build upon the content for any non commercial purpose, as long as you give appropriate credit, provide a link to the license, and indicate if changes were made. If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original. License details: <https://creativecommons.org/licenses/by-nc-sa/4.0/>



First edition, 2021

Published by University of Southern Denmark, in Odense, Denmark

To...



# Acknowledgements



# Contents

<b>1</b>	<i>Introduction</i>	<b>1</b>
1.1	<i>From UAVs to Modern Aerial Robots</i>	2
1.2	<i>Common Classes of Aerial Robots</i>	5
1.3	<i>Motivation</i>	6
1.3.1	<i>Path planning and computations scheduling</i>	6
1.3.2	<i>Objective</i>	8
1.4	<i>Outline of the Approach</i>	9
1.5	<i>Applications</i>	10
1.6	<i>Methodology</i>	10
1.7	<i>Contribution</i>	10
1.8	<i>Structure</i>	11
<b>2</b>	<i>Problem Formulation</i>	<b>13</b>
2.1	<i>Definitions of computations and motion</i>	13
2.2	<i>Definition of path functions</i>	14
2.3	<i>Definitions of stages and triggering points</i>	16
2.4	<i>Definition of the plan</i>	17
2.5	<i>Problem Statement</i>	20
2.5.1	<i>Planning problem</i>	20
2.5.2	<i>Coverage problem</i>	20
2.6	<i>Precision agriculture example</i>	20
2.6.1	<i>Paths sub-plan</i>	21
2.6.2	<i>Computations sub-plan</i>	25
2.6.3	<i>Planning problem with paths and computations sub-plans</i>	26
2.7	<i>Summary</i>	26
<b>3</b>	<i>State of the Art</i>	<b>27</b>
3.1	<i>Computations Energy Modeling</i>	27
3.1.1	<i>Heterogeneous elements modeling</i>	28
3.1.2	<i>GPU features modeling</i>	31
3.1.3	<i>CPU features modeling</i>	32
3.2	<i>Battery Modeling</i>	33

<b>3.3</b>	<i>Motion Planning</i>	34
3.3.1	<i>Coverage path planning</i>	36
3.3.2	<i>Optimal coverage</i>	37
<b>3.4</b>	<i>Planning for Autonomous Aerial Robots</i>	38
3.4.1	<i>Aerial coverage path planning</i>	38
3.4.2	<i>Optimal aerial coverage</i>	39
3.4.3	<i>Flight controllers</i>	41
<b>3.5</b>	<i>Planning Computations with Motion</i>	41
<b>3.6</b>	<i>Summary</i>	42
<b>4</b>	<i>Energy Models</i>	43
<b>4.1</b>	<i>Energy Model of the Computations</i>	43
4.1.1	<i>Computational energy of the aerial robot</i>	44
4.1.2	<i>Energy modeling for heterogeneous hardware</i>	45
4.1.3	<i>Measurement layer</i>	46
4.1.4	<i>Application specification</i>	47
4.1.5	<i>Predictive layer</i>	47
4.1.6	<i>Hardware platforms and benchmarks</i>	48
4.1.7	<i>Power measurements</i>	50
4.1.8	<i>The powprofiler tool</i>	51
4.1.9	<i>Energy-aware design of algorithms</i>	53
4.1.10	<i>ROS integration</i>	53
4.1.11	<i>Experimental evaluation</i>	53
<b>4.2</b>	<i>Battery Model</i>	54
4.2.1	<i>Batteries for aerial robots</i>	54
4.2.2	<i>Derivation of differential battery model</i>	54
<b>4.3</b>	<i>Energy Model of the Motion</i>	54
4.3.1	<i>Mechanical energy of the aerial robot</i>	54
4.3.2	<i>Fourier series of empirical data</i>	56
<b>4.4</b>	<i>Periodic Energy Model</i>	57
4.4.1	<i>Derivation of the differential periodic model</i>	57
4.4.2	<i>Nominal control</i>	62
4.4.3	<i>Parameters scale transformation</i>	64
4.4.4	<i>Aperiodic energy evolution</i>	65
<b>4.5</b>	<i>Contribution</i>	65
<b>4.6</b>	<i>Results</i>	65
4.6.1	<i>Validation</i>	67
4.6.2	<i>Assessment</i>	68
<b>4.7</b>	<i>Summary</i>	68
<b>5</b>	<i>Optimal Control Generation</i>	69
<b>5.1</b>	<i>A Brief History of Optimal Control</i>	70
<b>5.2</b>	<i>Optimization Problems with Dynamics</i>	71
5.2.1	<i>Continuous systems: unconstrained case</i>	71
5.2.2	<i>Continuous systems: constrained case</i>	72

5.2.3	<i>Perturbed systems</i>	72
5.2.4	<i>Multistage systems</i>	72
5.3	<i>State Estimation</i>	72
5.3.1	<i>The curve fitting problem</i>	72
5.3.2	<i>Period estimation</i>	72
5.3.3	<i>Discrete time Kalman filter</i>	72
5.3.4	<i>Continuous time Kalman filter</i>	73
5.3.5	<i>Nonlinear filtering</i>	73
5.4	<i>Numerical Simulation and Differentiation</i>	73
5.4.1	<i>Euler method</i>	73
5.4.2	<i>Runge-Kutta methods</i>	73
5.4.3	<i>Algorithmic differentiation</i>	73
5.5	<i>Direct Optimal Control Methods</i>	73
5.5.1	<i>Direct single shooting</i>	74
5.5.2	<i>Direct multiple shooting</i>	74
5.5.3	<i>Direct collocation</i>	74
5.6	<i>Numerical Optimization</i>	74
5.6.1	<i>Convexity</i>	74
5.6.2	<i>Optimality conditions</i>	74
5.6.3	<i>First order optimality conditions</i>	74
5.6.4	<i>Second order optimality conditions</i>	74
5.6.5	<i>Sequential quadratic programming</i>	74
5.6.6	<i>Nonlinear interior point methods</i>	74
5.7	<i>Results</i>	74
5.8	<i>Summary</i>	74
6	<i>Dynamic Planning</i>	75
6.1	<i>Vector Fields for Guidance</i>	75
6.2	<i>Derivation of the Guidance Action</i>	76
6.2.1	<i>Motion simulations</i>	76
6.2.2	<i>Energy simulations</i>	76
6.3	<i>Alteration of the Path</i>	76
6.4	<i>Model Predictive Control</i>	76
6.4.1	<i>Output model predictive control</i>	76
6.4.2	<i>Optimal control generation with model predictive control</i>	79
6.5	<i>Dynamic Planning Algorithm</i>	80
6.6	<i>Results</i>	80
6.7	<i>Summary</i>	80
7	<i>Summary and Future Directions</i>	81
7.1	<i>Summary</i>	81
7.2	<i>Contribution</i>	81
7.3	<i>Future Directions</i>	81
7.4	<i>Conclusion</i>	81

<i>Appendices</i>	83
<b>A <i>Implementation</i></b>	83
A.1 <i>Energy Models</i>	83
A.2 <i>State Estimation</i>	86
A.2.1 <i>Estimation of the period</i>	86
A.2.2 <i>Estimation of the state</i>	87
A.3 <i>Guidance</i>	87
A.4 <i>Optimal Control Generation</i>	88
<i>References</i>	91
<i>Index</i>	103

# Figures

<i>Opterra fixed-wing aerial robot</i>	2
<i>Hewitt-Sperry Automatic Airplane, first unmanned flying machine</i>	3
<i>NASA's Ingenuity Mars Helicopter</i>	4
<i>Skye, an omnidirectional spherical blimp</i>	6
<i>Different aerial robots in relation to the power, flight time, and M&amp;CE</i>	7
<i>The covering problem in a precision agriculture scenario</i>	8
<i>The hazard detection in the precision agriculture scenario</i>	9
<i>Diagram of the structure</i>	11
<i>Concept of a line as a path function</i>	15
<i>Concept of a circle as a path function</i>	16
<i>Definition of a plan</i>	19
<i>Detail of a stage in the FSM</i>	19
<i>Definition of a plan with a loop</i>	19
<i>Intuitive plan to cover a regular polygon with four sides</i>	21
<i>Fixed-wing aerial robot's plan to cover a regular polygon with four sides</i>	22
<i>Alteration of a path parameter of the fixed-wing aerial robot's plan</i>	24
<i>Overview of energy modeling for heterogeneous hardware.</i>	46
<i>Average power</i>	48
<i>Overall energy</i>	48
<i>Remaining battery capacity</i>	49
<i>Average power</i>	49
<i>Overall energy</i>	50
<i>Remaining battery capacity</i>	50
<i>ODROID XU3</i>	51
<i>NVIDIA Jetson TK1</i>	51
<i>NVIDIA Jetson TX2</i>	52
<i>NVIDIA Jetson Nano</i>	52
<i>Energy data of a fixed-wing aerial robot</i>	57
<i>Trajectory of the aerial robot flying the highest path configuration</i>	63
<i>Trajectory of the aerial robot flying the lowest path configuration</i>	63

<i>Concept of a path and computation parameter scale transformation . . . . .</i>	65
<i>Layer 2 model of darknet-gpu component . . . . .</i>	66
<i>Summary of the optimal control approach . . . . .</i>	70
<i>Path parameter in the flight of an aerial robot . . . . .</i>	75
<i>External interference on the path . . . . .</i>	76
<i>· · · · · . . . . .</i>	79

# Notation

$\exists$	there exists
$\in$	is an element of the set
$:=$	is defined
$f(\cdot)$	is function $f$
$f : \mathbb{C} \rightarrow \mathbb{D}$	$f$ maps set $\mathbb{C}$ to set $\mathbb{D}$
$\mathbb{Z}$	set of integers
$\mathbb{Z}_{\geq 0}$	set of positive integers
$\mathbb{Z}_{> 0}$	set of strictly positive integers
$\mathbb{R}$	set of reals
$\mathbb{R}_{\geq 0}$	set of positive reals
$[x]$	set of positive integers up to $x$ : $\{0, 1, \dots, x\}$ , with $x \in \mathbb{Z}_{\geq 0}$
$[x]_{> 0}$	set of strictly positive integers up to $x$ : $\{1, 2, \dots, x\}$ , with $x \in \mathbb{Z}_{> 0}$
$\mathbf{x}$	vector
$X$	matrix
$\mathbf{x}', X'$	transpose of a vector $\mathbf{x}$ or of a matrix $X$
$\mathbf{x}^{-1}, X^{-1}$	inverse of a vector $\mathbf{x}$ or of a matrix $X$
$x_i$	$i$ th set of parameters
$x_{i,j}$	$j$ th parameter of the $i$ th set of parameters
$\underline{x}_{i,j}$	lower bound of the parameter $x_{i,j}$
$\bar{x}_{i,j}$	upper bound of the parameter $x_{i,j}$
$x^*$	optimal with respect to a given cost



# Abbreviations

LP	linear program
QP	quadratic program
MPC	model predictive control
NLP	non linear program
UAV	unmanned aerial vehicle
UAS	unmanned aerial system
OCP	optimal control problem
BVP	boundary-value problem
STA	reconnaissance, surveillance, and target acquisition
GNSS	global navigation satellite system
IMU	inertial measurement unit
RPV	remotely piloted vehicle
GPS	global positioning system
SoC	state of charge
M&CE	difference of motion and computations energy
CNN	convolutional neural network
FPS	frames per second
FSM	finite state machine
DVS	dynamic voltage scaling
DNN	deep neural network
QoS	quality of service
CPP	coverage path planning



# Chapter 1

## Introduction

MOBILE ROBOTS are a class of robots with the ability to move through the environment (Corke, 2017). Most of these robots are power-demanding devices constrained by battery limitations. Although such limitations are a common challenge in many areas, they are critical in mobile robots' design and development. They influence the level of autonomy (Seewald, Garcia de Marina, Midtiby, et al., 2020), which in turn is expected to increase in the foreseeable future (Fisher et al., 2013).

To move, mobile robots combine different components which sense and interact with the surrounding environment (Mei, Lu, Y. C. Hu, et al., 2006). The analysis and interpretation of the data originating from these components often rely on high-level decisions. These are usually implemented on energy-demanding heterogeneous computing hardware. Planning an energy-aware path with a power-saving scheduling policy on such hardware is an underrepresented topic in the literature. Many past approaches focus almost exclusively on one of these topics. Some generate an energy-optimized path, despite the computations energy almost equaling the motion energy of some instances of low-energy mobile robots (Sudhakar et al., 2020). Moreover, due to the recent advancements in the computational capabilities of heterogeneous computing hardware, such as the introduction of powerful portable GPUs (Rizvi et al., 2017), the use of computations is on the rise (Abramov et al., 2012; Jaramillo-Avila et al., 2019; Satria et al., 2016). Others provide a power-saving scheduling policy. Yet, moving a mobile robot requires considerable energy expenditure over mere computations (Mei, Lu, Y. C. Hu, et al., 2004, 2005).

In this work, we focus on dynamic energy planning. We generate both an energy-aware plan of the path and a power-saving schedule of the computations. We plan these two aspects simultaneously, exploring their tradeoffs. We demonstrate the approach both in simulation and empirically, and we focus on aerial mobile robots. Although these systems share with the broader class of mobile robots stringent battery limitations, handling the battery in flight introduces additional complications. It is generally required landing to replace or recharge the battery (Zamanakos et al., 2020). Aerial robots are thus an ideal instance of energy-constrained systems that would benefit from a dynamic energy planning technique. In the remainder of this work, we thus focus our analysis on aerial robots.

There are many autonomous use cases involving aerial robots, such as precision agriculture, search and rescue, payload delivery, transportation, and many others. To formulate a mobile robot planning problem later in Chapter 2, we focus on precision agriculture and progressively build dynamic planning of a fixed-wing aerial robot flying over an agricultural field with little human input.



Fig. 1.1. Opterra fixed-wing aerial robot employed for precision agriculture (photo credit: Amit Ferencz Appel).

We investigate different physical aerial robotics platforms in this work but we focus most on the Opterra fixed-wing aerial robot ([Hobby, 2020](#)) adapted for precision agriculture. Precision agriculture is often put into practice ([Hajjaj and Sahari, 2014](#)) with ground mobile robots used for harvesting ([Aljanobi et al., 2010; De-An et al., 2011; F. Dong et al., 2011; Edan et al., 2000; Z. Li et al., 2008; Qingchun et al., 2012](#)), and unmanned aerial vehicles (UAVs) for preventing damage and ensuring better crop quality ([Daponte et al., 2019; Puri et al., 2017](#)). The aerial robot is shown in [Figure 1.1](#).

In the remainder of the chapter and before we introduce the problem in [Chapter 2](#), we briefly investigate the evolution of the field of aerial robotics in the next section. We then analyze the main aerial robots available today, and how they apply to dynamic energy planning in [Section 1.2](#). We then provide some further motivation for our planning in [Section 1.3](#) and the outline of the approach in [Section 1.4](#). Finally, we provide the structure of the remaining chapters in [Section 1.8](#).


This chapter connects to the remainder of this work as follows. Here we introduce and motivate the dynamic energy planning for autonomous aerial robots. We formalize the planning problem in [Chapter 2](#). We describe the derivation of a proper energy model to predict the future energy consumption of the planning problem in [Chapter 4](#). We estimate some coefficients of the model using robust estimation techniques in [Chapter 5](#). We implement an optimal configuration of the path and computations using data-driven control and other modern optimal control techniques in [Chapter 6](#). We use such configuration for guidance and scheduling of the aerial robot. The guidance moves physically the robot; the scheduling defines the granularity of the tasks being executed in flight. Moreover, we discuss previous approaches to solve the dynamic planning problem in [Chapter 3](#).

## 1.1 From UAVs to Modern Aerial Robots

Modern aerial robots are a valuable tool in robotic research and aerospace. They are found with different names in the literature. These include unmanned aerial vehicles (UAVs)<sup>1</sup>, unmanned aerial systems

---

<sup>1</sup>The term unmanned is sometimes replaced by uninhabited



**Fig. 1.2.** The Hewitt-Sperry Automatic Airplane, also denominated “flying bomb”, was developed in WWI and represents the first instance of a UAV (photo credit: United States Naval Institute).

(UASs), flying robots, or drones. Usually, we refer to drones, UAVs, and UASs when these systems are semi-autonomous, operated from the ground. UAS often denotes the entire infrastructure of unmanned flight in the aerospace jargon. Aerial or flying robots, on the other hand, have advanced levels of autonomy (Siciliano and Khatib, 2016). Nevertheless, all these systems have basic autonomous features such as position and altitude holding and leveling. The position holding is usually implemented using global navigation satellite system (GNSS), altitude holding using a barometer, and leveling using inertial measurement unit (IMU).

The origin of the field of aerial robotics, which deals with the design and development of aerial robots, dates back to the first guided missiles: unmanned (or uninhabited) flight has more than a century of developments (Siciliano and Khatib, 2016). Hewitt-Sperry Automatic Airplane, also denominated “flying bomb”, developed in 1917 during World War I (WWI) (Keane and Carr, 2013; Valavanis and Vachtsevanos, 2015) is often referred to as the first unmanned flying machine. It is shown in Figure 1.2. It has been developed 14 years after the first heavier-than-air flight in history, demonstrated on December 17, 1903, with the Wright Flyer I by Wilbur and Orville Wright (or the Wright brothers). The Hewitt-Sperry Automatic Airplane used a gyroscope similarly to modern aerial robots. The device, invented by Elmer Sperry (Keane and Carr, 2013), was mechanically connected to the control surfaces and successfully implemented a control feedback loop (Siciliano and Khatib, 2016).

In the early days, the first flying machines were referred to as remotely piloted vehicles (RPVs) (Anderson, 2005). Many instances from WWI on of these vehicles were designed for military purposes. In the 1950s, United States used a remotely controlled vehicle, the Ryan Firebee, for reconnaissance in Vietnam, and Israel was the first to use a RPV in a combat situation (Anderson, 2005). Other instances of these vehicles include the V-1 flying bomb from 1944 (deployed by the unified armed forces of Nazi Germany) and the Lockheed D-21 from 1962 (deployed by the United States Air Force). Global positioning system (GPS) at the end of 1970 allowed some more recent remotely piloted vehicles to be used in surveillance. These systems were later integrated with cameras and other sensors (Siciliano and Khatib, 2016), in what are the modern aerial robots.



**Fig. 1.3.** NASA's Ingenuity Mars Helicopter. A rotary-wing coax aerial robot that achieved the first powered, controlled flight on another planet on April 19, 2021. The project is solely a demonstration of technology (photo credit: NASA Jet Propulsion Laboratory).

In recent years, the unmanned flight has been applied in many civilian applications (González-Jorge et al., 2017). Modern aerial robots are increasingly used in remote sensing (Colomina and Molina, 2014; Milas et al., 2018; Noor et al., 2018; Tang and Shao, 2015), surveillance (Acevedo et al., 2014; Basilico and Carpin, 2015; Bürkle, 2009; Paucar et al., 2018; Ramasamy and Ghose, 2017), meteorology (Renzaglia et al., 2016; Schuyler et al., 2019), search and rescue (Cui et al., 2015; Hayat et al., 2017; Karaca et al., 2018; Pensieri et al., 2020; Seguin et al., 2018), precision agriculture (Daponte et al., 2019; Lottes et al., 2017; Popović et al., 2017; Puri et al., 2017; Sa et al., 2018), transportation, and payload delivery (Kellermann et al., 2020). The former four categories fall into the area of reconnaissance, surveillance, and target acquisition (RSTA) and do not require advanced autonomy. Precision agriculture, transportation, and payload delivery are often realized using to a greater or lesser extent some advanced levels of computational intelligence (Siciliano and Khatib, 2016). Modern aerial robots are designed to handle unexplored terrain with little interaction as opposed to the past UAVs operated mainly by a human operator (Siciliano and Khatib, 2016). Instances of modern aerial robots are expected to autonomously adapt and possibly interact in a broad variety of environmental conditions.

In summary, aerial robots have a relatively recent past. Some initial experiments of unmanned flights were performed shortly after the first heavier-than-air manned, powered flight. These initial experiments were mostly developed for military purposes, whereas modern aerial robots are used in a broad range of civil applications. Aerial robots are expected to grow significantly in numerous areas of robotics research ranging from agriculture to planetary exploration. For the latter, Figure 1.3 shows NASA's Ingenuity Mars Helicopter. A small coaxial aerial robot that performed the first powered, controlled flight on another planet on April 19, 2021. Aerial robots for planetary exploration are to be further deployed in future explorations endeavors, for instance, to study Saturn's moon Titan (Voosen, 2019).

Finally, we conclude this section with a quote from (Anderson, 2005): "the Wright brothers worked so hard to put humans in the air in flying machines, a hundred years later some [...] are working hard to take them out of flying machines".

## 1.2 Common Classes of Aerial Robots

Numerous different types of aerial robots have emerged ever since their first introduction. We briefly investigate the most studied classes in the robotics literature and relate them to the dynamic energy planning that we focus on in this work. The two most generic classes are heavier-than-air and lighter-than-air aerial robots. Heavier-than-air aerial robots are divided into fixed- and rotary-wings (Siciliano and Khatib, 2016), and some recent developments in bio-inspired robotics study flapping-wings (Floreano and Wood, 2015).

Rotary-wing aerial robots are highly maneuverable and can perform stationary vertical flight (commonly referred to as hovering) (Siciliano and Khatib, 2016). These systems can be classified into further categories, which include multirotors (such as quadrotors or quadcopters, hexacopters, and octocopters), conventional helicopters (these have one main and one tail rotor), and a coax (these have counter-rotating coaxial rotors) (Corke, 2017). Some examples of quadrotors are DJI Mavic Mini in (h), and DJI Phantom 4 in (j) in Figure 1.5. In the same figure, DJI Agras T16 in (g), and DJI Matrice 600 in (f) are hexacopters.

Fixed-wing aerial robots have wings to provide the lift, some control surfaces for maneuvering, and a propeller for forward thrust; a shared principle with a common passenger aircraft (Corke, 2017). An example constitutes the Opterra adapted for precision agriculture in Figure 1.1, Cumulus in (b), Ebee in (d), and Penguin BE in (c) (Haugen and Imsland, 2016) in Figure 1.5. Examples of flapping-wings are Delfly II in (k) (Percin et al., 2012), and Nano-Hummingbird in (l) in Figure 1.5. We discuss in detail heavier-than-air aerial robots in this work, as they are a common platform for robotics research. We focus on the dynamic forces which govern the flight of rotary- and fixed-wings aerial robots in Chapter 6.

Common instances of lighter-than-air aerial robots are blimps (or non-rigid airships). They usually rely on a gas—such as helium enclosed in a protected envelope (Burri et al., 2013)—to generate the lifting force (Fui Liew et al., 2017). An omnidirectional spherical blimp is shown in Figure 1.4. Blimps are similar to balloons but provide basic maneuverability, whereas, in a balloon, only the altitude can be controlled (Colombatti et al., 2011).

Some other classifications found in aerial robotics literature trade size and maneuverability and include classes as micro aerial vehicles (MAVs) or vertical take-off and landing (VTOLs) aerial robots. The former are aerial robots with all dimensions lower than 15 cm. The latter are aerial robots flying in a fixed-wing configuration except if taking-off and landing where they use thrust from rotors rather than lift from wings.

Among the classes in this section, rotary-wings are the most maneuverable and lighter-than-air aerial robots are the least. These, however, have the highest flight time followed by fixed-wing aerial robots. Mixed configurations, such as VTOLs, fall into the intersection of rotary and fixed-wings for what concerns maneuverability and flight time (Siciliano and Khatib, 2016). The energy requirements are critical for all aerial robots, but the difference of motion and computations energy (M&CE) varies greatly. The energy—inversely proportional to flight time—is highest in rotary-wings and lowest in lighter-than-air aerial robots as shown later in Figure 1.5. The dynamic energy planning approach thus relies on both power-saving task scheduling and energy-efficient path planning for the fixed-wings robots while relying almost exclusively on energy-efficient path planning for rotary-wing aerial robots. In the former M&CE is close to zero, in the latter is usually high except in energy optimized designs such as some rotary-wing MAVs. Hypothetically, in lighter-than-air aerial robots, M&CE might be negative; the energy planning approach would rely heavily on power-saving task scheduling.

The classification that we proposed in this section serves the scopes of our work. There are similar effort for classification by size and propulsion technology (Cabreira, Brisolara, et al., 2019; Hoffer et al., 2014)



**Fig. 1.4.** Skye, an omnidirectional spherical blimp developed by ETH Zürich for entertainment purposes. It has a camera system and combines the energy-efficient flight of a blimp with the characteristics of a quadrotor (photo credit: ETH Zürich).


but of course other classifications are possible. For instance categorizing aerial robots by the altitude they usually operate at (Watts et al., 2012).

## 1.3 Motivation

In this section, we provide a brief motivation for dynamic energy planning of these systems. Many applications that involve aerial robots have strict battery constraints. Although this is a common problem to most mobile robots, aerial robots are of particular concern. The autonomy of these systems is affected by the availability of the power source. A typical example of an aerial robotics scenario is a robot following a path and performing some onboard computations. For instance, the robot might detect ground patterns and notify other ground-based actors with little human interaction in precision agriculture or another application. Aerial robots in this situation often carry some heterogeneous computing hardware and a microcontroller. Energy requirements of such computing hardware are a further complication. Computing hardware is involved in autonomous capabilities and planning itself—both often require computer vision or other complex algorithms—whereas microcontroller runs motion primitives by directly interfacing actuators (such as servos for the control surfaces) and motors. Energy-wise, it is advantageous to schedule the computations on the computing hardware and simultaneously to plan the path.

### 1.3.1 Path planning and computations scheduling

It is uncommon to find a ready-to-use solution for both planning the path and scheduling the computations of these systems in an energy-aware fashion (we discuss in detail the state-of-the-art in this regard in [Chapter 3](#)). Planning the two aspects simultaneously would pose an advantage in terms of autonomy by, e.g., optimizing the path and computations in the function of the battery state of charge (SoC).



**Fig. 1.5.** Different aerial robots in relation to the power, flight time, and M&CE with a hypothetical fixed costs for computations energy. The power is expressed using a logarithmic scale. Heavier-than-air aerial robots (b)–(l) include flapping-wings (k), (l) and have a negative M&CE (computations scheduling is to be accounted for most in planning), whereas rotary-wings have a positive M&CE (f), (g) (path planning is to be accounted for most in dynamic planning). Some smaller rotary-wings have a M&CE closer to zero (h), (j). In general, rotary-wings have a short flight time. Fixed-wings (b)–(e) have a considerably longer flight time and M&CE close to zero (computations scheduling and path planning have both to be accounted for in dynamic planning). Lighter-than-air aerial robots (a) have hypothetically a relatively long flight time and lower than zero M&CE (photos credit: (b) to Sky-Watch, (f) to Rise Above, (g) to Aeromotus, (h) to Digital Photography Review, (j) to ePHOTOZine, and (l) to DARPA).

For certain classes of aerial robots with M&CE close or lower than zero, the autonomy can directly influence the battery state. For these classes, it is desirable to reschedule the computations energy-wise in-flight during a motion energy-demanding phase. For instance, a fixed-wing aerial robot might be flying headwinds (with the wind vector parallel and opposite to the direction of motion) and utilizing more energy than planned. It would be of advantage to reschedule the tasks accordingly to save energy needed for motion. During the same flight, the wind direction might suddenly change. The fixed-wing craft, now flying tailwinds, requires less motion energy. It could then potentially increase the level of computations by rescheduling the tasks. Later in the flight, the battery might be subject to sudden drops (due to e.g., temperature changes) requiring replanning again by, e.g., shortening the path. It is clear that planning the path and scheduling the computations simultaneously in all these cases is the most desirable course of action.



**Fig. 1.6.** The covering problem in a precision agriculture scenario. The aerial robot has to cover an agricultural field that forms a polygon (blue/transparent area in the frame) and run some autonomous tasks (photo credit: Amit Ferencz Appel).

In Figure 1.5 we show the M&CE against the flight time of different aerial robots. We observe that fixed-wings are the aerial robots that would advantage most from simultaneous path planning and computations scheduling. They have a M&CE close to zero and a relatively long flight time. Although some rotary-wings have M&CE also close to zero, their flight time is generally relatively short. Flapping-wing and lighter-than-air aerial robots require considerably less energy for the motion, and have a negative M&CE.

### 1.3.2 Objective

In the remainder of this work, we refer to computational tasks that can be scheduled in an energy-aware fashion as computations, opposed to the other tasks with no significant effect on energy consumption. We assume the aerial robot runs the computations on the heterogeneous computing hardware. As an example, we refer to an aerial robot in a precision agriculture scenario in Figure 1.1, which covers an agricultural field. In abstract terms, the field is represented by a polygon in Figure 1.6 and the aerial robot detects some patterns on such polygon using a convolutional neural network (CNN) in Figure 1.7. The aerial robot further communicates the position of a detected pattern to other, ground-based actors. Detecting the patterns usually involves heterogeneous computing elements (GPU and/or multiple CPU cores) and consumes a significant amount of energy as opposed to communication. Detection is a computation, while communication is an (energy-inexpensive) task.

We are interested in the energy optimization of the path and computations under uncertainty (atmospheric interferences) in-flight and refer to it as dynamic energy planning. Unlike most of the past mobile robotics planning literature, the approach that we propose plans these two aspects simultaneously. Such planning would find optimal tradeoffs between the path, computations, and energy requirements. Current generic planning solutions for aerial robots do not plan the path and computations dynamically, nor are they energy-aware. They are often semi-autonomous: the path and computations are static and usually defined using planning software (Daponte et al., 2019). Instances of the planning software include famous flight controllers (Paparazzi, 2016; PX4, 2016). Such a state of practice has prompted us to investigate the topics presented in this work. We will gradually propose a dynamic energy planning



**Fig. 1.7.** The aerial robot detects hazard on the agricultural field and communicate the detection to ground-based actors while it cover the polygon.

approach for aerial robots. It plans both the path and computations while the aerial robot is flying and its batteries draining.

We formally define the robot planning problem after outlining the approach in the next section.

## 1.4 Outline of the Approach

In this work, we address the increasing demands for autonomy of modern aerial robots with a dynamic planning approach. The approach provides a simultaneous energy-aware plan of the path and a power-saving schedule of the computations. To this end, we first need a user-defined initial plan that is then replanned energy-wise using an energy model for future prediction. Later, an algorithm inputs the initial plan, estimates the state of the energy model, evaluates future energy consumption and replans parameters relative to the path and computations. The plan consists of different stages. At each stage, the aerial robot flies a path and executes some computations. Furthermore, it contains some additional parameters to alter the path and computations along with an energy budget. The alterations are bounded. There are path constraint sets that bound the path alterations and computations constraint sets, one per each computation, that bound computations alterations.

We use the concept of different stages to model complex paths. For instance, the path might contain multiple circles and lines. We will see such plan later in [Section 2.6](#). The approach guides the aerial robot on different paths (the plan is composed of) using vector field ([De Marina et al., 2017](#)). The robot switches between the paths as soon as it reaches specific triggering points.

The approach further relies on `powprofiler`, a profiling and modeling tool that we introduce in [Section 4.1](#). The tool models the energy consumption of the computations and is later employed to estimate the future energy of the aerial robot in flight. To this end, we empirically derive and formally prove a periodic energy model that accounts for the uncertainty. We use Fourier analysis to derive the model and state estimation to address the uncertainty. Periodicity is often present due to repetitive patterns in the plan ([Seewald, Garcia de Marina, Midtiby, et al., 2020](#)). Indeed, mobile robots often iterate over a set of tasks and paths ([Seewald, Garcia de Marina, and Schultz, n.d.](#)). Given that the plan is periodic,

we expect the energy consumption to evolve (approximately) periodically. We describe in detail such model in [Section 4.4](#).

The replanning of the path and computations is achieved with modern optimal control techniques, such as state estimation in [Chapter 5](#), and model predictive control (MPC) ([Rawlings et al., 2017](#)) in [Chapter 6](#). The control is data-driven. Energy sensor data estimates some coefficients of the model used to predict the future energy consumption with uncertainty. The replanning is done under an energy budget—the battery capacity and other battery parameters. Our goal is to complete the plan with the highest possible parameters configuration.

## 1.5 Applications

The dynamic energy planning in this work applies to modern aerial robots with a certain degree of autonomy. By the latter, we mean that the robot performs at least a predefined set of tasks over a given space. Although most of the guidance in [Chapter 6](#) is designed for aerial robots specifically, the approach can be easily adapted to other mobile robots with energy constraints. We discuss applications out of aerial robotics domain further in [Chapter 7](#). For instance, we have applied the approach to the space robotics context ([Seewald, 2020](#)).

In the remainder of this work, we focus on the precision agriculture scenario in [Figure 1.6](#). In summary, the aerial robot covers a given agricultural field (a polygon) and searches for ground hazards. With the scenario, we validated the work experimentally. Path-wise, the aerial robot flies in circles and lines covering the polygon. Computation-wise, it detects hazards using the CNN and notifies grounded mobile robots employed for, e.g., harvesting. The approach alters the plan; it controls the processing rate and the radius of the circles affecting the distance between the lines. We will see this concrete scenario described formally in [Section 2.6](#) and solved progressively in the remaining chapters.

## 1.6 Methodology

## 1.7 Contribution

With this work, we contribute with a dynamic planning approach for aerial robots performing autonomous scenarios for different use-cases, under energy constraint, and in an uncertain environment. In particular, we plan both an energy-optimized path and a power-saving schedule. Indeed dynamic planning that incorporates both these aspects simultaneously is underrepresented in the literature.


The contribution in this work builds upon some other past contributions. In particular, our computational energy modeling relies on an automated profiling and modeling methodology that we proposed in ([Seewald, Schultz, Ebeid, et al., 2021](#)). The methodology is based on the `powprofiler` tool to derive an energy model for future energy prediction. We proposed an extension of `powprofiler` with a component-based energy modeling approach to abstract per-component energy in a dataflow computational network in ([Seewald, Schultz, Roeder, et al., 2019](#)). We later integrated the tool in a Robot Operating System (ROS) ([Quigley et al., 2009](#)) in ([Zamanakos et al., 2020](#)).

The agricultural scenario that we briefly introduced in [Section 1.3.2](#) is based on simulation of detections over a field under varying atmospheric conditions and with different scheduling options that we proposed in ([Zamanakos et al., 2020](#)), the energy modeling approach on some empirical observations.

We proposed a periodic energy modeling in (Seewald, Garcia de Marina, Midtiby, et al., 2020) using the empirical energy data of the Opterra aerial robot flying the precision agriculture scenario.

A dynamic planning approach that we proposed in (Seewald, Garcia de Marina, and Schultz, n.d.) relies on all the concepts that we propose in this work and derives simultaneously the energy-optimized path and the power-saving schedule. Additionally to dynamic planning for aerial robots, we studied the approach on different robots in (Seewald, 2020).

## 1.8 Structure



**Fig. 1.8.** Diagram of the structure of this work. The arrows are to be read with “the chapter influences” in the direction of the arrow. Chapter 1 serves as an introduction while Chapter 3 presents the state of the art. Chapter 2 presents the planning problem, which is solved in Chapter 5 using notions from Chapters 4–5.3. Chapter 5.3 presents the guidance action to move over a replanned. Chapter 7 concludes the work and proposes future directions and Appendix A the implementation.

The remainder of this work is illustrated in Figure 1.8 structured as follows. In this chapter, we introduced the dynamic energy planning for aerial robots. We define the planning problem in Chapter 2, and propose the solution to the problem in Chapter 5, which builds upon the topics presented in the remaining chapters. In particular, in Chapter 3 we present the state-of-the-art in energy modeling and planning for mobile robots. We include some energy models for heterogeneous computing hardware.

Dynamic planning requires accurate future energy predictions. We present the derivation of some energy models to address future energy predictions in Chapter 4. Specifically, we propose energy models for computations, motion, and the battery. We derive and formally prove a periodic energy model that we use in the remainder of this work to predict future energy consumption. The periodic energy model’s accuracy depends on the availability of measurements of energy data. We detail the process in Chapter 5. We describe how to estimate the coefficients of the periodic energy model and refine the future predictions with the available data.

Flying on a dynamic plan requires the derivation of a guidance action to guide the aerial robot in space. This process is elaborated in [Chapter 6](#). We discuss an approach to guide the aerial robot in space on the planned path. An optimal solution for the dynamic mobile robot planning problem relies on optimal control techniques. We describe such techniques also in [Chapter 6](#). Specifically, after summarizing some of these techniques, we propose an optimization algorithm to select the optimal parameters configuration for the path and computations simultaneously. Finally, we conclude our work in [Chapter 7](#) along some recommendations for future research direction.

We then present some additional information in appendices. In [Appendix A](#) we propose the implementation in MATLAB(R) of the planning problem, the model, the estimation technique, the guidance action, and the derivation of the optimal control.

# Chapter 2

# Problem Formulation

**I**N THIS CHAPTER, we discuss the planning problem that we are interested in solving. Such planning problem relies on the initial user-defined plan that we formally define later in [Section 2.4](#). We have briefly discussed the plan in [Section 1.4](#). It is replanned energy-wise in the eventuality of energy constraints dissatisfaction, and whenever the uncertainty affects the flight unexpectedly. The initial user-defined plan includes the computations and motion, so we define both these constructs. In particular, we provide formal definitions of some basic concepts in [Sections 2.1–2.3](#). These include the computations, motion, their energy, difference between computations and motion energy (M&CE) that we encountered in [Section 1.2](#), path, and some other plan-specific constructs. We then use all these to formulate the planning problem in [Section 2.5.1](#). We illustrate the problem on an example of the precision agriculture scenario in [Section 2.6](#).

The algorithm that we present in [Section 6.5](#) inputs the user-defined plan from this chapter for future energy modeling, estimation of the energy model, and guidance and solves the planning problem. It optimizes the plan with some parameters (which we also outlined briefly in [Section 1.4](#)) to plan the best configuration of computations and paths. The replanned plan is optimal energy-wise: the algorithm investigates the tradeoffs between paths and computations with varying battery and atmospheric conditions.

The chapter connects to the remainder of this work as follows. Here we formalize the plan, the planning problem, and some other basic constructs. We use the characteristics of the plan to derive an energy model in [Chapter 4](#), which we estimate from measured data in [Chapter 5](#). We solve the planning problem using modern optimal control techniques in [Chapter 6](#). With the solution, we refine the original problem in terms of both the path and computations. We guide the aerial robot using a vector field, where we use the plan's building blocks for the paths from this chapter. We discuss past approaches to solve the planning problem in [Chapter 3](#) and the concrete implementation in [Appendix A](#).

## 2.1 Definitions of computations and motion

Firstly, we define computations, motion, their energy, and M&CE. Our dynamic planning depends on these basic concepts.

**Definition 2.1.1: Computations/motion**

*Computations* are energy-demanding computational tasks. The aerial robot runs the computations on heterogeneous computing hardware that interfaces microcontrollers.

*Motion* is the act of the aerial robot moving in the surrounding environment. The aerial robot runs some primitives on microcontrollers that interface actuators, motors, and other components.

Autonomous capabilities are often achieved by interconnecting heterogeneous computing hardware and microcontrollers. We assume for the computations that the heterogeneous computing hardware runs a schedule characterized by some parameters. For instance, for the CNN detection from the precision agriculture scenario in Section 1.3.2, a parameter is the frames per second (FPS) rate. Alike for the computations, we assume for the motion that the robot travels some paths characterized by some other parameters. For instance, for the covering problem, a parameter changes the distance between the survey lines.

**Definition 2.1.2: Computations/motion and overall energy**

Given a path characterized by  $\rho$  parameters  $c_i^\rho := \{c_{i,1}, c_{i,2}, \dots, c_{i,\rho}\}$ , the *motion energy* is the energy spent by the aerial robot while moving on the path.

Given a schedule characterized by parameters  $c_i^\sigma := \{c_{i,\rho+1}, \dots, c_{i,\rho+\sigma}\}$ , the *computations energy* is the energy spent by heterogeneous computing hardware executing the schedule.

The *overall energy* is the sum of motion energy and computations energy.

Physically, motion energy is the energy spent by all the systems powering the aerial robot, excluding the heterogeneous computing hardware. We use watts for instantaneous or average measures of computations, motion, and overall energies, whereas joules for measures over a given time interval. We show in Section 2.3 what we mean by the characterization of paths and computations with some parameters.

M&CE that we introduced in Section 1.2 is the difference between average motion and computations energy. It is measured in watts, and it gives a measure of which of the two energy components is predominant. For M&CE greater than zero, the motion energy dominates over the computations. The dynamic planning approach plans first an energy-efficient path. If we return briefly to Figure 1.5, it is the case for rotary-wing aerial robots (f) and (g). On the contrary, for M&CE lower than zero, the computations energy dominates. The dynamic planning approach plans first a power-saving schedule. In the figure, it is the case for the lighter-than-air aerial robot (a) in Figure 1.5. For M&CE close to zero, both energy components are important energy-wise. The dynamic planning approach plans both an energy-efficient path and power-saving schedule to a similar extent. This M&CE is characteristic of fixed-wing aerial robots, such as (b)–(e) in Figure 1.5.

## 2.2 Definition of path functions

To model the path, we use multiple mathematical functions  $\varphi_1, \varphi_2, \dots$  that we call path functions. These functions express the path in 2D space at an altitude  $h \in \mathbb{R}$  for an inertial navigation frame  $\mathcal{O}_W$ . We discuss a generalization of the path functions in 3D space and how it affects the guidance in Chapter 7.




Fig. 2.1. The path is mathematical function  $\varphi(p(t)) = h$  that represents a line at an altitude  $h$ . A generic point  $p$  in 2D space intersects the plane formed by  $\varphi$  at a given value  $d$  of the  $z$ -axis.

**Definition 2.2.1: Path functions**

$\varphi_i : \mathbb{R}^2 \rightarrow \mathbb{R}$ ,  $\forall i \in \{1, 2, \dots\}$  are *path functions* used to model the path. They are a function of a generic time-dependent point  $p(t) := (x_{p(t)}, y_{p(t)})$  of the aerial robot flying in the 2D space and are continuous and twice differentiable.

We use this notion to guide the aerial robot using vector field in [Chapter 6](#). For instance, one can define a line as a path function with

$$\varphi(x, y) := ax + by + c, \quad (2.1)$$

where  $a, b, c \in \mathbb{R}$  are given constants. The generic point  $p(t)$  intersects  $\varphi(x, y)$  on a specific value  $d$  of the  $z$ -axis  $(p(t), d)$ . We illustrate the concept in [Figure 2.1](#) for  $c$  zero and  $a, b$  minus one and two. The point intersects the plane formed by the path function

$$\varphi(x, y) := 2y - x, \quad (2.2)$$

at  $d = \varphi(p)$ . The path that the aerial robot follows is then  $\varphi(x, y) = h$ .  $\varphi(p) - h$  is the distance on the  $z$ -axis.

Likewise with the line, one can define a circle as a path function with

$$\varphi(x, y) := (x - x_c)^2 + (y - y_c)^2 - r^2, \quad (2.3)$$

where  $x_c, y_c$  are given coordinates of the circle and  $r \in \mathbb{R}_{>0}$  the radius. We illustrate the circle path function in [Figure 2.2](#) for  $x_c, y_c$  both three and  $\sqrt{r}$  two.

In this work, we use lines and circles as path functions. We connect these functions using some specific points—the triggering points. However, one can define any mathematical function, with the only requirement being continuity and twice differentiability. We use the first derivative for the vector field, the second derivative to derive the control action. We explain both derivatives further in [Chapter 6](#).

$$\varphi(x, y) := (x - 3)^2 + (y - 3)^2 - 2$$




Fig. 2.2. The path function now represents a circle at an altitude  $h$ .  $p$  intersects the cone formed by  $\varphi$  at a given value  $d_2$  of the  $z$ -axis.

## 2.3 Definitions of stages and triggering points

The user-defined plan has several stages  $i = \{1, 2, \dots\}$ , and we assume that at each stage  $i$ , the aerial robot runs a schedule and travels a path function  $\varphi_i$  using a parameters set  $c_i$ . Parameters are variable values that we use to dynamically plan the path and computations since they influence the computations/motion energy in Definition 2.1.2. The path parameters are real-valued variable values ( $\mathbb{R}$ ), the computations parameters are integer-valued variable values ( $\mathbb{Z}$ ). We use the notation  $c_{i,j}$  to denote the  $j$ th parameter of the  $i$ th parameters set  $c_i$

$$c_i = \{c_{i,1}, c_{i,2}, \dots, c_{i,j}, \dots\}. \quad (2.4)$$

Parameters are bounded.  $\underline{c}_{i,j}$  is the lower bound of the parameter  $c_{i,j}$ .  $\bar{c}_{i,j}$  is the upper bound

$$\underline{c}_{i,j} \leq c_{i,j} \leq \bar{c}_{i,j}. \quad (2.5)$$

We assume there are  $\rho$  path-specific parameters and  $\sigma$  computations-specific parameters for every stage. It means that the path at stage  $i$  can be replanned with  $\rho$  path parameters  $c_i^\rho := \{c_{i,1}, c_{i,2}, \dots, c_{i,\rho}\}$ , while the computations (i.e., the energy-demanding computational task executed on heterogeneous computing hardware in Definition 2.1.1) with  $\sigma$  computation parameters  $c_i^\sigma := \{c_{i,\rho+1}, c_{i,\rho+2}, \dots, c_{i,\rho+\sigma}\}$ .

Returning to Section 2.1, by characterization of the path with parameters, we mean that we enhance  $\varphi_i$  with the path parameters  $c_i^\rho$ .  $\varphi_i : \mathbb{R}^2 \times \mathbb{R}^\rho \rightarrow \mathbb{R}$  is thus a (continuous twice differentiable) function of a point and the path parameters. We use the parameters to alter the path and change the energy

consumption. Similarly, by characterization of the schedule with parameters, we mean that we express the computations as the value of the computations parameters. These are also employed for energy alteration (by, e.g., decreasing the granularity of a given computation we lower instantaneous energy consumption). We discuss the alteration of the energy with path parameters and computation parameters further in [Section 4.4.2](#) and [Section 4.4.3](#) respectively.

Since at every stage, the aerial robot travels a path and executes a schedule both characterized by the parameters, we define the stage as a set that contains the path and path and computations parameters.

**Definition 2.3.1: Stage**

Given  $\mathbf{p}(t)$ , the  $i$ th *stage*  $\Gamma_i$  at time instant  $t$  of a plan  $\Gamma$  is

$$\begin{aligned}\Gamma_i := \{ & \varphi_i(\mathbf{p}(t), c_i^\rho), c_i^\sigma \mid \forall j \in [\rho]_{>0}, c_{i,j} \in \mathcal{C}_{i,j}, \\ & \forall k \in [\sigma]_{>0}, c_{i,\rho+k} \in \mathcal{S}_{i,k} \},\end{aligned}$$

where  $\mathcal{C}_{i,j} := [\underline{c}_{i,j}, \bar{c}_{i,j}] \subseteq \mathbb{R}$  is the  $j$ th path parameter constraint set, and  $\mathcal{S}_{i,k} := [\underline{c}_{i,\rho+k}, \bar{c}_{i,\rho+k}] \subseteq \mathbb{Z}_{\geq 0}$  the  $k$ th computation parameter constraint set.

We clarify in the next section why the stage contains the generic point of the aerial robot flying in 2D space.

For simplicity, we merge the computations and path constraint sets in a single constraint set.  $i$ th stage constraint set is then

$$\mathcal{U}_i := \begin{cases} \mathcal{C}_{i,j} & \text{for } c_{i,j} \text{ with } j \leq \rho \\ \mathcal{S}_{i,j-\rho} & \text{for } c_{i,j} \text{ with } \rho < j \leq \sigma \end{cases}. \quad (2.6)$$

To move from a given stage  $\Gamma_i$  to the next stage  $\Gamma_{i+1}$ , we define some specific points  $\mathbf{p}_{\Gamma_i}$ . As soon as the aerial robot reaches the proximity of these points

$$\|\mathbf{p}(t) - \mathbf{p}_{\Gamma_i}\| < \varepsilon, \quad (2.7)$$

where  $\varepsilon \in \mathbb{R}$  is a given constant value expressing the radius of an imaginary circle over the point  $\mathbf{p}_{\Gamma_i}$ , it switches to the next stage.

**Definition 2.3.2: Triggering and final point**

The point  $\mathbf{p}_{\Gamma_i}$  that allows the transition between  $\Gamma_i$  and  $\Gamma_{i+1}$  is called the *triggering point*. The last triggering point  $\mathbf{p}_{\Gamma_l}$  relative to the last stage  $\Gamma_l$  is called the *final point*.

## 2.4 Definition of the plan

Our dynamic planning relies on the concept of the aerial robot flying a set of paths and computations autonomously. Such an autonomous flight plan often presumes a certain degree of periodicity. One can observe the periodicity in the precision agriculture example in [Section 1.3.2](#). An ideal way to monitor the agricultural field in [Figure 1.6](#) is to define a basic pattern. The aerial robot flies over the field once and then iterates the basic pattern until it covers the desired area. It means that we can define the plan just as a set of stages, triggering points, a final point, and finally a shift which tells how these constructs (except the final point) shifts in space per each period. To simplify the planning problem to this latter case of plans with a pattern iterated over time, we consider some primitive paths.

**Definition 2.4.1: Primitive paths**

Given  $n \in \mathbb{Z}_{>0}$ , the paths  $\varphi_1, \dots, \varphi_n$  are called *primitive paths* if all the remaining paths in the plan are built from these paths with a *shift*  $\mathbf{d} := (x_d, y_d)$ .

Let us assume the number of stages in the plan is known and is  $l \in \mathbb{Z}$ . If the plan is built from the primitive paths, it means that  $n$  in [Definition 2.4.1](#) respects the inequation

$$n < l, \quad l/n \in \mathbb{Z}. \quad (2.8)$$

This means that  $n$  is a multiplier of  $l$ , whereas  $l/n$  is the multiplicand. One can then write the remaining paths from the  $n$  primitive paths as  $\varphi_{n+1}, \varphi_{n+2}, \dots, \varphi_{n+n}$ , or more generally  $\varphi_{(i-1)n+1}, \varphi_{(i-1)n+2}, \dots, \varphi_{(i-1)n+n}$ ,  $\forall i \in [l/n - 1]_{>0}$ . It can also be written formally

$$\varphi_{(i-1)n+j}(\mathbf{p} + (i-1)\mathbf{d}, c_1^\rho) - \varphi_{in+j}(\mathbf{p} + i\mathbf{d}, c_1^\rho) = e_j, \quad (2.9)$$

for a given shift  $\mathbf{d}$ , initial point  $\mathbf{p}$ , and initial value of path parameters  $c_1^\rho$ . The [Equation \(2.9\)](#) holds  $\forall i \in [l/n - 1]_{>0}, j \in [n]_{>0}$ .  $e_j \in \mathbb{R}$  is the  $j$ th constant difference.

Generally, if the plan is built from the primitive paths, it is not required to know a priori the number of stages  $l$ . The paths can be iterated up until the final point  $\mathbf{p}_{\Gamma_f}$ . We use the concept of primitive paths for the energy modeling in [Chapter 4](#), where we show from collected energy data that plans built from primitive paths often have a periodic energy evolution. Alternatively to the primitive paths, one can define the plan as a mere linear succession of stages along with the triggering and final points. In the latter case, the energy can be periodic, aperiodic, or semi-periodic. Aperiodicity affects the modeling and thus future energy predictions. We discuss the concrete meaning of periodicity, aperiodicity, and semi-periodicity in the context of energy modeling in [Section 4.4](#).

Formally, we define the plan as a finite state machine using the constructs of path functions in [Definition 2.2.1](#), stages and triggering points in [Definitions 2.3.1–2.3.2](#). It is on the plan's user side to decide to what extent the plan has periodic patterns or a linear succession of stages. We illustrate these two cases in [Figure 2.5](#) and [Figure 2.3](#), and the process of the design of a plan in [Section 2.6](#).


**Definition 2.4.2: Plan**

Given  $\mathbf{p}(t)$ , the *plan* is a finite state machine (FSM)  $\Gamma$ , where the state-transition function  $s : \bigcup_i \Gamma_i \times \mathbb{R}^2 \rightarrow \bigcup_i \Gamma_i$  maps a stage and a point to the next stage


$$s(\Gamma_i, \mathbf{p}(t)) := \begin{cases} \Gamma_{i+j} & \exists j \in \mathbb{Z}, \text{ if } \|\mathbf{p}(t) - \mathbf{p}_{\Gamma_i}\| < \varepsilon \\ \Gamma_i & \text{otherwise} \end{cases}.$$

The value  $\varepsilon$  in [Definition 2.4.2](#) is the same  $\varepsilon$  in [Equation \(2.7\)](#). We illustrate the definition of the plan, stage, triggering, and final points in [Figures 2.3–2.5](#).

In [Figure 2.3](#) we illustrate a plan with a linear succession of stages. The triggering point  $\mathbf{p}_{\Gamma_{i-1}}$  allows the transition to the stage  $\Gamma_i$ . The robot remains in the stage with any generic point  $\mathbf{p}(t_2)$ , where  $t_1 < t_2 < t_3$  are three different time instants. It eventually enters the stage  $\Gamma_{i+1}$  with the triggering point  $\mathbf{p}_{\Gamma_i}$  and so on, until it reaches the final point  $\Gamma_f$  is the accepting stage (it indicates that the robot has completed the plan). In [Figure 2.4](#) we illustrate that generally, one can express the basic constructs—such as path functions and triggering points—in the function of the  $i$ th trajectory parameters  $c_i^\rho$ , or any previous trajectory parameters, propagating the information therein if necessary. We further expand




**Fig. 2.3.** Definition of a plan  $\Gamma$  as an FSM. Each state is a stage  $\Gamma_i$ , the transition happens in the proximity of specific points called triggering points  $p_{\Gamma_i}$ . The accepting stage  $\Gamma_f$  indicates the termination of the plan.



**Fig. 2.4.** Detail of the stage  $\Gamma_i$  in the FSM. The triggering points used to transition between stages (states in the FSM) are expressed in the function of the last and/or previous triggering points.

on this notion in the example in Section 2.6, where we propagate a path parameter to all the following triggering points and path functions.



**Fig. 2.5.** Definition of a plan  $\Gamma$  with periodic patterns. Stages  $\Gamma_1, \Gamma_2, \dots, \Gamma_n$  containing primitive paths  $\varphi_1, \varphi_2, \dots, \varphi_n$  are iterated with a shift  $d$ .

In Figure 2.5 we illustrate a plan composed of  $n$  stages  $\Gamma_1, \Gamma_2, \dots, \Gamma_n$  (containing primitive paths  $\varphi_1, \varphi_2, \dots, \varphi_n$ ) that are reiterated with the shift  $\mathbf{d}$ .  $t_3 < t_4$  is another time instant.

A concept that we use in the remainder of this work, and particularly in energy modeling in [Chapter 4](#) and estimation in [Chapter 5.3](#), is the concept of period—the time required to fly the primitive paths  $\varphi_1, \varphi_2, \dots, \varphi_n$  (or generally  $\varphi_{(i-1)n+1}, \varphi_{(i-1)n+2}, \dots, \varphi_{(i-1)n+n}$ ).

### Definition 2.4.3: Period

For a given stage  $\Gamma_i$  and  $j \in \mathbb{Z}_{>0}$ , the *period*  $T \in \mathbb{R}_{>0}$  is the flight time measured in seconds between  $\varphi_{(i-1)n+j}$  and  $\varphi_{in+j}$ .

We assume the initial period is one and measure the period required to fly the paths physically or in simulation. The periods might be different for different  $j$ s due to atmospheric interferences. For the path functions, one can define the plan using primitive paths  $\varphi_1, \varphi_2, \dots, \varphi_n$  or define all the stages explicitly and find  $n$  searching the value which satisfies the [Equation \(2.9\)](#). If there is no such value, (e.g., when the plan is composed of only one stage or the plan is aperiodic), the period  $T$  from [Definition 2.4.3](#) can be determined empirically from energy data or assumed as the total flight time. The latter eventuality affects on the energy model. We discuss the period estimation further in [Section 5.3.2](#).

## 2.5 Problem Statement

### 2.5.1 Planning problem

The planning problem is then the problem of finding the optimal configurations of the parameters within some criteria. In our approach, we focus on energy criteria, such as the battery constraints. In particular, in the solution to the planning problem in [Section 6.5](#), we use a cost function (i.e., the function to maximize) that incorporates the energy model in [Section 4.4](#). Solving the planning problem by finding the optimal configurations within different criteria, such as shortest time, highest security, path tracking with the shortest detour, or others is equally possible. In the context of the TeamPlay project that funded a considerable part of this work, we aim to find, for instance, the tradeoffs between time, energy, and security criteria for a variety of use cases. We discuss the eventuality of solving the planning problem with criteria different from energy in [Chapter 7](#). We now use the concepts that we introduced in the previous sections and provide a formal definition of the planning problem that we are interested in solving in the remainder of this work.

#### Problem 2.5.1: Planning problem

Consider an initial plan  $\Gamma$  in [Definition 2.3.1](#). It is either composed of  $l$  stages or  $n$  stages and a shift  $d$ . We are interested in the *planning* of the *path* and *computations parameters*  $c_i, \forall i \in [l]_{>0}$ , or  $\forall i \in \{1, 2, \dots\}$  under energy constraints and uncertainty.

We are further interested in the guidance to the path and the scheduling of the computations resulting from such planning.

In the definition, there is a fixed number of stages in case all the stages are defined explicitly. Otherwise, there is a variable number of stages, in the sense that all the stages are reiterated using the primitive paths in [Definition 2.4.1](#) up until the aerial robot reaches the last triggering point  $\mathbf{p}_l$ .

### 2.5.2 Coverage problem


We formalize the coverage problem as follows. Given a polygon representing the space to be covered, a starting point, and a turn radius, we want to find the route that covers the polygon

## 2.6 Precision agriculture example

In this section, we discuss an example of a plan for the Opterra autonomous aerial robot in a precision agriculture scenario addressing the covering problem in [Figure 1.6](#). Path-wise, the aerial robot covers a polygon with variable quality of coverage. Computation-wise, it detects ground hazards and communicates eventual detection with other ground-based actors. To simplify the notation, we split the plan

into two sub-plans, one containing exclusively the paths and the other the computations. We discuss the paths sub-plan in [Section 2.6.1](#) and the computations sub-plan in [Section 2.6.2](#).

### 2.6.1 Paths sub-plan



**Fig. 2.6.** An intuitive plan to cover a regular polygon with four sides. The plan is composed of circles  $\varphi_2, \varphi_4$  and lines  $\varphi_1, \varphi_3$ . To switch between paths the aerial robot reaches the proximity of triggering points ( $p_{\Gamma_1} := (x_{\Gamma_1}, y_{\Gamma_1}), p_{\Gamma_2}, p_{\Gamma_3}, p_{\Gamma_4}$ ). The dashed blue line indicates the triggering points, and the black line is the planned flight. The rest of the polygon is covered iterating the primitive paths and triggering points with a shift.

In the paths sub-plan, we define the paths that form the plan of the agricultural scenario. We recall that in the scenario, the aerial robot covers the polygon in [Figure 1.6](#) path-wise. For simplicity, we assume the polygon has four sides (it is a rectangle). An intuitive static plan  $\Gamma$  can be composed of lines connected by circles. The distance between the lines can be then used as a measure of the quality of the coverage. Such intuitive static plan is illustrated in [Figure 2.6](#).

The intuitive plan can be used to solve the covering problem with a rotary-wing aerial robot. However, it is unsuitable for a fixed-wing aerial robot such as the Opterra. Fixed-wing aerial robots have considerably reduced maneuverability compared to rotary-wings. They are generally unable to perform quick turns in flight. An updated version of the intuitive plan for fixed-wing aerial robots is illustrated in [Figure 2.7](#). The paths that correspond to the fixed-wing aerial robot's plan are composed of four primitive paths

$$\varphi_1(\mathbf{p}(t)) := x - 10, \quad (2.10a)$$


$$\varphi_2(\mathbf{p}(t)) := (x - 85)^2 + (y - 10)^2 - 5625, \quad (2.10b)$$

$$\varphi_3(\mathbf{p}(t)) := x - 160, \quad (2.10c)$$

$$\varphi_4(\mathbf{p}(t)) := (x - 90)^2 + (y - 140)^2 - 4900, \quad (2.10d)$$

where  $x, y$ s are the  $x$ - and  $y$ -coordinates of a generic point  $\mathbf{p}(t)$ . The triggering points (the points in which proximity occurs the change of stages) are then the points

$$p_{\Gamma_1} := (10, 10), p_{\Gamma_2} := (160, 10), p_{\Gamma_3} := (160, 140), p_{\Gamma_4} := (20, 140). \quad (2.11)$$



**Fig. 2.7.** Fixed-wing aerial robot plan to cover a regular polygon with four sides. The plan covers the polygon with the same principle of the intuitive plan in [Figure 2.6](#) but preserving long turns necessary for the flight of a fixed-wing aerial robot. Likewise in [Figure 2.6](#), the entire polygon is covered iterating the primitive paths (gray lines) and triggering points. The dashed blue line indicates the triggering points, and the black line is the planned flight. The height and length of the polygon are  $y_{\Gamma_3} - y_{\Gamma_1}$  and  $l_{x_d}/4$ .

The covering problem can be solved using the paths in [Equation \(2.10\)](#), the triggering points in [Equation \(2.11\)](#), the remaining paths  $\varphi_5, \varphi_6, \dots, \varphi_l$ , and triggering points  $\mathbf{p}_{\Gamma_5}, \mathbf{p}_{\Gamma_6}, \dots, \mathbf{p}_{\Gamma_l}$  defined similarly to [Equations \(2.10–2.11\)](#). A generic solution for the covering problem defined as a pattern iterated over time is then defined with the paths

$$\varphi_i(\mathbf{p}(t)) := x - x_{\Gamma_1} - \lfloor i/4 \rfloor x_d, \quad (2.12a)$$

$$\varphi_{i+2}(\mathbf{p}(t)) := x - x_{\Gamma_2} - \lfloor i/4 \rfloor x_d, \quad (2.12b)$$

$\forall i \in \{1, 5, 9, \dots\}$ ,  $x_d$  is a shift on the  $x$ -axis,  $\lfloor i/4 \rfloor$  is the integer division. The expressions in [Equation \(2.12\)](#) correspond to the generalizations of the lines in [Equation \(2.10a\)](#) and [Equation \(2.10c\)](#). The generalizations of the circles in [Equation \(2.10b\)](#) and [Equation \(2.10d\)](#) are

$$\varphi_{i+1}(\mathbf{p}(t)) := (x - x_{\Gamma_1} - r_1 - \lfloor i/4 \rfloor x_d)^2 + (y - y_{\Gamma_1})^2 - r_1^2, \quad (2.13a)$$

$$\varphi_{i+3}(\mathbf{p}(t)) := (x - x_{\Gamma_2} + r_2 - \lfloor i/4 \rfloor x_d)^2 + (y - y_{\Gamma_3})^2 - r_2^2, \quad (2.13b)$$

where index  $i$  is defined the same way as in [Equation \(2.12\)](#) along the shift and integer division.  $r_1$  and  $r_2$  are given radii of the circles  $\varphi_2$  and  $\varphi_4$  in [Figure 2.7](#).

The triggering points can be expressed similarly with the expressions

$$\mathbf{p}_{\Gamma_i} := (x_{\Gamma_1} + \lfloor i/4 \rfloor x_d, y_{\Gamma_1}), \quad (2.14a)$$

$$\mathbf{p}_{\Gamma_{i+1}} := (x_{\Gamma_1} + 2r_1 + \lfloor i/4 \rfloor x_d, y_{\Gamma_1}), \quad (2.14b)$$

$$\mathbf{p}_{\Gamma_{i+2}} := (x_{\Gamma_1} + 2r_1 + \lfloor i/4 \rfloor x_d, y_{\Gamma_3}), \quad (2.14c)$$

$$\mathbf{p}_{\Gamma_{i+3}} := (x_{\Gamma_1} + 2r_1 - 2r_2 + \lfloor i/4 \rfloor x_d, y_{\Gamma_3}). \quad (2.14d)$$

We note from [Figure 2.7](#) and [Equations \(2.12–2.14\)](#) that  $y_{\Gamma_3} - y_{\Gamma_1}$  is the height of the polygon to be covered,  $2(r_1 - r_2)$  the distance between the covering lines (which is equal to the shift  $x_d$ ), and  $lx_d/4$  is the length of the polygon if the number of stages  $l$  is known.

The plan in [Equations \(2.12–2.14\)](#) is static. There is no path parameter that allows to alter the plan. We can easily transform such plan with the addition of a path parameter  $c_{4,1}$  relative to the radius of the second circle  $\varphi_4$  in [Figure 2.7](#)

$$r_2(c_{4,1}) := (r + c_{4,1}), \quad (2.15)$$


where  $r < r_1$  is a given positive constant initial radius and  $c_{4,1} \in (-r, 0]$ . We assume that the highest value is thus  $\bar{c}_{4,1} = 0$ , the lowest is strictly higher than the constant initial radius  $\underline{c}_{4,1} > -r$ .

We note from the expression in [Equation \(2.15\)](#) that [Equation \(2.14d\)](#) and [Equation \(2.13b\)](#) depend on the parameter  $c_{4,1}$  (they contain  $r_2$ , which depend on  $c_{4,1}$ ). They can be thereby dynamically replanned, resulting in an alteration of the quality of the coverage. They indeed change the distance between the survey lines. We can bound the alteration with

$$c_{i,1} \in [\underline{c}_{4,1}, \bar{c}_{4,1}] =: \mathcal{C}_{4,1} = (-r, 0], \quad \forall i. \quad (2.16)$$

The concept is illustrated in [Figure 2.8](#). The black line is the un-altered path until the triggering point  $\mathbf{p}_{\Gamma_3}$ , where the path splits depending on the value of the path parameter  $c_{4,1}$ . The alteration of the plan shortens or extends the flying time and thus influence the energy consumption over time. Since the last path  $\varphi_4$  is a function of the parameter  $c_{4,1}$ , the correct expression for [Equation \(2.13b\)](#) is

$$\varphi_{i+3}(\mathbf{p}(t), c_{4,1}) := (x - x_{\Gamma_2} + r_2(c_{4,1}) - \lfloor i/4 \rfloor x_d)^2 + (y - y_{\Gamma_3})^2 - r_2(c_{4,1})^2. \quad (2.17)$$



**Fig. 2.8.** Alteration of a path parameter of the fixed-wing aerial robot's plan in [Figure 2.7](#). The black line is the un-altered path up to the triggering point  $p_{13}^-$ , where the path can be altered with the parameter  $c_{4,1}$  relative to the radius  $r_2$  of  $\varphi_4$ . The alteration changes the distance between the survey lines hence extending or shortening the flying time. The longest distance is then  $2(r_1 - r_2(c_{4,1}))$ , the shortest  $2(r_1 - r_2(\bar{c}_{4,1}))$ . Same principle applies to path parameter  $c_{8,1}$  for the next two survey lines,  $c_{12,1}$ , and so on.

The last triggering point  $\mathbf{p}_{\Gamma_4}$  of the example in Equation (2.14d) is likewise a function of the parameter  $c_{4,1}$ ,

$$\mathbf{p}_{\Gamma_{i+3}}(c_{4,1}) := (x_{\Gamma_1} + 2r_1 - 2r_2(c_{4,1}) + \lfloor i/4 \rfloor x_d, y_{\Gamma_3}), \quad (2.18)$$

as it depends on the radius  $r_2$  of the circle  $\varphi_4$ . The same applies to all the following functions  $\varphi_5, \varphi_6, \varphi_7$ , since these are all a function of the triggering point  $\mathbf{p}_{\Gamma_4}$ . The path  $\varphi_8$  is then a function of the parameter  $c_{4,1}$  and  $c_{8,1}$  propagating the parameters for all the following paths  $\varphi_9, \varphi_{10}, \varphi_{11}$  and so on.

## 2.6.2 Computations sub-plan

In the computations sub-plan, we define the computations that form the plan of the agricultural scenario, opposed to the paths defined in the previous section. In the scenario, we are interested in monitoring the field in Figure 1.6. We detect ground hazards and communicate with other ground-based actors. We use a CNN implemented in a ROS node to detect the ground hazards. The CNN detection utilizes image frames from a downward-facing camera mounted on the aerial robot. We assume that there is one centralized work station on the ground to communicate with the ground-based actors. The communication between the aerial robot and the centralized work station occurs on another ROS node, which uses the technical standard for wireless communication IEEE 802.11 (Crow et al., 1997). It sends the detected images either unencrypted or using public-key infrastructure for encryption. We refer to these two computations as CNN and encryption ROS nodes. The schedule for the CNN ROS node is characterized by the FPS rate at which the frames are sent from the camera. The schedule for the encryption ROS node is characterized by a binary value that indicates whenever the encryption is enabled.

There are thus two computations parameters. A computation parameter is the FPS rate, and another computation parameter the encryption binary value. The CNN ROS node's computation parameter is  $c_{i,2}$ , and the encryption ROS node's computation parameter is  $c_{i,3}$ .

The upper and lower bounds of  $c_{i,3}$  are

$$c_{i,3} \in \mathcal{S}_{i,3} := \{0, 1\}, \forall i, \quad (2.19)$$

the parameter value thus indicates if the encryption is active (one) or data are sent unencrypted (zero).

For the upper and lower bound of  $c_{i,2}$ , we first note from the path plan in Section 2.6.1 that during the turns the aerial robot is not surveying the polygon. We thus place different constraints for different paths. For the circles in Equation (2.22b) and Equation (2.22d) the computation parameters constraint sets are

$$c_{i+1,2}, c_{i+3,2} \in \mathcal{S}_{i+1,2} = \mathcal{S}_{i+3,2} := \{0\}, \forall i \in \{1, 5, 9, \dots\}, \quad (2.20)$$

and thus the CNN ROS node is not detecting any hazard when it flies out of the polygon. On the contrary, for the lines in Equation (2.22a) and Equation (2.22c)

$$c_{i,2}, c_{i+2,2} \in \mathcal{S}_{i,2} = \mathcal{S}_{i+2,2} := [2, 10], \forall i \in \{1, 5, 9, \dots\}, \quad (2.21)$$

the the CNN ROS node is detecting hazard on the ground with a FPS rate between two and ten.

Energy-wise we expect the highest configuration of computations parameters to correspond to the highest instantaneous energy consumption. We use `powprofiler`, the profiling and modeling tool that we briefly outlined in Section 1.4 and that we introduce in Section 4.1, to measure and model the future energy consumption of different computations' configurations.

### 2.6.3 Planning problem with paths and computations sub-plans

The plan for the precision agriculture scenario is composed of stages containing the primitive paths in Equations (2.12–2.13), and the parameter dependent version in Equation (2.17). It further contains the path parameter  $c_{i,1}$ ,  $\forall i \in \{4, 8, \dots\}$ , the computations parameters  $c_{i,2}$  and  $c_{i,3}$ ,  $\forall i \in \{1, 2, \dots\}$ . In particular, the stages corresponding to the primitive paths are

$$\Gamma_i := \{\varphi_i(\mathbf{p}(t), c_{4,1}, c_{8,1}, \dots, c_{i-1,1}), c_{i,2}, c_{i,3}\}, \quad (2.22a)$$

$$\Gamma_{i+1} := \{\varphi_{i+1}(\mathbf{p}(t), c_{4,1}, c_{8,1}, \dots, c_{i-1,1}), c_{i+1,2}, c_{i+1,3}\}, \quad (2.22b)$$

$$\Gamma_{i+2} := \{\varphi_{i+2}(\mathbf{p}(t), c_{4,1}, c_{8,1}, \dots, c_{i-1,1}), c_{i+2,2}, c_{i+2,3}\}, \quad (2.22c)$$

$$\Gamma_{i+3} := \{\varphi_{i+3}(\mathbf{p}(t), c_{4,1}, c_{8,1}, \dots, c_{i-1,1}, c_{i+3,1}), c_{i+3,2}, c_{i+3,3}\}, \quad (2.22d)$$

$\forall i \in \{1, 5, 9, \dots\}$ . The path constraint set for the path parameter  $c_{i,1}$  is then defined in Equation (2.16), the computation constraint set for the computation parameter  $c_{i,2}$  in Equation (2.20) and for the computation parameter  $c_{i,3}$  in Equation (2.21). The triggering points

$$\mathbf{p}_{\Gamma_i}(c_{4,1}, \dots, c_{i-1,1}) := (x_{\Gamma_{i-4}}(c_{4,1}, \dots, c_{i-1,1}) + \lfloor i/4 \rfloor x_d, y_{\Gamma_1}), \quad (2.23a)$$

$$\mathbf{p}_{\Gamma_{i+1}}(c_{4,1}, \dots, c_{i-1,1}) := (x_{\Gamma_{i-4}}(c_{4,1}, \dots, c_{i-1,1}) + 2r_1 + \lfloor i/4 \rfloor x_d, y_{\Gamma_1}), \quad (2.23b)$$

$$\mathbf{p}_{\Gamma_{i+2}}(c_{4,1}, \dots, c_{i-1,1}) := (x_{\Gamma_{i-4}}(c_{4,1}, \dots, c_{i-1,1}) + 2r_1 + \lfloor i/4 \rfloor x_d, y_{\Gamma_3}), \quad (2.23c)$$

$$\begin{aligned} \mathbf{p}_{\Gamma_{i+3}}(c_{4,1}, \dots, c_{i+3,1}) := & (x_{\Gamma_{i-4}}(c_{4,1}, \dots, c_{i-1,1}) + 2r_1 - 2r_2(c_{i+3,1}) \\ & + \lfloor i/4 \rfloor x_d, y_{\Gamma_3}). \end{aligned} \quad (2.23d)$$

$\forall i \in \{5, 9, \dots\}$ . The initial points  $x_{\Gamma_1}$ ,  $y_{\Gamma_1}$ , and  $y_{\Gamma_3}$  are given along the shift  $x_d$  on the  $x$ -axis, and the radius of the first circle  $r_1$ . The function  $r_2$  which returns the radius of the second circle and it is a function of the path parameter  $c_{i,1}$ ,  $\forall i \in \{4, 8, \dots\}$  is given in Equation (2.15). The last triggering point  $\mathbf{p}_l$  is likewise given.

The solution to the planning problem are thus the three trajectories  $c_i^*(t) = \{c_{i,1}^*(t), c_{i,2}^*(t), c_{i,3}^*(t)\}$ ,  $\forall i \in \{1, 2, \dots\}$  that are optimal energy-wise under given energy constraint and uncertainty. Since each quadruple of stages in Equation (2.22) and triggering points in Equation (2.23) depends only on the last path parameter (of the quadruple), we further assume that  $c_{1,1} = c_{1,2} = c_{1,3} = c_{1,4}$  and more generally

$$c_{i,1} = c_{i+1,1} = c_{i+2,1} = c_{i+3,1}, \forall i \in \{1, 5, 9, \dots\}. \quad (2.24)$$

We derive the solution for the planning problem of the precision agriculture example in Section 6.4.1.

## 2.7 Summary

In this chapter, we defined the planning problem in Section 2.5.1. The problem requires some basic concepts, including path functions in Section 2.2 and plan in Section 2.4. The latter is composed of stages, triggering and final points in Section 2.3, and parameters that are used for dynamic replanning. Some parameters characterize the path, and some parameters characterize the computations.

Alternatively to defining all the stages manually, the user might define an autonomous scenario with a certain degree of periodicity using primitive paths and a shift as we saw in Section 2.4. We illustrated the concept of an autonomous scenario using the precision agriculture example, first introduced in Section 1.3.2, in Section 2.6.

# Chapter 3

## State of the Art

In this chapter, we discuss the state of the art in energy modeling and optimization of computing hardware and mobile robots and in dynamic energy planning for mobile robots. We are interested in using the two energy models (of computing hardware and mobile robot) for the energy planning of the path and computations. Generally, planning algorithms in robotics center around robot motion planning and deal with problems such as swarms, dynamics, and uncertainty (LaValle, 2006). Although there are several contributions applied to a variety of robots, we primarily focus on the literature that—similarly to our approach—plans the path along with computations. We especially emphasize approaches for mobile robots with energy constraints.

We split the chapter into multiple sections and replicate our workflow throughout the topic. Initially, we analyzed some contributions that quantify the energy consumption of computing hardware carried by mobile robots. Modeling the energy of these devices has laid the foundation for our dynamic energy planning. In [Section 3.1](#), we report our findings. We discuss the available approaches for battery modeling and the battery modeling and optimization of the mobile computing hardware in [Section 3.2](#). We then briefly discuss some approaches for motion planning, planning with dynamical systems, and planning for aerial robots in [Sections 3.3–3.4](#). Although simultaneous dynamic planning of computations and motion is underrepresented (Sudhakar et al., 2020), some recent contributions have proposed various techniques and further motivated our analysis. We report these in detail in [Section 3.5](#).

This chapter connects to the remainder of this work as follows. Here we discuss the state of the art of topics that allowed us to derive a dynamic energy planning approach for autonomous aerial robots. Based on these findings, we later propose a computations energy modeling technique to derive future energy consumption of mobile computing hardware along with motion in [Chapter 4](#). Planning in the context of mobile robots, under differential constraints, for aerial robots, and of computations and motion are the basis for the derivation of the optimal configuration in [Chapter 6](#) of the plan and the planning problem that we defined in [Chapter 2](#).

### 3.1 Computations Energy Modeling

There are several different energy modeling and optimization approaches for computations, usually under the topic of energy efficiency for computing hardware. Such hardware is carried by aerial robots that we analyze in this work and is often composed of heterogeneous elements: one or more CPUs and

a GPU as we outlined in [Section 1.3](#). Energy efficiency is critical for battery-constrained devices ([V. Rao et al., 2005](#)) and a limiting factor in improving further computing performance ([Horowitz, 2014](#)). We split some of the available approaches in the literature into different classes, depending on their modeling and optimization approach. We illustrate an overview of the approaches we consider in [Table 1](#). Due to the unpredictable nature of the heterogeneous elements, many contributions to energy modeling observe hardware characteristics and perform physical energy consumption measurements to derive an energy model. We analyze some of these contributions first. They treat the heterogeneous elements altogether and are of particular interest to our approach where we use heterogeneous mobile computing hardware. We then analyze the techniques that focus on the energy of GPUs. Finally, we analyze techniques that treat CPUs. Some of the latter are based on dynamic voltage scaling (DVS) that scales down both the supply voltage and the frequency when there is no high computations demand ([X. Chen and Touba, 2009](#); [Flautner et al., 2001](#)). A review of techniques with different computing elements that focus on predictive modeling is provided by O’Neal and Brisk ([O’Neal and Brisk, 2018](#)) with emphasis on heterogeneous models based on machine learning. Some other reviews that deal with energy modeling and focus on high-performance computing (HPC) systems are provided by O’Brien et al. ([O’Brien et al., 2017](#)) and Czarnul et al. ([Czarnul et al., 2019](#)). In the context of energy modeling, Czarnul et al. report existing tools for energy prediction in HPC systems and O’Brien et al. the accuracy of different models in the literature.

### **3.1.1 Heterogeneous elements modeling**

Modern computing hardware energy modeling and optimization techniques often deal with the heterogeneous computing elements altogether using statistical tools. Such tools are inexpensive to deploy and relatively accurate in predicting future computations energy consumption ([Bailey et al., 2014](#)). Although there are further optimizations available by looking at the elements (CPUs, GPUs) separately, these are often application and hardware-dependent. Instead, we focus on a generic computations energy model that can be used independently of the hardware and computations under analysis.

A model for heterogeneous elements is derived by Marowka ([Marowka, 2017](#)). The model is based on some power metrics: the scaled speedup, scaled performance per watt, and scaled performance per joule. The approach increases energy efficiency by choosing the configuration of the heterogeneous components—for instance, by enabling computations only on CPU cores—and hence, investigates the impact of different architectural choices on energy efficiency. In particular, the model is used to analyze the energy of three processing schemes: symmetric, asymmetric, and simultaneous. The former uses merely a multicore CPU. Asymmetric processing scheme both CPU and GPU. The software benchmark on this scheme consists of running a program on one of the computing elements at a time. The latter processing scheme is similar to the previous, but the software benchmark runs on CPU and GPU simultaneously. Our work extends the model and builds a computations model to the simultaneous processing scheme.

A more sophisticated statistical model relies on multivariate linear regression for heterogeneous elements and is derived by Bailey et al. ([Bailey et al., 2014](#)). The model eases the selection of the application’s configuration that maximizes performance under given power constraints. It is trained offline with a small set of benchmarks and works across multiple devices. The overall flow of the proposed approach is composed of two stages. The first stage is the offline training stage. The stage utilizes a small training set of benchmarks split into clusters. The model is built then with a regression per each cluster. After this stage, follows the online predicting stage. The latter uses the model to predict the power and per-

		Model	Technique	Accuracy	DVS	DFS	Platform	Mobile
Heterogeneous	Marowka Bailey et al.	Analytical Regression	Selection Configuration <sup>b</sup>	- 91% <sup>a</sup>	x x	x (✓)	Intel Core-i7-960 (CPU), NVIDIA GTX 280 (GPU) AMD A10-5800K (CPU), Radeon HD7660D (GPU) ARM7 OKI ML675003 (CPU), TI MSP430F1611 (micro-controller)	x
	Goraczko et al.	Analytical	Configuration <sup>b</sup>	-			AMD Phenom II X2 (CPU), NVIDIA GeForce 8800 (GPU)	x
	Ma et al.	-	Configuration	-		✓	ARM Cortex-A15 (CPU), NVIDIA GK20A (GPU)	✓
GP	Yang et al.	Analytical Analytical	Pruning Selection	-	x x	x [✓]	ARM Cortex-A15 (CPU), NVIDIA GK20A (GPU)	x
	Calore et al.	Analytical Regression (ML)	Selection Selection	91.06% <sup>c</sup> 90% <sup>d</sup>	x x	x [✓]	NVIDIA GTX280 (GPU) AMD Radeon HD 7970 (GPU)	x
	Hong and Kim Wu et al.	Regression (ML)	Selection	-	x x	x x	NVIDIA G80, GT200 (GPU) NVIDIA Tesla C2050 (GPU)	x
CPU	Collange et al.	-	Analytical	88.87% <sup>d</sup>	x	✓	NVIDIA GTX 480, Quadro FX5600 (GPU)	x
	Luo and Suda	-	Analytical	88.35% <sup>d</sup>	✓	✓		
	Leng et al.	-	Selection	95.7% <sup>c</sup>	x	x		
CPU	Lee and Brooks	Regression	Selection Selection	93% <sup>f</sup> 94% <sup>g</sup> , <sup>d</sup>	x x	✓ ✓	Intel Xeon E5540 (CPU) ARM Cortex-A15 (CPU)	x
	Takouna et al.	Regression	Selection	92–95% <sup>h</sup>	✓	✓	ARM Cortex-A15, Cortex-A7 (CPU)	x
	Reddy et al.	Analytical	Selection	95%	x	x	ARM Cortex-A9 (CPU)	x
CPU	Nikov et al.	Regression	Selection	96.2–97.2%	✓	✓	ARM Cortex-A15, Cortex-A7 (CPU)	x
	Nunez-Yanez and Lore	Regression	Selection					
	Walker et al.	Regression	Selection					

Table 1. Comparison of different computations energy models. The model is either an analytical expression or a regression. The energy optimization technique is the selection of some architectural parameters, of computations configurations. Scaling is split into DVS and dynamic frequency scaling DFS. (✓) scaling is used only in the model, not in the optimization technique. [✓] values are changed statically (or manually where appropriate such as in Marowka).

<sup>a</sup>accuracy under-limit against oracle with perfect knowledge

<sup>b</sup>optimization problem solved with ILP

<sup>c</sup>average accuracy for both power and time models against measuring hardware

<sup>d</sup>accuracy against built-in power monitors (if the accuracy is reported for multiple hardware or benchmarks, it is average)

<sup>e</sup>accuracy against median error, leveraging only the most relevant samples

<sup>f</sup>accuracy of 95% of the predictions

<sup>g</sup>accuracy on 60 workloads

<sup>h</sup>accuracy against related work

formance of a large set of applications (opposed to the relatively small number of benchmarks in the offline stage). Our work similarly models a subset of samples and infers properties of the entire search space. However, our work focuses on mobile computing hardware that we use for aerial robots.

A resource model for heterogeneous mobile devices developed by Goraczko et al. ([Goraczko et al., 2008](#)) considers both the time and power of a given run-time mode (Goraczko et al. use the term mode rather than configuration used by Marowka and Bailey et al.). Goraczko et al. use a CPU and a microcontroller as a heterogeneous platform opposed to GPU in the past approaches in this section. Energy-wise, the resource model uses DVS as some other models in [Section 3.1.3](#) but accounts for heterogeneous elements. The approach models multiple processors with a state machine then used to derive a software partitioning problem—the problem of deriving the optimal mode. The problem is solved with an optimization technique: integer linear programming (ILP). The optimization occurs over an energy cost and with given deadline constraints. The intuition of formally defining the problem of deriving the optimal mode is similar in our work, which we expanded further by merging the path in our dynamic energy planning.

A holistic approach for heterogeneous elements energy efficiency is proposed by Ma et al. ([Ma et al., 2012](#)). The approach achieves energy efficiency by splitting and distributing the workload among the heterogeneous elements. Ma et al. then use frequency scaling for the CPU and GPU, and DVS for the CPU. GPU-side, the frequency is determined with a lightweight machine learning algorithm. Energy in this approach is analyzed by empirical means, using two power meters. The testbed under analysis—NVIDIA GeForce GPUs and AMD Phenom II CPUs—does not include built-in power monitors, and overall, Ma et al. do not consider mobile computing heterogeneous hardware or derive a model for the energy. Nevertheless, the approach is of interest for energy implications of heterogeneous elements.

Recently, approaches are emerging to model the energy consumption of machine learning algorithms. Some computations-specific modeling approaches have been developed in this context by Yang et al. ([Yang, Y.-H. Chen, Emer, et al., 2017](#)), and more recently surveyed by Garc’ia-Mart’in et al. ([Garc’ia-Mart’in et al., 2019](#)). The latter is a literature review motivated by the lack of appropriate tools to build and measure power models in existing machine learning suites. Garc’ia-Mart’in et al. describe the state of the art of energy estimation for convolutional neural networks (CNNs) and data mining. Yang et al. evaluate an energy model of deep neural networks (DNNs) based on a network bitwidth, sparsity, and architecture. The methodology applies exclusively to DNNs, but has been extended and used with CNNs ([Yang, Y.-H. Chen, and Sze, 2017](#)) in an optimization loop to reduce the computations energy consumption. A survey to optimize and evaluate neural networks on some of the embedded platforms that we use in this work (NVIDIA Jetson TK1 and TX2) specifically is proposed in ([Mittal, 2019](#)).

A review of operating system level energy management techniques for heterogeneous element of computing hardware is carried by Kim et al. ([Y. G. Kim et al., 2018](#)). Although Kim et al. do not deal with energy models, they list energy management techniques such as power-saving schedule that we utilize to dynamically optimize the energy resource of the aerial robots. They also detail aspects such as Quality of Service (QoS) that we use to define execution boundaries for the computations.

Our initial approach ([Seewald, Ebeid, et al., 2019](#)) relied on external meters rather than internal power monitors. A similar technique has been developed by Calore et al. ([Calore et al., 2015](#)) to measure the energy efficiency of HPC systems. In both ours and Calore et al. approaches, the methodology is tested on the NVIDIA Jetson TK1 computing hardware that does not include built-in power monitors as opposed to other computing hardware that we analyze.

### 3.1.2 GPU features modeling

GPUs are used in several applications due to their high computational resources (Kasichayanula et al., 2012), which come at a price of increasing energy demands (Mittal and Vetter, 2014). It is hence unsurprising that for computations energy modeling, GPUs have their own modeling approaches. Here we discuss some of the approaches of interest to our work. Extensive reviews of the available methodologies are proposed by Mittal and Vetter (Mittal and Vetter, 2014) and by Bridges et al. (Bridges et al., 2016) but are not tailored to mobile computing hardware.

An energy model that analyzes GPU features is derived by Hong and Kim (S. Hong and H. Kim, 2010). The contribution consists of an integrated power and performance prediction model to derive the optimal number of active cores for a given application to achieve energy savings (S. Hong and H. Kim, 2010). The model is GPU specific: it consist of an analytical expression which estimates the GPU power and time in function of some parameters. Opposite to our work, it does not model the energy of the entire platform nor is deployed on mobile computing hardware. Nevertheless, it achieves high accuracy in terms of GPU power and time prediction.

A similar focus on GPU features is proposed by Wu et al. (G. Wu et al., 2015). The approach uses machine learning techniques to evaluate the performance and estimate the power from real GPU hardware. In particular, Wu et al. trains a neural network with different performance counters for various GPU configurations of a collection of applications, and derive the optimal values of these counters. The data gathered from one hardware are used to estimate the power and performance for multiple other GPU hardware. Like the approaches in Section 3.1.1, the approach is computation-independent and requires no source code analysis. Moreover, machine learning is an energy-expensive computation itself (García-Martín et al., 2019; Yang, Y.-H. Chen, Emer, et al., 2017), thus deterring similar approaches in our planning where we aim to preserve the energy as far as possible.

An empirical approach for energy evaluations of GPUs during various computations in the CUDA environment is proposed by Collange et al. (Collange et al., 2009). The approach measures and analyzes how computations impact instantaneous energy consumption. It observes a significant energy impact of memory accesses and generally analyzes the energy cost of parallel GPU computations. The work by Collange et al. thus aims to derive the optimal memory configuration of a given benchmark. However, it does not use the measured data to calibrate a model for energy estimation, nor focus on mobile computing devices.

Contrary to the previous approach of pure empirical measurements, Luo and Suda(C. Luo and Suda, 2011) proposes an analytical model for energy and performance estimation of GPUs. The model contains execution time and energy consumption prediction sub-models, where the latter follows from the former. The final analytical model for the energy estimation multiplies the execution time and the estimated power derived using an analytical expression. The work derives some observations on energy implication of a given benchmark, which is then not used nor hypothesized in any energy adaptation technique. The accuracy analysis, redefined by the authors with another analytical expression, shows a strong correlation between observation and the analytical model. We also derive an analytical expression. We further motivate such expression with empirical observation of energy data and employ a multivariate linear regression. We then focus on heterogeneous elements and mobile computing hardware.

A model based on a performance-per-watt metric for GPUs is proposed by Leng et al. (Leng et al., 2013). Developed for general-purpose GPU (GPGPU) powered devices, it is composed of multiple stages. An initial model is validated with some empirical measurements and eventually refined. The contribution suggests an integrated power and performance modeling framework, which inputs a con-

figuration to define micro-architectural and component parameters. It is then used in a feedback-driven optimization loop with the GPGPU. In our approach, we similarly input a configuration to the model but we specifies the computing hardware's computations rather than architectural parameters. We use the output of the model in an optimization loop but extend this latter stage together with the path. Computation-wise, we use both heterogeneous elements.

### 3.1.3 CPU features modeling

Numerous other contributions model the CPU energy specifically and investigate how to lower the power (Chowdhury and Chakrabarti, 2005; I. Hong et al., 1999; J. Luo and Jha, 2001) by some system-level modeling and optimization techniques including DVS, multiple asymmetric cores (such as the ARM big.LITTLE architecture), and power gating (Walker et al., 2017). They usually incorporate information about configuration parameters into the scheduler (Seewald, Schultz, Ebeid, et al., 2021) and focus on homogeneous opposite to heterogeneous systems in our work.

A model for microprocessors based on regression is proposed by Lee and Brooks (B. C. Lee and Brooks, 2006a,b). The model is built with a small number of samples of both the power and performance in a joint architecture-computations search space. Lee and Brooks provide extensive coverage of regression modeling and use the same model specification for power and performance. The entire search space is sampled uniformly at random, an approach that allows identifying trends and trade-offs between the parameters (B. C. Lee and Brooks, 2006a). The results show high accuracy even with a relatively small number of samples. We likewise use a regression model in our computations energy modeling approach but cover all the heterogeneous elements. Nonetheless, Lee and Brooks' approach is of interest to evaluate the accuracy of regression techniques and distributions of samples. Depending on the configuration space we sample the computations uniformly using a linear or exponential distribution of samples whereas Lee and Brooks samples architectural parameters. We specify the sampling distance in a configuration file.

Statistical multicore CPU power models are presented by Takouna et al. (Takouna et al., 2011). These models are based on the average running frequency and the number of active cores. Commonly to other computations energy models, they use multivariate linear regression. Although insightful in terms of multicore CPU power models, the approach does not model GPUs nor heterogeneous elements. Moreover, it is tailored on virtualized servers, opposed to mobile computing hardware that we focus on in this work. Moreover, Takouna et al. do not consider computations configurations in the regression, but a variable selection of architectural parameters.

An empirical CPU power model is presented by Reddy et al. (Reddy et al., 2017). The model uses measured data and simulates the energy consumption of a quad-core ARM Cortex-A15 and gem5, a full-system architectural performance simulator. To collect the measurements, the model uses built-in power monitors in the ODROID-XU3 platform and evaluates the model against sixty workloads reporting high accuracy (the average error between estimated and real power is less than six percent). Our model shares compatibility with the ODROID-XU3 platform but is not simulator-dependent. It further models heterogeneous computing hardware such as NVIDIA Jetson TK1, TX2, and Nano platforms.

Other models for mobile computing hardware based on the ODROID-XU3 platform are developed by Nunez-Yanez and Lore (Nunez-Yanez and Lore, 2013) and by Nikov et al. (Nikov et al., 2015). These models use hardware event registers and capture the state of the CPU under a representative workload. They have three modeling stages: data collection of a benchmark running on the platform occurs in the

first stage. The second and third stages are performed offline on a different architecture. They process the collected data (in the second stage) and generate the model (in the third stage) (Seewald, Schultz, Ebeid, et al., 2021). In (Nikov et al., 2015), the model deals with ARM big.LITTLE architecture. We use these models to evaluate the performance of our computations energy modeling.

A run-time model that uses performance monitoring counters (PMCs) for mobile computing hardware is proposed by Walker et al. (Walker et al., 2017). The approach is implemented on mobile CPUs such as ARM Cortex-A7 and Cortex-A15 and can be implemented on other CPUs. Likewise in (Reddy et al., 2017), the model can be used with the architectural performance simulator gem5, and likewise in (Nikov et al., 2015; Nunez-Yanez and Lore, 2013; Reddy et al., 2017), it is implemented on the ODROID-XU3 platform. The approach builds a linear regression for a given experiment for CPU power prediction. Although it considers CPU-powered computing hardware only, it is insightful in terms of proposed statistical rigor in building run-time CPU power models.

## 3.2 Battery Modeling

In this section, we describe some battery modeling approaches and focus on battery models that we can use with both the computing hardware and the aerial robot. There are several models for this purpose, each with its advantages and disadvantages. The state of the art in battery modeling is surveyed by Rao et al. (R. Rao et al., 2003). Physical models use ordinary and partial differential equations to accurately predict the battery evolution in time (R. Rao et al., 2003). These models come at a considerable time and computational cost (Doyle et al., 1993; Lotfi et al., 2017; Marcicki et al., 2013; Moura et al., 2017). Nevertheless, some hybrid models with less computational complexity have emerged as well (T. Kim and Qiao, 2011; T. Kim, Qiao, and Qu, 2019). Empirical models model the battery out of a set of empirical trials (Pedram and Q. Wu, 1999; Syracuse and Clark, 1997), in a similar way as many computations energy models in Section 3.1. They have a relatively low analytical insight (R. Rao et al., 2003), opposed to mixed models that derive some parameters from analytical expressions and experimental data (Rakhmatov and Vrudhula, 2001; R. Rao et al., 2003). Abstract methodologies use techniques such as the time evolution of an equivalent electrical circuit (Benini et al., 2001; Gold, 1997; Hasan et al., 2018; X. Hu et al., 2012; S. Lee et al., 2008; Xing et al., 2014) similarly to hybrid models (T. Kim and Qiao, 2011) but with less computational complexity. They have compelling trade-offs in terms of analytical insight, accuracy, and complexity (R. Rao et al., 2003) and are the models of our choice for battery modeling.

Abstract models with an equivalent electrical circuit are presented by Xing et al. (Xing et al., 2014) and Hasan et al. (Hasan et al., 2018). These models model the battery state of charge (SoC) with the evolution in time of a differential model of an equivalent circuit. The first model (Xing et al., 2014) utilizes an unscented Kalman filter to tune some parameters at each sampling step. the SoC is then estimated in the second model (Hasan et al., 2018) utilizing an eXogenous Kalman filter (Johansen and Fossen, 2017). We use the model from Hasan et al. for the battery modeling. We derive an equivalent circuit for a Li-ion aerial robot battery and evaluate the SoC over time with an equivalent differential equation to the one proposed in (Hasan et al., 2018).

A battery model for computing hardware specifically is proposed by Rao et al. (V. Rao et al., 2005). The approach consists of an abstract stochastic model that uses Markov processes with probabilities related to the physical characteristics of the battery (Panigrahi et al., 2001). Rao et al. improve further the accuracy of the model including some physical battery characteristics. The approach is useful in terms of evaluating models for computing hardware. Indeed our approach relies similarly on an abstract

model (Hasan et al., 2018), whereas we focus on models based on an equivalent electrical circuit which requires less battery-specific knowledge for modeling. We can then model the SoC with little information regarding what battery is mounted on the aerial robot.

A modeling technique for smartphones is proposed by Zhang et al. (L. Zhang et al., 2010). The approach consists of an automated modeling technique that uses knowledge of battery discharge behavior and battery voltage sensors. The technique models the power using a multivariate regression (similarly to our approach and many computations energy models in Section 3.1) and the battery using an equivalent circuit. Although the analysis is limited to smartphones, it is insightful in terms of automated modeling techniques for computing hardware. We have similarly derived an automated modeling technique for computations, battery, and entire system model that we integrate into our dynamic energy planning for aerial robots.

A battery model for the low-power design of computing hardware is presented by Benini et al. (Benini et al., 2001). The model is also derived from an equivalent circuit but is discrete-time and intended for system-level design environments. Although specific to this latter application, it evaluates different battery types: a first Li-ion implementation of the model is extended to various battery types with both non and rechargeable cells.

### 3.3 Motion Planning

Planning algorithms for mobile robots include broad and diverse topics. Energy-wise, the algorithms select an energy-optimized trajectory Mei, Lu, Y. C. Hu, et al., 2004, e.g., by maximizing the operational time Wahab et al., 2015. However, many studies apply to a limited number of robots C. H. Kim and B. K. Kim, 2005 and focus exclusively on planning the trajectory H. Kim and B.-K. Kim, 2008, despite compelling evidence for the energy consumption also being significantly influenced by computations Mei, Lu, Y. C. Hu, et al., 2005. In the remainder of this chapter and before discussing the studies in mobile robotics that deal with computations and motion energy, we detail planning in the literature. We are interested in planning both these aspects: the path and the computations. We further recall that we are specifically interested in coverage planning of a given space in an energy efficient way. We discuss the available literature on coverage planning for mobile robots later in this section and emphasize relevant studies for aerial robots in Section 3.4.1. There are several approaches in this sub-topic of motion planning (Cabreira, Brisolara, et al., 2019; H. Choset, 2001), including studies that derive an energy efficient cover (Cabreira, Franco, et al., 2018; Wei and Isler, 2018). In Section 3.4.2 we discuss these studies and focus on previous methodologies for the optimality of the cover.

Within simple motion planning opposed to the derivation of a cover, Mei et al. propose an energy-efficient motion planning for mobile robots distinguishing the two major energy consumers—the computations and motion energy. In (Mei, Lu, Y. C. Hu, et al., 2004) focus on optimizing the motion energy, although they analyzed the computations energy in a later iteration of their work (Mei, Lu, Y. C. Hu, et al., 2005) (we discuss this latter study in Section 3.5). Their motion plan is composed of a path plan and a velocity schedule; the path plan is similar to the our plan in Definition 2.4.2, whereas the velocity schedule contains velocities, accelerations, and decelerations along the route. Mei et al. then analyze the most energy efficient path plan and velocity schedule. The major contributions spans from analyzing the energy cost of a plan along the energy of turns and accelerations, the analysis of travelled against motors velocities, to experimental evaluations. We have likewise optimized the coverage plan in Section 2.6.1 compared to traditional coverage planning using e.g., boustrrophedon decomposition (LaValle, 2006).

We do not consider a velocity schedule in our dynamic planning due to the physical constraints of airborne systems. Nevertheless our approach is optimized against sudden accelerations. Indeed one of the observation Mei et al. underline is the energy cost of turns; to this end our algorithm minimizes the number of turns in the coverage. Recall the plan in [Figure 2.6](#) requires sudden decelerations opposed to the plan in [Figure 2.7](#) specifically optimized for fixed-wing crafts. The study uses Palm Pilot Robot Kit as experimental setup with polyurethane omnidirectional wheels and three MS492MH DC servo motors. Mei et al. use external power monitors to measure the power drain of the systems and 9 V along four 1.5 V batteries for the control circuit and motors respectively. They measure the energy efficiency in terms of squared meters over jouls and report an improvement of 50% by using an energy optimized path plan. Mei et al. study has encouraged our initial analysis in dynamic planning in many respects: Mei et al. are the first energy efficiency study we found that analyzed motion and computations energy, that analyze plan variations energy-wise, and that distinguish explicitly the need to account for computations energy ([Mei, Lu, Y. C. Hu, et al., 2005](#)). However, Mei et al. lack in further analysis of energy efficiency in path variations. Indeed they focus on straight lines, spirals, and the energy cost of turns rather whereas we focus on a generic variation in path within given limits. They do not address explicitly computations and motion planning but propose foundations for future studies.

Dressler and Fuchs undertake a different approach to energy efficient motion planning. In their work ([Dressler and Fuchs, 2005](#)) they focus on energy modeling of motion plans for given tasks (the term is not to be confused with computational tasks), where e.g., the mobile robot has to reach a location in space and take an image. Dressler and Fuchs propose a future planning direction based on energy control and battery management to allocate the tasks in an energy efficient way. The study models energy-consuming parts of the robot with some corresponding characteristic curves and it is hypothesized to a scenario for exploration and supervision of unknown surroundings. Dressler and Fuchs observe a linearly approximable of the SoC for some sub-tasks of a given task such as movement and wireless communication. The study lays basic for future analysis on the topic but does not investigate further dynamic planning for mobile robots. Although we don't model the energy of a given task, we similarly formulate the plan as a set of paths and computations in [Definition 2.4.2](#) of which we derive the optimal configuration energy wise. Although preliminary, the study has inadvertently introduced the differentiation between computations and motion energy components that we have built upon. The reported sub-tasks energy models are indeed relative to one or another of the two components. The wireless communication is relative to a computation that transfer data airborne, the movement to a path to reach the location. Dressler and Fuchs have further developed the approach, however, focused on sensor networks ([Dressler and Dietrich, 2006; Fuchs et al., 2006](#))

The majority of other contributions in the literature focus on optimizing motion planning to increase power efficiency. There are several studies that survey the available literature for mobile robots' planning, along some textbooks ([H. M. Choset et al., 2005; LaValle, 2006](#)). Notably, La Valle's textbook ([LaValle, 2006](#)) groups planning algorithms literature and focus on robot motion planning. Juliá et al. propose an extensive study of the most important methods for motion planning for autonomous exploration and mapping of unknown environments. The survey presents different techniques and classifies them for the level of multi-robot coordination and integration with simultaneous localization and mapping (SLAM) algorithm.

### 3.3.1 Coverage path planning

In autonomous mobile robots scenarios it is often required to explore every location in a given elemental region (Cao et al., 1988); this latter problem is defined in the literature as coverage path planning (CPP) problem. In this section we discuss briefly some surveys that deal with CPP in mobile robotics generically, while we discuss in detail approaches that involve aerial robots in this latter sub-topic in Section 3.4.1. In our work, we are dealing with this problem when we cover a given agricultural area in Problem 2.5.1.

The problem is related to the covering salesman problem, a variation of the famous travelling salesman problem (TSP) where the salesman visits a neighborhood of each city minimizing the travel length (E. M. Arkin and Hassin, 1994), except that the salesman must pass over all points rather than through all the neighborhoods (H. Choset, 2001). This problem is referred to also as lawnmower problem (Galceran and Carreras, 2013), and is proven to be NP-hard (E. M. Arkin, S. P. Fekete, et al., 2000). Early studies to solve the problem use heuristic with no guarantee on the coverage (H. Choset, 2001). For instance, Arkin and Hassin propose simple heuristic-based algorithms for constructing the tours (E. M. Arkin and Hassin, 1994). There have emerged a variety of approaches ever since. Arkin appears in other studies that extend the work and propose a continuous version for the covering salesman problem algorithm (E. Arkin et al., 1993; E. M. Arkin, S. P. Fekete, et al., 2000; S. Fekete et al., 1994) that solves the problem with lawn moving and milling algorithms (E. M. Arkin, S. P. Fekete, et al., 2000). To ensure a guarantee on the coverage, many approaches either implicitly or explicitly use cellular decomposition (exact or approximate), where the space to cover is decomposed into cells; the overall solution to the coverage planning problem is then the union of the solutions of the cells (H. Choset, 2001).

To cover each cell in a cellular decomposition, the robot can use simple back and forth motion parallel to the cell's boundaries—often referred to as boustrophedon motion (LaValle, 2006)—and the coverage planning is reduced to motion planning between the cells (H. Choset, 2001). Often, the cells are decomposed into trapezoids which yields to a popular class of solutions under the name of boustrophedon decomposition—since they are related to the boustrophedon motion; the origin cell is split in the eventuality the algorithm finds an obstacle (encounters a change in connectivity) (H. Choset, E. Acar, et al., 2000). Choset et al. propose exact cellular decomposition method (H. Choset and Pignon, 1998) that they complement with different motions in a latter instance of their work (H. Choset, E. Acar, et al., 2000) (they consider e.g., spirals, spikes, and diamond patterns and other interesting decompositions). Within the cellular decomposition algorithms, some approaches (E. U. Acar et al., 2002; H. Choset, E. Acar, et al., 2000) works with the concept of Morse function to indicate the location of cell boundaries. We show how does the boustrophedon decomposition proposed in Choset et al. work in Figure ???. Grid decomposition is another way of solving the coverage in the literature (Gabriely and Rimon, 2002; Shnaps and Rimon, 2016; Wei and Isler, 2018; Zelinsky et al., 1993) where the space is divided into equally sized cells. Other approaches are based of graphs (Cheng et al., 2019) or derive an optimal coverage (Huang, 2001; T.-K. Lee et al., 2011; Y. Li et al., 2011; Wei and Isler, 2018; Xu et al., 2011). The choice of approach depends on the practical application (Wei and Isler, 2018). The optimal coverage approaches are often a variation of known studies but with a cost that has to be optimized (Galceran and Carreras, 2013). Our work fits into these latter class of approaches. In the remainder of this section, we discuss two surveys that deal with coverage planning and further detail relevant studies on optimal coverage. We further detail approaches for CPP with aerial robots in detail in Section 3.4.1 and discuss how our work fits into the context of the available literature.

Choset propose a survey (H. Choset, 2001) of studies on coverage for robotics specifically rather than generic motion planning. The survey classifies the studies according to the decomposition algorithm;

the classification includes heuristic, and cellular decomposition based (these are approximate, partial-approximate, or exact cellular decompositions). Choset report that many methods for coverage planning with some guarantee in terms of either optimality or completeness are based on cellular decomposition—a geometric structure to represent the robots' free space. The methods decompose the free space in sub-regions, which are easy to cover (Galceran and Carreras, 2013). It is then enough to visit each one of these sub-regions (Galceran and Carreras, 2013). Grid based methods in Galceran and Carreras's survey that we discuss in the following paragraph correspond to approximate cellular decomposition methods.

More recently, Galceran and Carreras propose a survey (Galceran and Carreras, 2013) of the different approaches for coverage path planning. The survey classifies the algorithms among the others in online and offline classes where the former rely on stationary information under a known environment and the latter on sensor measurements to sweep the space (Galceran and Carreras, 2013). Notably, Galceran and Carreras report that most coverage planning algorithms decompose the space in sub-regions called cells to achieve coverage. The survey is extensive in terms of reviewed literature; it compromise studies focusing on cellular decomposition, cellular decomposition base on critical points of Morse functions (the latter can deal with generalized obstacles), graph (such as roads and streets networks), and grid algorithms. The work further surveys approaches based on detection of natural landmarks, approaches for robot with contact sensors, and operating in rectilinear environments; approaches for 3D environments, optimal coverage, for multiple robots, and based on reduction of localization error.

### 3.3.2 Optimal coverage

Huang analyzes an optimal coverage methodology based on the cellular decomposition into subregion. The study (Huang, 2001) emphasizes the cost of performing a turn and seek for a boustrophedon-like motion—Huang utilize round turns similarly to the intuitive plan in Figure 2.6—that minimizes the number of turns. To this end, Huang minimizes the sum of sub-region altitudes—a metrics related to the sweep direction of a sub-region. We illustrate the principle in Figure ??, where one sweeping direction produced a considerably different number of turns opposed to the other. Huang proposed the methodology for both convex and non-convex shapes and propose a dynamic programming to find the sweep direction in the optimal coverage. The approach performs better to other approaches by considering possible different sweep direction for different sub-regions. The study is insightful in terms of analyzing the coverage optimality of different direction in a boustrophedon-like motion. We similarly try to optimize the turns in our dynamic planning.

Arkin et al. have focused (E. M. Arkin, Bender, et al., 2001, 2005) on optimal coverage and have similarly to Huang considered the length of the tour along the number of turns. Both Arkin et al. and Huang indeed remark that in many routing problems, the cost is dominated by turns where the robot might have to slow (E. M. Arkin, Bender, et al., 2001). Arkin et al. studies are insightful in terms of algorithmic rigour. They indeed prove that coverage planning with turn costs in NP-complete even with objective being merely minimizing the turns and propose various approximation algorithms to compute nearly optimal covering tours. Nevertheless, the two studies and the study proposed by Huang are inconclusive in terms of nonholonomic robot constraints: they do not consider aspects such as the radius of the turn for the optimal coverage. They also do not consider the eventuality of replanning in case external interferences affect the feasibility of the original plan. The latter scenario can happen in the eventuality of an aerial robot suffering a sudden battery drop while on a given optimal tour.

Shnaps and Rimon propose a solution to this latter problem and focus to robotics scenarios explicitly. In the study (Shnaps and Rimon, 2016), a robot has to cover an unknown environment with a strict battery

constraint. Starting from a given point, the robot equipped with position and obstacles sensors navigates the environment and eventually covers the entire space. In a battery discharge event, the robot returns to the starting point to recharge the battery. Shnaps and Rimon propose battery powered coverage algorithm for the task and model the energy cost with the path length. The proposed algorithm divides the space to cover into equally sized cells in a grid. Although insightful in terms of coverage planning for battery powered robots, the approach does not account for aerial robots. Indeed in this latter class the robots would require to land to recharge or replace the battery. Wei and Isler consider also the eventuality of strict energy constraints for mobile robots and revisit Shnaps and Rimon's approach. In the study (Wei and Isler, 2018), they propose an algorithm for robots restricted to axis-parallel motion generalized to arbitrary polygons. Alike in Shnaps and Rimon's approach (Shnaps and Rimon, 2016), they divide the space into equally sized cells in a grid. The approach is tested on aerial robots, but is limited to rotary-wing crafts and generally unsuitable for nonholonomic robot constraints. In both Shnaps and Rimon's and Wei and Isler's approaches, the energy optimality is considered within CPP rather than and intergrated dynamic planning and scheduling approach in our work.

## 3.4 Planning for Autonomous Aerial Robots

Many other studies for energy efficiency of aerial robots limit to energy optimal motion planning (Kreciglowa et al., 2017; Morbidi et al., 2016; X. Wang et al., 2017). They do not consider coverage planning nor considers distrubances. Kreciglowa et al. focus on the best trajectory between two howevering configurations in terms of energy efficiency (Kreciglowa et al., 2017). Morbidi et al. generates energy optimal paths solving optimal control problems (OCPs) to obtain the angular accelerations of four electrical motors of a quadrotor rotary-wing aerial robot (Morbidi et al., 2016). Wang et al. propose a study (X. Wang et al., 2017) of motion planning applied to fixed-wing aerial robot. The approach pass through a set of waypoints by sattisfying a given constraint on curvature.

Popović et al. propose an interseting study (Popović et al., 2017) for planning and subsequent replanning to satisfy dynamic constraints. The study addresses the environment disturbances and sensors uncertainty using a high-dependent noise model and accounts for a limited time bidget. Popović et al. plan path online using a combination of evolutionary optimization and global viewpoint selection and validates the approach using a precision agriculture scenario of detecting weeds. Although the study has similarities with our scenario, it does not account for different aerial robots, nor perfom a dynamic energy replanning (of both the path and computations) in function of battery state. Furthermore, the scenario under analysis does not require a complete coverage opposed making it unsuitable for some applications we consider such as hazard detection. Hayat et al. propose an approach (Hayat et al., 2017) that is similarly based on an evolutionary optimization in terms of multiple aerial robots planning of tasks and paths (the notion of task refers a specific action to be performed) for a search and rescue scenario. The approach share same limitations with Popović et al.

### 3.4.1 Aerial coverage path planning

In the context of aerial robots, the survey (Galceran and Carreras, 2013) proposed Galceran and Carreras that we discussed in Section 3.3 focus on optimal coverage (Xu et al., 2011) and multi-robot coverage (Ahmadzadeh et al., 2008; Araújo et al., 2013; Barrientos et al., 2011; Maza and Ollero, 2007). Our work come into the intersection of optimal coverage and coverage performed using aerial robots. Indeed in our coverage planning we dynamically refine a plan to achieve optimal behavior energy-wise.

Cabreira et al. propose a survey (Cabreira, Brisolara, et al., 2019) that covers CPP exclusively for aerial robots. The study classifies the algorithms using the classification introduced by Choset (H. Choset, 2001) from Section 3.3 of the cellular decomposition technique employed. Within the same section, Galceran and Carreras (Galceran and Carreras, 2013)—that also employed the classification of the cellular decomposition technique—share with this survey the classification regarding the approach for coverage planning that can be either online or offline. The survey further focus on the shape of the coverage area and reports the performance metrics such as the path length, coverage time, and number of turning maneuvers, among the others. The survey focuses on single and cooperative strategies for exact cellular decomposition, and on strategies based on full and partial information from approximate cellular decomposition. Markably, they survey studies based on genetic algorithms and ant colony optimization, and focus on different covering strategies including Zamboni similar to the fixed-wing plan in Figure 2.7. Araújo et al. also analize covering strategies (Araújo et al., 2013) for a given cell of interest. They describe the boustrophedon (that appears under the name “lawnmower”) and Zamboni motion discussed in this work and additional spiral, spiral-like, dubins path, modified boustrophedon and Zamboni.

While CPP under uncertainty for aerial robots appears in Cabreira et al.’s survey, there are two surveys (Dadkhah and Mettler, 2012; Goerzen et al., 2010) with Mettler that review approaches dealing with uncertainty in general terms of aerial robotos motion planning. The former survey (Goerzen et al., 2010) emphasize a classification based on differential constraints, and groups the motion planning algorithm to these with and without differential dynamics. The survey observes a lack in approaches that deal with uncertainty; indeed, the latter survey (Dadkhah and Mettler, 2012) analyze such approaches specifically. The survey groups the motion planning approaches by the class of uncertainty they address. For instance, in case of uncertainty in vehicles’ dynamics, the survey propose studies based on optimal control and artificial intelligence, and in case of environment knowledge uncertainty, studies based on mapping, due to atmospheric conditions, or sensors noise.

Nam et al. propose an approach (Nam et al., 2016) for CPP for aerial robots, that generates the covering tour offline flight. The approach use a grid decomposition method, and the grids are visited using a wavefront algorithm i.e., a specialized version of Dijkstra’s algorithm that optimizes the number of stages to reach the goal (LaValle, 2006). Using the wavefront algorithm they generate the optimal path between given points in space but do not focus further on optimal criteria, indeed the practical analysis shows the result not being optimized for e.g., number of turns. Furthermore the approach focus on rotary-wing UAVs and the planning happens prior to the flight, it does not account for energy (motion nor computations) explicitly, nor deal with the eventuality of replanning in the eventuality an unexpected event occurs.

Sadat et al. propose an interesting approach (Sadat et al., 2014) for non uniformly shaped areas distributed into clusters. The approach performs adaptive coverage depending on the distributions of the regions of interest in the space. Sadat et al. use coverage trees for the purpose (a structure where the child nodes cover exactly the same area as the parents but with higher resolution), and propose different strategies to visit the tree (breadth-first, depth-first, and shortcut heuristic). Although interesting in terms of defining the covering area in a sparse way, the approach does not account for the aerial robot’s battery nor discuss other aerial robots than the rotary-wings.

### 3.4.2 Optimal aerial coverage

Di Franco and Buttazzo propose an energy-aware CPP for aerial robots. The study (Di Franco and Buttazzo, 2015) focus on energy and other requirements, such as coverage and resolution. The model is

generic for a given drone and outputs the energy consumption as a function of velocity and operating conditions by means of an interpolating curve of the power measurements. In particular, for future energy predictions Di Franco and Buttazzo derive an energy model from real measurements flying the drone in several scenarios (during maximum acceleration and deceleration, horizontal flight, climbing, descending, hovering, and turns). Thus the study considers different analytical expressions derived from the interpolations for the scenarios. The study considers a search area that forms a polygon surveyed with the boustrophedon decomposition similarly to [Figure 2.6](#) but with sharp turns. Di France and Buttazzo consider the quality of the coverage by e.g., varying the distance between the survey lines in case the total energy derived from the model is lower than the available energy in an extension ([Di Franco and Buttazzo, 2016](#)) to the original study ([Di Franco and Buttazzo, 2015](#)), however, they do not plan this aspect in flight, nor focus on other aspects of the aerial robot flying (such as the quality of the computations being executed). Moreover, the energy model is plan specific; indeed different paths have different analytical expression for the future energy opposed to our model in [Section 4.4](#) that is generic once trained with enough measurements for a given plan variation. The study is nevertheless useful in terms of defining the energy cost of a given coverage, and insights into how the variations in the survey quality affects the power consumption. The study focuses on IRIS rotary wing aerial robot (it has four 850 Kv motors), a GoPro camera mounted on a Gimbal stabilizer, and a PX4 flight controller. The systems are powered with a 3S 11 volts and 5.5 amperes per hour lithium polymer battery (LiPo) battery. The aerial robot is not equipped with a mobile computing hardware for computations and the study does not consider other classes of aerial robots.

Concerning other related approaches for aerial coverage path planning, Li et al. propose a study ([Y. Li et al., 2011](#)) based on enhanced cellular decomposition method. Li et al. plan the coverage in a polygon area and derive a covering methodology that minimizes the number of turns. The turns, already considered in the generic CPP by Arkin et al. and Huang ([E. M. Arkin, Bender, et al., 2001, 2005; Huang, 2001](#)), are here further showed less efficient from energy, duration, and tour length points of view. For complex polygons, Li et al. propose a convex decomposition algorithm for minimum width sum based on the greedy recursive method. To connect the decomposed sub-regions, the authors propose a minimum traversal algorithm of weighted undirected graph. The approach is complete in terms of algorithmic analysis. Li et al. propose the algorithms along complexity analysis and simulate the coverage on polygons of various shapes. They show their algorithms being optimal in terms of turns, nevertheless, they do not consider further different requirements for different aerial robots. Indeed a fixed-wing aerial robot has a greater turning radius compared to its rotary-wing counterparts. Moreover, Li et al. plan the coverage offline; they do not consider unexpected occurrences derived from robot's and environment's uncertainty such as sudden battery discharge, wind gusts, and other atmospheric condition, whereas we take these aspects into account in our dynamic planning. They further consider only path planning, opposed to planning the path along the computations energy-wise while optimizing the battery usage.

Mannadiar and Rekleitis and Xu et al. propose studies ([Mannadiar and Rekleitis, 2010; Xu et al., 2011, 2014](#)) on near to optimal complete coverage computed using a sequence of waypoints. The algorithm is near optimal rather than optimal because waypoint control has less maneuverability against velocity control and cannot guarantee optimality in terms of the tour length ([Xu et al., 2014](#)). The coverage algorithm ([Mannadiar and Rekleitis, 2010](#)) was first presented by Mannadiar and Rekleitis and extended to non-holonomic robots ([Xu et al., 2011, 2014](#)) by Xu et al. The algorithm is based on cellular decomposition of a known environment with an arbitrary number of obstacles. The algorithm feeds the decomposed cells into a Reeb graph—an encoding used to compute a cyclic path where critical points

are vertices and cells are edges of the graph (Fomenko and Kunii, 1997)–and solves the Chinese postman problem (Eiselt and Laporte, 2000) on the graph for the coverage order. The resulting path ensures that no cells is going to traversed twice with the robot returning to the starting point. The approach is interesting in terms of analysis for different aerial robots. Indeed Xu et al. analyze possible planning strategies for fixed-wing aerial robots and affirm that this latter class of robots lack the maneuverability needed to follow a sharp-turned path. Likewise Xu et al., we also focused on this by generating paths that, among the other classes, can be followed by a fixed-wing aerial robots. Xu et al. add additional turning segment to the path by adding curlicue orbits at corners whereas we incorporate the turning maneuver in our dynamic planning rather than embedding external segments. Moreover, the studies do not focus an energy-efficient coverage path planning, on eventual replanning in case of adverse events, nor involve power-saving scheduling.

Other approaches for the optimality of the coverage focus explicitly on energy consumption of the aerial robot. Cabreira et al. and Artemenko et al. propose studies (Artemenko et al., 2016; Cabreira, Franco, et al., 2018) in this direction, focusing on photogrammetry and localization scenarios. Cabreira et al. propose spiral coverage for limited shapes of the coverage space and alter the velocity to achieve energy saving. Artemenko et al. propose a boustrophedon motion with smoothed turns using Bézier curves and analyze other motions. However, both Cabreira and Artemenko et al.’s studies focus on a peculiar scenario rather than on generic coverage. Another interesting study provides an efficient coverage using different motion patterns for specific locations such as urban areas (Dille and Singh, 2013) but does not derive a generalized methodology. Others deal with optimal coverage deriving approaches (Bouzid et al., 2017; Valente et al., 2013) for rotary-wing aerial robot using interesting novel algorithms to find the optimal tour in a graph. In particular Valente et al. use harmony search—a meta-heuristic algorithm based on musical harmony (Geem, 2009)—and Bouzid et al. use genetic algorithm. Generally all the studies in this paragraph focus on rotary-wing aerial robots. Although interesting in terms of analyzing the energy efficiency, the studies do not propose replanning, nor power-saving scheduling.

### 3.4.3 Flight controllers

## 3.5 Planning Computations with Motion

Sudhakar et al. examine the trade-off between motion and computation energy for mobile robots in their recent study (Sudhakar et al., 2020), focusing on robots with a comparable energy consumption for what concerns motion and computations. The robot moves on a path with a given length and velocity and expends some motion energy. Computations-wise, the robot computes a specific number of nodes and expends some computations energy. Sundhakar et al. derive first an analytical expression for energy prediction which incorporates the path’s length and velocity and the number of computations’ nodes. The approach they propose consists an algorithm for anytime planning—a planning approach that identifies an initial feasible plan then refined towards optimal over time (Karaman, Walter, et al., 2011). The algorithm eventually stops the refinements when it estimates computations energy exceeding the potential savings in terms of motion energy (Sudhakar et al., 2020). To derive a path for the robot’s motion, the algorithm uses a Bayes estimation on the edges of a graph in a sampling-based path planning algorithm—probabilistic RoadMaps (PRM\*) widely used in practice (Karaman and Frazzoli, 2011; LaValle, 2006). Notably, Sundhakar et al. emphasize the importance of considering both the motion and computations for robots energy-optimal planning; we share similar findings except for the study’s prime in analysis of trade-offs between motion and computations energy. By a closer inspection of the

scientific literature, there are other studies that have focused in this direction. Apart our contribution in this direction, Mei et al. and Sadrpour et al. propose studies that deal with motion and computations energy of mobile robots (Mei, Lu, Y. C. Hu, et al., 2005; Mei, Lu, Y. C. Hu, et al., 2006; Sadrpour et al., 2013a,b).

Mei et al., that we already analyzed for their contribution to motion planning in Section 3.3, have proposed a study (Mei, Lu, Y. C. Hu, et al., 2005) analyzing the both motion and computations energy. The study differentiates the microcontroller and embedded computer the mobile robot carries for a more flexible robot's design. To this end, Mei et al. derive an energy model from empirical data and importantly, show that the motion accounts for less than 50% of the total power consumption. Motivated by this finding that on Pioneer 3DX ActivMedia—different version of Pioneer mobile robots from Adept MobileRobots were a popular at the time of publication within the research community (Anguelov et al., 2004; Erickson, 2003; Lemay et al., 2004)—they propose real time scheduling and dynamic power management to reduce the power consumption. The latter dynamically adjusts power states (by e.g., DVS, DFS, and peripherals selection) of components without compromising overall performance (Mei, Lu, Y. C. Hu, et al., 2005), and the former schedule computations energy-wise. The study is of particular interest as they quantify the computations contribution to the overall energy expenditure of mobile robots. We further extend the study; it was indeed one of the starting points of our analysis although it does not implement the proposed techniques practically, nor focus on planning within battery constraints; a research gap we are filling with our dynamic planning. Although Mei et al. have extended their analysis in future instances (Mei, Lu, Y. C. Hu, et al., 2005a,b; Mei, Lu, Y. C. Hu, et al., 2006) to CPP using a multiple robots with both time and energy constraints and to the problem of repeated coverage (Mei, Lu, C. Lee, et al., 2006), they have not implemented computations scheduling nor focus on dynamic replanning of the coverage with sudden battery discharge; an aspect that is of particular interest for aerial robots. (Brateman et al., 2006; W. Zhang and J. Hu, 2007)

Sadrpour et al., 2013a,b

(Ondráška et al., 2015) (Lahijanian et al., 2018)

More complex planning that similarly focus on the concept of the plan being a set of tasks and a path, all focus on the trajectory (Mei, Lu, Y. C. Hu, et al., 2005; Mei, Lu, Y. C. Hu, et al., 2006) and apply to a small number of robots Sadrpour et al., 2013a,b.

Our approach shares the same principle of differentiating the microcontroller from the companion computer with (Mei, Lu, Y. C. Hu, et al., 2004, 2005). The controller acts on the actuators and reads the sensors, while the companion computer (can be found with different names in literature, such as secondary or embedded computer), performs computationally heavy operations. A similar approach for mobile robots is presented by (Dressler and Fuchs, 2005). However, both contributions neither elaborate further on computational elements of a heterogeneous platform, such as GPU, nor focus on different robots except the one under analysis.

Our approach towards energy modeling shares a similar principle as the one presented by (Sadrpour et al., 2013a,b) for Unmanned Ground Vehicles or UGVs. They propose a linear regression-based technique in the absence of real measurements and a Bayesian networks-based one in their presence. We used a simplified approximation technique to limit the number of computations needed while focusing rather on an accurate battery prediction.

### 3.6 Summary

## Chapter 4

# Energy Models

### 4.1 Energy Model of the Computations

Numerous new challenges have been introduced in embedded systems through evolution from small and predictable to large and complex architectures featuring different computational units. Limited energy availability, security considerations, and time requirements are among the most common challenges and significantly impact the level of autonomy of modern heterogeneous systems. These systems use many-core architectures, where a CPU executes along a general-purpose GPU or GPGPU with energy-efficient small cores. A parallel CPU-GPU execution is a core aspect to achieve the best possible energy efficiency and speed-up (Woo and H.-H. S. Lee, 2008).

In this paper, we focus on limited energy availability for mobile heterogeneous devices powered by a battery and present a coarse-grained computation-oriented energy modeling approach.

The model *describes energy usage as a function of component configuration* and is based on physical measurements of power consumption of the on-board computing elements.

The term *computing* is used here to denote the energy consumed by the software components of a complex embedded system. Estimates indicate that more than 50% of power consumption of complex devices featuring mechanical and computational units can occur due to computational operations, with the motion accounting for the remaining (Mei, Lu, Y. C. Hu, et al., 2004, 2005). Energy efficiency concerns are not limited to battery-powered devices, but also to the high-end systems (Mudge, 2001), and thus it is becoming more important for computer architects as power consumption is growing with the introduction of new processors.

Complex software applications are often composed of many components interacting concurrently to achieve a specific functionality. Our approach aims to predict the energy consumption of a provided set of software components, in a specific configuration, executed according to a given scheduling policy. Statistical methods are used to derive a predictive model allowing prediction of the components' total power consumption as scheduling and configuration parameters are varied. High-level modeling of using a battery as energy-source is used to model the energy that would be drained from the system during computation. The energy model is segmented into two layers: the measurement layer, which describes energy consumption as a function of time, and the predictive layer, which describes energy consumption as a function of component configuration and scheduling. The model generation process starts from the developer, who specifies the configuration space within which software components can

run on a given system. A profiling process collects power samples for every component configuration (measurement layer). A model that maps configuration parameters to an energy metric, such as overall energy or average power, is generated from the data, showing the energy evolution for every possible configuration (predictive layer).

#### 4.1.1 Computational energy of the aerial robot

We use software for drones as a case study for energy efficiency. Drones (known also as aerial robots, Unmanned Aerial Vehicles, or UAVs) are often composed of two computational units. A controller that manages real-time control of the physical aspects of the drone, and a companion computer that handles heavy computations. The latter is often a heterogeneous parallel system. A coarse-grained model of these systems can be used for energy-aware planning and optimization from a computational point of view. Moreover, energy constraints are of particular interest for drones, since their level of autonomy is directly proportional to the power-to-compute (Fabiani et al., 2007). Unlike their grounded counterparts, drones must trade-off size, weight, and power, resulting in strict limits to their energy source that may not accommodate their computational needs. Operating from a limited energy source, typically a lithium-ion battery, can significantly reduce the amount of autonomy that the drone can carry on. One of the reasons why this happens is the high energy demand required by complex parallel algorithms used in several use cases, from computer vision to data processing. To this extent, many tasks in aerial robotics are still not fully autonomous. Advanced operations that require a significant level of autonomy, such as path planning, obstacle avoidance, environment mapping, and object detection, often involve human interaction. Thus there is still little difference between flying robots and their manned counterparts, except that the pilot operates from a ground station rather than onboard (Siciliano and Khatib, 2016).

As a concrete example, we present the drone use case that recognize an object while performing some computationally heavy operations. The use case is composed of two components, object detection algorithm (`darknet-gpu`) that recognize a pattern using a neural network, and matrix exponentiation (`matrix-gpu`) that simulates heavy operations with varying scheduling patterns using sleep of different durations between consecutive operations. Both the components execute mostly on GPU. In a configuration file, the developer specifies these parameters per component:

- a) for `darknet-gpu` a frame-per-seconds rate [5.8, 32] from the lowest acceptable, to the highest achievable, and
- b) for `matrix-gpu` two sets of rates, the matrix size [256, 4096] from smallest to largest, and sleep interval [0, 10] from no sleep to 10 seconds.

A profiling process generates models that map time to power, one per combination in the configuration file. Based on this a high-level model is generated which combines component parameters to energy consumption. The energy consumption is estimated for any parameter combinations not profiled. This information is useful to define a proper trade-off between parameters and decide eventually, what configuration has to be used to optimize energy consumption. The information about the battery state, included in the analysis, enables the developer to select a specific runtime configuration (for instance, one that will allow completing the mission without recharging the battery by just adjusting the combinations of components and their parameters).

In our experiments, the resulting model shows an almost linear behavior for the `darknet-gpu` component, highlighting the energy behavior for any configuration in the interval [5.8, 32]. The `matrix-gpu`

model shows the energy evolution with different scheduling options and addresses the impact of different scheduling to the battery depletion. Results for both components are presented and further discussed in Section ??.

With this work we have:

1. designed a computation-oriented energy modeling approach for heterogeneous platforms,
2. evaluated the outcomes of the model on several benchmarks and devices,
3. assessed the model's validity against external measurements and a fine-grained approach, and
4. developed a profiling tool for computation-oriented energy modeling.

The tool, named `powprofiler`, is written in C++ and distributed under MIT license.<sup>1</sup> The tool was used to perform all of the experiments reported in this paper and is designed to be used, among others, in mobile robotics scenarios. It can profile a set of components being executed in a number of possible configurations and from this, build an energy model. The model allows the system under analysis to define an appropriate tradeoff between consumed energy and computations performed. This information can be used to increase energy efficiency, often linked to the level of autonomy in many modern scenarios, and meet the power requirements. For example, a drone can dynamically adjust autonomous detection capabilities to fit the current battery state of charge (referred to in this paper as SoC). Similarly, an autonomous vehicle can increase the amount of computation only when the collision detection system is required, and a mobile robot can automatically schedule tasks to compute in an energy-aware fashion. In these examples, awareness of precise computational energy cost can potentially lead to significant energy savings. Key to the approach is flexibility in terms of easy support for different heterogeneous platforms and extensibility to other classes of systems outside the mobile robotics domain.

#### 4.1.2 Energy modeling for heterogeneous hardware

In this paper, we aim to provide a tool for automatic generation of hardware-specific energy models of a given application. The energy model is generated through a profiling process which collects several power samples and builds an energy abstraction upon them. Computational energy is addressed by mapping a component configuration to an energy metric, such as average power or overall energy. Our approach includes several on-board computing elements, such as CPU and GPU, and analyzes their role in the tradeoff related power decisions.

Figure 4.1 shows an overview of our approach. For a specific application on the system under study, the developer describes how components behave in a configuration file. For each component, any parameter range or value can be specified. By varying the parameters and scheduling policy, the tool generates  $n$  combinations of components called configurations  $\mathcal{D} = \{d_1, d_2, \dots, d_n\}$ . Once the set  $\mathcal{D}$  is generated, the profiling process starts by collecting a set of samples and by generating a layer 1 model for every configuration  $d_k$  (with  $1 \leq k \leq n$ ). The layer 1 model maps a time interval  $t$  to a power measure  $f(t)$  and estimates the power-to-compute value for a given component. Later, the model is integrated with battery state evolution and quantified in the amount of SoC left in the battery. Finally, both  $f(t)$  and SoC are used to generate a layer 2 model, that maps a set of configurations  $\mathcal{D}$  to the energy metric (i.e., average power consumption or overall energy usage) and SoC  $g(\mathcal{D})$ . This information can be used to select the best configuration and define a better scheduling policy to optimize the average computational energy.

---

<sup>1</sup><https://bitbucket.org/adamseew/powprofiler>




Fig. 4.1. Overview of energy modeling for heterogeneous hardware.

The modeling approach is tested across four different platforms, ODROID XU3, NVIDIA TK1, TX2, and Nano (see Section ?? for details), and a selection of benchmark components is used. Each component has a set of configuration parameters varied inside defined boundaries, that represent the acceptable rate of quality of service or QoS. We use the following benchmark components: a random matrix of a predefined size that is multiplied by another or exponentiated by a given exponent on CPU (`matrix-cpu`) or GPU (`matrix-gpu`). A computer vision component built upon the darknet (Redmon, 2013–2016; Redmon and Farhadi, 2017) implementation of the YOLO library (Redmon, Divvala, et al., 2016), that uses a deep neural network to detect an object from a video stream on CPU (`darknet-cpu`) or GPU (`darknet-gpu`), and NVIDIA custom-made benchmarks, modified so they can be iterated several times over a time interval, that perform matrix multiplication (`nvidia-matrix`) and quicksort (`nvidia-quicks`) of a given size on GPU.

#### 4.1.3 Measurement layer

The measurement layer describes an energy sample for a given configuration and scheduling of a component executed on specific hardware as a function of time. It provides average power or overall energy over a time interval for every computational unit that allows power measurement.

The developer provides for every application a number of components in the configuration file along with their parameters. An application in this layer is structured as several configured components that execute in parallel according to a specific scheduling policy. First, immediate power consumption is measured. This information is used to model the power into the power-to-compute and battery drain. An *application specification*, described later in this section, is used to define all the possible configurations of an application in the configuration file. The power is measured throughout a time interval set by the developer. Multiple metrics can be captured at this level and sampled at a fixed rate specified in the application specification, including CPU, GPU, and total power. Other metrics, as the system's load and sensors' evolution, can be added by extending the approach. Based on the information obtained at this layer, the energy that the computation would draw from a battery can be estimated using the

*battery model*, also described later in this section. As a concrete example, Figure ?? shows the total energy usage as a function of time for CPU and GPU of the NVIDIA TX2 board executing the `darknet-gpu` component in four different QoS configurations.

#### 4.1.4 Application specification

The application specification is used to define all the computations to run for a specific energy model. It depends on the schedule that is used when performing measurements, in the sense that scheduling policies will be specific to the kind of scheduling supported by this scheduler. Currently, only a basic application specification is supported that corresponds to the capabilities of the `powprofiler` tool described later in Subsection ?? . Support for more advanced models is considered future work. In particular, a dynamic measurement-oriented scheduler should be adopted in the future to define the optimal scheduling policy during computation.

The basic application specification is defined as follows. The choice between component implementations (if needed) is implicitly supported by requiring the developer to select the specific component implementation to use for the measurement. Components are configured by providing concrete, fixed values for all of their configuration parameters. A scheduling policy is implicitly supported by requiring each component to provide parameters that explicitly control fixed scheduling patterns in time (e.g., what rate to execute, when to execute). Components are assumed to implicitly control scheduling in space, for example by having different implementations for CPU and GPU (and hence being explicitly selected as part of the application configuration).

#### 4.1.5 Predictive layer

The predictive model is expressed in terms of the measurement layer and describes “average power over time frame” and other similar coarse-grained metrics as a function of component configuration parameters and scheduling policies.

The predictive model concerns the average power over a time frame as a function of varying application models (i.e., configuration parameters, scheduling policy, ...). The average power can be any of the outputs of the measuring layer, such as average power used by the embedded board, or average power drained from a battery. First-layer measurements are used to generate functions that map application models to energy metrics. Any aspect of the application model can be varied, as defined by the *sampling strategy* described later in this section. Varying selected aspects of the application model corresponds to changes in component configuration parameters and scheduling policies, thus making it possible to determine the average power as a function of specific variations of selected component configuration parameters and aspects of the scheduling policy. Due to the potentially large configuration space, it is critical that a model covering all relevant parameter/scheduling variations can be generated from a subset of samples. This is handled by the *approximation method*, also described later in this section.

As a concrete example, Figure 4.3 shows the total average energy usage of the TX2 board executing the `matrix-gpu` component as a function of the size and exponent parameters. Results are discussed in further detail in the context of experimental results, see Section ??.




Fig. 4.2. Average power




Fig. 4.3. Overall energy

#### 4.1.6 Hardware platforms and benchmarks

In the following section, we present hardware platforms under study, the two measuring technique to obtain power metrics, and a summary of the profiling tool. Finally, Experimental Methodology outlines our experimental approach before introducing results in the next Section.

We studied four different hardware platforms, ODROID XU<sub>3</sub>, NVIDIA Jetson TK<sub>1</sub>, TX<sub>2</sub>, and Nano that are shown in Figure ??

**ODROID XU<sub>3</sub>** Provides an ARM Cortex-A15 and -A7 CPU, 2 GBytes of LPDDR<sub>3</sub> RAM, a MALI GPU, and storage via microSD. It includes built-in sensors that enable accurate power measurements of the two CPUs, RAM, and GPU.

**NVIDIA TK<sub>1</sub>** Provides an ARM Cortex-A15 CPU, 2 GBytes of DDR<sub>3L</sub> RAM, 16 GB of non-volatile storage, and an NVIDIA Kepler GPU with 192 CUDA cores. The TK<sub>1</sub> does not provide any built-in sensor for power measurement, so an external sensor is used to measure the total power consumed.

**NVIDIA TX<sub>2</sub>** Provides an ARM Cortex-A57 CPU, 8 GBytes of LPDDR<sub>4</sub> RAM, 32 GB of non-volatile storage, and an NVIDIA Pascal GPU with 256 CUDA cores. The TX<sub>2</sub> comes with on-board power measurement functionality that can measure the power of different components, and was used in our model to gather independently the instantaneous power usage of the CPU, GPU, and the whole board.




Fig. 4.4. Remaining battery capacity




Fig. 4.5. Average power

NVIDIA Nano Provides an ARM Cortex-A57 CPU, 4 GBytes of LPDDR4 RAM, an NVIDIA Maxwell GPU with 128 CUDA cores, and storage via microSD. Similarly to the TX2, the Nano comes with on-board power measurement functionality that is able to measure the power of different components and can be used within our model to gather independently the instantaneous power usage of the CPU, GPU, and the whole board.

Platform	CPU	GPU	RAM	Memory	Board	Sensors
ODROID	A15, A7	MALI	2 GB	microSD	94x70	✓
TK1	A15	Kepler	2 GB	16 GB	125x95	-
TX2	A57	Pascal	8 GB	32 GB	170x170	✓
Nano	A57	Maxwell	4 GB	microSD	100x80	✓

Table 1. Summary of hardware platforms under analysis.

Several benchmarks (see Section ??) have been performed on the four hardware platforms under study. (Not all benchmarks components are compatible with every platform, e.g., GPU-based benchmarks are implemented in CUDA which only runs on NVIDIA platforms, limiting the set of experiments that can be performed.)




Fig. 4.6. Overall energy




Fig. 4.7. Remaining battery capacity

#### 4.1.7 Power measurements

We use two different power measurements techniques for our experiments: the current shunt and current probe. With the current shunt method, an internal circuit on the embedded board composed of a shunt resistor is used, along with a digital acquisition unit. It is the preferred approach as it can precisely sample the power consumption of specific computing elements as CPU and GPU. Such circuits are present on the ODROID XU3 and NVIDIA TX2 or Nano boards and can be sampled directly by the `powprofiler` tool described in Subection ??.

As an alternative to the current shunt method, we have also implemented the current probe method, where an external circuit measures the power on the connection to the main embedded board (i.e., the carrier board). We adopted the current probe method to measure the overall power consumption of the NVIDIA TKr. This measurement setup consists of three hardware units, henceforth referred to as nodes. The first node is the board under analysis, the second node a multimeter that performs the sampling of the power consumption at a specific sampling frequency, and the third node is an external computer that collects the data for subsequent processing by `powprofiler`. The whole setup is described in detail in our prior work (Seewald, Ebeid, et al., 2019). Data and metrics are stored for use with `powprofiler`, essentially allowing an arbitrary power measurement technique for the system under analysis. This means that a layer 2 model can be generated from the data with no distinction of what type of measuring device was used to obtain the layer 1 model.

All experiments reported in this section are performed using the standard performance governor present in each of the systems under observation. In particular, dynamic effects such as DVFS have




Fig. 4.8. ODROID XU3




Fig. 4.9. NVIDIA Jetson TK1

not been disabled. Our experiments have not revealed any effects on performance due to, e.g., ambient temperature or the temperature of the embedded systems increasing.

#### 4.1.8 The `powprofiler` tool

The `powprofiler` tool implements all the features described in this paper and is designed to be useable for heterogeneous parallel embedded systems. The tool supports all the platforms described in Section ???. It is designed for extensibility and can, in principle, support any Linux-based embedded device that provides power measurement metrics. Concretely, to support a new embedded device, a subclass defining the device-specific features can be derived from a virtual class, and only requires the implementation of a function that returns the current measurements in the form of a weighted vector where every element can represent a different metric. In a first iteration, the tool profiles a set of configurations of a component and builds a layer 1 model as described in Section ???. Once `powprofiler` obtains power profiles




Fig. 4.10. NVIDIA Jetson TX2



Fig. 4.11. NVIDIA Jetson Nano

and other metrics that are considered useful for the purpose of energy modeling, it builds a predictive model as described in [Section ??](#). The tool relies on `gnuplot` utility to visualize energy evolution if the configuration search space allows it. Automatically generated output includes CSV files containing measured data as well as the 2D- and 3D-plots shown in this paper.

The tool measures the instantaneous energy consumption of a subset of possible computation parameters within the computation constraint sets and builds an energy model: a linear interpolation, one per computation.

The computations are implemented by software components, e.g., ROS nodes in a ROS-based system (see [Subsection 4.1.10](#)). The user implements these nodes such that they change the computational load according to node-specific ROS parameters—the computation parameters. In a generic software component system, the user maps the computational load to the arguments ([Seewald, Schultz, Roeder, et al., 2019](#)).

Component \ Platform	Odroid-XU3	NVIDIA		
		TK1	TX2	Nano
CPU	A15+A7	A15	A57	A57
GPU	MALI	Kepler	Pascal	Maxwell
matrix-cpu	✓	✓	✓	✓
matrix-gpu	-	✓	✓	✓
darknet-cpu	(✓)	(✓)	✓	(✓)
darknet-gpu	-	-	✓	(✓)
nvidia-matrix	-	(✓)	✓	(✓)
nvidia-quicks	-	(✓)	✓	(✓)

Table 2. Benchmark components: platforms and modeling approach. ✓: supported and included in this paper, (✓): supported but not included in this paper, -: not supported.

We note that while the path can differ for each stage, the tasks remain the same. However, the user can inhibit or enable a computation varying its computation constraint set.

Let us define the output from `powprofiler` formally.

**Definition 4.1.1: Instantaneous computational energy**

$g : \mathbb{Z}_{\geq 0} \rightarrow \mathbb{R}_{\geq 0}$  as the instantaneous computational energy consumption value obtained using the `powprofiler` tool.

### 4.1.9 Energy-aware design of algorithms

### 4.1.10 ROS integration

### 4.1.11 Experimental evaluation

The power modeling experiments described in this paper are, unless otherwise mentioned, done using `powprofiler` tool. The tool uses two temporal schemes to profile data. A component can be profiled for a specific amount of time with the first, or until it terminates its computation with the second. The second scheme is used for all the components that end in a specific amount of time, i.e., matrix multiplication. The first for components that run continuously, i.e., an image detection algorithm operating on an image stream. For both, the longer the profiling, the better the accuracy.

Ideally, any component combination can be profiled by specifying possible sets of parameters in the configuration file. Each entry corresponds to a component and defines how its execution is varied as described in application specification described in Subsection 4.1.4. In summary, a layer 1 model is evaluated and stored for every possible combination. The layer 1 model is then integrated with the battery model. Data containing energy consumption, battery drain, and other information as system load, are evaluated into the layer 2 model. This model builds an  $n$ -dimensional function and provides energy consumption data for every possible combination. The missing data are integrated using estimation with the approximation technique describe in Subsection ???. The  $n$ -dimensional space is derived by the use of the battery model to map each value with a weight describing the SoC.

As an example of energy modeling, we implemented a combination of three different parameters and generated a surface that shows approximately where the minimum power consumption is expected. Figure 4.3 and Figure 4.7 show how the output of the predictive model includes, but is not limited to,

overall energy in Figure 4.3 and Figure 4.6 and average power consumption in Figure 4.2 and Figure 4.5 for all the combinations.

## 4.2 Battery Model

### 4.2.1 Batteries for aerial robots

### 4.2.2 Derivation of differential battery model

The battery model is a mathematical abstraction that models draining energy from a battery used to power the mobile robot. It was derived from the state-space problem representation of the empirical battery model through an equivalent electrical circuit, presented by Hasan et al. Hasan et al., 2018. The battery evolution model can be represented in this way using an ordinary differential equation that is a function of the power drained from the system, and represents the SoC of the battery at a given instant

$$\frac{d}{dt} \text{SoC}(t) = -\frac{I_{\text{int}}(t)}{Q_c}, \quad (4.1)$$

$$I_{\text{int}}(t) = \frac{U_{\text{int}} - \sqrt{U_{\text{int}}^2 - 4 \cdot R_{\text{int}} \cdot U_{\text{sta}} \cdot I_{\text{load}}(t)}}{2 \cdot R_{\text{int}}}, \quad (4.2)$$

where  $Q_c$  is the constant nominal capacity,  $U_{\text{int}}$  is the internal battery voltage,  $I_{\text{int}}$  is the current load that depends on the power requirements,  $R_{\text{int}}$  is the internal resistance of the battery,  $U_{\text{ext}}$  is the external battery voltage,  $U_{\text{sta}}$  is the stabilized voltage (a fixed value determined by the load of the system), and  $I_{\text{load}}$  is the current required by the load. The constants are chosen to describe a small drone battery. The external battery voltage  $U_{\text{ext}}$  can be also expressed as follows:

$$U_{\text{ext}}(t) = U_{\text{int}} - R_{\text{int}} \cdot I_{\text{int}}(t) \quad (4.3)$$

The approach allows modeling the computational system not only in terms of the overall power consumption but also in terms of the actual amount of power drained from the battery. This is especially important with a mobile robot dependent on a limited and time-dependent energy supply, running computationally heavy parallel algorithms. Critically, although this mathematical model is a simple abstraction, it models how a stable power consumption over time can induce less drain from the battery compared to using the same amount of energy distributed in a number of spikes. The battery model allows this information to be determined for specific usage scenarios and thus provides a useful way to determine what configuration corresponds to the best power usage combination for a mobile use case.

## 4.3 Energy Model of the Motion

### 4.3.1 Mechanical energy of the aerial robot

In this subsection, a regression technique to build a mechanical energy model is described. The model is specific for an Opterra drone, but an equivalent technique can be applied to any fixed-wing drone. Key to the technique is the distinction between three phases of the flight: take-off, cruise, and landing. The distinction between these three phases follows from experimental data, as we observed that different flights present similar behavior and almost identical tendencies. This means that each phase has a different altitude and overall time evolution concerning motor torque and power drain. In particular, less

variability in energy evolution is observed during the cruise and take-off. This applies when we analyze a single test flight, and when we analyze a set of flights regarding their phases. In the latter, we observed little variability in the cruise phase of different flights, as this is performed mostly by the autopilot with variability often due to wind conditions, while take-off of a fixed-wing drone usually presents a similar set of controls with little variability. Landing is observed to be the phase that presents the largest variability in the collected data, as the procedure requires specific and conditions-dependent maneuvers. Furthermore, glide slope and ground effect, specific to landing site conditions, also affect the controls sequence.

A weighted average time derived from collected data of 28 seconds, 10 minutes, and 1 minute, for respectively take-off, cruise, and landing, is assumed to model a test mission that we use in this paper. The information is used in the regression technique to map time to the current energy consumption. Regression itself consists of a phase-specific third-order Fourier series, as the data often presents a periodic behavior and tends to diverge for higher orders while not mapping precisely to the power evolution in time for lower ones. The following equation represents the power as a function of time  $t$  for each of the three phases:

$$f(t) = \sum_{n=0}^3 a_n \cos\left(\frac{nt}{\xi}\right) + b_n \sin\left(\frac{nt}{\xi}\right), \quad (4.4)$$

where  $a_n, b_n$  are the Fourier series coefficients,  $\xi$  is a characteristic time, and:

$$f(t), t, a_n, b_n, \xi \in \mathbb{R}, \quad (4.5)$$

The Mechanical energy evolution in time can be expressed through a three-dimensional vector  $\mathbf{f}$ :

$$\mathbf{f}(t) = [f_1(t) \quad f_2(t) \quad f_3(t)]^T, \quad (4.6)$$

where  $f_1(t), f_2(t), f_3(t)$  are the energy evolutions in time for take-off, cruise, and landing respectively.

The mechanical energy model from Equations (4.4–4.6), can also be expressed in a matrix form:

$$\mathbf{f}(t) = \begin{bmatrix} {}^1a_0 & {}^1b_0 & \dots & {}^1a_3 & {}^1b_3 \\ {}^2a_0 & {}^2b_0 & \dots & {}^2a_3 & {}^2b_3 \\ {}^3a_0 & {}^3b_0 & \dots & {}^3a_3 & {}^3b_3 \end{bmatrix} \begin{bmatrix} \cos \frac{0t}{\xi} \\ \sin \frac{0t}{\xi} \\ \vdots \\ \cos \frac{3t}{\xi} \\ \sin \frac{3t}{\xi} \end{bmatrix}. \quad (4.7)$$

The constants  $a_n, b_n$ , and  $\xi$ , for the regressions  $f_i(t)$  with  $i \in 1, 2, 3$  (and thus for  $\mathbf{f}(t)$ ) were found using the Levenberg-Marquardt algorithm implemented in Matlab. The above procedure, however, just accounts for one flight. A further analysis concerns the generation of power trajectories through the technique for each test flight. An interpolating curve is then built using a probabilistic approach, that simply indicates a weight for a given flight  $k$ . This can be particularly useful as some flights can be affected by other conditions such as wind, temperature, or battery state at the beginning of the mission, thus affecting the model behavior unexpectedly. Given  $k$  flights and a vector of weights  $\mathbf{w}$ , the mechanical model can be in this fashion expressed using an equivalent expression to Equation (4.5):

$$\tilde{\mathbf{f}}(t) = \begin{bmatrix} f_{1,1}(t) & f_{1,2}(t) & f_{1,3}(t) \\ \vdots & \vdots & \vdots \\ f_{k,1}(t) & f_{k,2}(t) & f_{k,3}(t) \end{bmatrix}^T \begin{bmatrix} w_1 \\ \vdots \\ w_k \end{bmatrix}, \quad (4.8)$$

where  $w_i$  is the associated weight for a specific flight  $i$ , that expresses its accuracy according to the set of all the collected flights, and:

$$\begin{aligned} \mathbf{w} &\in \mathbb{R}^k, \\ w_i &\in [0, 1], \\ w_1 + w_2 + \dots + w_k &= 1. \end{aligned} \quad (4.9)$$

Based on a simple reordering, Equations (4.7–4.9) can be also expressed:

$$\tilde{\mathbf{f}}(t) = \begin{bmatrix} {}^{1,1}a_0 & {}^{1,2}a_0 & {}^{1,3}a_0 \\ {}^{1,1}b_0 & {}^{1,2}b_0 & {}^{1,3}b_0 \\ \vdots & \vdots & \vdots \\ {}^{1,1}a_3 & {}^{1,2}a_3 & {}^{1,3}a_3 \\ {}^{1,1}b_3 & {}^{1,2}b_3 & {}^{1,3}b_3 \\ {}^{2,1}a_0 & {}^{2,2}a_0 & {}^{2,3}a_0 \\ {}^{2,1}b_0 & {}^{2,2}b_0 & {}^{2,3}b_0 \\ \vdots & \vdots & \vdots \\ {}^{k,1}a_3 & {}^{k,2}a_3 & {}^{k,3}a_3 \\ {}^{k,1}b_3 & {}^{k,2}b_3 & {}^{k,3}b_3 \end{bmatrix}^T \begin{bmatrix} w_1 \cos \frac{0t}{\xi} \\ w_1 \sin \frac{0t}{\xi} \\ \vdots \\ w_1 \cos \frac{3t}{\xi} \\ w_1 \sin \frac{3t}{\xi} \\ w_2 \cos \frac{0t}{\xi} \\ w_2 \sin \frac{0t}{\xi} \\ \vdots \\ w_k \cos \frac{3t}{\xi} \\ w_k \sin \frac{3t}{\xi} \end{bmatrix}. \quad (4.10)$$


Equation (4.10) can be used to derive all the constants for the three phases of the flight, and thus to describe the power consumption in the function of time for take-off, cruise, and landing. Table 3 outlines the constants that we obtained on the Opterra fixed-wing drone test flights of the agricultural use-case.

Table 3. Constants for the mechanical energy model

	take-off	cruise	landing
$a_0$	29.97	27.22	27.21
$a_1$	1.57	0.3737	-0.9512
$b_1$	-1.963	1.194	1.276
$a_2$	0.3876	0.6513	0.9357
$b_2$	-1.552	0.2954	0.965
$a_3$	-0.2869	0.5039	0.4913
$b_3$	-0.547	-0.2864	-0.1192
$\xi$	0.1525	0.1799	0.1296

### 4.3.2 Fourier series of empirical data

Some collected energy data from the Opterra (in Figure 1.1) adapted for precision agriculture scenario along its power spectrum back the choice of the periodic energy model. A periodic energy evolution of a fixed-wing aerial robot flying a plan and covering the polygon in Figure 1.6 (we describe the fixed-wing aerial robot plan in detail in Section 2.6) is shown in Figure 4.12a. Figure 4.12b shows its frequency spectrum (the data are uniformly sampled). The spectrum is centered at zero frequency, which peaks



**Fig. 4.12.** Empirical energy data collected flying a fixed-wing aerial robot's plan and covering the polygon in Figure 1.6. The data shows that the energy signal is periodic over time as the fixed-wing aerial robot reiterates a set of paths.

at  $4 \cdot 10^5$  and indicates the shift on the power-axis in Figure 4.12a. The power spectrum shows that the energy evolution from Figure 4.12a needs approximately three frequencies to be modeled. To obtain the spectrum in frequency space, we computed the Fourier transform.

## 4.4 Periodic Energy Model

Let us suppose the aerial robot is operating in an autonomous scenario. Such a robot is often expected to iterate a set of tasks and paths periodically (see Section 1.4). For instance, the aerial robot might be covering a polygon such as the one proposed in Section 2.6. Since the paths and tasks are periodically iterated over time, we expect the energy to evolve similarly. We will ease the assumption of the periodic evolution in practice to periodic with disturbance or aperiodic evolutions in Section 4.4.4.

We motivate the choice of a periodic energy model further with some empirical energy data of the Opterra fixed-wing aerial robot flying the agricultural scenario in Figure 4.12a and Figure 4.12b.

In the remainder of this section, we first derive a differential periodic energy model and provide a formal proof in Section 4.4.1. We enhance the model with the path and computations parameters in Section 4.4.2, to predict the energy consumption of a given configuration of parameters. We explain how we convert the parameters into actual energy consumption in Section 4.4.3, and discuss the model's behavior for aperiodic energy evolutions in Section 4.4.4.

### 4.4.1 Derivation of the differential periodic model

In the remainder of this section, we refer to the instantaneous energy consumption evolution simply as the energy signal. We model the energy using energy coefficients  $\mathbf{q} \in \mathbb{R}^m$  that characterize such energy signal. The coefficients are derived from Fourier analysis (the size of the energy coefficients vector  $m$  is related to the order of the Fourier series in Section 4.3.2) and estimated using a state estimator in Chapter 5.3. We prove a relation between the energy signal and the energy coefficients in Lemma 4.4.1.

Let us consider a periodic energy signal of period  $T$ , and a Fourier series of an arbitrary order  $r \in \mathbb{Z}_{\geq 0}$  for the purpose of modeling of the energy signal

$$h(t) = a_0/T + (2/T) \sum_{j=1}^r (a_j \cos \omega_j t + b_j \sin \omega_j t), \quad (4.11)$$

where  $h : \mathbb{R}_{\geq 0} \rightarrow \mathbb{R}$  maps time to the instantaneous energy consumption,  $\omega := 2\pi/T$  is the angular frequency, and  $a_0, a_j, b_j \in \mathbb{R}$  the Fourier series coefficients  $\forall j \in [r]_{>0}$ .

The energy signal can be modeled by [Equation \(4.11\)](#) and by the output of a linear model

$$\dot{\mathbf{q}}(t) = A\mathbf{q}(t) + B\mathbf{u}(t), \quad (4.12a)$$

$$y(t) = C\mathbf{q}(t), \quad (4.12b)$$

where  $y(t) \in \mathbb{R}$  is the instantaneous energy consumption. We discuss matrices  $A$ ,  $C$ , and  $B$  in [Equation \(4.14\)](#), [Equation \(4.16\)](#), and [Equation \(4.48\)](#) respectively.

The state  $\mathbf{q}(t)$  contains the energy coefficients

$$\mathbf{q}(t) = \begin{bmatrix} a_0(t) & a_1(t) & \beta_1(t) & \cdots & a_r(t) & \beta_r(t) \end{bmatrix}', \quad (4.13)$$

where  $\mathbf{q}(t) \in \mathbb{R}^m$  with  $m = 2r + 1$ . The state transition matrix

$$A = \begin{bmatrix} 0 & 0^{1 \times 2} & 0^{1 \times 2} & \cdots & 0^{1 \times 2} \\ 0^{2 \times 1} & A_1 & 0^{2 \times 2} & \cdots & 0^{2 \times 2} \\ 0^{2 \times 1} & 0^{2 \times 2} & A_2 & \cdots & 0^{2 \times 2} \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ 0^{2 \times 1} & 0^{2 \times 2} & 0^{2 \times 2} & \cdots & A_r \end{bmatrix}, \quad (4.14)$$

where  $A \in \mathbb{R}^{m \times m}$ . In matrix  $A$ , the top left entry is zero, the diagonal entries are  $A_1, \dots, A_r$ , the remaining entries are zeros. Matrix  $0^{i \times j}$  is a zero matrix of  $i$  rows and  $j$  columns. The submatrices  $A_1, A_2, \dots, A_r$  are defined

$$A_j := \begin{bmatrix} 0 & \omega j \\ -\omega j & 0 \end{bmatrix}, \quad (4.15)$$

$\forall j \in [r]_{>0}$ . The output matrix

$$C = (1/T) \begin{bmatrix} 1 & 1 & 0 & \cdots & 1 & 0 \end{bmatrix}, \quad (4.16)$$

where  $C \in \mathbb{R}^m$ .

The linear model in [Equation \(4.12\)](#) allows us to include the control in the model of [Equation \(4.11\)](#) as described in [Section 4.4.2](#). In the remainder we formally proof the equivalence and equality of the models in [Equation \(4.11\)](#) and [Equation \(4.12\)](#).

#### Lemma 4.4.1: Signal, output equality

Suppose control  $\mathbf{u}$  is a zero vector, matrices  $A$ ,  $C$  are described by [Equations \(4.14–4.16\)](#), and the initial guess  $\mathbf{q}_0$  is

$$\mathbf{q}_0 = \begin{bmatrix} a_0 & a_1/2 & b_1/2 & \cdots & a_r/2 & b_r/2 \end{bmatrix}'.$$

Then, the signal  $h$  in [Equation \(4.11\)](#) is equal to the output  $y$  in [Equation \(4.12\)](#).

*Proof.* The proof justifies the choice of the items of the matrices  $A$ ,  $C$  and of the initial guess  $\mathbf{q}_0$  in [Equations \(4.13–4.16\)](#). We write these elements such that the coefficients of the series  $a_0, \dots, b_r$  are the same as the coefficients of the state  $\alpha_0, \dots, \beta_r$ .

Let us re-write the Fourier series expression in [Equation \(4.11\)](#) in its complex form with the well-known Euler's formula

$$e^{it} = \cos t + i \sin t, \quad (4.17)$$

where  $i$  is the imaginary unit.

With  $t = \omega_j t$ , we find the expression for

$$\cos \omega_j t = (e^{i\omega_j t} + e^{-i\omega_j t})/2, \quad (4.18a)$$

$$\sin \omega_j t = (e^{i\omega_j t} - e^{-i\omega_j t})/(2i), \quad (4.18b)$$

by substitution of  $\sin \omega_j t$  and  $\cos \omega_j t$  respectively. This leads ([Kuo, 1967](#))

$$\begin{aligned} h(t) = a_0/T + (1/T) \sum_{j=1}^r & e^{i\omega_j t} (a_j - ib_j) + \\ & (1/T) \sum_{j=1}^r e^{-i\omega_j t} (a_j + ib_j). \end{aligned} \quad (4.19)$$

The solution at time  $t$  of the model in [Equation \(4.12\)](#) under the assumptions in the lemma (the control is a zero vector) can be expressed

$$\mathbf{q}(t) = e^{At} \mathbf{q}_0. \quad (4.20)$$

Both the solution and the system in [Equation \(4.12\)](#) are well-established expressions derived using standard textbooks ([Kuo, 1967; Ogata, 2002](#)).

To solve the matrix exponential  $e^{At}$ , we use the eigenvectors matrix decomposition method ([Moler and Van Loan, 2003](#)).

The method works on the similarity transformation

$$A = VDV^{-1}. \quad (4.21)$$

The power series definition of  $e^{At}$  implies ([Moler and Van Loan, 2003](#))

$$e^{At} = V e^{Dt} V^{-1}. \quad (4.22)$$

We consider the non-singular matrix  $V$ , whose columns are eigenvectors of  $A$

$$V := \begin{bmatrix} v_0 & v_1^0 & v_1^1 & \dots & v_r^0 & v_r^1 \end{bmatrix}. \quad (4.23)$$

We then consider the diagonal matrix of eigenvalues

$$D = \text{diag}(\lambda_0, \lambda_1^0, \lambda_1^1, \dots, \lambda_r^0, \lambda_r^1). \quad (4.24)$$

$\lambda_0$  is the eigenvalue associated to the first item of  $A$ .  $\lambda_j^0, \lambda_j^1$  are the two eigenvalues associated with the block  $A_j$ . We can write

$$AV = VD. \quad (4.25)$$

We apply the approach in terms of [Equation \(4.12\)](#) (under the assumptions made in the lemma)

$$\dot{\mathbf{q}}(t) = A\mathbf{q}(t). \quad (4.26)$$

The linear combination of the initial guess and the generic solution

$$F\mathbf{q}(0) = \gamma_0 v_0 + \sum_{k=0}^1 \sum_{j=1}^r \gamma_j v_j^k, \quad (4.27a)$$

$$F\mathbf{q}(t) = \gamma_0 e^{\lambda_0 t} v_0 + \sum_{k=0}^1 \sum_{j=1}^r \gamma_j e^{\lambda_j t} v_j^k, \quad (4.27b)$$

where

$$F = \begin{bmatrix} 1 & \cdots & 1 \end{bmatrix}, \quad (4.28)$$

$F \in \mathbb{R}^m$  is a column vector of ones.

Let us consider the expression in [Equation \(4.27b\)](#). It represents the linear combination of all the coefficients of the state at time  $t$ . It can also be expressed in the following form

$$\begin{aligned} F\mathbf{q}(t)/T &= \gamma_0 e^{\lambda_0 t} v_0/T + (1/T) \sum_{j=1}^r \gamma_j e^{\lambda_j t} v_j^0 + \\ &\quad (1/T) \sum_{j=1}^r \gamma_j e^{\lambda_j t} v_j^1. \end{aligned} \quad (4.29)$$

We prove that the eigenvalues  $\lambda$  and eigenvectors  $V$  are such that [Equation \(4.29\)](#) is equivalent to [Equation \(4.19\)](#).

The matrix  $A$  is a block diagonal matrix, so we can express its determinant as the multiplication of the determinants of its blocks

$$\det(A) = \det(0) \det(A_1) \det(A_2) \cdots \det(A_r). \quad (4.30)$$

We now conclude the proof by computing the first determinant and the others separately.

By computing the first determinant, we prove that the first terms in [Equation \(4.19\)](#) and [Equation \(4.29\)](#) match. We find the eigenvalue from  $\det(0) = 0$ , which is  $\lambda_0 = 0$ . The corresponding eigenvector can be chosen arbitrarily

$$(0 - \lambda_0)v_0 = \begin{bmatrix} 0 & \cdots & 0 \end{bmatrix}, \quad (4.31)$$

$\forall v_0$ , thus we choose

$$v_0 = \begin{bmatrix} 1 & 0 & \cdots & 0 \end{bmatrix}. \quad (4.32)$$

The sizes of the zero vector and of  $v_0$  in [Equations \(4.31–4.32\)](#) are both  $\mathbb{R}^m$ .

We find the value  $\gamma_0$  in [Equation \(4.29\)](#) so that the terms are equal

$$\gamma_0 = \begin{bmatrix} a_0 & 0 & \cdots & 0 \end{bmatrix}, \quad (4.33)$$

where  $\gamma_0 \in \mathbb{R}^m$ .

Then, we prove the other determinants. In this way, we prove that all the terms in the sum of both [Equation \(4.19\)](#) and [Equation \(4.29\)](#) match.

By computing the second determinant, we prove that the first terms in both summaries in [Equation \(4.19\)](#) and [Equation \(4.29\)](#) match. We thus focus on the first block  $A_1$ , and find the eigenvalues from

$$\det(A_1 - \lambda I) = 0. \quad (4.34)$$

The polynomial  $\lambda^2 + \omega^2$ , gives two complex roots—the two eigenvalues

$$\lambda_1^0 = i\omega, \quad (4.35a)$$

$$\lambda_1^1 = -i\omega. \quad (4.35b)$$

The eigenvector associated with the eigenvalue  $\lambda_1^0$  is

$$v_1^0 = \begin{bmatrix} 0 & -i & 1 & 0 & \cdots & 0 \end{bmatrix}' . \quad (4.36)$$

The eigenvector associated with the eigenvalue  $\lambda_1^1$  is

$$v_1^1 = \begin{bmatrix} 0 & i & 1 & 0 & \cdots & 0 \end{bmatrix}' . \quad (4.37)$$

Both eigenvectors are equally sized  $v_1^0, v_1^1 \in \mathbb{R}^m$ .

Again, we find the values  $\gamma_1$  in [Equation \(4.29\)](#) such that the equivalences

$$\begin{cases} e^{i\omega t}(a_1 - ib_1) &= \gamma_1 e^{i\omega t} v_1^0 \\ e^{-i\omega t}(a_1 + ib_1) &= \gamma_1 e^{i\omega t} v_1^1 \end{cases}, \quad (4.38)$$

hold. They hold for

$$\gamma_1 = \begin{bmatrix} 0 & b_1 & a_1 & 0 & \cdots & 0 \end{bmatrix}. \quad (4.39)$$

The proof for the remaining  $r - 1$  blocks is equivalent.

The initial guess  $\mathbf{q}_0$  is build such that the sum of the coefficients is the same in both the signals. In the output matrix, the frequency  $1/T$  accounts for the period in [Equation \(4.19\)](#), [Equation \(4.29\)](#), and [Equation \(4.11\)](#). At time instant zero, the coefficients  $b_j$  are not present and the coefficients  $a_j$  are doubled for each  $j = 1, 2, \dots, r$  (thus we multiply by a half the corresponding coefficients in  $\mathbf{q}_0$ ). To match the outputs  $h(t) = y(t)$ , or equivalently

$$F\mathbf{q}(t)/T = C\mathbf{q}(t), \quad (4.40)$$

we define

$$C := (1/T) \begin{bmatrix} 1 & 1 & 0 & \cdots & 1 & 0 \end{bmatrix}. \quad (4.41)$$

We thus conclude that the signal and the output are equal and that the lemma holds. ■

We note for practical reasons that the signal would still be periodic with another linear combination of coefficients. For instance

$$C := d \begin{bmatrix} 1 & 1 & 0 & \cdots & 1 & 0 \end{bmatrix}, \quad (4.42)$$

equivalent to

$$C := d \begin{bmatrix} 1 & 0 & 1 & \cdots & 0 & 1 \end{bmatrix}, \quad (4.43)$$

or

$$C := d \begin{bmatrix} 1 & \cdots & 1 \end{bmatrix}, \quad (4.44)$$

for a constant value  $d \in \mathbb{R}$ .

#### 4.4.2 Nominal control

Let us suppose that at time instant  $t$  the plan in [Definition 2.4.2](#) reached the  $i$ th stage  $\Gamma_i$  and the control contains the configuration of path and computations parameters

$$c_i(t) = \begin{bmatrix} c_i^\rho(t) & c_i^\sigma(t) \end{bmatrix}', \quad (4.45)$$

where  $c_i(t) \in \mathbb{R}^n$  with  $n = \rho + \sigma$  differs from the nominal control  $\mathbf{u}(t)$  in [Equation \(4.12\)](#). We include the control in the nominal control exploiting the following observation.

##### Observation

We observe that:

- A change in path parameters affects the energy indirectly. It alters the time when the aerial robot reaches the final point  $\mathbf{p}_{\Gamma_f}$ , and enters the accepting stage  $\Gamma_f$ .
- A change in computation parameters affects the energy directly. It alters the instantaneous energy consumption as more computations require more power (and vice versa).

The second bullet point in the observation is easily verified. The `powprofiler` profiling tool models the energy consumption of the heterogeneous computing hardware the mobile robot is caring. A variation in the computation parameter affects the schedule (as the schedule is characterized by the computation parameter in [Definition 2.1.2](#)) and hence the instantaneous energy consumption of the mobile robot.

The first bullet point in the observation can be verified by inspection of the example in [Section 2.6](#). It is clear that if we decrease the parameter  $c_{4,1}$ , which is relative to the radius of the circle, the flying time decreases. This is further shown in [Figure 4.13](#) and [Figure 4.14](#). [Figure 4.13](#) illustrates the trajectory of the aerial robot (composed of all the paths  $\varphi_1, \varphi_2 \dots$ ) flying at the highest configuration of the path parameter  $c_{i,1} = \bar{c}_{4,1}$ . [Figure 4.14](#) then illustrate the trajectory flying at the lowest configuration  $c_{i,1} = \underline{c}_{4,1}$ . The flying time differs significantly, along with the quality of the coverage of the polygon (the agricultural field in [Figure 1.6](#)). In [Figure 4.14](#), the parameter  $c_{4,1}$  that alters the radius and center of the upper circle (defined originally in [Section 2.6](#)) is replanned as, e.g., averse atmospheric conditions do not allow to terminate the original plan in [Figure 4.13](#).

We use the observation later in [Section 6.4.2](#) to check that the time to completely discharge the battery is greater than the flight time and replan the path parameters accordingly. We replan the computation parameters to maximize the instantaneous energy consumption against the maximum battery discharge rate.


The nominal control is

$$\mathbf{u}(t) := \hat{\mathbf{u}}(t) - \hat{\mathbf{u}}(t - \Delta t), \quad (4.46)$$


where  $\hat{\mathbf{u}}(t)$  is defined as the energy estimate of a given control sequence at time instant  $t$ ,  $\hat{\mathbf{u}}(t - \Delta t)$  at the previous time instant  $t - \Delta t$

$$\hat{\mathbf{u}}(t) := \text{diag}(\nu_i) c_i(t) + \tau_i, \quad (4.47)$$

where  $\text{diag}(\nu_i)$  is a diagonal matrix with the parameters  $\nu_{i,j} \in \nu_i, \forall j \in [n]_{>0}$ .



**Fig. 4.13.** The trajectory of the aerial robot flying paths  $\varphi_1, \varphi_2, \dots, \varphi_i$  from Section 2.6 with the highest configuration of the path parameter  $c_{4,1} = \bar{c}_{4,1}$ . This configuration of path parameter has the longest time but the shortest distance between the lines and thus the highest quality of the coverage in [Figure 1.6](#).



**Fig. 4.14.** The trajectory of the aerial robot similarly as in [Figure 4.13](#) but with the lowest configuration of the path parameter  $c_{4,1} = \underline{c}_{4,1}$ . This configuration has the longest distance between the lines and thus the lowest quality of the coverage in [Figure 1.6](#).

The input matrix is then

$$B = \begin{bmatrix} 0^{1 \times \rho} & 1 & \cdots & 1 \\ 0^{1 \times \rho} & 0 & \cdots & 0 \\ \vdots & \vdots & \ddots & \vdots \\ 0^{1 \times \rho} & 0 & \cdots & 0 \end{bmatrix}, \quad (4.48)$$

where  $B \in \mathbb{R}^{m \times n}$  contains zeros except the first row where the first  $\rho$  columns are still zeros and the remaining  $\sigma$  are ones.

$\hat{\mathbf{u}}(t)$  is a stage-dependent scale transformation with

$$\mathbf{v}_i = \begin{bmatrix} v_i^\rho & v_i^\sigma \end{bmatrix}', \quad (4.49a)$$

$$\tau_i = \begin{bmatrix} \tau_i^\rho & \tau_i^\sigma \end{bmatrix}', \quad (4.49b)$$

scaling factors. They quantify the contribution to the plan of a given parameter in terms of time for the first  $\rho$  parameters, and instantaneous energy consumption for the remaining  $\sigma$  (we use the same notation for the path and computation scaling factors as for the parameters).

The nominal control  $\mathbf{u}(t)$  is then the difference of these contributions of two consecutive controls  $c_i(t - \Delta t), c_i(t)$  applied to the system.

$B\mathbf{u}(t)$  merely includes the difference in the instantaneous energy consumption into the model in Equation (4.12). Matrix  $B$  ignores the time contribution of the path parameters in  $c_i$ . We use them to verify that the flying time is lower than the battery time in Section 6.5.

#### 4.4.3 Parameters scale transformation

To transform the control  $c_i(t)$  at  $i$ th stage and time instant  $t$  we use different approaches for the path and computation scaling factors.

The scaling factors for the path parameters from Equation (4.49) are derived empirically. For example, we can obtain the scaling factor  $v_{4,1}$  relative to the alteration  $c_{4,1}$  of the upper circle  $\varphi_4$  from Section 2.6 by measuring the time needed to compute the path with the lowest configuration  $\underline{c}_{4,1}, \underline{t}$  in Figure 4.14, and the highest  $\bar{t}$  in Figure 4.13.

The variation of the control hence results in an approximate measure of the plan's time variation with factors

$$v_{i,j} = ((\bar{t} - \underline{t}) / (\bar{c}_{i,j} - \underline{c}_{i,j})) / \rho, \quad (4.50a)$$

$$\tau_{i,j} = (\underline{c}_{i,j}(\bar{t} - \underline{t}) / (\bar{c}_{i,j} - \underline{c}_{i,j}) + \underline{t}) / \rho, \quad (4.50b)$$

$\forall j \in [\rho]^+$ . Moreover, let the factors be zero when the parameters set  $c_i^\rho = \{\emptyset\}$ . We use the latter to initialize the algorithm in Section 6.5.

The scaling factors for the computations parameters from Equation (4.49) are derived using `powprofiler`, the open-source modeling tool from Section 4.1.8. We estimate the energy cost of a given schedule (a given computations configuration) with the function  $g$  from Definition 4.1.1. For instance, if the computation is the CNN ROS node, the computation parameter  $c_{1,2}$  corresponds to the FPS rate. The tool then measures power according to the detection frequency.

The scaling factors add the computational energy component to the model in Equation (4.12). They are derived similarly to Equation (4.50)

$$v_{i,j} = (g(\bar{c}_{i,j}) - g(c_{i,j})) / (\bar{c}_{i,j} - c_{i,j}), \quad (4.51a)$$

$$\tau_{i,j} = c_{i,j}(g(c_{i,j}) - g(\bar{c}_{i,j})) / (\bar{c}_{i,j} - c_{i,j}) + g(c_{i,j}), \quad (4.51b)$$

$\forall j \in [\rho + 1, n]$ . Moreover, let the factors be zero when the parameters set  $c_i^\sigma = \{\emptyset\}$ .




Fig. 4.15. The concept of a path and computation parameter scale transformation. Without any battery constraints, the dynamic energy planning selects the highest configuration which respects the control constraint (inner rectangle) from Equation (2.6).

The concept of a path and a computation parameter scale transformation is illustrated in Figure 4.15. The energy domain is bounded by the output of `powprofiler`, while the flight time domain by the empirical data. The dynamic energy planning selects the highest possible configuration under the constraints. Currently, the highest configuration of parameters corresponds to the highest configuration of parameters  $(\bar{c}_{i,1}, \bar{c}_{i,2})$  (blue point in the figure). We will show in Section 6.4.1 the optimal control derivation over a time horizon  $N$  under given battery constraints.

#### 4.4.4 Aperiodic energy evolution

### 4.5 Contribution

### 4.6 Results

This Section shows and assesses experimental results for the benchmarks, and validates the presented approach.

We now describe the experimental results of the benchmarks previously introduced. A summary of these results is outlined in Table 4.

#### Matrix Exponentiation

Execution of GPU matrix exponentiation, while varying size and exponent parameters, was previously shown in Figure 4.3. The figure shows the average power as well as overall energy consumption along with the battery depletion as a function of size and exponent parameters. Average power consumption

Component	ODROID XU3	NVIDIA		
		TK1	TX2	Nano
matrix-cpu	5284 J	4067 J	2413 J	2736 J
matrix-gpu	-	81 J	45 J	39 J
darknet-cpu	(-)	(-)	2400 J	(-)
darknet-gpu	-	-	5255 J	(-)
nvidia-matrix	-	(-)	4054 J	(-)
nvidia-quicks	-	(-)	1995 J	(-)

Table 4. The overall energy consumption for each benchmark. Unsupported platforms are indicated by ‘-’ and ‘(-)’ indicates supported but not included in this paper.

Fig. 4.16. Layer 2 model of darknet-gpu component running under four configurations, respectively 5.8, 10, 25 and 32 frames-per-second. The figure shows the per-minute energy consumption in terms of CPU, GPU, and overall. On the right side, energy consumption for any possible frame per second rate is shown along with SoC (the y2-axis, the y-axis is shared with the left side).

is reported independently of the running time of the component and thus does not reflect the total power consumption. For small problem sizes, the computation terminates before reaching the maximal power level. This effect is visible in Figure ?? (also previously shown), where power consumption is low at the beginning and then reaches the maximum, for which reason the average power consumption is low for small problem sizes. Battery depletion is reported in terms of the total amount of energy consumed by the computation for the duration of the execution. The effect of introducing “scheduling” in the form of sleep of various durations in between iterations of the matrix computations can be seen in Figure 4.7. Here, the duration of the sleep affects the total power consumption: the higher the sleep value in between the iterations, the greater the battery depletion.

CPU vs GPU comparison shows, expectedly, that matrix-gpu is very performant compared to matrix-cpu. While the matrix-cpu requires 2 413 J, matrix-gpu requires only 45 J for the same operation on the TX2 board. Therefore, running the benchmark on GPU results in 16% more SoC against the same trial on CPU. Such a high speed-up is observed due to the highly parallelizable nature of the matrix exponentiation and hence cannot be used as a general rule. From our experiments, we additionally observe the power-related effect of running components sequentially versus in parallel on different computational units. Although the CPU and GPU are different computational units, the energy consumed by running components independently (i.e., sequentially in some order) on CPU and GPU is 20% larger compared to running them in parallel, even when subtracting the base power consumed by the board. Thus energy can be conserved by running computations in parallel on the CPU and GPU, compared to scheduling them sequentially.

## Darknet

We modified the darknet component to simulate different scheduling options and evaluated the outcome on a video stream: darknet now accepts an argument that indicates the amount of sleep between two invocations of the image recognition algorithm. In this way, we were able to simulate different frames-per-second options and assess the power evolution using the model.

Our experimental data depicted in Figure 4.16 shows that an increment in frames-per-second corresponds to an increased power consumption along with a higher battery depletion. The resulting model can be used to define an appropriate trade-off that represents an acceptable rate of QoS, by i.e., correlating the FPS rate to the battery depletion and hence highlighting the dynamic behavior of a mobile scenario. Moreover, we observe that `darknet-cpu` consumes less energy per minute compared to the `darknet-gpu` component, but is considerably slower: while running `darknet-cpu` for one minute on TX2 board requires 2 400 J, `darknet-gpu` requires 5 255 J. When considering the energy cost per frame the computation is however considerably more efficient on GPU, where it requires just 1.3 J per frame, against the 175 J on GPU.

## NVIDIA

The `nvidia-matrix` benchmark differs from `matrix-gpu`, even if both perform matrix multiplication on GPU, since `nvidia-matrix` includes a significant CPU computation after GPU matrix multiplication to check whether the two match. The `matrix-gpu` benchmark was similarly tested during development, but does not perform this test at runtime. We observe that the `nvidia-matrix` benchmark has a similar energy behavior to `matrix-gpu`, with the problem size affecting the overall energy and henceforth battery depletion. Average power consumption on GPU is however higher for `matrix-gpu` while it is approximately the same on CPU for both benchmarks (presumably none of the two benchmarks focus on energy efficiency on CPU). For the quicksort benchmark, as expected energy consumption increases with the problem size, as more operations are performed. Nevertheless quicksort differs from matrix multiplication: there is more noise due to a higher dependence on the random data that is being sorted.

### 4.6.1 Validation

We validate our approach by: a) demonstrating that `powprofiler` can be used on a number of heterogeneous platforms, b) comparing model generated with internal metrics to external physical measurements on the TX2, and c) comparing the model to a fine-grained one.

A cross-platform comparison shows energy-related behavior of running the same benchmark on different boards. We observed, for instance, that the most energy-efficient board for `matrix-cpu` benchmark is TX2, which consumes 2 413 J to perform the operation, followed by Nano with 2 736 J, TK1 with 4 067 J, and ODROID with 5 284 J.

A measurement analysis is used to compare internal against external power metrics on the TX2 board. We observe that both externally and internally measured power models are close one to each other, with an error of less than 3% measured over one minute. The externally measured power exceeds the internally measured power — this is natural as the externally measured power also includes the carrier board, which requires additional energy to operate. Moreover, the measurements performed using `powprofiler` include the power consumed by `powprofiler` itself, while the multimeter setup excludes `powprofiler`'s energy from the evaluation. We therefore assume that the tool has a marginal effect on power consumption and that the model is showing realistic behavior.

In a last validation step, we compared our approach to fine-grained energy model of Nunez et al. (Nunez-Yanez and Lore, 2013) and Nikov et al. (Nikov et al., 2015) for the ODROID-XU3 embedded board. To relate the two approaches for energy-modeling, we used the `matrix-cpu` benchmark component as follows. First, we evaluated the matrix exponentiation benchmark by raising a 512 by

$512$  matrix to the 30th power ( $512^{30}$ ) to train the fine-grained model. We obtained a value of expected energy per operation that we compared to the measured one and measured a relative error of 3.42%. Second, we applied an equivalent approach to our model. We sampled some configurations that were distant from the expected one, concretely we ran configurations  $512^x$  with  $x \in \{5, 15, 25, 35, \dots\}$ , and we used the approximation method described in [Section ??](#) to evaluate the energy of the configuration  $512^{30}$ . This value was then compared to the measured one and we obtained a relative error of 2.25%. We can conclude that both models produce similar results on this benchmark, and have a similar relative error even if they adopt a different approach towards energy-modeling.

#### 4.6.2 Assessment

We performed a number of experiments on different boards. Most of the data in this paper were obtained from NVIDIA TX2 due to the similarity with TK1 and Nano and the easy accessibility of the internal power measurement units. These data allowed us to validate our model, and to show that different scheduling options can correspond to different energy models. The model can describe energy consumption and instantaneous power, together with the battery depletion.

Coarse-grained whole-system energy modeling can take into account some behaviors that cannot otherwise easily be observed. As an example, consider the effect of simple scheduling previously shown in [Figure 4.7](#). Here, we expected that introducing a higher sleep period between executions would result in an energy cost. We used the model to investigate this assumption, and we found that it is not always happening. For instance, a period of 2.5s between two consecutive schedules of  $512^{12}$  matrix exponentiation iterated for 12 times is more energy-efficient than executing the whole  $512^{144}$  operation. The model can relate these observations, provide information about the battery depletion, and predict the total time the system can operate on a given energy source. It can also highlight battery-specific behaviors since different scheduling options drain battery differently. In particular, Using the `powprofiler` tool on the NVIDIA TX2, we experimentally observe that:

- Running a set of components separately, and simply adding their energy consumption (while excluding base energy), leads to a different model versus running them in parallel ([Section 4.6](#)). This behavior was observed for matrix exponentiation components running on separate computational units (CPU, GPU).
- Scheduling of computations directly impacts the battery drain: processing a computation in its entirety with a steady power load drains the battery less than scheduling that same computation into smaller steps with resulting spikes in the power load ([Section 4.6.2](#)). This behavior was observed for a matrix exponentiation component running on CPU.

#### 4.7 Summary

# Chapter 5

## Optimal Control Generation


**T**HIS chapter provides essential theoretical background on optimal control theory necessary to derive an optimal configuration of the path and computations of the mobile robot. It solves the problem posed in [Section 2](#) and illustrate an algorithm that generates the optimal configuration dynamically. The algorithm relies on a modern optimal control technique known as model predictive control (MPC), where the optimal control trajectory is evaluated on a receding horizon for each optimization step ([Rawlings et al., 2017](#)).

Optimal control deals with finding optimal ways to control a dynamic system ([Sethi, 2019](#)). It determines the control signal—the evolution in time of the decision variables—such that the model satisfies the dynamics and simultaneously optimizes a performance index ([Kirk, 2004](#)).

Many optimization problems originating in fields such as robotics, economics, and aeronautics can be formulated as optimal control problems (OCPs) ([Von Stryk and Bulirsch, 1992](#)). Optimization is often called mathematical programming ([Nocedal and Wright, 2006](#)) a term that means finding ways to solve the optimization problem. One can often find programming in this context in terms such as linear program (LP), quadratic program (QP), and nonlinear program (NLP). NLPs is the class of optimization problems that we use to derive the optimal configuration. OCPs can be seen as optimization problems with the added difficulty of continuous dynamics. The latter is to be integrated over the optimization horizon using numerical simulation. In the algorithm, we formulate the dynamic planning problem as an OCP that we solve with a numerical method: we transform the OCP in an NLP using numerical simulation and solve the NLP using numerical optimization, as proposed in ([Rawlings et al., 2017](#)). The process is illustrated in [Fig. 5.1](#).

A typical performance measure for an OCP is built such that the system: reaches a target set  $\mathcal{Q}_f$  in minor time, reaches a given final state  $\mathbf{q}_f$  with minimum deviation, maintains the state evolution as close as possible to a given desired evolution, or reaches the target set with the minimum control expenditure effort ([Kirk, 2004](#)). In energy planning, it is desired to focus on the latter performance measure.

The outline of the chapter is as follows. After a brief history of optimal control, we introduce formally the OCP subject to continuous dynamics. We then illustrate numerical simulation approaches to convert the infinite-dimensional continuous dynamics into finite-dimensional discrete dynamics. We formulate later in the chapter the dynamic planning problem for the optimal configuration of the path and computations with proper constraints. Finally, we illustrate MPC to solve OCP on a receding



**Fig. 5.1.** Summary of the optimal control approach. The problem is formulated as an OCP, into finite-dimensional discrete NLP using numerical simulation. NLP is solved using numerical optimization and the optimal configuration for a given time horizon is returned to the aerial robot. The following horizon is evaluated again in a technique known as MPC.

horizon. We propose an algorithm to solve such OCP using a numerical method on the horizon along with the analysis of its practical feasibility.

The chapter builds on the rest of the work as follows. In the OCP formulation, we use the estimated state from [Chapter 5.3](#) of a perfect model in [Chapter 4](#) to solve the planning problem in [Section 2](#) and guide the aerial robot with the obtained optimal configuration from this chapter with the technique in [Chapter 6](#).

## 5.1 A Brief History of Optimal Control

Optimal control originates from the calculus of variations ([Sethi, 2019](#)), based on the work of Euler and Lagrange. Calculus of variations solves the problem of determining the arguments of an integral, such that its value is maximum (or minimum). The equivalent problem in calculus is to determine the argument of a function where the function is maximum (or minimum). The work by Euler and Lagrange was later extended by Legendre, Hamilton, and Weierstrass ([Paulen and Fikar, 2016](#)). It has gained a renewed interest in the mid-twentieth century, as modern calculators offered practical ways of solving some OCPs for nonlinear and time-varying systems that were earlier impracticable ([Bryson and Ho, 1975](#)).

The conversion of the calculus of variation problems in OCPs requires the addition of the control variable to the dynamics ([Sethi, 2019](#)).

There are numerous methods to analytically and numerically solve these continuous time OCPs, although analytical solution is often impracticable except for very limited state dimensions ([Rawlings et al., 2017](#)). In the early day of optimal control, some analytical solutions were proposed with dynamic programming ([Bellman, 1957](#)), and with maximum (or minimum) principle ([Pontryagin et al., 1962](#)).

In computer science dynamic programming is fundamental to compute optimal solutions, yet it's original form was developed to solve optimal control problems ([LaValle, 2006](#)). Dynamic programming in optimal control theory is based on a partial differential equation of the performance index named Hamilton-Jacobi-Bellman (HJB) equation, which is solved either analytically for small dimensional state space problems, or numerically ([Rawlings et al., 2017](#)). Dynamic programming can be shown to be equivalent to the principle ([Paulen and Fikar, 2016](#)). The principle is related to HJB equation in that it provides optimality conditions an optimal trajectory must satisfy ([LaValle, 2006](#)). HJB offer sufficient conditions for optimality while the principle necessary; yet it is useful to find suitable candidates for optimality ([LaValle, 2006](#)).

All the numerical approaches discretize infinite-dimensional problems at a certain point (Rawlings et al., 2017).

A first class of these approaches solves the optimality conditions in continuous time using first-order necessary conditions of optimality from the principle (Böhme and Frank, 2017). This is done by algebraic manipulation using an expression that is similar to the HJB equation, and results in a boundary-value problem (BVP) (Rawlings et al., 2017). The class is commonly referred to as the indirect methods. The BVP is solved by discretization at the very end (Rawlings et al., 2017) and/or gradient-based resolution (Paulen and Fikar, 2016).

On the contrary, modern optimal control often first discretizes the control and state variables in the OCP to a finite dimensional optimization problem (usually NLP), which is then solved with numerical optimization (using gradient-based techniques). This other class of numerical approaches is referred to as direct methods. Some direct methods are single and multiple shooting and collocation methods. We employ direct methods in this chapter.

Modern OCPs are often solved on a finite and receding horizon using an approximation of the true dynamics using MPC techniques. It is a more systematic technique which allows to control a model by re-optimizing the OCP repeatedly (Paulen and Fikar, 2016; Poe and Mokhatab, 2017). It takes into account external interferences by re-estimating the model's state (with techniques that we introduced in Chapter 5.3). MPC is extensively treated in modern optimal control literature (Camacho and Alba, 2007; Kwon and Han, 2005; Rawlings et al., 2017; Rossiter, 2004; L. Wang, 2009).

## 5.2 Optimization Problems with Dynamics

### 5.2.1 Continuous systems: unconstrained case

Given a state variable  $\mathbf{q}$  composed of  $m$  states and a control variable  $\mathbf{u}$  composed of  $n$  controls, the state variable dynamics at a given time instant  $t$  can be described by a differential model

$$\dot{\mathbf{q}}(t) = f(\mathbf{q}(t), \mathbf{u}(t), t), \quad \mathbf{q}(t_0) = \mathbf{q}_0 \text{ given, } \forall t \in [t_0, T], \quad (5.1)$$

where  $t_0 \in \mathbb{R}_{\geq 0}$  is a given initial time instant, and  $\mathbf{q}_0 \in \mathbb{R}^m$  a given initial state guess. The latter can be derived empirically from a previous execution or using some initial sensor data.  $f : \mathbb{R}^m \times \mathbb{R}^n \times \mathbb{R}_{\geq 0} \rightarrow \mathbb{R}^m$  maps the current state, control and time to the next state. The notations for  $\dot{\mathbf{q}}(t) := d\mathbf{q}(t)/dt$ ,  $\mathbf{q}$ , and  $\mathbf{u}$  are the same from Chapter 4. The function  $f$  is assumed to be continuously differentiable. Physically, Equation (5.1) specifies the instantaneous change in state variable of a perfect model with no disturbances.

If the control trajectory  $\mathbf{u}(t_0), \mathbf{u}(t_1), \dots, \mathbf{u}(T - \Delta t)$  is known for a given time horizon  $t_0 \leq t \leq T$ , the model in Equation (5.1) can be derived to obtain the state trajectory  $\mathbf{q}(t_0), \mathbf{q}(t_1), \dots, \mathbf{q}(T)$ , where  $\Delta t$  is the instantaneous change in time. The last state at the final time instant  $T$  is derived from the last control at the time instant  $T - \Delta t$ . The state trajectory has indeed one item more than the control trajectory.

Optimal control finds a control trajectory which maximizes (or minimizes) a performance index

$$L = l_f(\mathbf{q}(T), T) + \int_{t_0}^T l(\mathbf{q}(t), \mathbf{u}(t), t) dt, \quad (5.2)$$

where  $l$ ,  $l_f$  are given instantaneous and final cost functions. The instantaneous cost function maps state, controls, and time to a value that quantifies the cost of a given instant  $l : \mathbb{R}^m \times \mathbb{R}^n \times \mathbb{R}_{\geq 0} \rightarrow \mathbb{R}$ . The final cost function maps the state and time to a value which quantifies the cost of the final instant

$l_f : \mathbb{R}^m \times \mathbb{R}_{\geq 0} \rightarrow \mathbb{R}$ . The performance index  $L \in \mathbb{R}$  is then the sum of all the contribution on the time horizon.

Performance index found in (Bryson and Ho, 1975) is also found in literature as cost function in (Simon, 2006; Stengel, 1994), objective function in (S. S. Rao, 2019; Rawlings et al., 2017; Sethi, 2019), or performance measure (Kirk, 2004).

The control variable is usually constrained

$$\mathbf{u}(t) \in \mathcal{U}(t), \quad \forall t \in [t_0, T], \quad (5.3)$$

where  $\mathcal{U}(t) \subseteq \mathbb{R}^m$  is the control constraint set. It delimits all the feasible values of the control for the horizon. There can be different control constraint sets for different instants.

The Equations (5.1–5.3) forms unconstrained OCPs. These problems are formalized

$$\begin{aligned} & \max_{\mathbf{q}(t), \mathbf{u}(t)} l_f(\mathbf{q}(T), T) + \int_{t_0}^T l(\mathbf{q}(t), \mathbf{u}(t), t) dt, \\ & \text{s.t. } \dot{\mathbf{q}}(t) = f(\mathbf{q}(t), \mathbf{u}(t), t), \\ & \mathbf{u}(t) \in \mathcal{U}(t), \quad \mathbf{q}(t) \in \mathcal{Q}(t), \\ & \mathbf{q}(t_0) = \mathbf{q}_0 \text{ given.} \end{aligned} \quad (5.4)$$

The evolution of the model is used to derive an optimal control trajectory  $\mathbf{u}(t)$  from an initial guess of the state  $\mathbf{q}_0$  and the horizon. This initial simplistic controller does not represent a realistic scenario. The controller implies that the horizon is known. However, it is often the case that only the initial time step of the horizon  $[t_0, T]$  is known. In the model from Chapter 4 it is indeed unknown apriori when the aerial robot plan terminates. Moreover the controller does not include any constraint on the state  $\mathbf{q}$ , although mobile robots are often bounded by strict battery requirements. Lastly, the optimal control generated with such controller is static given the initial state and the horizon. It is unrealistic to assume that the state of the aerial robot travelling the optimal control  $\mathbf{u}$  does not change for instants  $t_0 + \Delta t, t_0 + 2\Delta t, \dots, T$ .

All these initial assumption (known final time step, absence of state constraints, static optimal control law) will be eased in the remaining of the chapter.

### 5.2.2 Continuous systems: constrained case

### 5.2.3 Perturbed systems

### 5.2.4 Multistage systems

## 5.3 State Estimation

### 5.3.1 The curve fitting problem

### 5.3.2 Period estimation

### 5.3.3 Discrete time Kalman filter

As the environment uncertainty and measurement error evolve in a normal distribution, we use a Kalman filter (Simon, 2006; Stengel, 1994) for the purpose of state estimation.

The prediction is done using

$$\hat{\mathbf{q}}_{k+1}^- = A\hat{\mathbf{q}}_k + B\mathbf{u}_k, \quad (5.5a)$$

$$P_{k+1}^- = AP_k A' + Q, \quad (5.5b)$$

where  $\hat{\mathbf{q}}_k^-, \hat{\mathbf{q}}_k \in \mathbb{R}^j$  depicts the estimate of the state before and after measurement (or simply estimate), and  $P_k, P_k^- \in \mathbb{R}^{j \times j}$  the error covariance matrix (i.e., the variance of the estimate).

The estimation of the state and the update of the predicted output is done using

$$K_k = (CP_{k+1}^- C' + R)^{-1}(P_{k+1}^- C'), \quad (5.6a)$$

$$\hat{\mathbf{q}}_{k+1} = \hat{\mathbf{q}}_{k+1}^- + K_k(y_k^s + y_k^c - C\hat{\mathbf{q}}_{k+1}^-), \quad (5.6b)$$

$$P_{k+1} = (I - K_k C)P_{k+1}^-, \quad (5.6c)$$

$$\hat{y}_k = C\hat{\mathbf{q}}_{k+1}, \quad (5.6d)$$

where  $K_k \in \mathbb{R}^j$  is the gain of the Kalman filter, and  $I$  the identity matrix.  $y_k^s, y_k^c$  are the instantaneous energy readings:  $y_k^s \in \mathbb{R}_{\geq 0}$  the robot sensor, i.e., the energy due to the trajectory, and  $y_k^c$  the energy of a given software configuration described in .... The noise covariance matrices  $Q \in \mathbb{R}^{j \times j}, R \in \mathbb{R}$  indicates the uncertainty and measurement error covariance respectively, and  $\hat{y}_k \in \mathbb{R}_{\geq 0}$  is the estimated energy.

Equations (5.5–5.6) converge to the predicted energy evolution as follows. An initial guess of the values  $\hat{\mathbf{q}}_0, P_0$  is derived empirically from collected data. It is worth considering that an appropriate guess of these parameters allows the algorithm to converge to the desired energy evolution in a shorter amount of time. The tuning parameters  $Q, R$  are also derived from the collected data, and may differ due to i.e., different sensors used to measure the instantaneous energy consumption, or different atmospheric conditions accounting for the process noise.

At time  $k = 0$ , the initial estimate before measurement of the state and of the error covariance matrix is updated in Equations (5.5a–5.5b) respectively. The value of  $\hat{\mathbf{q}}_1^-$  is then used in Equation (5.6b) to estimate the current state along with the data from the sensor  $y_0$  (e.g., the energy sensor of the flight controller of the fixed-wing craft), where the sensor noise covariance matrix  $R$  accounts for the amount of uncertainty in the measurement. The estimated output  $\hat{y}_0$  is then obtained from Equation (5.6d). The algorithm is iterative. At time  $k = 1$  the values  $\hat{\mathbf{q}}_1, P_1$  computed at previous step are used to estimate the values  $\hat{\mathbf{q}}_2, P_2$ , and  $y_1$ .

### 5.3.4 Continuous time Kalman filter

### 5.3.5 Nonlinear filtering

## 5.4 Numerical Simulation and Differentiation

### 5.4.1 Euler method

### 5.4.2 Runge-Kutta methods

### 5.4.3 Algorithmic differentiation

## 5.5 Direct Optimal Control Methods

### 5.5.1 Direct single shooting

### 5.5.2 Direct multiple shooting

### 5.5.3 Direct collocation

## 5.6 Numerical Optimization

### 5.6.1 Convexity

### 5.6.2 Optimality conditions

### 5.6.3 First order optimality conditions

### 5.6.4 Second order optimality conditions

### 5.6.5 Sequential quadratic programming

### 5.6.6 Nonlinear interior point methods

## 5.7 Results

## 5.8 Summary

# Chapter 6

## Dynamic Planning

### 6.1 Vector Fields for Guidance

The use of vector fields for guidance is widely discussed in the literature (De Marina et al., 2017; Gonçalves et al., 2010; Kapitanyuk et al., 2017; Lindemann and LaValle, 2005; Panagou, 2014; Zhou and Schwager, 2014).




Fig. 6.1. A path parameter in the flight of an aerial robot can be used to alter the overall energy consumption

The set

$$\mathcal{P}_i := \{\mathbf{p}(t) \mid \varphi_i(\mathbf{p}(t), c_i^\rho), c_i^\rho \in \mathcal{U}_i\}, \quad (6.1)$$

delimits the area where the  $i$ th path  $\varphi_i$  is free to evolve using the path parameters  $c_i^\rho$  (the gray area in Figure 6.1).  $\varphi_i$  is a function of the two coordinates and the path parameters, and is equal to zero when a point  $\mathbf{p}(t)$  is on the path. Physically, this means the aerial robot is flying exactly over the nominal trajectory.




Fig. 6.2. Effects of the external interference (wind) on the flight.

We derive the new position  $\mathbf{p}_{k+1}$  computing the vector field

$$\nabla \varphi_i := \begin{bmatrix} \partial \varphi_i / \partial x \\ \partial \varphi_i / \partial y \end{bmatrix}, \quad (6.2)$$

and the direction to follow in the form of velocity vector [De Marina et al., 2017](#)

$$\dot{\mathbf{p}}_d(\mathbf{p}_k) := E \nabla \varphi_i - k_e \varphi_i \nabla \varphi_i, \quad (6.3)$$

where  $E$  specifies the rotation (it influence the tracking direction). For instance

$$E = \begin{bmatrix} 0 & 1 \\ -1 & 0 \end{bmatrix}, \quad (6.4)$$

is the counter clockwise direction,  $-E$  the clockwise direction.

$k_e \in \mathbb{R}_{\geq 0}$  is the gain to adjusts the speed of convergence. The direction the velocity vector  $\dot{\mathbf{p}}_d$  is pointing at is generally different from the course heading  $\dot{\mathbf{p}}$  due to the atmospheric interferences (wind  $w \in \mathbb{R}$  in the top of [Figure 6.1](#)).

## 6.2 Derivation of the Guidance Action

### 6.2.1 Motion simulations

### 6.2.2 Energy simulations

## 6.3 Alteration of the Path

## 6.4 Model Predictive Control

### 6.4.1 Output model predictive control

In this section, we derive the optimal control over a finite time horizon  $N$  for an estimated state  $\hat{\mathbf{q}}$ . The control is the configuration of the path and computations parameters, and it differs from the nominal control. In [Section 4.4.2](#), we presented a motivation for such control based on empirical observations. The optimal control is then the best possible configuration of the path and computations parameters energy-wise with battery constraints.

To derive the optimal control, we use the estimated state  $\hat{\mathbf{q}}$  in [Section 5.3](#), opposed to the ideal state in [Chapter 4](#). The estimated state is different from the ideal state  $\mathbf{q}$  due to the uncertainty. The name of output model predictive control in the literature refers to the notion that some available outputs are

used to estimate the not fully known state (Rawlings et al., 2017). For a differential model, such as the periodic model in Equation (4.12) in Section 4.4, state estimation is done utilizing filtering techniques that include the Kalman filter in Section 5.3.

The derivation of the optimal control involves the definition of an OCP and its transformation into an NLP. Before, however, we re-evaluate the output constraints. The output of the model in Equation (4.12) is the instantaneous energy consumption  $y$  that we stated earlier evolves in  $\mathbb{R}$ . Nevertheless, aerial robots are bounded by strict energy budgets due to battery limitations, as we motivated in Section 1.3. Hence, we redefine the original output constraint ( $\mathbb{R}$ ) to include the battery model in Section 4.2. We consider SoC  $b$  of the mobile robot's battery with the simplistic differential model in Equations (4.1–4.2)

$$\dot{b}(y(t), t) = -k_b \left( V - \sqrt{V^2 - 4R_r y(t)} \right) / (2R_r Q_c), \quad (6.5)$$

where  $k_b$  is the battery coefficient determined experimentally,  $V \in \mathbb{R}$  is the internal battery voltage measured in volts,  $R_r \in \mathbb{R}$  the resistance measured in ohms, and  $Q_c \in \mathbb{R}$  the constant nominal capacity measured in amperes per hour.

We note the one can compute the maximum instantaneous energy consumption by multiplying the constant nominal capacity, the SoC, and the internal battery voltage. We assume the maximum energy consumption cannot be negative

$$0 \leq y(t) \leq b(y(t), t) Q_c V, \quad (6.6)$$

and therefore, we define a time-varying constraint for the output in Definition 6.4.1, being the maximum instantaneous energy consumption dependent on the SoC  $b$  from Equation (6.5), which is dependent on time and the instantaneous energy consumption (at the previous time step).

---

**Definition 6.4.1: Output constraint**

The *output constraint* is the set

$$\mathcal{Y}(t) := \{y \mid y \in [0, b(y(t), t) Q_c V] \subseteq \mathbb{R}_{\geq 0}\},$$

where  $b(y(t), t) Q_c V$  is the maximum instantaneous energy consumption.

We assume the mobile robot carries a battery energy sensor and obtain the initial state of charge  $b(y(t_0), t_0)$  utilizing the output of such sensor. This is often the case of aerial robots with a flight controller, which returns various metrics including the battery state of charge.

The evaluation of the output constraint requires numerical simulation being the battery model in Equation (6.5) differential, similarly to the energy dynamics of the periodic model in Equation (4.12). The numerical simulation can be computed using the Euler method in Section 5.4.1. or the Runge-Kutta method in Section 5.4.2.

The OCP can be stated similarly as in Section 5.2.2, with the constraints: the control constraint in Equation (2.6), the output constraint in Definition 6.4.1, and the dynamics with the ideal state evolution

in Equation (4.12)

$$\max_{\mathbf{q}(t), c_i(t)} l_f(\mathbf{q}(T), T) + \int_{t_0}^T l(\mathbf{q}(t), c_i(t), t) dt, \quad (6.7a)$$

$$\text{s.t. } \dot{\mathbf{q}} = f(\mathbf{q}(t), c_i(t), t), \quad (6.7b)$$

$$c_i(t) \in \mathcal{U}_i, \mathbf{q}(t) \in \mathbb{R}^m, \quad (6.7c)$$

$$y(t) \in \mathcal{Y}(t), \quad (6.7d)$$

$$\mathbf{q}(t_0) = \hat{\mathbf{q}}_0 \text{ given (last estimate state), and} \quad (6.7e)$$

$$b(y(t_0), t_0) = b_0 \text{ given,} \quad (6.7f)$$

where constraints in Equations (6.7b–6.7d) are evaluated on  $t \in [t_0, T]$ .  $\mathbf{q}(t)$  and  $c_i(t)$  are the state and control trajectories.

The sizes of the state and control ( $m$  and  $n$ ) are defined in Section 4.4 and Section 4.4.2.

The dynamic evolution in Equation (6.7b) is then the periodic model in Equation (4.12) together with the scale transformation from Section 4.4.3

$$f(\mathbf{q}(t), c_i(t), t) = A\mathbf{q}(t) + B\text{diag}(v_i)(c_i(t) - c_i(t - \Delta t)), \quad (6.8)$$

where  $c_i(t - \Delta t)$  is the control at the time instant preceding  $t$ .

The instantaneous cost function is defined with the quadratic expression

$$l(\mathbf{q}(t), c_i(t), t) = \mathbf{q}'(t)Q\mathbf{q}(t) + c'_i(t)Rc_i(t), \quad (6.9)$$

where  $Q \in \mathbb{R}^{m \times m}$ ,  $R \in \mathbb{R}^{n \times n}$  are positive semidefinite matrices.

The final cost function is alike defined with a quadratic expression but with no control

$$l_f(\mathbf{q}(T), T) = \mathbf{q}'(T)Q_f\mathbf{q}(T), \quad (6.10)$$

where  $Q_f \in \mathbb{R}^{m \times m}$  is a positive semidefinite matrix.

The optimization horizon is limited to  $N$  measured in seconds, meaning the controller will select the optimal control trajectory  $c_i^*(t)$  over  $[t_0, T]$ , with  $T = t_0 + N$ . At each time instant, the controller refines the control trajectory which respects the constraints: the dynamics in Equation (6.7b) and Equation (6.8), and the control constraint in Equation (6.7c). To evaluate the state trajectory-needed for the instantaneous cost function  $l$  and the final cost function  $l_f$ —the controller evaluates the battery trajectory  $b(y(t), t)$ . It then maximizes the instantaneous cost function  $l$  for all the time instants but  $T$  ( $t_0 \leq t < t_0 + N$ ), and the final cost function  $l_f$  in Equation (6.10) for the time instant  $T$  ( $t = t_0 + N$ ).

The dynamics constraint satisfaction requires to evolve the perfect model  $f$  in Equation (6.8) over horizon  $[t_0, t_0 + N]$  beginning from the last estimated state  $\mathbf{q}_0 = \hat{\mathbf{q}}(t_0)$  at time instant  $t_0$ . The battery constraint is likewise evolved beginning from the last battery measurement  $b_0$  obtained from the battery energy sensor also at time instant  $t_0$ .

The OCP from Equation (6.7) is infinite dimensional, being the system dynamics in Equation (6.7b) and the battery dynamics in Equation (6.5) given in continuous opposed to discrete time. Such an infinite dimensional OCP has an infinite dimension of constraints and decision variables since there are infinite time instants between  $t_0$  and  $t_0 + N$ . We discretize the infinite dimensional OCP and discuss the solution to the planning problem in Chapter 2 in Section 6.4.2.




Fig. 6.3. .

### 6.4.2 Optimal control generation with model predictive control

In this section we combine the notions from the previous sections in this chapter and Chapters 4–6 and provide a solution to the planning problem in Chapter 2.

First, we need to transform the OCP in Equation (6.7) into an NLP. The optimization problem to be solved numerically in the discrete form is effectively an NLP, due to the nonlinearity in the cost functions  $l$ ,  $l_f$ , and in the constraints

$$\max_{\mathbf{q}(k), c_i(k)} l_f(\mathbf{q}(T), T) + \sum_{k \in \mathcal{K}} l_d(\mathbf{q}(k), c_i(k), k), \quad (6.11a)$$

$$\text{s.t. } \mathbf{q}(k + h) = f_d(\mathbf{q}(k), c_i(k), k), \quad (6.11b)$$

$$c_i(k) \in \mathcal{U}_i, \mathbf{q}(k) \in \mathbb{R}^m, \quad (6.11c)$$

$$y(k) \in \mathcal{Y}(k), \quad (6.11d)$$

$$\mathbf{q}(t_0) = \hat{\mathbf{q}}_0 \text{ given (last estimated state), and} \quad (6.11e)$$

$$b(y(t_0), t_0) = b_0 \text{ given,} \quad (6.11f)$$

where the constraints in Equations (6.11b–6.11d) are now evaluated on a finite interval  $k \in \mathcal{K} = \{t_0, t_0 + h, t_0 + 2h, \dots, T\}$ , and  $h$  is a given distance between two time instants; the smaller the distance the more precise the simulation. The other expressions are analogous to Equation (6.7).

We use numerical simulation to transform Equation (6.7) into Equation (6.11). We can use either the Runge-Kutta methods in Section 5.4.2, or the Euler method in Section 5.4.1. For simplicity, we show the transformation with the Euler method. The instantaneous cost function  $l_d$

$$l_d(\mathbf{q}(k), c_i(k), k) = h l(\mathbf{q}(k), c_i(k), k), \quad (6.12)$$

where  $l$  is given in Equation (6.9).

The discrete dynamic evolution in Equation (6.11b)

$$f_d(\mathbf{q}(k), c_i(k), k) = A_d \mathbf{q}(k) + B \text{diag}(\nu_i)(c_i(k) - c_i(k - h)), \quad (6.13)$$

where  $A_d$  is the discretized version of the state transition matrix  $A$  and for small enough interval of  $h$

$$A_d = (hA + \text{diag}(1, 1, \dots, 1)), \quad (6.14)$$

where  $\text{diag}(1, 1, \dots, 1) \in \mathbb{R}^{m \times m}$  is a diagonal matrix of ones. We discretize the battery dynamics in Equation (6.5)

$$b_d(y(k+h), k+h) = b(y(k), k) + h b(y(k+h), k+h). \quad (6.15)$$

We transformed the OCP in Equation (6.7) into an NLP in Equation (6.11) by first discretizing and thus effectively implementing the direct multiple shooting method in Section 5.5.2. We note that we can implement the single shooting method by keeping only the initial state as the decision variable  $\hat{q}_0$  opposed to using the interval boundary time points as a decision variable in the multiple shooting method (Rawlings et al., 2017).

---

## 6.5 Dynamic Planning Algorithm

## 6.6 Results

## 6.7 Summary

## **Chapter 7**

# **Summary and Future Directions**

**7.1 Summary**

**7.2 Contribution**

**7.3 Future Directions**

**7.4 Conclusion**



# Appendix A

## Implementation

### A.1 Energy Models

To build the model in MATLAB(R) one can use the function `build_model` from Listing A.1.

```
1 function [model] = build_model(dat)
2
3     m = 2*dat.r+1;
4
5     Aj = @(dat.omega,j) [0 dat.omega*j;-dat.omega*j 0];
6     A = zeros(m);
7     A(1,1) = 0;
8
9     B = [zeros(1,dat.rho) ones(1,dat.sigma)];
10
11    C = [1];
12
13    for i = 1:dat.r
14        A(2*i:2*i+1,2*i:2*i+1) = Aj(dat.omega,i);
15        C = [C 1 0];
16        B = [B;zeros(1,dat.rho+dat.sigma)];
17    end
18
19    model.A = A;
20    model.B = B;
21    model.C = C;
22
23    model.est_u = @(c) dat.nu*c+dat.tau;
24    model.u = @(u1,u0) u1-u0;
25
26 end
```

Listing A.1. Function `build_model` that creates the energy model.

The function builds the matrices from Equation (4.12). In particular matrix  $A$  from Equation (4.14),  $B$  from Equation (4.48), and  $C$  from Equation (4.16). The term  $1/T$  is missing in  $C$  as we motivated in the proof of Lemma 4.4.1 in Equation (4.42). The nominal control from Equation (4.46) is  $u$ , and the

energy estimate of a given control sequence at time instant  $t$  and the previous time instant  $t - \Delta t$  from Equation (4.47) is `est_u`.

The function requires the structure `dat` illustrated in Listing A.2. The structure contains some information about the model. In particular, `r` is the order  $r$  of the model from Subsection 4.4, `omega` is the angular frequency  $\omega$ , `rho` the number of path parameters to alter the path  $\rho$ , and `sigma` the number of computation parameters to alter the computations  $\sigma$ . The path parameters are defined in Equation (??), and the computation parameters are defined in Equation (??). Furthermore, `delta_T` is the sampling step  $\Delta t$ , and `nu` and `tau` are scaling factors ( $\nu$  and  $\tau$ ) from Equation (4.49).

```

1 dat.r = 3;
2 dat.omega = 2*pi/period;
3 dat.rho = 1;
4 dat.sigma = 1;
5 dat.delta_T = .01;
6 dat.nu = nu;
7 dat.tau = tau;
```

**Listing A.2.** Struct `dat` used by function `build_model` to build the model.

The function `build_model` and the structure `dat` can be used along an initial guess of parameters and a time horizon to model the future energy consumption using the Euler or Runge-Kutta methods for numerical integration. The Euler method is described in Subsection 5.4.1 and implemented in Listing A.3, the Runge-Kutta method in Subsection 5.4.2 and Listing A.5. For the Runge-Kutta method, we use the fourth-order fixed size standard method.

```

1 function [q,y] = evolve_model_euler(model,dat,init)

3     m = 2*dat.r+1;
4     Ad = model.A*dat.delta_T+eye();

6     q0 = init.q0;

8     q = q0;
9     y = C*q0;

11    est_u0 = init.est_u0;
12    est_u1 = model.est_u(init.c_chain(1));

14    i = 2;

16    for init.t0+dat.delta_T:dat.delta_T:init.tf
17        q0 = Ad*q0+model.B*model.u(est_u1,est_u0);
18        est_u0 = est_u1;

20        if i <= size(init.c_chain,2)
21            est_u1 = model.est_u(init.c_chain(i));
22            i = i+1;
23        end

25        q = [q;q0.'];
26        y = [y;C*q0];
27    end
28 end
```

**Listing A.3.** Euler method for numerical integration of the model.

The function `evolve_model_euler` in Listing A.3 evolve the model in Equation (4.12) from an initial time  $t_0$  to the final time  $t_f$ . This information is passed to function using the structure `init` from Listing A.4.

```
1 init.t0 = 0;
2 init.tf = 60;
3 init.q0 = q0;
4 init.est_u0 = est_u0;
5 init.c_chain = c_chain;
```

**Listing A.4.** Structure `init` with numerical integrator's initializations.

In Listing A.4, the field `t0` indicates the initial time  $t_0$  (the mathematical simulation starts at  $t_0 + \Delta t$  assuming the instant  $t_0$  corresponds to the state  $\mathbf{q}(t_0) = \mathbf{q}_0$ ). The field `tf` indicates the final time  $t_f$  when the simulation stops. This is usually  $t_0 + N$  where  $N$  is the optimization horizon. Both fields are expressed in seconds. The field `q0` indicates the initial state guess at time instant  $t_0$ ,  $\mathbf{q}_0$ , and finally `c_chain` the sequence of controls. If we assume that the horizon is  $N := t_f - t_0$  with  $(t_f - t_0) \in \mathbb{R}_{>0}$ , then the user is expected to provide  $N - 1$  controls. Finally, the field `est_u0` contains the control energy estimate at time  $t_0$ , the value  $\hat{\mathbf{u}}(t_{-1})$ . If  $t_0$  is the initial time step, then `est_u0` is set to zero.

```
1 % TODO
```

**Listing A.5.** Runge-Kutta fourth order method for numerical integration of the model.

Before calling structure `dat`, it is necessary to define the scaling factors  $v_1, v_2, \dots, v_\rho$  and  $\tau_1, \tau_2, \dots, \tau_\rho$  for the path parameters, and  $v_{\rho+1}, v_{\rho+2}, \dots, v_{\rho+\sigma}$  and  $\tau_{\rho+1}, \tau_{\rho+2}, \dots, \tau_{\rho+\sigma}$  for the computation parameters. For example, we suppose there is one path and one computation parameters.

```
1 nu1 = -(max_t-min_t)/min_c1;
2 tau1 = -min_c1*(min_t-max_t)/min_c1+min_t;

4 nu2 = (g_max_c2-g_min_c2)/(max_c2-min_c2);
5 tau2 = min_c2*(g_min_c2-g_max_c2)/(max_c2-min_c2)+g_min_c2;

7 nu = [nu1;nu2];
8 tau = [tau1;tau2];
```

**Listing A.6.** Implementation of path and computation parameters scaling factors.

**Listing A.6** has to run before **Listing A.2**.

The scaling factors can be defined according to Equation (4.50) for the path parameter on Line 1 and according to Equation (4.51) for the computation parameter on Line 4.

Let us assume that the one path parameter  $c_1$  doesn't change for the stages  $i = \{1, 2, \dots, l\} \cdot \text{max\_t}$  and  $\text{min\_t}$  are the maximum and minimum times that correspond to the time needed to hypothetically execute the path with parameter  $c_1 = \bar{c}_1$  and with parameter value  $c_1 = \underline{c}_1$ . A guess for these values can be obtained empirically; we obtained them by running the simulation. They correspond to  $\bar{t}$  and  $\underline{t}$  in Equation (4.50).

Let us further assume that the one computation parameter  $c_2$  doesn't change for the stages  $i = \{1, 2, \dots, l\} \cdot \text{max\_c2}$  and  $\text{min\_c2}$  are the minimum and maximum configuration of the computation parameter  $c_2$  defined in Definition 2.3.1.  $g_{\text{max\_c2}}$  and  $g_{\text{min\_c2}}$  are values retrieved from `powprofiler` and they correspond to  $g(\bar{c}_2)$  and  $g(\underline{c}_2)$  in Equation (4.51). Function  $g$  is formally defined in Definition 4.1.1.

A possible call to the functions `build_model` and `evolve_model_euler` or `evolve_model_rk4` from Listing A.1 and Listing A.3 or Listing A.5 is illustrated in Listing A.7.

```

1 model = build_model(dat);
2 [q,y] = evolve_model_euler(model,dat,init);
```

**Listing A.7.** An example to build a differential model and evolve it over a horizon  $N$ .

A generic routine to plot the resulting modeled energy and the coefficients  $\mathbf{q}$  in Equation (4.12) is illustrated in [Listing A.8](#).

```

1 time = dat.t0:model.delta_T:dat.tf;

3 figure;
4 plot(time,y)
5 title('energy evolution');
6 ylabel('power (W)');
7 xlabel('time (sec)');

9 figure;
10 m = 2*dat.r+1;
11 t = tiledlayout(m,1);
12 title_str = {'alpha','beta'};
13 nexttile,plot(time,q(1,1:end))
14 title(strcat(title_str(1),0));

16 for i=2:m
17     nexttile,plot(time,q(i,1:end))
18     title(strcat(title_str(mod(i,2)+1),i-1));
19 end

21 title(t,'coefs evolution');
22 xlabel(t,'time (sec)');
23 ylabel(t,'value');
```

**Listing A.8.** A generic plotting routine for them modeled energy and coefficients evolution.

We describe the estimation of  $T$ , the period in structure `dat`, in [Subsection A.2.1](#). We generate the  $N - 1$  controls in [Section A.4](#). For benchmarking, one can define the lowest (or similarly the highest) level of parameters with [Listing A.9](#). It has to run before defining the structure `init` in [Listing A.4](#).

```

1 c_chain = min_c1*ones(1,N-1);
2 c_chain = [c_chain;min_c2*ones(1,N-1)];
```

**Listing A.9.** Implementation of the lowest possible control for benchmarking.

## A.2 State Estimation

### A.2.1 Estimation of the period

```

1 % iterating trajectories in the plan to get the constant n (to measure the
  period)
2 d = [];
3 p = [0; 0];
4 n = 0;

6 for traj = transpose(path) % per each trajectory
```

```

8     traj = split(traj, ';');
9     traj = str2sym(traj(3));

11    x = p(1);
12    y = p(1);
13    di = double(subs(traj));
14    x = p(1)-sp(1);
15    y = p(2)-sp(2);

17    if ismember(double(subs(traj)), d)
18        break;
19    else
20        d = [d di];
21    end

23    n = n+1;
24 end

26 fprintf('n is %d\n', n);

```

Listing A.10. Estimation of the period.

## A.2.2 Estimation of the state

```

1 minus_q1 = Ad*q0+B*est_u();

3 minus_P1 = Ad*P0*Ad.'+Q;

5 K1 = (minus_P1*C.')*(C*minus_P1*C.'+R)^-1;
6 q1 = minus_q1+K1*(pow(end)-C*minus_q1);
7 P1 = (eye(size(q0,1))+K1*C)*minus_P1;

9 q0 = q1;
10 P0 = P1;

12 y = [y; C*q1];
13 q = [q q0];

```

Listing A.11. Estimation of the state using Kalman filter.

## A.3 Guidance

```

1 function [u_theta] = gvf_control_2D(p, dot_p, ke, kd, path, grad, hess, dir)

3     if (nargin(path) > 1) % function handle has two arguments (circle)
4         e = path(p(:,1), p(:,2));
5         n = grad(p(:,1), p(:,2));
6     else % one argument (line)
7         e = path(p(:,1));
8         n = grad();
9     end

11    H = hess();
12    E = [0 -1; 1 0];
13    tau = dir*E*n;

```

```

15 dot_pd = tau_ke*enn; % (7)
16 ddot_pd = (E_ke*eye(2))*H*dot_p-ke*n'*dot_p*n; % (10)
17 ddot_pdhat = -E*(dot_pd*dot_pd')*E*ddot_pd/norm(dot_pd)^3; % (9)

19 dot_Xid = ddot_pdhat'*E*dot_pd/norm(dot_pd); % (13)

21 u_theta = dot_Xid+kd*dot_p'*E*dot_pd/(norm(dot_p)*norm(dot_pd)); % (16)
22 end

```

Listing A.12. Guidance vector field.

```

1 u_theta = gvf_control_2D(log_p(:,end).',pdot,ke,kd,path,grad,hess,dir);

3 th_delta = kp*(hd-h)-kvv*vv;
4 wbx = dot(w,[cos(theta),sin(theta)]);
5 vs = cth*(th_nominal+th_delta)+wbx;
6 L = cl*vs*vs;
7 av = 1/m*(L-W);

9 vv = vv+av*delta_T;
10 h = h+vv*delta_T;

12 % Horizontal unicycle model
13 sh = cth*(th_nominal+th_delta);
14 pdot = sh*[cos(theta);sin(theta)]+w;

16 p = p+pdot*delta_T;
17 theta = theta+u_theta*delta_T;
18 theta = wrapToPi(theta); % normalizing between -pi and pi

```

Listing A.13. Call to the guidance function and dynamics evolution.

## A.4 Optimal Control Generation

```

1 function [c_chain q_chain] = mpc(min_c1,max_c1,min_c2,max_c2,c1,c2,N,eu,b0,
2 b,qc,int_v,q0,Ad,B,C,u,est_u,k,delta_T,r)
2 import casadi.* % import casadi for optimal control

4 interval = k+delta_T:delta_T:k+N; % no k+1 in the formula as we add the
5 % initial condition implicitly
6 hh = length(interval);

8 opti = casadi.Opti(); % define opt problem
9 Q = opti.variable(2*r+1,N);
10 U = opti.variable(2,N-1);
11 L = opti.variable(1,N);
12 log_Q = opti.variable(2*r+1, hh);
13 log_b = opti.variable(1, hh);

15 opti.set_initial(Q(:,1),q0);

17 opti.subject_to(C*Q(:,1)-b0*qc*int_v <= 0);
18 opti.subject_to(U(1,:)==c1);
19 opti.subject_to(min_c2 <= U(2,:)<= max_c2);
20 opti.subject_to(min_c1 <= U(1,:)<= max_c1);

```

```

22     eeu = eu; % control estimate (from model)
23     eeu = est_u(c1,c2);

25     jjj = 1;
26     dQ = q0; % initial state
27     log_Q(:,1) = dQ;

29     for jj=1:hh-1
30         dQ = Ad*dQ+B*u(eeu,eeu);
31         eeu = eeu;
32         b0 = b0+delta_T*b(C*dQ); % battery dynamics

34         log_Q(:,jj+1) = dQ;
35         log_b(jj+1) = b0;

37         if mod(jj,1/delta_T) == 0 % every sum in the MPC
38             L(jjj) = C*dQ;

40             if (jjj < N)
41                 eeu = est_u(U(1,jjj),U(2,jjj));
42             end

44             opti.subject_to(Q(:,jjj+1)-dQ == 0); % dynamics const
45             opti.subject_to(C*Q(:,jjj+1)-b0*qc*int_v <= 0); % battery const

47             jjj = jjj+1;
48         end
49     end

51     opti.minimize(-sum(L.^2));
52     opti.solver('ipopt');

54     try
55         sol = opti.solve();
56         c_chain = sol.value(U); % optimal control u on N
57     catch
58         c_chain = [ones(1,N-1)*min_c1;ones(1,N-1)*min_c2]; % there is no
59             control which satisfies consts
60     end

61     q_chain = opti.debug.value(Q);
62 end

```

Listing A.14. Model predictive control.



# References

1. Abramov, A., Pauwels, K., Papon, J., Worgotter, F., and Dellen, B. (2012). "Real-time segmentation of stereo videos on a portable system with a mobile gpu". In: *IEEE Transactions on Circuits and Systems for Video Technology* 22.9, pp. 1292–1305 (cit. on p. 1).
2. Acar, E. U., Choset, H., Rizzi, A. A., Atkar, P. N., and Hull, D. (2002). "Morse Decompositions for Coverage Tasks". In: *The International Journal of Robotics Research* 21.4, pp. 331–344 (cit. on p. 36).
3. Acevedo, J. J., Arrue, B. C., Diaz-Banez, J. M., Ventura, I., Maza, I., and Ollero, A. (2014). "One-to-one coordination algorithm for decentralized area partition in surveillance missions with a team of aerial robots". In: *Journal of Intelligent & Robotic Systems* 74.1, pp. 269–285 (cit. on p. 4).
4. Ahmadzadeh, A., Keller, J., Pappas, G., Jadbabaie, A., and Kumar, V. (2008). "An Optimization-Based Approach to Time-Critical Cooperative Surveillance and Coverage with UAVs". In: *Experimental Robotics: The 10th International Symposium on Experimental Robotics*. Berlin, Heidelberg: Springer Berlin Heidelberg, pp. 491–500 (cit. on p. 38).
5. Aljanobi, A., Al-Hamed, S., and Al-Suhaiibani, S. (2010). "A setup of mobile robotic unit for fruit harvesting". In: *19th International Workshop on Robotics in Alpe-Adria-Danube Region (RAAD 2010)*. IEEE, pp. 105–108 (cit. on p. 2).
6. De-An, Z., Jidong, L., Wei, J., Ying, Z., and Yu, C. (2011). "Design and control of an apple harvesting robot". In: *Biosystems engineering* 110.2, pp. 112–122 (cit. on p. 2).
7. Anderson, J. D. (2005). *Introduction to flight*. McGraw-Hill Higher Education (cit. on pp. 3, 4).
8. Anguelov, D., Koller, D., Parker, E., and Thrun, S. (2004). "Detecting and modeling doors with mobile robots". In: *IEEE International Conference on Robotics and Automation, 2004. Proceedings. ICRA '04. 2004*. Vol. 4, pp. 3777–3784 (cit. on p. 42).
9. Araújo, J., Sujit, P., and Sousa, J. (2013). "Multiple UAV area decomposition and coverage". In: *2013 IEEE Symposium on Computational Intelligence for Security and Defense Applications (CISDA)*, pp. 30–37 (cit. on pp. 38, 39).
10. Arkin, E., Fekete, S., and Mitchell, J. (1993). "The lawnmower problem". In: *Proceedings of the 5th Canadian Conference on Computational Geometry*, pp. 461–466 (cit. on p. 36).
11. Arkin, E. M., Bender, M. A., Demaine, E. D., Fekete, S. P., Mitchell, J. S. B., and Sethia, S. (2001). "Optimal Covering Tours with Turn Costs". In: *Proceedings of the Twelfth Annual ACM-SIAM Symposium on Discrete Algorithms*. USA: Society for Industrial and Applied Mathematics, pp. 138–147 (cit. on pp. 37, 40).
12. — (2005). "Optimal Covering Tours with Turn Costs". In: *SIAM Journal on Computing* 35.3, pp. 531–566 (cit. on pp. 37, 40).
13. Arkin, E. M., Fekete, S. P., and Mitchell, J. S. (2000). "Approximation algorithms for lawn mowing and milling". In: *Computational Geometry* 17.1, pp. 25–50 (cit. on p. 36).
14. Arkin, E. M. and Hassin, R. (1994). "Approximation algorithms for the geometric covering salesman problem". In: *Discrete Applied Mathematics* 55.3, pp. 197–218 (cit. on p. 36).

15. Artemenko, O., Dominic, O. J., Andryeyev, O., and Mitschele-Thiel, A. (2016). "Energy-Aware Trajectory Planning for the Localization of Mobile Devices Using an Unmanned Aerial Vehicle". In: *2016 25th International Conference on Computer Communication and Networks (ICCCN)*, pp. 1–9 (cit. on p. 41).
16. Bailey, P. E., Lowenthal, D. K., Ravi, V., Rountree, B., Schulz, M., and De Supinski, B. R. (2014). "Adaptive configuration selection for power-constrained heterogeneous systems". In: *2014 43rd International Conference on Parallel Processing*. IEEE, pp. 371–380 (cit. on p. 28).
17. Barrientos, A., Colorado, J., Cerro, J. d., Martinez, A., Rossi, C., Sanz, D., and Valente, J. (2011). "Aerial remote sensing in agriculture: A practical approach to area coverage and path planning for fleets of mini aerial robots". In: *Journal of Field Robotics* 28.5, pp. 667–689 (cit. on p. 38).
18. Basilico, N. and Carpin, S. (2015). "Deploying teams of heterogeneous UAVs in cooperative two-level surveillance missions". In: *2015 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 610–615 (cit. on p. 4).
19. Bellman, R. E. (1957). *Dynamic Programming*. Princeton: Princeton University Press (cit. on p. 70).
20. Benini, L., Castelli, G., Macii, A., Macii, E., Poncino, M., and Scarsi, R. (2001). "Discrete-time battery models for system-level low-power design". In: *IEEE Transactions on Very Large Scale Integration (VLSI) Systems* 9.5, pp. 630–640 (cit. on pp. 33, 34).
21. Böhme, T. J. and Frank, B. (2017). "Indirect Methods for Optimal Control". In: *Hybrid Systems, Optimal Control and Hybrid Vehicles: Theory, Methods and Applications*. Cham: Springer International Publishing, pp. 215–231 (cit. on p. 71).
22. Bouzid, Y., Bestaoui, Y., and Siguerdidjane, H. (2017). "Quadrotor-UAV optimal coverage path planning in cluttered environment with a limited onboard energy". In: *2017 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 979–984 (cit. on p. 41).
23. Brateman, J., Xian, C., and Lu, Y.-h. (2006). "Energy-Efficient Scheduling for Autonomous Mobile Robots". In: *2006 IFIP International Conference on Very Large Scale Integration*, pp. 361–366 (cit. on p. 42).
24. Bridges, R. A., Imam, N., and Mintz, T. M. (2016). "Understanding GPU Power: A Survey of Profiling, Modeling, and Simulation Methods". In: *ACM Comput. Surv.* 49.3, pp. 1–27 (cit. on p. 31).
25. Bryson, A. E. and Ho, Y.-C. (1975). *Applied optimal control: optimization, estimation and control*. Hemisphere Publishing Corporation (cit. on pp. 70, 72).
26. Bürkle, A. (2009). "Collaborating miniature drones for surveillance and reconnaissance". In: *Unmanned/Unattended Sensors and Sensor Networks VI*. Vol. 7480. International Society for Optics and Photonics, 74800H (cit. on p. 4).
27. Burri, M., Gasser, L., Käch, M., Krebs, M., Laube, S., Ledergerber, A., Meier, D., Michaud, R., Mosimann, L., Müri, L., et al. (2013). "Design and control of a spherical omnidirectional blimp". In: *2013 IEEE/RSJ International Conference on Intelligent Robots and Systems*. IEEE, pp. 1873–1879 (cit. on p. 5).
28. Cabreira, T. M., Brisolara, L. B., and Ferreira Jr., P. R. (2019). "Survey on Coverage Path Planning with Unmanned Aerial Vehicles". In: *Drones* 3.1 (cit. on pp. 5, 34, 39).
29. Cabreira, T. M., Franco, C. D., Ferreira, P. R., and Buttazzo, G. C. (2018). "Energy-Aware Spiral Coverage Path Planning for UAV Photogrammetric Applications". In: *IEEE Robotics and Automation Letters* 3.4, pp. 3662–3668 (cit. on pp. 34, 41).
30. Calore, E., Schifano, S. F., and Tripiccione, R. (2015). "Energy-performance tradeoffs for HPC applications on low power processors". In: *European Conference on Parallel Processing*. Springer, pp. 737–748 (cit. on p. 30).
31. Camacho, E. F. and Alba, C. B. (2007). *Model predictive control*. London: Springer-Verlag (cit. on p. 71).
32. Cao, Z. L., Huang, Y., and Hall, E. L. (1988). "Region filling operations with random obstacle avoidance for mobile robots". In: *Journal of Robotic Systems* 5.2, pp. 87–102 (cit. on p. 36).
33. Chen, X. and Touba, N. A. (2009). "Ch. 2 - Fundamentals of CMOS design". In: *Electronic Design Automation*. Ed. by L.-T. Wang, Y.-W. Chang, and K.-T. Cheng. Boston: Morgan Kaufmann, pp. 39–95 (cit. on p. 28).

34. Cheng, K. P., Mohan, R. E., Nhan, N. H. K., and Le, A. V. (2019). "Graph Theory-Based Approach to Accomplish Complete Coverage Path Planning Tasks for Reconfigurable Robots". In: *IEEE Access* 7, pp. 94642–94657 (cit. on p. 36).
35. Choset, H., Acar, E., Rizzi, A., and Luntz, J. (2000). "Exact cellular decompositions in terms of critical points of Morse functions". In: *Proceedings 2000 ICRA. Millennium Conference. IEEE International Conference on Robotics and Automation. Symposia Proceedings (Cat. No.00CH37065)*. Vol. 3, pp. 2270–2277 (cit. on p. 36).
36. Choset, H. (2001). "Coverage for robotics—A survey of recent results". In: *Annals of Mathematics and Artificial Intelligence* 31, pp. 113–126 (cit. on pp. 34, 36, 39).
37. Choset, H. M., Lynch, K. M., Hutchinson, S., Kantor, G., Burgard, W., Kavraki, L., Thrun, S., and Arkin, R. C. (2005). *Principles of robot motion: theory, algorithms, and implementation*. MIT press (cit. on p. 35).
38. Choset, H. and Pignon, P. (1998). "Coverage Path Planning: The Boussphedon Cellular Decomposition". In: *Field and Service Robotics*. Springer London, pp. 203–209 (cit. on p. 36).
39. Chowdhury, P. and Chakrabarti, C. (2005). "Static task-scheduling algorithms for battery-powered DVS systems". In: *IEEE Transactions on Very Large Scale Integration (VLSI) Systems* 13.2, pp. 226–237 (cit. on p. 32).
40. Collange, S., Defour, D., and Tisserand, A. (2009). "Power Consumption of GPUs from a Software Perspective". In: *Computational Science – ICCS 2009*. Ed. by G. Allen, J. Nabrzyski, E. Seidel, G. D. van Albada, J. Dongarra, and P. M. A. Sloot. Berlin, Heidelberg: Springer Berlin Heidelberg, pp. 914–923 (cit. on p. 31).
41. Colombatti, G., Aboudan, A., La Gloria, N., Debei, S., and Flamini, E. (2011). "Lighter-Than-Air UAV with slam capabilities for mapping applications and atmpsphere analysys." In: *Memorie della Società Astronomica Italiana Supplementi* 16, p. 42 (cit. on p. 5).
42. Colomina, I. and Molina, P. (2014). "Unmanned aerial systems for photogrammetry and remote sensing: A review". In: *ISPRS Journal of Photogrammetry and Remote Sensing* 92, pp. 79–97 (cit. on p. 4).
43. Corke, P. (2017). *Robotics, Vision and Control: Fundamental Algorithms in MATLAB*. 2nd. Springer Publishing Company, Incorporated (cit. on pp. 1, 5).
44. Crow, B. P., Widjaja, I., Kim, J. G., and Sakai, P. T. (1997). "IEEE 802.11 wireless local area networks". In: *IEEE Communications magazine* 35.9, pp. 116–126 (cit. on p. 25).
45. Cui, J. Q., Phang, S. K., Ang, K. Z., Wang, F., Dong, X., Ke, Y., Lai, S., Li, K., Li, X., Lin, F., et al. (2015). "Drones for cooperative search and rescue in post-disaster situation". In: *2015 IEEE 7th international conference on cybernetics and intelligent systems (CIS) and IEEE conference on robotics, automation and mechatronics (RAM)*. IEEE, pp. 167–174 (cit. on p. 4).
46. Czarnul, P., Proficz, J., and Krzywaniak, A. (2019). "Energy-aware high-performance computing: survey of state-of-the-art tools, techniques, and environments". In: *Scientific Programming* 2019 (cit. on p. 28).
47. Dadkhah, N. and Mettler, B. (2012). "Survey of motion planning literature in the presence of uncertainty: Considerations for UAV guidance". In: *Journal of Intelligent & Robotic Systems* 65.1, pp. 233–246 (cit. on p. 39).
48. Daponte, P., De Vito, L., Glielmo, L., Iannelli, L., Liuzza, D., Picariello, F., and Silano, G. (2019). "A review on the use of drones for precision agriculture". In: *IOP Conference Series: Earth and Environmental Science*. Vol. 275. 1. IOP Publishing, p. 012022 (cit. on pp. 2, 4, 8).
49. De Marina, H. G., Kapitanyuk, Y. A., Bronz, M., Hattenberger, G., and Cao, M. (2017). "Guidance algorithm for smooth trajectory tracking of a fixed wing UAV flying in wind flows". In: *2017 IEEE International Conference on Robotics and Automation (ICRA)*. IEEE, pp. 5740–5745 (cit. on pp. 9, 75, 76).
50. Di Franco, C. and Buttazzo, G. (2015). "Energy-Aware Coverage Path Planning of UAVs". In: *2015 IEEE International Conference on Autonomous Robot Systems and Competitions*, pp. 111–117 (cit. on pp. 39, 40).
51. — (2016). "Coverage path planning for UAVs photogrammetry with energy and resolution constraints". In: *Journal of Intelligent & Robotic Systems* 83.3, pp. 445–462 (cit. on p. 40).

52. Dille, M. and Singh, S. (2013). "Efficient Aerial Coverage Search in Road Networks". In: *AIAA Guidance, Navigation, and Control (GNC) Conference*, pp. 1–20 (cit. on p. 41).
53. Dong, F., Heinemann, W., and Kasper, R. (2011). "Development of a row guidance system for an autonomous robot for white asparagus harvesting". In: *Computers and Electronics in Agriculture* 79.2, pp. 216–225 (cit. on p. 2).
54. Doyle, M., Fuller, T. F., and Newman, J. (1993). "Modeling of Galvanostatic Charge and Discharge of the Lithium/Polymer/Insertion Cell". In: *Journal of The Electrochemical Society* 140.6, pp. 1526–1533 (cit. on p. 33).
55. Dressler, F. and Dietrich, I. (2006). "Lifetime Analysis in Heterogeneous Sensor Networks". In: *9th EUROMICRO Conference on Digital System Design (DSD'06)*, pp. 606–616 (cit. on p. 35).
56. Dressler, F. and Fuchs, G. (2005). "Energy-aware operation and task allocation of autonomous robots". In: *Proceedings of the Fifth International Workshop on Robot Motion and Control, 2005. RoMoCo'05*. IEEE, pp. 163–168 (cit. on pp. 35, 42).
57. Edan, Y., Rogozin, D., Flash, T., and Miles, G. E. (2000). "Robotic melon harvesting". In: *IEEE Transactions on Robotics and Automation* 16.6, pp. 831–835 (cit. on p. 2).
58. Eiselt, H. A. and Laporte, G. (2000). "A Historical Perspective on Arc Routing". In: *Arc Routing: Theory, Solutions and Applications*. Boston, MA: Springer US, pp. 1–16 (cit. on p. 41).
59. Erickson, D. (2003). "Non-learning artificial neural network approach to motion planning for the Pioneer robot". In: *Proceedings 2003 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS 2003) (Cat. No.03CH37453)*. Vol. 1, pp. 112–117 (cit. on p. 42).
60. Fabiani, P., Fuertes, V., Piquereau, A., Mampey, R., and Teichteil-Königsbuch, F. (2007). "Autonomous flight and navigation of VTOL UAVs: from autonomy demonstrations to out-of-sight flights". In: *Aerospace Science and Technology* 11.2-3, pp. 183–193 (cit. on p. 44).
61. Fekete, S., Arkin, E., and Mitchell, J. (1994). "The lawnmower problem and other geometric path covering problems". In: *15th International Symposium on Mathematical Programming* (cit. on p. 36).
62. Fisher, M., Dennis, L., and Webster, M. (2013). "Verifying autonomous systems". In: *Communications of the ACM* 56.9, pp. 84–93 (cit. on p. 1).
63. Flautner, K., Reinhardt, S., and Mudge, T. (2001). "Automatic Performance Setting for Dynamic Voltage Scaling". In: *Proceedings of the 7th Annual International Conference on Mobile Computing and Networking*. MobiCom '01. Rome, Italy: Association for Computing Machinery, pp. 260–271 (cit. on p. 28).
64. Floreano, D. and Wood, R. J. (2015). "Science, technology and the future of small autonomous drones". In: *Nature* 521.7553, pp. 460–466 (cit. on p. 5).
65. Fomenko, A. T. and Kunii, T. L. (1997). *Topological modeling for visualization*. Springer Japan (cit. on p. 41).
66. Fuchs, G., Truchat, S., and Dressler, F. (2006). "Distributed Software Management in Sensor Networks using Profiling Techniques". In: *2006 1st International Conference on Communication Systems Software Middleware*, pp. 1–6 (cit. on p. 35).
67. Fui Liew, C., DeLatte, D., Takeishi, N., and Yairi, T. (2017). "Recent Developments in Aerial Robotics: A Survey and Prototypes Overview". In: *arXiv e-prints*, arXiv-1711 (cit. on p. 5).
68. Gabriely, Y. and Rimon, E. (2002). "Spiral-STC: an on-line coverage algorithm of grid environments by a mobile robot". In: *Proceedings 2002 IEEE International Conference on Robotics and Automation (Cat. No.02CH37292)*. Vol. 1, pp. 954–960 (cit. on p. 36).
69. Galceran, E. and Carreras, M. (2013). "A survey on coverage path planning for robotics". In: *Robotics and Autonomous Systems* 61.12, pp. 1258–1276 (cit. on pp. 36–39).
70. García-Martín, E., Rodrigues, C. F., Riley, G., and Grahn, H. (2019). "Estimation of energy consumption in machine learning". In: *Journal of Parallel and Distributed Computing* 134, pp. 75–88 (cit. on pp. 30, 31).
71. Geem, Z. W. (2009). *Music-inspired harmony search algorithm: theory and applications*. Vol. 191. Springer (cit. on p. 41).

72. Goerzen, C., Kong, Z., and Mettler, B. (2010). "A survey of motion planning algorithms from the perspective of autonomous UAV guidance". In: *Journal of Intelligent and Robotic Systems* 57.1, pp. 65–100 (cit. on p. 39).
73. Gold, S. (1997). "A PSPICE macromodel for lithium-ion batteries". In: *The Twelfth Annual Battery Conference on Applications and Advances*, pp. 215–222 (cit. on p. 33).
74. Gonçalves, V. M., Pimenta, L. C., Maia, C. A., Dutra, B. C., and Pereira, G. A. (2010). "Vector fields for robot navigation along time-varying curves in  $n$ -dimensions". In: *IEEE Transactions on Robotics* 26.4, pp. 647–659 (cit. on p. 75).
75. González-Jorge, H., Martínez-Sánchez, J., Bueno, M., et al. (2017). "Unmanned aerial systems for civil applications: A review". In: *Drones* 1.1, p. 2 (cit. on p. 4).
76. Goraczko, M., Liu, J., Lymberopoulos, D., Matic, S., Priyantha, B., and Zhao, F. (2008). "Energy-optimal software partitioning in heterogeneous multiprocessor embedded systems". In: *2008 45th ACM/IEEE Design Automation Conference*. IEEE, pp. 191–196 (cit. on p. 30).
77. Hajjaj, S. S. H. and Sahari, K. S. M. (2014). "Review of research in the area of agriculture mobile robots". In: *The 8th International Conference on Robotic, Vision, Signal Processing & Power Applications*. Springer, pp. 107–117 (cit. on p. 2).
78. Hasan, A., Skriver, M., and Johansen, T. A. (2018). "Exogenous kalman filter for state-of-charge estimation in lithium-ion batteries". In: *2018 IEEE Conference on Control Technology and Applications (CCTA)*. IEEE, pp. 1403–1408 (cit. on pp. 33, 34, 54).
79. Haugen, J. and Imsland, L. (2016). "Monitoring Moving Objects Using Aerial Mobile Sensors". In: *IEEE Transactions on Control Systems Technology* 24.2, pp. 475–486 (cit. on p. 5).
80. Hayat, S., Yanmaz, E., Brown, T. X., and Bettstetter, C. (2017). "Multi-objective UAV path planning for search and rescue". In: *2017 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 5569–5574 (cit. on pp. 4, 38).
81. Hobby, H. (2020). *Opterra 2m Wing BNF Basic*. URL: <https://www.horizonhobby.com/opterra-2m-wing-bnf-basic-p-ef111150> (visited on 02/02/2020) (cit. on p. 2).
82. Hoffer, N. V., Coopmans, C., Jensen, A. M., and Chen, Y. (2014). "A survey and categorization of small low-cost unmanned aerial vehicle system identification". In: *Journal of Intelligent & Robotic Systems* 74.1, pp. 129–145 (cit. on p. 5).
83. Hong, I., Kirovski, D., Qu, G., Potkonjak, M., and B, S. M. (1999). "Power optimization of variable-voltage core-based systems". In: *IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems* 18.12, pp. 1702–1714 (cit. on p. 32).
84. Hong, S. and Kim, H. (2010). "An integrated GPU power and performance model". In: *ACM SIGARCH Computer Architecture News*. Vol. 38. 3. ACM, pp. 280–289 (cit. on p. 31).
85. Horowitz, M. (2014). "Computing's energy problem (and what we can do about it)". In: *2014 IEEE International Solid-State Circuits Conference Digest of Technical Papers (ISSCC)*. IEEE, pp. 10–14 (cit. on p. 28).
86. Hu, X., Li, S., and Peng, H. (2012). "A comparative study of equivalent circuit models for Li-ion batteries". In: *Journal of Power Sources* 198, pp. 359–367 (cit. on p. 33).
87. Huang, W. (2001). "Optimal line-sweep-based decompositions for coverage algorithms". In: *Proceedings 2001 ICRA. IEEE International Conference on Robotics and Automation (Cat. No.01CH37164)*. Vol. 1, pp. 27–32 (cit. on pp. 36, 37, 40).
88. Jaramillo-Avila, U., Aitken, J. M., and Anderson, S. R. (2019). "Visual saliency with foveated images for fast object detection and recognition in mobile robots using low-power embedded GPUs". In: *2019 19th International Conference on Advanced Robotics (ICAR)*. IEEE, pp. 773–778 (cit. on p. 1).
89. Johansen, T. A. and Fossen, T. I. (2017). "The exogenous kalman filter (xkf)". In: *International Journal of Control* 90.2, pp. 161–167 (cit. on p. 33).
90. Kapitanyuk, Y. A., Proskurnikov, A. V., and Cao, M. (2017). "A guiding vector-field algorithm for path-following control of nonholonomic mobile robots". In: *IEEE Transactions on Control Systems Technology* 26.4, pp. 1372–1385 (cit. on p. 75).

91. Karaca, Y., Cicek, M., Tatli, O., Sahin, A., Pasli, S., Beser, M. F., and Turedi, S. (2018). "The potential use of unmanned aircraft systems (drones) in mountain search and rescue operations". In: *The American journal of emergency medicine* 36.4, pp. 583–588 (cit. on p. 4).
92. Karaman, S. and Frazzoli, E. (2011). "Sampling-based algorithms for optimal motion planning". In: *The International Journal of Robotics Research* 30.7, pp. 846–894 (cit. on p. 41).
93. Karaman, S., Walter, M. R., Perez, A., Frazzoli, E., and Teller, S. (2011). "Anytime Motion Planning using the RRT\*". In: *2011 IEEE International Conference on Robotics and Automation*, pp. 1478–1483 (cit. on p. 41).
94. Kasichayanula, K., Terpstra, D., Luszczek, P., Tomov, S., Moore, S., and Peterson, G. D. (2012). "Power Aware Computing on GPUs". In: *2012 Symposium on Application Accelerators in High Performance Computing*, pp. 64–73 (cit. on p. 31).
95. Keane, J. F. and Carr, S. S. (2013). "A brief history of early unmanned aircraft". In: *Johns Hopkins APL Technical Digest* 32.3, pp. 558–571 (cit. on p. 3).
96. Kellermann, R., Biehle, T., and Fischer, L. (2020). "Drones for parcel and passenger transportation: A literature review". In: *Transportation Research Interdisciplinary Perspectives* 4, p. 100088 (cit. on p. 4).
97. Kim, C. H. and Kim, B. K. (2005). "Energy-saving 3-step velocity control algorithm for battery-powered wheeled mobile robots". In: *Proceedings of the 2005 IEEE international conference on robotics and automation*. IEEE, pp. 2375–2380 (cit. on p. 34).
98. Kim, H. and Kim, B.-K. (2008). "Minimum-energy translational trajectory planning for battery-powered three-wheeled omni-directional mobile robots". In: *2008 10th International Conference on Control, Automation, Robotics and Vision*. IEEE, pp. 1730–1735 (cit. on p. 34).
99. Kim, T. and Qiao, W. (2011). "A Hybrid Battery Model Capable of Capturing Dynamic Circuit Characteristics and Nonlinear Capacity Effects". In: *IEEE Transactions on Energy Conversion* 26.4, pp. 1172–1180 (cit. on p. 33).
100. Kim, T., Qiao, W., and Qu, L. (2019). "An Enhanced Hybrid Battery Model". In: *IEEE Transactions on Energy Conversion* 34.4, pp. 1848–1858 (cit. on p. 33).
101. Kim, Y. G., Kong, J., and Chung, S. W. (2018). "A Survey on Recent OS-Level Energy Management Techniques for Mobile Processing Units". In: *IEEE Transactions on Parallel and Distributed Systems* 29.10, pp. 2388–2401 (cit. on p. 30).
102. Kirk, D. E. (2004). *Optimal control theory: an introduction*. Courier Corporation (cit. on pp. 69, 72).
103. Kreciglowa, N., Karydis, K., and Kumar, V. (2017). "Energy efficiency of trajectory generation methods for stop-and-go aerial robot navigation". In: *2017 International Conference on Unmanned Aircraft Systems (ICUAS)*. IEEE, pp. 656–662 (cit. on p. 38).
104. Kuo, B. (1967). *Automatic Control Systems*. Electrical engineering series. Prentice-Hall (cit. on p. 59).
105. Kwon, W. H. and Han, S. H. (2005). *Receding horizon control: model predictive control for state models*. London: Springer-Verlag (cit. on p. 71).
106. Lahijanian, M., Svorenova, M., Morye, A. A., Yeomans, B., Rao, D., Posner, I., Newman, P., Kress-Gazit, H., and Kwiatkowska, M. (2018). "Resource-Performance Tradeoff Analysis for Mobile Robots". In: *IEEE Robotics and Automation Letters* 3.3, pp. 1840–1847 (cit. on p. 42).
107. LaValle, S. M. (2006). *Planning algorithms*. Cambridge university press (cit. on pp. 27, 34–36, 39, 41, 70).
108. Lee, B. C. and Brooks, D. M. (2006a). "Accurate and Efficient Regression Modeling for Microarchitectural Performance and Power Prediction". In: *Proceedings of the 12th International Conference on Architectural Support for Programming Languages and Operating Systems*. New York, NY, USA: Association for Computing Machinery, pp. 185–194 (cit. on p. 32).
109. — (2006b). "Statistically rigorous regression modeling for the microprocessor design space". In: *ISCA-33: Workshop on Modeling, Benchmarking, and Simulation* (cit. on p. 32).
110. Lee, S., Kim, J., Lee, J., and Cho, B. (2008). "State-of-charge and capacity estimation of lithium-ion battery using a new open-circuit voltage versus state-of-charge". In: *Journal of Power Sources* 185.2, pp. 1367–1373 (cit. on p. 33).

111. Lee, T.-K., Baek, S.-H., Choi, Y.-H., and Oh, S.-Y. (2011). "Smooth coverage path planning and control of mobile robots based on high-resolution grid map representation". In: *Robotics and Autonomous Systems* 59.10, pp. 801–812 (cit. on p. 36).
112. Lemay, M., Michaud, F., Letourneau, D., and Valin, J.-M. (2004). "Autonomous initialization of robot formations". In: *IEEE International Conference on Robotics and Automation, 2004. Proceedings. ICRA '04. 2004*. Vol. 3, pp. 3018–3023 (cit. on p. 42).
113. Leng, J., Hetherington, T., ElTantawy, A., Gilani, S., Kim, N. S., Aamodt, T. M., and Reddi, V. J. (2013). "GPUWatch: Enabling Energy Optimizations in GPGPUs". In: *SIGARCH Comput. Archit. News* 41.3, pp. 487–498 (cit. on p. 31).
114. Li, Y., Chen, H., Joo Er, M., and Wang, X. (2011). "Coverage path planning for UAVs based on enhanced exact cellular decomposition method". In: *Mechatronics* 21.5. Special Issue on Development of Autonomous Unmanned Aerial Vehicles, pp. 876–885 (cit. on pp. 36, 40).
115. Li, Z., Liu, J., Li, P., and Li, W. (2008). "Analysis of workspace and kinematics for a tomato harvesting robot". In: *2008 International Conference on Intelligent Computation Technology and Automation (ICICTA)*. Vol. 1. IEEE, pp. 823–827 (cit. on p. 2).
116. Lindemann, S. R. and LaValle, S. M. (2005). "Smoothly blending vector fields for global robot navigation". In: *Proceedings of the 44th IEEE Conference on Decision and Control*. IEEE, pp. 3553–3559 (cit. on p. 75).
117. Lotfi, N., Landers, R. G., Li, J., and Park, J. (2017). "Reduced-Order Electrochemical Model-Based SOC Observer With Output Model Uncertainty Estimation". In: *IEEE Transactions on Control Systems Technology* 25.4, pp. 1217–1230 (cit. on p. 33).
118. Lottes, P., Khanna, R., Pfeifer, J., Siegwart, R., and Stachniss, C. (2017). "UAV-based crop and weed classification for smart farming". In: *2017 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 3024–3031 (cit. on p. 4).
119. Luo, C. and Suda, R. (2011). "A Performance and Energy Consumption Analytical Model for GPU". In: *2011 IEEE Ninth International Conference on Dependable, Autonomic and Secure Computing*, pp. 658–665 (cit. on p. 31).
120. Luo, J. and Jha, N. K. (2001). "Battery-aware static scheduling for distributed real-time embedded systems". In: *Proceedings of the 38th annual Design Automation Conference*. ACM, pp. 444–449 (cit. on p. 32).
121. Ma, K., Li, X., Chen, W., Zhang, C., and Wang, X. (2012). "GreenGPU: A Holistic Approach to Energy Efficiency in GPU-CPU Heterogeneous Architectures". In: *2012 41st International Conference on Parallel Processing*. IEEE, pp. 48–57 (cit. on p. 30).
122. Mannadiar, R. and Rekleitis, I. (2010). "Optimal coverage of a known arbitrary environment". In: *2010 IEEE International Conference on Robotics and Automation*, pp. 5525–5530 (cit. on p. 40).
123. Marcicki, J., Canova, M., Conlisk, A. T., and Rizzoni, G. (2013). "Design and parametrization analysis of a reduced-order electrochemical model of graphite/LiFePO<sub>4</sub> cells for SOC/SOH estimation". In: *Journal of Power Sources* 237, pp. 310–324 (cit. on p. 33).
124. Marowka, A. (2017). "Energy-aware modeling of scaled heterogeneous systems". In: *International Journal of Parallel Programming* 45.5, pp. 1026–1045 (cit. on p. 28).
125. Maza, I. and Ollero, A. (2007). "Multiple UAV cooperative searching operation using polygon area decomposition and efficient coverage algorithms". In: *Distributed Autonomous Robotic Systems* 6. Tokyo: Springer Japan, pp. 221–230 (cit. on p. 38).
126. Mei, Y., Lu, Y.-H., Hu, Y. C., and Lee, C. G. (2004). "Energy-efficient motion planning for mobile robots". In: *IEEE International Conference on Robotics and Automation, 2004. Proceedings. ICRA'04. 2004*. Vol. 5. IEEE, pp. 4344–4349 (cit. on pp. 1, 34, 42, 43).
127. — (2005). "A case study of mobile robot's energy consumption and conservation techniques". In: *ICAR'05. Proceedings., 12th International Conference on Advanced Robotics, 2005*. IEEE, pp. 492–497 (cit. on pp. 1, 34, 35, 42, 43).

128. Mei, Y., Lu, Y.-H., Hu, Y., and Lee, C. (2005a). "Deployment Strategy for Mobile Robots with Energy and Timing Constraints". In: *Proceedings of the 2005 IEEE International Conference on Robotics and Automation*, pp. 2816–2821 (cit. on p. 42).
129. — (2005b). "Reducing the number of mobile sensors for coverage tasks". In: *2005 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 1426–1431 (cit. on p. 42).
130. Mei, Y., Lu, Y.-H., Hu, Y. C., and Lee, C. G. (2006). "Deployment of mobile robots with energy and timing constraints". In: *IEEE Transactions on robotics* 22.3, pp. 507–522 (cit. on pp. 1, 42).
131. Mei, Y., Lu, Y.-H., Lee, C., and Hu, Y. (2006). "Energy-efficient mobile robot exploration". In: *Proceedings 2006 IEEE International Conference on Robotics and Automation, 2006. ICRA 2006*. Pp. 505–511 (cit. on p. 42).
132. Milas, A. S., Cracknell, A. P., and Warner, T. A. (2018). "Drones - the third generation source of remote sensing data". In: *International Journal of Remote Sensing* 39.21, pp. 7125–7137 (cit. on p. 4).
133. Mittal, S. (2019). "A Survey on optimized implementation of deep learning models on the NVIDIA Jetson platform". In: *Journal of Systems Architecture* 97, pp. 428–442 (cit. on p. 30).
134. Mittal, S. and Vetter, J. S. (2014). "A Survey of Methods for Analyzing and Improving GPU Energy Efficiency". In: *ACM Comput. Surv.* 47.2, pp. 1–23 (cit. on p. 31).
135. Moler, C. and Van Loan, C. (2003). "Nineteen dubious ways to compute the exponential of a matrix, twenty-five years later". In: *SIAM review* 45.1, pp. 3–49 (cit. on p. 59).
136. Morbidi, F., Cano, R., and Lara, D. (2016). "Minimum-energy path generation for a quadrotor UAV". In: *2016 IEEE International Conference on Robotics and Automation (ICRA)*. IEEE, pp. 1492–1498 (cit. on p. 38).
137. Moura, S. J., Argomedo, F. B., Klein, R., Mirtabatabaei, A., and Krstic, M. (2017). "Battery State Estimation for a Single Particle Model With Electrolyte Dynamics". In: *IEEE Transactions on Control Systems Technology* 25.2, pp. 453–468 (cit. on p. 33).
138. Mudge, T. (2001). "Power: A first-class architectural design constraint". In: *Computer* 34.4, pp. 52–58 (cit. on p. 43).
139. Nam, L. H., Huang, L., Li, X. J., and Xu, J. F. (2016). "An approach for coverage path planning for UAVs". In: *2016 IEEE 14th International Workshop on Advanced Motion Control (AMC)*, pp. 411–416 (cit. on p. 39).
140. Nikov, K., Nunez-Yanez, J. L., and Horsnell, M. (2015). "Evaluation of hybrid run-time power models for the ARM big. LITTLE architecture". In: *2015 IEEE 13th International Conference on Embedded and Ubiquitous Computing*. IEEE, pp. 205–210 (cit. on pp. 32, 33, 67).
141. Nocedal, J. and Wright, S. (2006). *Numerical optimization*. Springer Science & Business Media (cit. on p. 69).
142. Noor, N. M., Abdullah, A., and Hashim, M. (2018). "Remote sensing UAV/drones and its applications for urban areas: a review". In: *IOP conference series: Earth and environmental science*. Vol. 169. 1. IOP Publishing, p. 012003 (cit. on p. 4).
143. Nunez-Yanez, J. and Lore, G. (2013). "Enabling accurate modeling of power and energy consumption in an ARM-based System-on-Chip". In: *Microprocessors and Microsystems* 37.3, pp. 319–332 (cit. on p. 32, 33, 67).
144. O'Brien, K., Pietri, I., Reddy, R., Lastovetsky, A., and Sakellariou, R. (2017). "A Survey of Power and Energy Predictive Models in HPC Systems and Applications". In: *ACM Comput. Surv.* 50.3, pp. 1–38 (cit. on p. 28).
145. O'Neal, K. and Brisk, P. (2018). "Predictive Modeling for CPU, GPU, and FPGA Performance and Power Consumption: A Survey". In: *2018 IEEE Computer Society Annual Symposium on VLSI (ISVLSI)*, pp. 763–768 (cit. on p. 28).
146. Ogata, K. (2002). *Modern Control Engineering*. Prentice Hall (cit. on p. 59).
147. Ondrúška, P., Gurău, C., Marchegiani, L., Tong, C. H., and Posner, I. (2015). "Scheduled perception for energy-efficient path following". In: *2015 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 4799–4806 (cit. on p. 42).

148. Panagou, D. (2014). "Motion planning and collision avoidance using navigation vector fields". In: *2014 IEEE International Conference on Robotics and Automation (ICRA)*. IEEE, pp. 2513–2518 (cit. on p. 75).
149. Panigrahi, D., Chiasseroni, C., Dey, S., Rao, R., Raghunathan, A., and Lahiri, K. (2001). "Battery life estimation of mobile embedded systems". In: *VLSI Design 2001. Fourteenth International Conference on VLSI Design*, pp. 57–63 (cit. on p. 33).
150. Paparazzi (2016). *UAV open-source project*. URL: <http://wiki.paparazziuav.org/> (visited on 09/01/2016) (cit. on p. 8).
151. Paucar, C., Morales, L., Pinto, K., Sánchez, M., Rodríguez, R., Gutierrez, M., and Palacios, L. (2018). "Use of drones for surveillance and reconnaissance of military areas". In: *International Conference of Research Applied to Defense and Security*. Springer, pp. 119–132 (cit. on p. 4).
152. Paulen, R. and Fikar, M. (2016). "Solution of Optimal Control Problems". In: *Optimal Operation of Batch Membrane Processes*. Cham: Springer International Publishing, pp. 37–56 (cit. on pp. 70, 71).
153. Pedram, M. and Wu, Q. (1999). "Design Considerations for Battery-Powered Electronics". In: *Proceedings of the 36th Annual ACM/IEEE Design Automation Conference*. New York, NY, USA: Association for Computing Machinery, pp. 861–866 (cit. on p. 33).
154. Pensieri, M. G., Garau, M., and Barone, P. M. (2020). "Drones as an Integral Part of Remote Sensing Technologies to Help Missing People". In: *Drones* 4.2, p. 15 (cit. on p. 4).
155. Percin, M., Eisma, J., Van Oudheusden, B., Remes, B., Ruijsink, R., and De Wagter, C. (2012). "Flow Visualization in the Wake of the Flapping-Wing MAV 'DelFly II' in Forward Flight". In: *30th AIAA Applied Aerodynamics Conference*. AIAA (cit. on p. 5).
156. Poe, W. A. and Mokhatab, S. (2017). "Process Control". In: *Modeling, Control, and Optimization of Natural Gas Processing Plants*. Ed. by W. A. Poe and S. Mokhatab. Boston: Gulf Professional Publishing, pp. 97–172 (cit. on p. 71).
157. Pontryagin, L. S., Mishchenko, E., Boltyanskii, V., and Gamkrelidze, R. (1962). *The mathematical theory of optimal processes*. Wiley (cit. on p. 70).
158. Popović, M., Hitz, G., Nieto, J., Sa, I., Siegwart, R., and Galceran, E. (2017). "Online informative path planning for active classification using UAVs". In: *2017 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 5753–5758 (cit. on pp. 4, 38).
159. Puri, V., Nayyar, A., and Raja, L. (2017). "Agriculture drones: A modern breakthrough in precision agriculture". In: *Journal of Statistics and Management Systems* 20.4, pp. 507–518 (cit. on pp. 2, 4).
160. PX4 (2016). *PX4 open-source autopilot*. URL: <https://px4.io/> (visited on 09/01/2016) (cit. on p. 8).
161. Qingchun, F., Wengang, Z., Quan, Q., Kai, J., and Rui, G. (2012). "Study on strawberry robotic harvesting system". In: *2012 IEEE International Conference on Computer Science and Automation Engineering (CSAE)*. Vol. 1. IEEE, pp. 320–324 (cit. on p. 2).
162. Quigley, M., Conley, K., Gerkey, B., Faust, J., Foote, T., Leibs, J., Wheeler, R., and Ng, A. Y. (2009). "ROS: an open-source Robot Operating System". In: *ICRA workshop on open source software*. Vol. 3. 3.2, p. 5 (cit. on p. 10).
163. Rakhatmatov, D. and Vrudhula, S. (2001). "An analytical high-level battery model for use in energy management of portable electronic systems". In: *IEEE/ACM International Conference on Computer Aided Design. ICCAD 2001. IEEE/ACM Digest of Technical Papers (Cat. No.01CH37281)*, pp. 488–493 (cit. on p. 33).
164. Ramasamy, M. and Ghose, D. (2017). "A heuristic learning algorithm for preferential area surveillance by unmanned aerial vehicles". In: *Journal of Intelligent & Robotic Systems* 88.2, pp. 655–681 (cit. on p. 4).
165. Rao, R., Vrudhula, S., and Rakhatmatov, D. N. (2003). "Battery modeling for energy aware system design". In: *Computer* 36.12, pp. 77–87 (cit. on p. 33).
166. Rao, S. S. (2019). *Engineering optimization: theory and practice*. John Wiley & Sons (cit. on p. 72).
167. Rao, V., Singhal, G., Kumar, A., and Navet, N. (2005). "Battery model for embedded systems". In: *18th International Conference on VLSI Design held jointly with 4th International Conference on Embedded Systems Design*, pp. 105–110 (cit. on pp. 28, 33).

168. Rawlings, J. B., Mayne, D. Q., and Diehl, M. (2017). *Model predictive control: theory, computation, and design*. Vol. 2. Madison, Wisconsin: Nob Hill Publishing (cit. on pp. 10, 69–72, 77, 80).
169. Reddy, B. K., Walker, M. J., Balsamo, D., Diestelhorst, S., Al-Hashimi, B. M., and Merrett, G. V. (2017). “Empirical CPU power modelling and estimation in the gem5 simulator”. In: *2017 27th International Symposium on Power and Timing Modeling, Optimization and Simulation (PATMOS)*, pp. 1–8 (cit. on pp. 32, 33).
170. Redmon, J. (2013–2016). *Darknet: Open Source Neural Networks in C*. <http://pjreddie.com/darknet/> (cit. on p. 46).
171. Redmon, J., Divvala, S., Girshick, R., and Farhadi, A. (2016). “You only look once: Unified, real-time object detection”. In: *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 779–788 (cit. on p. 46).
172. Redmon, J. and Farhadi, A. (2017). “YOLO9000: Better, Faster, Stronger”. In: *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*. Honolulu, USA, pp. 6517–6525 (cit. on p. 46).
173. Renzaglia, A., Reymann, C., and Lacroix, S. (2016). “Monitoring the evolution of clouds with UAVs”. In: *2016 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 278–283 (cit. on p. 4).
174. Rizvi, S. T. H., Cabodi, G., Patti, D., and Gulzar, M. M. (2017). “A general-purpose graphics processing unit (gpgpu)-accelerated robotic controller using a low power mobile platform”. In: *Journal of Low Power Electronics and Applications* 7.2, p. 10 (cit. on p. 1).
175. Rossiter, J. A. (2004). *Model-based predictive control: a practical approach*. Boca Raton, Florida: CRC press (cit. on p. 71).
176. Sa, I., Chen, Z., Popović, M., Khanna, R., Liebisch, F., Nieto, J., and Siegwart, R. (2018). “weedNet: Dense Semantic Weed Classification Using Multispectral Images and MAV for Smart Farming”. In: *IEEE Robotics and Automation Letters* 3.1, pp. 588–595 (cit. on p. 4).
177. Sadat, S. A., Wawerla, J., and Vaughan, R. T. (2014). “Recursive non-uniform coverage of unknown terrains for UAVs”. In: *2014 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pp. 1742–1747 (cit. on p. 39).
178. Sadrpour, A., Jin, J., and Ulsoy, A. G. (2013a). “Mission Energy Prediction for Unmanned Ground Vehicles Using Real-time Measurements and Prior Knowledge”. In: *Journal of Field Robotics* 30.3, pp. 399–414 (cit. on p. 42).
179. Sadrpour, A., Jin, J., and Ulsoy, A. G. (2013b). “Experimental validation of mission energy prediction model for unmanned ground vehicles”. In: *2013 American Control Conference*. IEEE, pp. 5960–5965 (cit. on p. 42).
180. Satria, M. T., Gurumani, S., Zheng, W., Tee, K. P., Koh, A., Yu, P., Rupnow, K., and Chen, D. (2016). “Real-time system-level implementation of a telepresence robot using an embedded GPU platform”. In: *2016 Design, Automation & Test in Europe Conference & Exhibition (DATE)*. IEEE, pp. 1445–1448 (cit. on p. 1).
181. Schuyler, T. J., Gohari, S., Pundsack, G., Berchoff, D., and Guzman, M. I. (2019). “Using a balloon-launched unmanned glider to validate real-time WRF modeling”. In: *Sensors* 19.8, p. 1914 (cit. on p. 4).
182. Seewald, A. (2020). “Beyond Traditional Energy Planning: the Weight of Computations in Planetary Exploration”. In: *IROS Workshop on Planetary Exploration Robots: Challenges and Opportunities (PLANROBO20)*. ETH Zurich, Department of Mechanical and Process Engineering, p. 3 (cit. on pp. 10, 11).
183. Seewald, A., Ebeid, E., and Schultz, U. P. (2019). “Dynamic Energy Modelling for SoC Boards: Initial Experiments”. In: *HLPGPU 2019: High-Level Programming for Heterogeneous and Hierarchical Parallel Systems*, p. 4 (cit. on pp. 30, 50).
184. Seewald, A., Garcia de Marina, H., Midtiby, H. S., and Schultz, U. P. (2020). “Mechanical and Computational Energy Estimation of a Fixed-Wing Drone”. In: *2020 Fourth IEEE International Conference on Robotic Computing (IRC)*. IEEE, pp. 135–142 (cit. on pp. 1, 9, 11).

185. Seewald, A., Garcia de Marina, H., and Schultz, U. P. (n.d.). *Energy-Aware Dynamic Planning Algorithm for Autonomous UAVs*. In preparation (available online: <https://github.com/adamseew/iros-2021>) (cit. on pp. 9, 11).
186. Seewald, A., Schultz, U. P., Ebeid, E., and Midtiby, H. S. (2021). "Coarse-Grained Computation-Oriented Energy Modeling for Heterogeneous Parallel Embedded Systems". In: *International Journal of Parallel Programming* 49.2, pp. 136–157 (cit. on pp. 10, 32, 33).
187. Seewald, A., Schultz, U. P., Roeder, J., Rouxel, B., and Grelck, C. (2019). "Component-based computation-energy modeling for embedded systems". In: *Proceedings Companion of the 2019 ACM SIGPLAN International Conference on Systems, Programming, Languages, and Applications: Software for Humanity*. ACM, pp. 5–6 (cit. on pp. 10, 52).
188. Seguin, C., Blaqui  re, G., Loundou, A., Michelet, P., and Markarian, T. (2018). "Unmanned aerial vehicles (drones) to prevent drowning". In: *Resuscitation* 127, pp. 63–67 (cit. on p. 4).
189. Sethi, S. P. (2019). *Optimal Control Theory: Applications to Management Science and Economics*. Cham: Springer International Publishing (cit. on pp. 69, 70, 72).
190. Shnaps, I. and Rimon, E. (2016). "Online Coverage of Planar Environments by a Battery Powered Autonomous Mobile Robot". In: *IEEE Transactions on Automation Science and Engineering* 13.2, pp. 425–436 (cit. on pp. 36–38).
191. Siciliano, B. and Khatib, O. (2016). *Springer handbook of robotics*. Springer. Chap. 44, pp. 1012–1014 (cit. on pp. 3–5, 44).
192. Simon, D. (2006). *Optimal state estimation: Kalman, H infinity, and nonlinear approaches*. John Wiley & Sons (cit. on p. 72).
193. Stengel, R. F. (1994). *Optimal control and estimation*. Courier Corporation (cit. on p. 72).
194. Sudhakar, S., Karaman, S., and Sze, V. (2020). "Balancing Actuation and Computing Energy in Motion Planning". In: *2020 IEEE International Conference on Robotics and Automation (ICRA)*. IEEE, pp. 4259–4265 (cit. on pp. 1, 27, 41).
195. Syracuse, K. and Clark, W. (1997). "A statistical approach to domain performance modeling for oxy-halide primary lithium batteries". In: *The Twelfth Annual Battery Conference on Applications and Advances*, pp. 163–170 (cit. on p. 33).
196. Takouna, I., Dawoud, W., and Meinel, C. (2011). "Accurate Multicore Processor Power Models for Power-Aware Resource Management". In: *2011 IEEE Ninth International Conference on Dependable, Autonomic and Secure Computing*, pp. 419–426 (cit. on p. 32).
197. Tang, L. and Shao, G. (2015). "Drone remote sensing for forestry research and practices". In: *Journal of Forestry Research* 26.4, pp. 791–797 (cit. on p. 4).
198. Valavanis, K. P. and Vachtsevanos, G. J. (2015). *Handbook of unmanned aerial vehicles*. Vol. 1. Springer (cit. on p. 3).
199. Valente, J., Del Cerro, J., Barrientos, A., and Sanz, D. (2013). "Aerial coverage optimization in precision agriculture management: A musical harmony inspired approach". In: *Computers and Electronics in Agriculture* 99, pp. 153–159 (cit. on p. 41).
200. Von Stryk, O. and Bulirsch, R. (1992). "Direct and indirect methods for trajectory optimization". In: *Annals of operations research* 37.1, pp. 357–373 (cit. on p. 69).
201. Voosen, P. (2019). *NASA to fly drone on Titan* (cit. on p. 4).
202. Wahab, M., Rios-Gutierrez, F., and El Shahat, A. (2015). *Energy modeling of differential drive robots*. IEEE (cit. on p. 34).
203. Walker, M. J., Diestelhorst, S., Hansson, A., Das, A. K., Yang, S., Al-Hashimi, B. M., and Merrett, G. V. (2017). "Accurate and Stable Run-Time Power Modeling for Mobile and Embedded CPUs". In: *IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems* 36.1, pp. 106–119 (cit. on pp. 32, 33).
204. Wang, L. (2009). *Model predictive control system design and implementation using Matlab*. London: Springer Science & Business Media (cit. on p. 71).

205. Wang, X., Jiang, P., Li, D., and Sun, T. (2017). "Curvature Continuous and Bounded Path Planning for Fixed-Wing UAVs". In: *Sensors* 17.9 (cit. on p. 38).
206. Watts, A. C., Ambrosia, V. G., and Hinkley, E. A. (2012). "Unmanned Aircraft Systems in Remote Sensing and Scientific Research: Classification and Considerations of Use". In: *Remote Sensing* 4.6, pp. 1671–1692 (cit. on p. 6).
207. Wei, M. and Isler, V. (2018). "Coverage Path Planning Under the Energy Constraint". In: *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 368–373 (cit. on pp. 34, 36, 38).
208. Woo, D. H. and Lee, H.-H. S. (2008). "Extending Amdahl's law for energy-efficient computing in the many-core era". In: *Computer* 41.12, pp. 24–31 (cit. on p. 43).
209. Wu, G., Greathouse, J. L., Lyashevsky, A., Jayasena, N., and Chiou, D. (2015). "GPGPU performance and power estimation using machine learning". In: *2015 IEEE 21st International Symposium on High Performance Computer Architecture (HPCA)*. IEEE, pp. 564–576 (cit. on p. 31).
210. Xing, Y., He, W., Pecht, M., and Tsui, K. L. (2014). "State of charge estimation of lithium-ion batteries using the open-circuit voltage at various ambient temperatures". In: *Applied Energy* 113, pp. 106–115 (cit. on p. 33).
211. Xu, A., Viriyasuthee, C., and Rekleitis, I. (2011). "Optimal complete terrain coverage using an Unmanned Aerial Vehicle". In: *2011 IEEE International Conference on Robotics and Automation*, pp. 2513–2519 (cit. on pp. 36, 38, 40).
212. — (2014). "Efficient complete coverage of a known arbitrary environment with applications to aerial operations". In: *Autonomous Robots* 36.4, pp. 365–381 (cit. on p. 40).
213. Yang, T.-J., Chen, Y.-H., Emer, J., and Sze, V. (2017). "A method to estimate the energy consumption of deep neural networks". In: *2017 51st asilomar conference on signals, systems, and computers*. IEEE, pp. 1916–1920 (cit. on pp. 30, 31).
214. Yang, T.-J., Chen, Y.-H., and Sze, V. (2017). "Designing energy-efficient convolutional neural networks using energy-aware pruning". In: *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 5687–5695 (cit. on p. 30).
215. Zamanakos, G., Seewald, A., Midtby, H. S., and Schultz, U. P. (2020). "Energy-Aware Design of Vision-Based Autonomous Tracking and Landing of a UAV". In: *2020 Fourth IEEE International Conference on Robotic Computing (IRC)*. IEEE, pp. 294–297 (cit. on pp. 1, 10).
216. Zelinsky, A., Jarvis, R., Byrne, J. C., and Yuta, S. (1993). "Planning Paths of Complete Coverage of an Unstructured Environment by a Mobile Robot". In: *In Proceedings of International Conference on Advanced Robotics*, pp. 533–538 (cit. on p. 36).
217. Zhang, L., Tiwana, B., Qian, Z., Wang, Z., Dick, R. P., Mao, Z. M., and Yang, L. (2010). "Accurate Online Power Estimation and Automatic Battery Behavior Based Power Model Generation for Smartphones". In: *Proceedings of the Eighth IEEE/ACM/IFIP International Conference on Hardware/Software Codesign and System Synthesis*. New York, NY, USA: Association for Computing Machinery, pp. 105–114 (cit. on p. 34).
218. Zhang, W. and Hu, J. (2007). "Low power management for autonomous mobile robots using optimal control". In: *2007 46th IEEE Conference on Decision and Control*, pp. 5364–5369 (cit. on p. 42).
219. Zhou, D. and Schwager, M. (2014). "Vector field following for quadrotors using differential flatness". In: *2014 IEEE International Conference on Robotics and Automation (ICRA)*. IEEE, pp. 6567–6572 (cit. on p. 75).

# Index

- Bézier curves, 41
- barometer, 3
- blimps, 5
- boustrophedon decomposition, 34
- boustrophedon motion, 36
- breadth-first strategy, 39
- chinese postman problem, 41
- coax, 5
- colony optimization, 39
- computations, 14
- computations energy, 14
- computations parameters, 16
- control surface, 6
- convolutional neural network, 8
- coverage path planning, 36
- coverage planning algorithms, 37
- covering salesman problem, 36
- CPU, 8
- CUDA, 31
- data mining, 30
- data-driven control, 2
- deep neural network, 30
- depth-first strategy, 39
- difference of motion and computations energy, 14
- dynamic voltage scaling, 28
- evolutionary optimization, 38
- finite state machine, 18
- fixed-wings, 5
- flapping-wings, 5
- frames per second, 14
- gems, 32
- genetic algorithm, 39
- genral purpose GPU, 31
- global navigation satellite system, 3
- global positioning system, 3
- GPU, 1, 8
- gyroscope, 3
- harmony search, 41
- heavier-than-air aerial robots, 5
- helicopters, 5
- heterogeneous computing hardware, 6
- Hewitt-Sperry automatic airplane, 3
- hexacopters, 5
- hovering, 5
- inertial measurement unit, 3
- integer linear programming, 30
- Li-ion battery, 33
- lighter-than-air aerial robots, 5
- lithium polymer battery, 40
- Lockheed D-21, 3
- Markov processes, 33
- meteorology, 4
- micro aerial vehicles, 5
- microcontroller, 6
- Morse functions, 37
- motion, 14
- motion energy, 14
- motor, 6

- multicore CPU, 32
- multirotors, 5
  - octocopters, 5
  - omnidirectional wheels, 35
- Opterra fixed-wing aerial robot, 2
- output constraint, 77
- output model predictive control, 76
- overall energy, 14
- path functions, 15
- path parameters, 16
- payload delivery, 4
- performance monitoring counters, 33
- period, 19
- planning problem, 20
- precision agriculture, 2
- primitive paths, 18
- quadcopters, 5
- quadrotors, 5
- quality of service, 30
- reconnaissance, surveillance, and target acquisition, 4
- Reeb graph, 40
- remote sensing, 4
- remotely piloted vehicles, 3
- rotary-wings, 5
- Ryan Firebee, 3
- search and rescue, 4
- servo, 6
- shift, 18
- shortcut heuristic, 39
- stage, 17
- stochastic battery model, 33
- surveillance, 4
- tradeoffs, 8
- travelling salesman problem, 36
- unmanned aerial systems, 2
- unmanned aerial vehicles, 2
- V-I flying bomb, 3
- vertical take-off and landing, 5
- wavefront algorithm, 39
- World War I, 3
- Wright brother, 3
- Zamboni motion, 39