Fortify Audit Workbench

Developer Workbook

1scan_coube

Table of Contents

Executive Summary
Project Description
Issue Breakdown by Fortify Categories
Results Outline

© Copyright 2008-2026 Open Text.

Executive Summary

This workbook is intended to provide all necessary details and information for a developer to understand and remediate the different issues discovered during the 1scan_coube project audit. The information contained in this workbook is targeted at project managers and developers.

This section provides an overview of the issues uncovered during analysis.

Project Name:	1scan_coube
Project Version:	
SCA:	Results Present
WebInspect:	Results Not Present
WebInspect Agent:	Results Not Present
Other:	Results Not Present

Issues by Priority



Top Ten Critical Categories



© Copyright 2008-2026 Open Text.

Project Description

This section provides an overview of the Fortify scan engines used for this project, as well as the project meta-information.

SCA

Date of Last Analysis:	Feb 16, 2026 12:56 PM	**Engine Version:**	25.4.0.0135
Host Name:	DESKTOP-SMV77FE	**Certification:**	VALID
Number of Files:	4,104	**Lines of Code:**	331,201

Rulepack Name	Rulepack Version
Fortify Secure Coding Rules, Community, Cloud	2025.4.0.0009
Fortify Secure Coding Rules, Community, Universal	2025.4.0.0009
Fortify Secure Coding Rules, Core, Android	2025.4.0.0009
Fortify Secure Coding Rules, Core, Annotations	2025.4.0.0009
Fortify Secure Coding Rules, Core, Cloud	2025.4.0.0009
Fortify Secure Coding Rules, Core, Java	2025.4.0.0009
Fortify Secure Coding Rules, Core, JavaScript	2025.4.0.0009
Fortify Secure Coding Rules, Core, Kotlin	2025.4.0.0009
Fortify Secure Coding Rules, Core, SQL	2025.4.0.0009
Fortify Secure Coding Rules, Core, Universal	2025.4.0.0009
Fortify Secure Coding Rules, Extended, Configuration	2025.4.0.0009
Fortify Secure Coding Rules, Extended, Content	2025.4.0.0009
Fortify Secure Coding Rules, Extended, Java	2025.4.0.0009
Fortify Secure Coding Rules, Extended, JavaScript	2025.4.0.0009
Fortify Secure Coding Rules, Extended, JSP	2025.4.0.0009
Fortify Secure Coding Rules, Extended, SQL	2025.4.0.0009

© Copyright 2008-2026 Open Text.

Issue Breakdown by Fortify Categories

The following table depicts a summary of all issues grouped vertically by Fortify Category. For each category, the total number of issues is shown by Fortify Priority Order, including information about the number of audited issues.

Category	Fortify Priority (audited/total)				Total Issues
	Critical	High	Medium	Low	
Android Bad Practices: Missing Component Permission	0	0 / 1	0	0	0 / 1
Android Bad Practices: Missing Google Play Services Updated Security Provider	0	0 / 2	0	0	0 / 2
Android Bad Practices: Missing Network Security Configuration	0	0 / 2	0	0	0 / 2
Credential Management: Hardcoded API Credentials	0 / 6	0 / 4	0	0	0 / 10
Cross-Site Request Forgery	0	0	0	0 / 3	0 / 3
Dockerfile Misconfiguration: Default User Privilege	0	0 / 1	0	0	0 / 1
Insecure Transport	0 / 1	0	0	0	0 / 1
Insecure Transport: Disabled App Transport Security	0 / 1	0	0	0	0 / 1
Insecure Transport: External Link	0	0	0 / 1	0	0 / 1
Key Management: Hardcoded Encryption Key	0 / 1	0	0	0	0 / 1
Password Management: Hardcoded Password	0 / 1	0	0	0	0 / 1
Password Management: Password in Comment	0	0	0	0 / 1	0 / 1
Password Management: Password in Configuration File	0	0 / 2	0	0	0 / 2
Privacy Violation	0 / 8	0	0	0	0 / 8
Privilege Management: Android Camera	0	0 / 1	0	0	0 / 1
Privilege Management: Android Data Storage	0	0 / 2	0	0	0 / 2
Privilege Management: Unnecessary Permission	0	0 / 4	0	0	0 / 4
Weak Cryptographic Hash	0	0	0	0 / 137	0 / 137
XML Entity Expansion Injection	0	0	0	0 / 1	0 / 1
XML External Entity Injection	0	0 / 1	0	0	0 / 1

© Copyright 2008-2026 Open Text.

Results Outline

Android Bad Practices: Missing Component Permission (1 issue)

Abstract

The program does not explicitly assign an access permission to this public component.

Explanation

Any application can access public components that are not explicitly assigned an access permission in their manifest definition. The default value of the `exported` attribute for the activity, receiver, and service components in an Android application depends on the presence or absence of an `intent-filter`. Presence of an `intent-filter` implies, the component is intended for external use, thus setting the `exported` attribute to true. This component is now accessible to any other applications on the Android platform. **Example 1:** The following is an example of an Android activity with an `intent-filter` and no explicit access permission set.

```
<activity android:name=".AndroidActivity"/>
<intent-filter android:label="activityName"/>
<action android:name=".someFunAction"/>
</intent-filter>
...
</activity>
```

This activity can be exploited by malicious applications.

Recommendation

Components without explicit access permissions should be exceptions. Unless, the component is really intended to be accessible to all, developers should protect components from misuse by malicious applications by explicitly defining the access permissions in the manifest file. **Example 2:** The following is the declaration of the activity component from `Example 1`, rewritten with explicitly assigned access permission.

```
<activity android:name=".AndroidActivity" android:permission="FriendsOnly"/>
<intent-filter android:label="activityName"/>
<action android:name=".someFunAction"/>
</intent-filter>
...
</activity>
```

Issue Summary



© Copyright 2008-2026 Open Text.

Engine Breakdown

	SCA	WebInspect	SecurityScope	Total
Android Bad Practices: Missing Component Permission	1	0	0	1
Total	**1**	**0**	**0**	**1**

Android Bad Practices: Missing Component Permission — High

Package: .src.main

coube-mobile/android/app/src/main/AndroidManifest.xml, line 42 (Android Bad Practices: Missing Component Permission)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-mobile/android/app/src/main/AndroidManifest.xml:42
Taint Flags:

```
39  android:launchMode="singleTask"
40  android:windowSoftInputMode="adjustResize"
41  android:exported="true"
42  android:theme="@style/BootTheme">
43  <intent-filter>
44  <action android:name="android.intent.action.MAIN" />
45  <category android:name="android.intent.category.LAUNCHER" />
```


© Copyright 2008-2026 Open Text.

Android Bad Practices: Missing Google Play Services Updated Security Provider (2 issues)

Abstract

The application does not use the Google Play Service Updated Security Provider which may leave it vulnerable to future vulnerabilities in OpenSSL Library.

Explanation

Android relies on a security Provider to provide secure network communications. However, from time to time, vulnerabilities are found in the default security provider. To protect against these vulnerabilities, Google Play services provides a way to automatically update a device's security provider to protect against known exploits. By calling Google Play services methods, your app can ensure that it's running on a device that has the latest updates to protect against known exploits.

Recommendation

The simplest way to patch the security provider is to call the synchronous method `installIfNeeded()`. This is appropriate if user experience won't be affected by the thread blocking while it waits for the operation to finish, otherwise it should be done in an asynchronous way. **Example 1:** The following code implements a sync adapter that updates the security provider. Since a sync adapter runs in the background, it's okay if the thread blocks while waiting for the security provider to be updated. The sync adapter calls `installIfNeeded()` to update the security provider. If the method returns normally, the sync adapter knows the security provider is up-to-date. If the method throws an exception, the sync adapter can take appropriate action (such as prompting the user to update Google Play services).

```
public class SyncAdapter extends AbstractThreadedSyncAdapter {

...

// This is called each time a sync is attempted; this is okay, since the
// overhead is negligible if the security provider is up-to-date.
@Override
public void onPerformSync(Account account, Bundle extras, String authority,
ContentProviderClient provider, SyncResult syncResult) {
try {
ProviderInstaller.installIfNeeded(getContext());
} catch (GooglePlayServicesRepairableException e) {

// Indicates that Google Play services is out of date, disabled, etc.

// Prompt the user to install/update/enable Google Play services.

GooglePlayServicesUtil.showErrorNotification(e.getConnectionStatusCode(),
getContext());

// Notify the SyncManager that a soft error occurred.
syncResult.stats.numIOExceptions++;
return;

} catch (GooglePlayServicesNotAvailableException e) {
// Indicates a non-recoverable error; the ProviderInstaller is not able
// to install an up-to-date Provider.

// Notify the SyncManager that a hard error occurred.
syncResult.stats.numAuthExceptions++;
```


© Copyright 2008-2026 Open Text.

```
return;
}

// If this is reached, you know that the provider was already up-to-date,
// or was successfully updated.
}
}
```

Issue Summary



Engine Breakdown

	SCA	WebInspect	SecurityScope	Total
Android Bad Practices: Missing Google Play Services Updated Security Provider	2	0	0	2
Total	**2**	**0**	**0**	**2**

Android Bad Practices: Missing Google Play Services Updated Security Provider — High

Package: .src.debug

coube-mobile/android/app/src/debug/AndroidManifest.xml, line 8 (Android Bad Practices: Missing Google Play Services Updated Security Provider)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-mobile/android/app/src/debug/AndroidManifest.xml:8
Taint Flags:

```
5  <application
6  android:usesCleartextTraffic="true"
7  tools:targetApi="28"
8  tools:ignore="GoogleAppIndexingWarning"/>
9 </manifest>
10
11 undefined
```


© Copyright 2008-2026 Open Text.

Android Bad Practices: Missing Google Play Services Updated Security Provider — High

Package: .src.main

coube-mobile/android/app/src/main/AndroidManifest.xml, line 33 (Android Bad Practices: Missing Google Play Services Updated Security Provider)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-mobile/android/app/src/main/AndroidManifest.xml:33
Taint Flags:

```
30  android:roundIcon="@mipmap/ic_launcher_round"
31  android:allowBackup="false"
32  android:theme="@style/AppTheme"
33  android:supportsRtl="true">
34  <meta-data android:name="com.transistorsoft.locationmanager.license"
android:value="463364d4d4acf85119fd6c65179ffd4b8ea53ddb134625c6d7ec7f207431b70f" />
35  <activity
36  android:name=".MainActivity"
```


© Copyright 2008-2026 Open Text.

Android Bad Practices: Missing Network Security Configuration (2 issues)

Abstract

The application does not use Network Security Configuration.

Explanation

The Network Security Configuration feature lets apps customize their network security settings in a safe, declarative configuration file without modifying app code. These settings can be configured for specific domains and for a specific app. The key capabilities of this feature are as follows: - Custom trust anchors: Customize which Certificate Authorities (CA) are trusted for an app's secure connections. For example, trusting particular self-signed certificates or restricting the set of public CAs that the app trusts. - Debug-only overrides: Safely debug secure connections in an app without added risk to the installed base. - Cleartext traffic opt-out: Protect apps from accidental usage of cleartext traffic. - Certificate pinning: Restrict an app's secure connection to particular certificates.

Recommendation

Set up a Network Security Configuration to improve the security posture of your app.

Issue Summary



Engine Breakdown

	SCA	WebInspect	SecurityScope	Total
Android Bad Practices: Missing Network Security Configuration	2	0	0	2
Total	**2**	**0**	**0**	**2**

Android Bad Practices: Missing Network Security Configuration — High

Package: .src.debug

coube-mobile/android/app/src/debug/AndroidManifest.xml, line 8 (Android Bad Practices: Missing Network Security Configuration)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

© Copyright 2008-2026 Open Text.

Android Bad Practices: Missing Network Security Configuration — High

Package: .src.debug

coube-mobile/android/app/src/debug/AndroidManifest.xml, line 8 (Android Bad Practices: Missing Network Security Configuration)

Sink:
File: coube-mobile/android/app/src/debug/AndroidManifest.xml:8
Taint Flags:

```
5  <application
6  android:usesCleartextTraffic="true"
7  tools:targetApi="28"
8  tools:ignore="GoogleAppIndexingWarning"/>
9 </manifest>
10
11 undefined
```

Package: .src.main

coube-mobile/android/app/src/main/AndroidManifest.xml, line 33 (Android Bad Practices: Missing Network Security Configuration)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-mobile/android/app/src/main/AndroidManifest.xml:33
Taint Flags:

```
30  android:roundIcon="@mipmap/ic_launcher_round"
31  android:allowBackup="false"
32  android:theme="@style/AppTheme"
33  android:supportsRtl="true">
34  <meta-data android:name="com.transistorsoft.locationmanager.license"
android:value="463364d4d4acf85119fd6c65179ffd4b8ea53ddb134625c6d7ec7f207431b70f" />
35  <activity
36  android:name=".MainActivity"
```


© Copyright 2008-2026 Open Text.

Credential Management: Hardcoded API Credentials (10 issues)

Abstract

Hardcoded API credentials can compromise system security in a way that is not easy to remedy.

Explanation

Never hardcode credentials, including usernames, passwords, API keys, API secrets, and API Tokens. Not only are hardcoded credentials visible to all of the project developers, they are extremely difficult to update. After the code is in production, the credentials cannot be changed without patching the software. If the credentials are compromised, the organization must choose between security and system availability.

Recommendation

Make sure that API credentials are either loaded from a configuration file that is only available in the runtime environment or from environment variables.

Issue Summary



Engine Breakdown

	SCA	WebInspect	SecurityScope	Total
Credential Management: Hardcoded API Credentials	10	0	0	10
Total	**10**	**0**	**0**	**10**

Credential Management: Hardcoded API Credentials — Critical

Package: .src.config

coube-mobile/src/config/env.ts, line 13 (Credential Management: Hardcoded API Credentials)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-mobile/src/config/env.ts:13
Taint Flags:

© Copyright 2008-2026 Open Text.

Credential Management: Hardcoded API Credentials — Critical

Package: .src.config

coube-mobile/src/config/env.ts, line 13 (Credential Management: Hardcoded API Credentials)

```
10 // export const ENV = {
11 // API_HOST: 'https://platform.coube.kz',
12 // TELEGRAM_CHAT_ID: '303599057',
13 // TELEGRAM_ERROR_BOT_TOKEN: '7916362970:AAGSA5f_CG55R3wBiS1npc5-vQmhRfWGPYw',
14 // TELEGRAM_SUCCESS_BOT_TOKEN: '8180947625:AAGGNOyADcmuFJYtJLBSjNzDUjwL73Ovksg',
15 // };
16
```

coube-mobile/src/config/env.ts, line 14 (Credential Management: Hardcoded API Credentials)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-mobile/src/config/env.ts:14
Taint Flags:

```
11 // API_HOST: 'https://platform.coube.kz',
12 // TELEGRAM_CHAT_ID: '303599057',
13 // TELEGRAM_ERROR_BOT_TOKEN: '7916362970:AAGSA5f_CG55R3wBiS1npc5-vQmhRfWGPYw',
14 // TELEGRAM_SUCCESS_BOT_TOKEN: '8180947625:AAGGNOyADcmuFJYtJLBSjNzDUjwL73Ovksg',
15 // };
16
17 export default ENV;
```

coube-mobile/src/config/env.ts, line 4 (Credential Management: Hardcoded API Credentials)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-mobile/src/config/env.ts:4
Taint Flags:

```
1 // Stage конфигурация
2 export const ENV = {
3  API_HOST: 'https://stage-platform.coube.kz',
4  TELEGRAM_SUCCESS_BOT_TOKEN: '8045958660:AAHm3vcMcdboNY8RvwmBxhrvhmZTzaDOBrI',
5  TELEGRAM_ERROR_BOT_TOKEN: '8004263459:AAGf7orVGDVkf4choVNlSHgKOXL7OuQdzYw',
6  TELEGRAM_CHAT_ID: '303599057',
```


© Copyright 2008-2026 Open Text.

Credential Management: Hardcoded API Credentials — Critical

Package: .src.config

coube-mobile/src/config/env.ts, line 4 (Credential Management: Hardcoded API Credentials)

```
7 };
```

coube-mobile/src/config/env.ts, line 5 (Credential Management: Hardcoded API Credentials)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-mobile/src/config/env.ts:5
Taint Flags:

```
2 export const ENV = {
3  API_HOST: 'https://stage-platform.coube.kz',
4  TELEGRAM_SUCCESS_BOT_TOKEN: '8045958660:AAHm3vcMcdboNY8RvwmBxhrvhmZTzaDOBrI',
5  TELEGRAM_ERROR_BOT_TOKEN: '8004263459:AAGf7orVGDVkf4choVNlSHgKOXL7OuQdzYw',
6  TELEGRAM_CHAT_ID: '303599057',
7 };
8
```

Package: coube-frontend.public

coube-frontend/public/firebase-messaging-sw.js, line 5 (Credential Management: Hardcoded API Credentials)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-frontend/public/firebase-messaging-sw.js:5
Taint Flags:

```
2 importScripts('https://www.gstatic.com/firebasejs/10.12.2/firebase-messaging-compat.js');
3
4 firebase.initializeApp({
5  apiKey: 'AIzaSyCsoIEvSnIReAaxMxloxxWjcRvEKyjKTcI',
6  authDomain: 'coube-kz.firebaseapp.com',
7  projectId: 'coube-kz',
8  messagingSenderId: '1008005646022',
```


© Copyright 2008-2026 Open Text.

Credential Management: Hardcoded API Credentials — Critical

Package: coube-frontend.src

coube-frontend/src/firebase.js, line 5 (Credential Management: Hardcoded API Credentials)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-frontend/src/firebase.js:5
Taint Flags:

```
2 import { getMessaging } from 'firebase/messaging';
3
4 const firebaseConfig = {
5  apiKey: 'AIzaSyCsoIEvSnIReAaxMxloxxWjcRvEKyjKTcI',
6  authDomain: 'coube-kz.firebaseapp.com',
7  projectId: 'coube-kz',
8  storageBucket: 'coube-kz.firebasestorage.app',
```

Credential Management: Hardcoded API Credentials — High

Package: coube-backend.docs

coube-backend/docs/routes-contracts-api.md, line 39 (Credential Management: Hardcoded API Credentials)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-backend/docs/routes-contracts-api.md:39
Taint Flags:

```
36
37 ```bash
38 curl -X GET "http://localhost:8080/api/reports/routes-contracts/analysis?agreementType=contract&page=0&size=20" \
39  -H "Authorization: Bearer eyJhbGci..." \
40  -H "X-Organization-Id: 140" \
41  -H "Accept: application/json"
42 ```
```

coube-backend/docs/routes-contracts-api.md, line 115 (Credential Management: Hardcoded API Credentials)

Issue Details

Kingdom: Security Features

© Copyright 2008-2026 Open Text.

Credential Management: Hardcoded API Credentials — High

Package: coube-backend.docs

coube-backend/docs/routes-contracts-api.md, line 115 (Credential Management: Hardcoded API Credentials)

Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-backend/docs/routes-contracts-api.md:115
Taint Flags:

```
112
113 ```bash
114 curl -X GET "http://localhost:8080/api/reports/routes-contracts/metrics" \
115  -H "Authorization: Bearer eyJhbGci..." \
116  -H "X-Organization-Id: 140" \
117  -H "Accept: application/json"
118 ```
```

coube-backend/docs/routes-contracts-api.md, line 183 (Credential Management: Hardcoded API Credentials)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-backend/docs/routes-contracts-api.md:183
Taint Flags:

```
180
181 ```bash
182 curl -X GET "http://localhost:8080/api/reports/routes-contracts/charts?
dateFrom=2024-01-01&dateTo=2024-12-31" \
183  -H "Authorization: Bearer eyJhbGci..." \
184  -H "X-Organization-Id: 140" \
185  -H "Accept: application/json"
186 ```
```

coube-backend/docs/routes-contracts-api.md, line 245 (Credential Management: Hardcoded API Credentials)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-backend/docs/routes-contracts-api.md:245

© Copyright 2008-2026 Open Text.

Credential Management: Hardcoded API Credentials | High

Package: coube-backend.docs

coube-backend/docs/routes-contracts-api.md, line 245 (Credential Management: Hardcoded API Credentials)

Taint Flags:

```
242
243 ```bash
244 curl -X GET "http://localhost:8080/api/reports/routes-contracts/export?agreementType=contract&dateFrom=2024-01-01&dateTo=2024-12-31" \
245  -H "Authorization: Bearer eyJhbGci..." \
246  -H "X-Organization-Id: 140" \
247  --output routes_contracts_analysis.xlsx
248 ```
```


© Copyright 2008-2026 Open Text.

Cross-Site Request Forgery (3 issues)

Abstract

HTTP requests must contain a user-specific secret to prevent an attacker from making unauthorized requests.

Explanation

A cross-site request forgery (CSRF) vulnerability occurs when: 1. A web application uses session cookies. 2. The application acts on an HTTP request without verifying that the request was made with the user's consent. A nonce is a cryptographic random value that is sent with a message to prevent replay attacks. If the request does not contain a nonce that proves its provenance, the code that handles the request is vulnerable to a CSRF attack (unless it does not change the state of the application). This means a web application that uses session cookies has to take special precautions to ensure that an attacker can't trick users into submitting bogus requests. Imagine a web application that allows administrators to create new accounts as follows:

```
var req = new XMLHttpRequest();
req.open("POST", "/new_user", true);
body = addToPost(body, new_username);
body = addToPost(body, new_passwd);
req.send(body);
```

An attacker might set up a malicious web site that contains the following code.

```
var req = new XMLHttpRequest();
req.open("POST", "http://www.example.com/new_user", true);
body = addToPost(body, "attacker");
body = addToPost(body, "haha");
req.send(body);
```

If an administrator for `example.com` visits the malicious page while she has an active session on the site, she will unwittingly create an account for the attacker. This is a CSRF attack. It is possible because the application does not have a way to determine the provenance of the request. Any request could be a legitimate action chosen by the user or a faked action set up by an attacker. The attacker does not get to see the Web page that the bogus request generates, so the attack technique is only useful for requests that alter the state of the application. Applications that pass the session identifier in the URL rather than as a cookie do not have CSRF problems because there is no way for the attacker to access the session identifier and include it as part of the bogus request.

Recommendation

Applications that use session cookies must include some piece of information in every form post that the back-end code can use to validate the provenance of the request. One way to do that is to include a random request identifier or nonce, as follows:

```
RequestBuilder rb = new RequestBuilder(RequestBuilder.POST, "/new_user");
body = addToPost(body, new_username);
body = addToPost(body, new_passwd);
body = addToPost(body, request_id);
rb.sendRequest(body, new NewAccountCallback(callback));
```

Then the back-end logic can validate the request identifier before processing the rest of the form data. When possible, the request identifier should be unique to each server request rather than shared across every request for a particular session. As with session identifiers, the harder it is for an attacker to guess the request identifier, the harder it is to conduct a successful CSRF attack. The token should not be easily guessed and it should be protected in the same way that session tokens are protected, such as using SSLv3. Additional mitigation techniques include: **Framework protection:** Most modern web application frameworks embed CSRF protection and they will automatically include and verify CSRF tokens. **Use a Challenge-Response control:** Forcing the customer to respond to a challenge sent by the server is a

© Copyright 2008-2026 Open Text.

strong defense against CSRF. Some of the challenges that can be used for this purpose are: CAPTCHAs, password re-authentication and one-time tokens. **Check HTTP Referer/Origin headers:** An attacker won't be able to spoof these headers while performing a CSRF attack. This makes these headers a useful method to prevent CSRF attacks. **Double-submit Session Cookie:** Sending the session ID Cookie as a hidden form value in addition to the actual session ID Cookie is a good protection against CSRF attacks. The server will check both values and make sure they are identical before processing the rest of the form data. If an attacker submits a form in behalf of a user, he won't be able to modify the session ID cookie value as per the same-origin-policy. **Limit Session Lifetime:** When accessing protected resources using a CSRF attack, the attack will only be valid as long as the session ID sent as part of the attack is still valid on the server. Limiting the Session lifetime will reduce the probability of a successful attack. The techniques described here can be defeated with XSS attacks. Effective CSRF mitigation includes XSS mitigation techniques.

Issue Summary



Engine Breakdown

	SCA	WebInspect	SecurityScope	Total
Cross-Site Request Forgery	3	0	0	3
Total	**3**	**0**	**0**	**3**

Cross-Site Request Forgery — Low

Package: .src.api

coube-mobile/src/api/index.ts, line 393 (Cross-Site Request Forgery)

Issue Details

Kingdom: Encapsulation
Scan Engine: SCA (Structural)

Sink Details

Sink: AssignmentStatement
Enclosing Method: uploadCourierPhoto()
File: coube-mobile/src/api/index.ts:393
Taint Flags:

```
390  console.log(' headers:', JSON.stringify(Object.keys(headers)));
391
392  const response = await fetch(url, {
393  method: 'POST',
394  headers,
```


© Copyright 2008-2026 Open Text.

Cross-Site Request Forgery | Low

Package: .src.api

coube-mobile/src/api/index.ts, line 393 (Cross-Site Request Forgery)

```
395  body: formData,
396  });
```

Package: .src.services

coube-mobile/src/services/telegram.ts, line 40 (Cross-Site Request Forgery)

Issue Details

Kingdom: Encapsulation
Scan Engine: SCA (Structural)

Sink Details

Sink: AssignmentStatement
Enclosing Method: sendToBot()
File: coube-mobile/src/services/telegram.ts:40
Taint Flags:

```
37  headers: {
38  'Content-Type': 'application/json',
39  },
40  method: 'POST',
41  });
42
43  if (!response.ok) {
```

Package: .src.utils

coube-frontend/src/utils/notifications.js, line 104 (Cross-Site Request Forgery)

Issue Details

Kingdom: Encapsulation
Scan Engine: SCA (Structural)

Sink Details

Sink: AssignmentStatement
Enclosing Method: sendTokenToBackend()
File: coube-frontend/src/utils/notifications.js:104
Taint Flags:

```
101  }
102
103  const response = await fetch('/api/v1/notifications/register', {
104  method: 'POST',
105  headers,
106  body: JSON.stringify({ token }),
107  });
```


© Copyright 2008-2026 Open Text.

Dockerfile Misconfiguration: Default User Privilege (1 issue)

Abstract

The Dockerfile does not specify a USER, so it defaults to running with a root user.

Explanation

When a `Dockerfile` does not specify a `USER`, Docker containers run with super user privileges by default. These super user privileges are propagated to the code running inside the container, which is usually more permission than necessary. Running the Docker container with super user privileges broadens the attack surface which might enable attackers to perform more serious forms of exploitation.

Recommendation

It is good practice to run your containers as a non-root user when possible. To modify a docker container to use a non-root user, the Dockerfile needs to specify a different user, such as:

```
RUN useradd myLowPrivilegeUser
USER myLowPrivilegeUser
```

Issue Summary



Engine Breakdown

	SCA	WebInspect	SecurityScope	Total
Dockerfile Misconfiguration: Default User Privilege	1	0	0	1
Total	**1**	**0**	**0**	**1**

Dockerfile Misconfiguration: Default User Privilege — High

Package: coube-backend

coube-backend/Dockerfile, line 2 (Dockerfile Misconfiguration: Default User Privilege)

Issue Details

Kingdom: Environment
Scan Engine: SCA (Configuration)

Sink Details

© Copyright 2008-2026 Open Text.

Dockerfile Misconfiguration: Default User Privilege — High

Package: coube-backend

coube-backend/Dockerfile, line 2 (Dockerfile Misconfiguration: Default User Privilege)

Sink: FROM
File: coube-backend/Dockerfile:2
Taint Flags:

```
1 # Этап сборки
2 FROM eclipse-temurin:23-jdk AS builder
3 WORKDIR /app
4
5 # Копируем файлы конфигурации и Gradle wrapper
6
7 undefined
```


© Copyright 2008-2026 Open Text.

Insecure Transport (1 issue)

Abstract

The application uses an insecure protocol instead of a secure protocol to communicate with the server.

Explanation

All communication over HTTP, FTP, or gopher is unauthenticated and unencrypted. It is therefore subject to compromise, especially in the mobile environment where devices frequently connect to unsecured, public, wireless networks using WiFi connections. **Example 1:** The following Spring Boot configuration file disables TLS protocol and therefore uses the HTTP protocol.

```
server.ssl.enabled=false
```

Example 2: The following Spring configuration file requires using HTTP protocol.

```
<intercept-url pattern="/member/**"  access="ROLE_USER" requires-
channel="http"/>
```

Recommendation

Use secure protocols such as HTTPS to exchange data with the server whenever possible. **Example 3:** The following Spring Boot configuration file enables TLS protocol.

```
server.ssl.enabled=true
```

Example 4: The following Spring configuration file requires using HTTPs protocol.

```
<intercept-url pattern="/member/**"  access="ROLE_USER" requires-
channel="https"/>
```

Issue Summary



Engine Breakdown

	SCA	WebInspect	SecurityScope	Total
Insecure Transport	1	0	0	1
Total	**1**	**0**	**0**	**1**

© Copyright 2008-2026 Open Text.

Insecure Transport — Critical

Package: .src.debug

coube-mobile/android/app/src/debug/AndroidManifest.xml, line 8 (Insecure Transport)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-mobile/android/app/src/debug/AndroidManifest.xml:8
Taint Flags:

```
5  <application
6  android:usesCleartextTraffic="true"
7  tools:targetApi="28"
8  tools:ignore="GoogleAppIndexingWarning"/>
9 </manifest>
10
11 undefined
```


© Copyright 2008-2026 Open Text.

Insecure Transport: Disabled App Transport Security (1 issue)

Abstract

Disabling App Transport Security (ATS) partially or entirely may expose the application to network attacks.

Explanation

App Transport Security (ATS) enforces best practices for secure network connections such as TLS 1.2 and forward secrecy and will be updated in the future to reflect Apple's network best practices. App Transport Security (ATS) is enabled by default when using `NSURLSession`, `NSURLConnection`, or `CFURL` in iOS 9 or OS X El Capitan which enforces the application to use `HTTPS` with `TLS 1.2` for all the network communications with the back end server. The application is configured to partially or entirely opt-out of App Transport Security (ATS) which leaves the application at risk of suffering man-in-the-middle attacks and other network-based attacks. **Example 1:** The following entries in the application `Info.plist` will entirely disable App Transport Security:

```
<key>NSAppTransportSecurity</key>
<dict>
<!--Include to allow all connections (DANGER)-->
<key>NSAllowsArbitraryLoads</key>
<true/>
</dict>
```

Example 2: The following entries in the application `Info.plist` will disable App Transport Security for `yourserver.com`:

```
<key>NSAppTransportSecurity</key>
<dict>
<key>NSExceptionDomains</key>
<dict>
<key>yourserver.com</key>
<dict>
<!--Include to allow subdomains-->
<key>NSIncludesSubdomains</key>
<true/>
<!--Allow plain HTTP requests-->
<key>NSTemporaryExceptionAllowsInsecureHTTPLoads</key>
<true/>
<!--Downgrades TLS version-->
<key>NSTemporaryExceptionMinimumTLSVersion</key>
<string>TLSv1.1</string>
</dict>
</dict>
</dict>
```

Recommendation

Do not disable App Transport Security (ATS). If your back end server requires an insecure connection, contact the server administrator to request better security.

Issue Summary

© Copyright 2008-2026 Open Text.



Engine Breakdown

	SCA	WebInspect	SecurityScope	Total
Insecure Transport: Disabled App Transport Security	1	0	0	1
Total	**1**	**0**	**0**	**1**

Insecure Transport: Disabled App Transport Security — Critical

Package: coube-mobile.ios.coube

coube-mobile/ios/coube/Info.plist, line 60 (Insecure Transport: Disabled App Transport Security)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-mobile/ios/coube/Info.plist:60
Taint Flags:

```
57  <key>NSAllowsArbitraryLoads</key>
58  <false/>
59  <key>NSAllowsLocalNetworking</key>
60  <true/>
61  </dict>
62  <key>NSCameraUsageDescription</key>
63  <string>Камера используется для фотографирования повреждений груза, накладных документов и маркировки товаров</string>
```


© Copyright 2008-2026 Open Text.

Insecure Transport: External Link (1 issue)

Abstract

The file links to a third-party site over an unencrypted channel.

Explanation

Ensure that hyperlinks on your web pages only link to secure locations to prevent any user-compromise when navigating around your website. Even if the link redirects from an insecure protocol (such as HTTP) to a secure protocol (such as HTTPS), the initial connection over an unencrypted channel enables an attacker to perform a man-in-the-middle (MiTM) attack. This enables the attacker to control the page the resulting landing page. **Example 1:** Consider the following hyperlink:

```
<a href="http://www.example.com/index.html"/>
```

If an attacker is listening to the network traffic between the user and the server, the attacker can imitate or manipulate `www.example.com` to load their own web page. Links to third-party websites might not initially be considered important to secure, but any compromise can appear to a user as coming from a link on your web page and can therefore lower user trust in using your platform.

Recommendation

Keep control over the web pages linked on your website, and if possible ensure that the links are always loaded over a secure protocol. If an insecure protocol is required by the destination server, provide a warning to inform the user that there is some additional risk from clicking the link. Do not include scripts or other artifacts from third-party sites where possible.

Issue Summary



Engine Breakdown

	SCA	WebInspect	SecurityScope	Total
Insecure Transport: External Link	1	0	0	1
Total	**1**	**0**	**0**	**1**

Insecure Transport: External Link	Medium

Package: .src.main.resources.templates

coube-backend/src/main/resources/templates/acts_template.html, line 175 (Insecure Transport: External Link)

Issue Details

© Copyright 2008-2026 Open Text.

Insecure Transport: External Link — Medium

Package: .src.main.resources.templates

coube-backend/src/main/resources/templates/acts_template.html, line 175 (Insecure Transport: External Link)

Kingdom: Security Features
Scan Engine: SCA (Content)

Sink Details

Sink:
File: coube-backend/src/main/resources/templates/acts_template.html:175
Taint Flags:

```
172  <td class="column13"> </td>
173  <td class="column14"> </td>
174  <td class="column15"> </td>
175  <td class="column16 style17 s style17" colspan="3"><a href="http://online.zakon.kz/
Document/?link_id=1004352905" title="Приказ Министра финансов Республики Казахстан от 27
октября 2014 года № 458 О внесении изменения в приказ Министра финансов Республики Казахстан
от 20 декабря 2012 года № 562 «Об утверждении форм первичных учетных
документов»">к приказу Министра финансов</a></td>
176  </tr>
177  <tr class="row2">
178  <td class="column1"> </td>
```


© Copyright 2008-2026 Open Text.

Key Management: Hardcoded Encryption Key (1 issue)

Abstract

Hardcoded encryption keys can compromise security in a way that is not easy to remedy.

Explanation

Never hardcode an encryption key because it makes the encryption key visible to all of the project's developers, and makes fixing the problem extremely difficult. Changing the encryption key after the code is in production requires a software patch. If the account that the encryption key protects is compromised, the organization must choose between security and system availability. **Example 1:** The following example shows an encryption key inside a .pem file:

```
...
-----BEGIN RSA PRIVATE KEY-----
MIICXwIBAAKBgQCtVacMo+w+TFOm0p8MlBWvwXtVRpF28V+o0RNPx5x/1TJTlKEl
...
DiJPJY2LNBQ7jS685mb6650JdvH8uQl6oeJ/aUmq63o2zOw=
-----END RSA PRIVATE KEY-----
...
```

Anyone with access to the code can see the encryption key. After the application has shipped, there is no way to change the encryption key unless the program is patched. An employee with access to this information can use it to break into the system. Any attacker with access to the application executable can extract the encryption key value.

Recommendation

Never check in encryption keys to your source control system, and never hardcode them. Always obfuscate and manage encryption keys in an external source. Storing encryption keys in plain text anywhere on the system enables anyone with sufficient permissions to read and potentially misuse the encryption key.

Issue Summary



Engine Breakdown

	SCA	WebInspect	SecurityScope	Total
Key Management: Hardcoded Encryption Key	1	0	0	1
Total	**1**	**0**	**0**	**1**

© Copyright 2008-2026 Open Text.

Key Management: Hardcoded Encryption Key — Critical

Package: .src.main.resources.notification-config

coube-backend/src/main/resources/notification-config/coube-notifications-account-key.json, line 5 (Key Management: Hardcoded Encryption Key)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-backend/src/main/resources/notification-config/coube-notifications-account-key.json:5
Taint Flags:

```
2  "type": "service_account",
3  "project_id": "coube-kz",
4  "private_key_id": "a59d49a88268086a9faa7a6e931173f06d1e5d95",
5  "private_key": "-----BEGIN PRIVATE KEY-----
\nMIIEvwIBADANBgkqhkiG9w0BAQEFAASCBKkwggSlAgEAAoIBAQDa5O1sarNSjnZq\nkALPlJjg2cEgoxSA6EcvFkYKwUiL
w4SI76pL\n3Z5Ucu9YPfQVpOEPCaqtGkpMATvbpiEtgawEeZB59BeI0NcPzF39GbPhhTT5ud6s\nWcNr/SnTCMtIDy/
4AthiizYmx+ZyIg1WNb6nJksmirkxha4vnGNXa67qBKBZVUJg\nsoSyWS0NbW7aFit9btsAY2x8Qv1ZMcTkNIDr5c7oVs6cx
FYx38Ucm\nWBBtpUFPAgMBAAECggEAVO+7yPPmPUSWYmcbEB0i7SzRqa5eCF8ZMAY+i3HQimKc\nIaQV0JQ+NMNXWU0HEoDM
uubSMK/qawglCa9aZyY83QV\nL6k/
bEUXcJrsfuQ6byDn34wXpoyfr78Vzl7OW5rSndatunpaLKw99o76JjYvD127\nhT2H9P3Zad0okejY111JgkuNJSdr45pNal
3WkyX6NMJZzV1ptZX4W+XraKxF5Zt0CjAS8NnQa7LR\nsR56EIemXXhPSOzAcCgzinqJnOqxk+a4AOJ33MV8wQKBgQDsx4nc
w5jXHt0wx2th+p79pEUnvlnZfc87BO/
cjKizxFNJ9lPr3+u3MmL\nNdO3PovW6qUon6wqqV8hfiDNVRG8uwUfSjNMyo9I8exaXvWGjgqd6SHqJbR4H2Dg\nP0EqDzdF
V\n1mnDzLaPnieY7G8e8Z0tLIJwEDBizkCtNOJlwUoYVvdgdcl7ZKDgCpH8Dcn1kN6+
\nJ5cJgw9UcQKBgQCitR+001FUubDSmXWQh9J2B69EeM6el+5gMw4XF3lOZOaqFq5t\nmCzUc8oo0CVl2miXXmmKNobrbjL0
SnI3xr9tujZ9FZsY\nfFmyPEOoIa6ED1rzAqqjBrAqgYx5Oz7L+kuiRmB553oEAAyO/s/
pDv1rawKBgQDU\n7yfMkjit15Kd26eHv2LEiWTeCpJomLmOkCzEd50MX6nCvf6ZbHQQgMObBvkgZZBC\npkR8skxsI0vzVp4
7wNtJlZrX22lCmOromK4w+zUIFyFGbb0KU2zt0FMfGhz6PXQxM+W/J\nTrFiHFYg0NFDJPxdM14ZOmVFed6PRMz2/
xGshjC6WstikLwejxwxEY7muzsYb76W\nuXfmqrTCYvKrOkZ4F2Rg0KndTQ==\n-----END PRIVATE KEY-----\n",
6  "client_email": "firebase-adminsdk-fbsvc@coube-kz.iam.gserviceaccount.com",
7  "client_id": "113683450309446304155",
8  "auth_uri": "https://accounts.google.com/o/oauth2/auth",
```


© Copyright 2008-2026 Open Text.

Password Management: Hardcoded Password (1 issue)

Abstract

Hardcoded passwords can compromise system security in a way that is difficult to remedy.

Explanation

Never hardcode passwords. Not only does it expose the password to all of the project's developers, it also makes fixing the problem extremely difficult. After the code is in production, a program patch is probably the only way to change the password. If the account protected by the password is compromised, the organization must choose between security and system availability. **Example 1:** The following URL uses a hardcoded password:

```
...
https://user:secretpassword@example.com
...
```

Example 2: The following ODBC connection string uses a hardcoded password:

```
...
server=Server;database=Database;UID=UserName;PWD=Password;Encrypt=yes;
...
```

Recommendation

Example 3: The following ODBC connection string addresses the hardcoded password issue in `Example 2` by implementing Integrated Windows Authentication:

```
...
server=Server;database=Database;Trusted_Connection=yes;Encrypt=yes;
...
```

Never use hardcoded passwords. Always obfuscate and manage passwords in an external source. Storing passwords in plain text anywhere on the system enables anyone with sufficient permissions to read and potentially misuse the password.

Issue Summary



Engine Breakdown

	SCA	WebInspect	SecurityScope	Total
Password Management: Hardcoded Password	1	0	0	1
Total	**1**	**0**	**0**	**1**

© Copyright 2008-2026 Open Text.

Password Management: Hardcoded Password — Critical

Package: .src.test.java.kz.coube.backend.common.utils

coube-backend/src/test/java/kz/coube/backend/common/utils/HttpUtilsTest.java, line 11 (Password Management: Hardcoded Password)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-backend/src/test/java/kz/coube/backend/common/utils/HttpUtilsTest.java:11
Taint Flags:

```
8
9  @Test
10  void verifyBasicHeaderIsValidBase64() {
11  final var validValue = "Basic dGVzdDp0ZXN0UGFzc3dvcmQxMjM0";
12  var result = HttpUtils.getBasicAuthHeaderValue("test", "testPassword1234");
13  assertEquals(validValue, result, "Basic header not matched!");
14  }
```


© Copyright 2008-2026 Open Text.

Password Management: Password in Comment (1 issue)

Abstract

Storing passwords or password details in plain text anywhere in the system or system code might compromise system security in a way that is not easy to remedy.

Explanation

It is never a good idea to hardcode a password. Storing password details within comments is equivalent to hardcoding passwords. Not only is the password visible to the project's developers, it also makes fixing the problem extremely difficult. After the code is in production, the password is now leaked to the outside world and cannot be protected or changed without patching the software. If the account protected by the password is compromised, the owners of the system must choose between security and availability.
Example 1: The following comment specifies the default password to connect to a database:

```
...
// Default username for database connection is "scott"
// Default password for database connection is "tiger"
...
```

This code will run successfully, but anyone who has access to it will have access to the password. An employee with access to this information can use it to break into the system.

Recommendation

Passwords should never be hardcoded and should generally be obfuscated and managed in an external source. Storing passwords in plain text anywhere on the system allows anyone with sufficient permissions to read and potentially misuse the password.

Issue Summary



Engine Breakdown

	SCA	WebInspect	SecurityScope	Total
Password Management: Password in Comment	1	0	0	1
Total	**1**	**0**	**0**	**1**

© Copyright 2008-2026 Open Text.

Password Management: Password in Comment | Low

Package: .src.main.java.kz.coube.backend.auth.keycloak.service

coube-backend/src/main/java/kz/coube/backend/auth/keycloak/service/KeycloakUserService.java, line 34 (Password Management: Password in Comment)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Structural)

Sink Details

Sink: Comment
File: coube-backend/src/main/java/kz/coube/backend/auth/keycloak/service/KeycloakUserService.java:34
Taint Flags:

```
31  .username(userRegistrationData.phone())
32  .attributes(
33  new Attributes(userRegistrationData.phone(), userRegistrationData.orgIinBin(), null))
34  .credentials(List.of(Credential.fromPassword("password"))) // TODO: mock otp password
35  .build();
36
37  backendClient.post()
```


© Copyright 2008-2026 Open Text.

Password Management: Password in Configuration File (2 issues)

Abstract

Storing a plain text password in a configuration file may result in a system compromise.

Explanation

Storing a plain text password in a configuration file allows anyone who can read the file access to the password-protected resource. Developers sometimes believe that they cannot defend the application from someone who has access to the configuration, but this attitude makes an attacker's job easier. Good password management guidelines require that a password never be stored in plain text.

Recommendation

A password should never be stored in plain text. An administrator should be required to enter the password when the system starts. If that approach is impractical, a less secure but often adequate solution is to obfuscate the password and scatter the de-obfuscation material around the system so that an attacker has to obtain and correctly combine multiple system resources to decipher the password. Some third-party products claim the ability to manage passwords in a more secure way. For example, WebSphere Application Server 4.x uses a simple XOR encryption algorithm for obfuscating values, but be skeptical about such facilities. WebSphere and other application servers offer outdated and relatively weak encryption mechanisms that are insufficient for security-sensitive environments. For a secure solution the only viable option is a proprietary one.

Issue Summary



Engine Breakdown

	SCA	WebInspect	SecurityScope	Total
Password Management: Password in Configuration File	2	0	0	2
Total	**2**	**0**	**0**	**2**

Password Management: Password in Configuration File — High

Package: coube-mobile.android

coube-mobile/android/gradle.properties, line 48 (Password Management: Password in Configuration File)

Issue Details

© Copyright 2008-2026 Open Text.

Password Management: Password in Configuration File — High

Package: coube-mobile.android

coube-mobile/android/gradle.properties, line 48 (Password Management: Password in Configuration File)

Kingdom: Environment
Scan Engine: SCA (Configuration)

Sink Details

Sink: MYAPP_UPLOAD_STORE_PASSWORD
File: coube-mobile/android/gradle.properties:48
Taint Flags:

```
45
46 MYAPP_UPLOAD_STORE_FILE=my-upload-key.keystore
47 MYAPP_UPLOAD_KEY_ALIAS=my-key-alias
48 MYAPP_UPLOAD_STORE_PASSWORD=L578s#
49 MYAPP_UPLOAD_KEY_PASSWORD=L578s#
50
51 undefined
```

coube-mobile/android/gradle.properties, line 49 (Password Management: Password in Configuration File)

Issue Details

Kingdom: Environment
Scan Engine: SCA (Configuration)

Sink Details

Sink: MYAPP_UPLOAD_KEY_PASSWORD
File: coube-mobile/android/gradle.properties:49
Taint Flags:

```
46 MYAPP_UPLOAD_STORE_FILE=my-upload-key.keystore
47 MYAPP_UPLOAD_KEY_ALIAS=my-key-alias
48 MYAPP_UPLOAD_STORE_PASSWORD=L578s#
49 MYAPP_UPLOAD_KEY_PASSWORD=L578s#
50
51 undefined
52 undefined
```


© Copyright 2008-2026 Open Text.

Privacy Violation (8 issues)

Abstract

Mishandling private information, such as customer passwords or social security numbers, can compromise user privacy and is often illegal.

Explanation

Privacy violations occur when: 1. Private user information enters the program. 2. The data is written to an external location, such as the console, file system, or network. **Example 1:** The following code stores user's plain text password to the local storage.

```
localStorage.setItem('password', password);
```

Although many developers treat the local storage as a safe location for data, it should not be trusted implicitly, particularly when privacy is a concern. Private data can enter a program in a variety of ways: - Directly from the user in the form of a password or personal information - Accessed from a database or other data store by the application - Indirectly from a partner or other third party Sometimes data that is not labeled as private can have a privacy implication in a different context. For example, student identification numbers are usually not considered private because there is no explicit and publicly-available mapping to an individual student's personal information. However, if a school generates identification numbers based on student social security numbers, then the identification numbers should be considered private. Security and privacy concerns often seem to compete with each other. From a security perspective, you should record all important operations so that any anomalous activity can later be identified. However, when private data is involved, this practice can create risk. Although there are many ways in which private data can be handled unsafely, a common risk stems from misplaced trust. Programmers often trust the operating environment in which a program runs, and therefore believe that it is acceptable to store private information on the file system, in the registry, or in other locally-controlled resources. However, even if access to certain resources is restricted, this does not guarantee that the individuals who do have access can be trusted. For example, in 2004, an unscrupulous employee at AOL sold approximately 92 million private customer email addresses to a spammer marketing an offshore gambling web site [1]. In response to such high-profile exploits, the collection and management of private data is becoming increasingly regulated. Depending on its location, the type of business it conducts, and the nature of any private data it handles, an organization may be required to comply with one or more of the following federal and state regulations: - Safe Harbor Privacy Framework [3] - Gramm-Leach Bliley Act (GLBA) [4] - Health Insurance Portability and Accountability Act (HIPAA) [5] - California SB-1386 [6] Despite these regulations, privacy violations continue to occur with alarming frequency.

Recommendation

When security and privacy demands clash, privacy should usually be given the higher priority. To accomplish this and still maintain required security information, cleanse any private information before it exits the program. To enforce good privacy management, develop and strictly adhere to internal privacy guidelines. The guidelines should specifically describe how an application should handle private data. If your organization is regulated by federal or state law, ensure that your privacy guidelines are sufficiently strenuous to meet the legal requirements. Even if your organization is not regulated, you must protect private information or risk losing customer confidence. The best policy with respect to private data is to minimize its exposure. Applications, processes, and employees should not be granted access to any private data unless the access is required for the tasks that they are to perform. Just as the principle of least privilege dictates that no operation should be performed with more than the necessary privileges, access to private data should be restricted to the smallest possible group.

Issue Summary

© Copyright 2008-2026 Open Text.



Engine Breakdown

	SCA	WebInspect	SecurityScope	Total
Privacy Violation	8	0	0	8
Total	**8**	**0**	**0**	**8**

Privacy Violation — Critical

Package: .src.components

coube-mobile/src/components/EmulatorSendLocationButton.tsx, line 40 (Privacy Violation)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Data Flow)

Source Details

Source: Read latitude
From: handleForceLocation
File: coube-mobile/src/components/EmulatorSendLocationButton.tsx:31

```
28  accuracy: location.coords.accuracy || 0,
29  heading: location.coords.heading || 0,
30  point: {
31  lat: location.coords.latitude,
32  lng: location.coords.longitude,
33  },
34  speed: location.coords.speed || 0,
```

Sink Details

Sink: ~JS_Generic.log()
Enclosing Method: handleForceLocation()
File: coube-mobile/src/components/EmulatorSendLocationButton.tsx:40
Taint Flags: PRIVATE

```
37  };
38
39  await sendDriverLocation(locationData);
40  console.log('Эмулирована отправка геолокации:', locationData);
```


© Copyright 2008-2026 Open Text.

Privacy Violation — Critical

Package: .src.components

coube-mobile/src/components/EmulatorSendLocationButton.tsx, line 40 (Privacy Violation)

```
41  } catch (error) {
42  console.error('Error sending location:', error);
43  }
```

coube-mobile/src/components/EmulatorSendLocationButton.tsx, line 40 (Privacy Violation)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Data Flow)

Source Details

Source: Read longitude
From: handleForceLocation
File: coube-mobile/src/components/EmulatorSendLocationButton.tsx:32

```
29  heading: location.coords.heading || 0,
30  point: {
31  lat: location.coords.latitude,
32  lng: location.coords.longitude,
33  },
34  speed: location.coords.speed || 0,
35  timestamp: new Date(location.timestamp).toISOString(),
```

Sink Details

Sink: ~JS_Generic.log()
Enclosing Method: handleForceLocation()
File: coube-mobile/src/components/EmulatorSendLocationButton.tsx:40
Taint Flags: PRIVATE

```
37  };
38
39  await sendDriverLocation(locationData);
40  console.log('Эмулирована отправка геолокации:', locationData);
41  } catch (error) {
42  console.error('Error sending location:', error);
43  }
```

Package: .src.screens

coube-mobile/src/screens/ProfileScreen.tsx, line 71 (Privacy Violation)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Data Flow)

© Copyright 2008-2026 Open Text.

Privacy Violation — Critical

Package: .src.screens

coube-mobile/src/screens/ProfileScreen.tsx, line 71 (Privacy Violation)

Source Details

Source: Read latitude
From: handleSendGeolocation
File: coube-mobile/src/screens/ProfileScreen.tsx:63

```
60  accuracy: location.coords.accuracy || 0,
61  heading: location.coords.heading || 0,
62  point: {
63  lat: location.coords.latitude,
64  lng: location.coords.longitude,
65  },
66  speed: location.coords.speed || 0,
```

Sink Details

Sink: ~JS_Generic.log()
Enclosing Method: handleSendGeolocation()
File: coube-mobile/src/screens/ProfileScreen.tsx:71
Taint Flags: PRIVATE

```
68  },
69  };
70  await sendDriverLocation(locationData);
71  console.log('Эмулирована отправка геолокации:', locationData);
72  } catch (error) {
73  console.error('Error sending location:', error);
74  }
```

coube-mobile/src/screens/ProfileScreen.tsx, line 71 (Privacy Violation)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Data Flow)

Source Details

Source: Read longitude
From: handleSendGeolocation
File: coube-mobile/src/screens/ProfileScreen.tsx:64

```
61  heading: location.coords.heading || 0,
62  point: {
63  lat: location.coords.latitude,
64  lng: location.coords.longitude,
65  },
66  speed: location.coords.speed || 0,
67  timestamp: new Date(location.timestamp).toISOString(),
```


© Copyright 2008-2026 Open Text.

Privacy Violation — Critical

Package: .src.screens

coube-mobile/src/screens/ProfileScreen.tsx, line 71 (Privacy Violation)

Sink Details

Sink: ~JS_Generic.log()
Enclosing Method: handleSendGeolocation()
File: coube-mobile/src/screens/ProfileScreen.tsx:71
Taint Flags: PRIVATE

```
68  },
69  };
70  await sendDriverLocation(locationData);
71  console.log('Эмулирована отправка геолокации:', locationData);
72  } catch (error) {
73  console.error('Error sending location:', error);
74  }
```

coube-mobile/src/screens/GeolocationScreen.tsx, line 280 (Privacy Violation)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Data Flow)

Source Details

Source: Read latitude
From: GeolocationScreen
File: coube-mobile/src/screens/GeolocationScreen.tsx:280

```
277  {currentLocation && (
278  <View style={styles.locationInfo}>
279  <Text style={styles.locationTitle}>Текущее местоположение:</Text>
280  <Text>Широта: {currentLocation.coords.latitude}</Text>
281  <Text>Долгота: {currentLocation.coords.longitude}</Text>
282  <Text>Точность: {currentLocation.coords.accuracy}м</Text>
283  <Text>Скорость: {currentLocation.coords.speed || 0} м/с</Text>
```

Sink Details

Sink: Read children
Enclosing Method: GeolocationScreen()
File: coube-mobile/src/screens/GeolocationScreen.tsx:280
Taint Flags: PRIVATE

```
277  {currentLocation && (
278  <View style={styles.locationInfo}>
279  <Text style={styles.locationTitle}>Текущее местоположение:</Text>
280  <Text>Широта: {currentLocation.coords.latitude}</Text>
281  <Text>Долгота: {currentLocation.coords.longitude}</Text>
282  <Text>Точность: {currentLocation.coords.accuracy}м</Text>
```


© Copyright 2008-2026 Open Text.

Privacy Violation — Critical

Package: .src.screens

coube-mobile/src/screens/GeolocationScreen.tsx, line 280 (Privacy Violation)

```
283  <Text>Скорость: {currentLocation.coords.speed || 0} м/с</Text>
```

coube-mobile/src/screens/GeolocationScreen.tsx, line 281 (Privacy Violation)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Data Flow)

Source Details

Source: Read longitude
From: GeolocationScreen
File: coube-mobile/src/screens/GeolocationScreen.tsx:281

```
278  <View style={styles.locationInfo}>
279  <Text style={styles.locationTitle}>Текущее местоположение:</Text>
280  <Text>Широта: {currentLocation.coords.latitude}</Text>
281  <Text>Долгота: {currentLocation.coords.longitude}</Text>
282  <Text>Точность: {currentLocation.coords.accuracy}м</Text>
283  <Text>Скорость: {currentLocation.coords.speed || 0} м/с</Text>
284  <Text>Направление: {currentLocation.coords.heading || 0}°</Text>
```

Sink Details

Sink: Read children
Enclosing Method: GeolocationScreen()
File: coube-mobile/src/screens/GeolocationScreen.tsx:281
Taint Flags: PRIVATE

```
278  <View style={styles.locationInfo}>
279  <Text style={styles.locationTitle}>Текущее местоположение:</Text>
280  <Text>Широта: {currentLocation.coords.latitude}</Text>
281  <Text>Долгота: {currentLocation.coords.longitude}</Text>
282  <Text>Точность: {currentLocation.coords.accuracy}м</Text>
283  <Text>Скорость: {currentLocation.coords.speed || 0} м/с</Text>
284  <Text>Направление: {currentLocation.coords.heading || 0}°</Text>
```

Package: .src.service

coube-mobile/src/service/geolocation.ts, line 586 (Privacy Violation)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Data Flow)

Source Details

Source: Read latitude
From: handleLocation

© Copyright 2008-2026 Open Text.

Privacy Violation | Critical

Package: .src.service

coube-mobile/src/service/geolocation.ts, line 586 (Privacy Violation)

File: coube-mobile/src/service/geolocation.ts:590

```
587  accuracy: location.coords.accuracy,
588  event: location.event,
589  is_moving: location.is_moving,
590  lat: location.coords.latitude,
591  lng: location.coords.longitude,
592  speed: location.coords.speed,
593  timestamp: location.timestamp
```

Sink Details

Sink: ~JS_Generic.log()
Enclosing Method: handleLocation()
File: coube-mobile/src/service/geolocation.ts:586
Taint Flags: PRIVATE

```
583
584  private handleLocation = async (location: Location) => {
585  try {
586  console.log('[^?^? Location] Received:', {
587  accuracy: location.coords.accuracy,
588  event: location.event,
589  is_moving: location.is_moving,
```

coube-mobile/src/service/geolocation.ts, line 586 (Privacy Violation)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Data Flow)

Source Details

Source: Read longitude
From: handleLocation
File: coube-mobile/src/service/geolocation.ts:591

```
588  event: location.event,
589  is_moving: location.is_moving,
590  lat: location.coords.latitude,
591  lng: location.coords.longitude,
592  speed: location.coords.speed,
593  timestamp: location.timestamp
594  });
```

Sink Details

© Copyright 2008-2026 Open Text.

Privacy Violation | Critical

Package: .src.service

coube-mobile/src/service/geolocation.ts, line 586 (Privacy Violation)

Sink: ~JS_Generic.log()
Enclosing Method: handleLocation()
File: coube-mobile/src/service/geolocation.ts:586
Taint Flags: PRIVATE

```
583
584  private handleLocation = async (location: Location) => {
585  try {
586  console.log('[^?^? Location] Received:', {
587  accuracy: location.coords.accuracy,
588  event: location.event,
589  is_moving: location.is_moving,
```


© Copyright 2008-2026 Open Text.

Privilege Management: Android Camera (1 issue)

Abstract

The application declares the use of a permission that controls access to the device's camera.

Explanation

This permission has a "dangerous" protection level. Permissions designated as dangerous imply an increased risk to user data privacy or device operation. In this case, access to the camera can pose a danger to user privacy and personal safety. Applications that require camera access must manage it with the utmost caution. **Example 1:** The element of AndroidManifest.xml declares usage of the `CAMERA` permission, which enables an application to access the device's camera.

```
<uses-permission android:name="android.permission.CAMERA"/>
```

Recommendation

Validate that implemented application features require camera access to function properly. If camera access is absolutely necessary, then consider the following data privacy suggestions: - Remediate any critical security vulnerabilities in the application to reduce risk and magnitude of compromise to data privacy. - Avoid storing media retrieved from the camera to external storage. If you must transfer media from the camera, use encryption to protect the data in transit and at rest. - Ensure that your privacy policy discloses how the application collects, uses, and shares media and metadata obtained from the camera. - Assess the regulatory and compliance implications of camera access and use, and ensure conformance with applicable laws and standards governing the protection of private information. - Promptly and properly dispose of media and data retrieved from the camera when it is no longer needed.

Issue Summary



Engine Breakdown

	SCA	WebInspect	SecurityScope	Total
Privilege Management: Android Camera	1	0	0	1
Total	**1**	**0**	**0**	**1**

© Copyright 2008-2026 Open Text.

Privilege Management: Android Camera — High

Package: .src.main

coube-mobile/android/app/src/main/AndroidManifest.xml, line 12 (Privilege Management: Android Camera)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-mobile/android/app/src/main/AndroidManifest.xml:12
Taint Flags:

```
9  <uses-permission android:name="android.permission.FOREGROUND_SERVICE_LOCATION" />
10  <uses-permission android:name="android.permission.POST_NOTIFICATIONS" />
11  <uses-permission android:name="android.permission.WAKE_LOCK" />
12  <uses-permission android:name="android.permission.CAMERA" />
13
14  <uses-permission android:name="android.permission.READ_EXTERNAL_STORAGE"
android:maxSdkVersion="32" />
15  <uses-permission android:name="android.permission.WRITE_EXTERNAL_STORAGE"
android:maxSdkVersion="32" />
```


© Copyright 2008-2026 Open Text.

Privilege Management: Android Data Storage (2 issues)

Abstract

The program requests permission to write data to Android's external storage.

Explanation

Files written to external storage are readable and writeable by arbitrary programs and users. Programs must never write sensitive information, for instance personally identifiable information, to external storage. When you connect the Android device via USB to a PC or other device it enables USB mass storage mode. Any file written to external storage can be read and modified in this mode. In addition, files in external storage will remain there even after the application that wrote them is uninstalled, further increasing the risk that any sensitive information stored in them will be compromised. **Example 1:**The element of AndroidManifest.xml declares usage of the `WRITE_EXTERNAL_STORAGE` permission, which enables an application to write to external storage.

```
<uses-permission android:name="android.permission.WRITE_EXTERNAL_STORAGE"/>
```

Example 2: The element of AndroidManifest.xml declares usage of the `READ_EXTERNAL_STORAGE` permission, which enables and application to read from external storage.

```
<uses-permission android:name="android.permission.READ_EXTERNAL_STORAGE"/>
```

Recommendation

Do not write sensitive information or data that must later be trusted to external storage. Instead, write to a program-specific location, such as a SQLite database (provided by the Android platform). Any databases you create will be accessible by name to any class in the program, but not outside the program. **Example 3:** Create a new SQLite database by creating a subclass of `SQLiteOpenHelper` and override the `OnCreate()` method.

```
public class MyDbOpenHelper extends SQLiteOpenHelper {

private static final int DATABASE_VERSION = 2;
private static final String DICTIONARY_TABLE_NAME = "dictionary";
private static final String DICTIONARY_TABLE_CREATE =
"CREATE TABLE " + DICTIONARY_TABLE_NAME + " (" +
KEY_WORD + " TEXT, " +
KEY_DEFINITION + " TEXT);";

DictionaryOpenHelper(Context context) {
super(context, DATABASE_NAME, null, DATABASE_VERSION);
}

@Override
public void onCreate(SQLiteDatabase db) {
db.execSQL(DICTIONARY_TABLE_CREATE);
}
}
```

Another option is to write to the device's internal storage. By default, files saved to the internal storage are private to the program that writes them and are inaccessible to other programs and to the user's direct means. When the user uninstalls a program, files stored on internal storage are also removed, diminishing the chance that something important will be left around. **Example 4:** The following code creates and writes a private file to the device's internal storage. The declaration `Context.MODE_PRIVATE` creates the file (or replaces a file of the same name) and makes it private to current program.

```
String FILENAME = "hello_file";
String string = "hello world!";
```


© Copyright 2008-2026 Open Text.

```
FileOutputStream fos = openFileOutput(FILENAME, Context.MODE_PRIVATE);
fos.write(string.getBytes());
fos.close();
```

Issue Summary



Engine Breakdown

	SCA	WebInspect	SecurityScope	Total
Privilege Management: Android Data Storage	2	0	0	2
Total	**2**	**0**	**0**	**2**

Privilege Management: Android Data Storage — High

Package: .src.main

coube-mobile/android/app/src/main/AndroidManifest.xml, line 14 (Privilege Management: Android Data Storage)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-mobile/android/app/src/main/AndroidManifest.xml:14
Taint Flags:

```
11  <uses-permission android:name="android.permission.WAKE_LOCK" />
12  <uses-permission android:name="android.permission.CAMERA" />
13
14  <uses-permission android:name="android.permission.READ_EXTERNAL_STORAGE"
android:maxSdkVersion="32" />
15  <uses-permission android:name="android.permission.WRITE_EXTERNAL_STORAGE"
android:maxSdkVersion="32" />
16
17  <!-- Queries для eGov Mobile (Android 11+) -->
```

coube-mobile/android/app/src/main/AndroidManifest.xml, line 15 (Privilege Management: Android Data Storage)

Issue Details

© Copyright 2008-2026 Open Text.

Privilege Management: Android Data Storage | High

Package: .src.main

coube-mobile/android/app/src/main/AndroidManifest.xml, line 15 (Privilege Management: Android Data Storage)

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-mobile/android/app/src/main/AndroidManifest.xml:15
Taint Flags:

```
12  <uses-permission android:name="android.permission.CAMERA" />
13
14  <uses-permission android:name="android.permission.READ_EXTERNAL_STORAGE"
android:maxSdkVersion="32" />
15  <uses-permission android:name="android.permission.WRITE_EXTERNAL_STORAGE"
android:maxSdkVersion="32" />
16
17  <!-- Queries для eGov Mobile (Android 11+) -->
18  <queries>
```


© Copyright 2008-2026 Open Text.

Privilege Management: Unnecessary Permission (4 issues)

Abstract

The application fails to adhere to the principle of least privilege, which greatly amplifies the risk posed by other vulnerabilities.

Explanation

An application should only have the minimum permissions required for its proper execution. Extra permissions might deter users from installing the application. This permission might be unnecessary for this program.

Recommendation

Consider whether the application requires the requested permission in order to function properly. If it does not, you should remove the permission from the `AndroidManifest.xml` file. Do no over-permission the application by requesting more permissions than it really needs. This can lead to other malicious applications installed on the device taking advantage of such over-permissioned applications to adversely impact the user experience and the stored data. Additionally, extra permissions may unnecessarily discourage customers from installing your application.

Issue Summary



Engine Breakdown

	SCA	WebInspect	SecurityScope	Total
Privilege Management: Unnecessary Permission	4	0	0	4
Total	**4**	**0**	**0**	**4**

Privilege Management: Unnecessary Permission — High

Package: .src.main

coube-mobile/android/app/src/main/AndroidManifest.xml, line 5 (Privilege Management: Unnecessary Permission)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

© Copyright 2008-2026 Open Text.

Privilege Management: Unnecessary Permission — High

Package: .src.main

coube-mobile/android/app/src/main/AndroidManifest.xml, line 5 (Privilege Management: Unnecessary Permission)

Sink:
File: coube-mobile/android/app/src/main/AndroidManifest.xml:5
Taint Flags:

```
2  xmlns:tools="http://schemas.android.com/tools">
3  <uses-sdk tools:overrideLibrary="ru.vvdev.yamap,com.yandex.maps.mobile" />
4  <uses-permission android:name="android.permission.INTERNET" />
5  <uses-permission android:name="android.permission.ACCESS_FINE_LOCATION" />
6  <uses-permission android:name="android.permission.ACCESS_COARSE_LOCATION" />
7  <uses-permission android:name="android.permission.ACCESS_BACKGROUND_LOCATION" />
8  <uses-permission android:name="android.permission.FOREGROUND_SERVICE" />
```

coube-mobile/android/app/src/main/AndroidManifest.xml, line 11 (Privilege Management: Unnecessary Permission)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-mobile/android/app/src/main/AndroidManifest.xml:11
Taint Flags:

```
8  <uses-permission android:name="android.permission.FOREGROUND_SERVICE" />
9  <uses-permission android:name="android.permission.FOREGROUND_SERVICE_LOCATION" />
10  <uses-permission android:name="android.permission.POST_NOTIFICATIONS" />
11  <uses-permission android:name="android.permission.WAKE_LOCK" />
12  <uses-permission android:name="android.permission.CAMERA" />
13
14  <uses-permission android:name="android.permission.READ_EXTERNAL_STORAGE"
android:maxSdkVersion="32" />
```

coube-mobile/android/app/src/main/AndroidManifest.xml, line 4 (Privilege Management: Unnecessary Permission)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-mobile/android/app/src/main/AndroidManifest.xml:4
Taint Flags:

```
1 <manifest xmlns:android="http://schemas.android.com/apk/res/android"
2  xmlns:tools="http://schemas.android.com/tools">
```


© Copyright 2008-2026 Open Text.

Privilege Management: Unnecessary Permission — High

Package: .src.main

coube-mobile/android/app/src/main/AndroidManifest.xml, line 4 (Privilege Management: Unnecessary Permission)

```
3  <uses-sdk tools:overrideLibrary="ru.vvdev.yamap,com.yandex.maps.mobile" />
4  <uses-permission android:name="android.permission.INTERNET" />
5  <uses-permission android:name="android.permission.ACCESS_FINE_LOCATION" />
6  <uses-permission android:name="android.permission.ACCESS_COARSE_LOCATION" />
7  <uses-permission android:name="android.permission.ACCESS_BACKGROUND_LOCATION" />
```

coube-mobile/android/app/src/main/AndroidManifest.xml, line 6 (Privilege Management: Unnecessary Permission)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Configuration)

Sink Details

Sink:
File: coube-mobile/android/app/src/main/AndroidManifest.xml:6
Taint Flags:

```
3  <uses-sdk tools:overrideLibrary="ru.vvdev.yamap,com.yandex.maps.mobile" />
4  <uses-permission android:name="android.permission.INTERNET" />
5  <uses-permission android:name="android.permission.ACCESS_FINE_LOCATION" />
6  <uses-permission android:name="android.permission.ACCESS_COARSE_LOCATION" />
7  <uses-permission android:name="android.permission.ACCESS_BACKGROUND_LOCATION" />
8  <uses-permission android:name="android.permission.FOREGROUND_SERVICE" />
9  <uses-permission android:name="android.permission.FOREGROUND_SERVICE_LOCATION" />
```


© Copyright 2008-2026 Open Text.

Weak Cryptographic Hash (137 issues)

Abstract

Weak cryptographic hashes cannot guarantee data integrity and should not be used in security-critical contexts.

Explanation

MD2, MD4, MD5, RIPEMD-160, and SHA-1 are popular cryptographic hash algorithms often used to verify the integrity of messages and other data. However, as recent cryptanalysis research has revealed fundamental weaknesses in these algorithms, they should no longer be used within security-critical contexts. Effective techniques for breaking MD and RIPEMD hashes are widely available, so those algorithms should not be relied upon for security. In the case of SHA-1, current techniques still require a significant amount of computational power and are more difficult to implement. However, attackers have found the Achilles' heel for the algorithm, and techniques for breaking it will likely lead to the discovery of even faster attacks.

Recommendation

Discontinue the use of MD2, MD4, MD5, RIPEMD-160, and SHA-1 for data-verification in security-critical contexts. Currently, SHA-224, SHA-256, SHA-384, SHA-512, and SHA-3 are good alternatives. However, these variants of the Secure Hash Algorithm have not been scrutinized as closely as SHA-1, so be mindful of future research that might impact the security of these algorithms.

Issue Summary



Engine Breakdown

	SCA	WebInspect	SecurityScope	Total
Weak Cryptographic Hash	137	0	0	137
Total	**137**	**0**	**0**	**137**

Weak Cryptographic Hash	Low

Package: .src.main.resources.db.migration

coube-backend/src/main/resources/db/migration/._V20251030030000__create_claims_disputes.sql, line 1 (Weak Cryptographic Hash)

Issue Details

© Copyright 2008-2026 Open Text.

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration

coube-backend/src/main/resources/db/migration/._V20251030030000__create_claims_disputes.sql, line 1 (Weak Cryptographic Hash)

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20251030030000__create_claims_disputes_sql()
File: coube-backend/src/main/resources/db/migration/._V20251030030000__create_claims_disputes.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250602234824__add_executor_to_transportation.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250602234824__add_executor_to_transportation_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20250602234824__add_executor_to_transportation.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@ATTR^@^@^@^@^@^@^@
@^@^@^@@^@^@^@^K^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^A^@^@^@@
^@^@^@^K^@^@^Ucom.apple.provenance^@^A^B^@,^R<4S@@]
2
3 undefined
4 undefined
5 undefined
6 undefined
7 undefined
```

coube-backend/src/main/resources/db/migration/applications/._V20251022133410__add_courier_fields_to_transportation.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20251022133410__add_courier_fields_to_transportation_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20251022133410__add_courier_fields_to_transportation.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@ATTR^@^@^@^@^@^@^@
@^@^@^@@^@^@^@^K^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^A^@^@^@@
^@^@^@^K^@^@^Ucom.apple.provenance^@^A^B^@,^R<4S@@]
2
3 undefined
4 undefined
5 undefined
6 undefined
7 undefined
```


© Copyright 2008-2026 Open Text.

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20251022133410__add_courier_fields_to_transportation.sql, line 1 (Weak Cryptographic Hash)

coube-backend/src/main/resources/db/migration/applications/._V20260121101500__change_egov_token_type.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20260121101500__change_egov_token_type_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20260121101500__change_egov_token_type.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@ATTR^@^@^@^@^@^@^@
^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250302133850__add-device-tokens.sql, line 1 (Weak Cryptographic Hash)

```
3 undefined
4 undefined
5 undefined
6 undefined
7 undefined
```

coube-backend/src/main/resources/db/migration/applications/._V20250318154931__create_history.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250318154931__create_history_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20250318154931__create_history.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250426152639__add_sign_type.sql, line 1 (Weak Cryptographic Hash)

```
1 ^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250708135800__alter_agreement_executor_tables.sql, line 1 (Weak Cryptographic Hash)

Sink: mac()
Enclosing Method: _plsql_block1__v20250708135800__alter_agreement_executor_tables_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20250708135800__alter_agreement_executor_tables.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20251221192000__added_primary_key.sql, line 1 (Weak Cryptographic Hash)

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20251221192000__added_primary_key_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20251221192000__added_primary_key.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20251208120500__create_courier_warehouse_table.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20251208120500__create_courier_warehouse_table_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20251208120500__create_courier_warehouse_table.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250704094446__alter_invoice_service_tables.sql, line 1 (Weak Cryptographic Hash)

coube-backend/src/main/resources/db/migration/applications/._V20250629001725__create_registies.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250629001725__create_registies_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20250629001725__create_registies.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250220170919__add-transport.sql, line 1 (Weak Cryptographic Hash)

```
5 undefined
6 undefined
7 undefined
```

coube-backend/src/main/resources/db/migration/applications/._V20251022133710__create_courier_integration_log.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20251022133710__create_courier_integration_log_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20251022133710__create_courier_integration_log.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250712001700__alter_agreements_table.sql, line 1 (Weak Cryptographic Hash)

```
1 ^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250722011500__add_route_change_fields_to_transportation.sq line 1 (Weak Cryptographic Hash)

Sink: mac()
Enclosing Method: _plsql_block1__v20250722011500__add_route_change_fields_to_transportation_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20250722011500__add_route_change_fields_to_transportation.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250205190042__create_contract.sql, line 1 (Weak Cryptographic Hash)

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250205190042__create_contract_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20250205190042__create_contract.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250730173150__create_agreement_change_history_table.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250730173150__create_agreement_change_history_table_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20250730173150__create_agreement_change_history_table.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250709143600__alter_contract_table.sql, line 1 (Weak Cryptographic Hash)

coube-backend/src/main/resources/db/migration/applications/._V20250829222500__create_agreement_vehicle_body_table.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250829222500__create_agreement_vehicle_body_table_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20250829222500__create_agreement_vehicle_body_table.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@ATTR^@^@^@^@^@^@^@
^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20251221201000__create_warehouse_logist_assignment.sql, line 1 (Weak Cryptographic Hash)

```
3 undefined
4 undefined
5 undefined
6 undefined
7 undefined
```

coube-backend/src/main/resources/db/migration/applications/._V20250708151200__create_agreement_country_table.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250708151200__create_agreement_country_table_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20250708151200__create_agreement_country_table.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250904204140__employee_transport_mtm.sql, line 1 (Weak Cryptographic Hash)

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250522200517__add_agreement.sql, line 1 (Weak Cryptographic Hash)

Sink: mac()
Enclosing Method: _plsql_block1__v20250522200517__add_agreement_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20250522200517__add_agreement.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250806151600__add_executor_employee_id_columns.sql, line 1 (Weak Cryptographic Hash)

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250806151600__add_executor_employee_id_columns_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20250806151600__add_executor_employee_id_columns.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250728190200__add_transportation_requirement_fields.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250728190200__add_transportation_requirement_fields_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20250728190200__add_transportation_requirement_fields.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250829233845__add_trailer_registration_certificate_id.sql__add line 1 (Weak Cryptographic Hash)

```
5 undefined
6 undefined
7 undefined
```

coube-backend/src/main/resources/db/migration/applications/._V20250423210113__add_agreement_number.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250423210113__add_agreement_number_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20250423210113__add_agreement_number.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250728210516__alter_acts_table.sql, line 1 (Weak Cryptographic Hash)

```
^@^@^@^K^@^@^Ucom.apple.provenance^@^A^B^@,^R<4S►►]
2
3 undefined
4 undefined
5 undefined
6 undefined
7 undefined
```

coube-backend/src/main/resources/db/migration/applications/._V20251208150500__insert_teez_pvz_warehouse_table.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20251208150500__insert_teez_pvz_warehouse_table_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20251208150500__insert_teez_pvz_warehouse_table.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@►
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250722031000__add_pending_route_history_to_transportation.s line 1 (Weak Cryptographic Hash)

File: coube-backend/src/main/resources/db/migration/applications/._V20250722031000__add_pending_route_history_to_transportation.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250430165044__remove_not_null.sql, line 1 (Weak Cryptographic Hash)

Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250430165044__remove_not_null_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20250430165044__remove_not_null.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250310160735__add_driver_way.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250310160735__add_driver_way_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20250310160735__add_driver_way.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250710112700__alter_agreement_executor_table.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250710112700__alter_agreement_executor_table_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20250710112700__alter_agreement_executor_table.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250711160400__alter_transporatations_table.sql, line 1 (Weak Cryptographic Hash)

coube-backend/src/main/resources/db/migration/applications/._V20260120111500__create_egov_sign_sessions_table.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20260120111500__create_egov_sign_sessions_table_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20260120111500__create_egov_sign_sessions_table.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20251128120500__add_target_delivery_date_transportation.sql, line 1 (Weak Cryptographic Hash)

```
3 undefined
4 undefined
5 undefined
6 undefined
7 undefined
```

coube-backend/src/main/resources/db/migration/applications/._V20250628174824__create_invoices_and_acts.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250628174824__create_invoices_and_acts_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20250628174824__create_invoices_and_acts.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250309170738__device-token-deleted.sql, line 1 (Weak Cryptographic Hash)

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250829120100__add_factoring_used_to_transportation.sql, line 1 (Weak Cryptographic Hash)

Enclosing Method: _plsql_block1__v20250829120100__add_factoring_used_to_transportation_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20250829120100__add_factoring_used_to_transportation.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.applications

coube-backend/src/main/resources/db/migration/applications/._V20250731051450__alter_agreement_executor.sql, line 1 (Weak Cryptographic Hash)

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250731051450__alter_agreement_executor_sql()
File: coube-backend/src/main/resources/db/migration/applications/._V20250731051450__alter_agreement_executor.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.dictionaries

coube-backend/src/main/resources/db/migration/dictionaries/._V20250824200000__create_factoring_payment_delay_value_table.s line 1 (Weak Cryptographic Hash)

```
7 undefined
```

coube-backend/src/main/resources/db/migration/dictionaries/._V20250817170900__add_deleted_column_to_dictionaries.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250817170900__add_deleted_column_to_dictionaries_sql()
File: coube-backend/src/main/resources/db/migration/dictionaries/._V20250817170900__add_deleted_column_to_dictionaries.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.dictionaries

coube-backend/src/main/resources/db/migration/dictionaries/._V20250205172212__insert_dictionaries.sql, line 1 (Weak Cryptographic Hash)

```
2
3 undefined
4 undefined
5 undefined
6 undefined
7 undefined
```

coube-backend/src/main/resources/db/migration/dictionaries/._V20250126143457__create_dictionaries.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250126143457__create_dictionaries_sql()
File: coube-backend/src/main/resources/db/migration/dictionaries/._V20250126143457__create_dictionaries.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.dictionaries

coube-backend/src/main/resources/db/migration/dictionaries/._V20250718170100__alter_more.sql, line 1 (Weak Cryptographic Hash)

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.dictionaries

coube-backend/src/main/resources/db/migration/dictionaries/._V20250430172727__add_more.sql, line 1 (Weak Cryptographic Hash)

Sink: mac()
Enclosing Method: _plsql_block1__v20250430172727__add_more_sql()
File: coube-backend/src/main/resources/db/migration/dictionaries/._V20250430172727__add_more.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.dictionaries

coube-backend/src/main/resources/db/migration/dictionaries/._V20250824195700__create_payment_delay_value_table.sql, line 1 (Weak Cryptographic Hash)

Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250824195700__create_payment_delay_value_table_sql()
File: coube-backend/src/main/resources/db/migration/dictionaries/._V20250824195700__create_payment_delay_value_table.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.executor

coube-backend/src/main/resources/db/migration/executor/._V20251022120000__create_executor_schema.sql, line 1 (Weak Cryptographic Hash)

Package: .src.main.resources.db.migration.factoring

coube-backend/src/main/resources/db/migration/factoring/._V20250819145325__alter_payout_request_add_delay_days.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250819145325__alter_payout_request_add_delay_days_sql()
File: coube-backend/src/main/resources/db/migration/factoring/._V20250819145325__alter_payout_request_add_delay_days.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.factoring

coube-backend/src/main/resources/db/migration/factoring/._V20250819012900__alter_factor_add_bank_requisites.sql, line 1 (Weak Cryptographic Hash)

```
1 ^@^@^@^K^@^@^Ucom.apple.provenance^@^A^B^@,^R<4S►►]
2
3 undefined
4 undefined
5 undefined
6 undefined
7 undefined
```

coube-backend/src/main/resources/db/migration/factoring/._V20260114114500__add_avr_email_sent_at_to_payout_request.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20260114114500__add_avr_email_sent_at_to_payout_request_sql()
File: coube-backend/src/main/resources/db/migration/factoring/._V20260114114500__add_avr_email_sent_at_to_payout_request.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@►
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.factoring

coube-backend/src/main/resources/db/migration/factoring/._V20250818211100__alter_payout_request_add_signer_full_name.sql, line 1 (Weak Cryptographic Hash)

File: coube-backend/src/main/resources/db/migration/factoring/._V20250818211100__alter_payout_request_add_signer_full_name.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.factoring

coube-backend/src/main/resources/db/migration/factoring/._V20250712150000__alter_factor_add_offer_url.sql, line 1 (Weak Cryptographic Hash)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250712150000__alter_factor_add_offer_url_sql()
File: coube-backend/src/main/resources/db/migration/factoring/._V20250712150000__alter_factor_add_offer_url.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.factoring

coube-backend/src/main/resources/db/migration/factoring/._V20250824195800__create_factor_tariff_table.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250824195800__create_factor_tariff_table_sql()
File: coube-backend/src/main/resources/db/migration/factoring/._V20250824195800__create_factor_tariff_table.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.factoring

coube-backend/src/main/resources/db/migration/factoring/._V20250630151800__create_factoring_agreement.sql, line 1 (Weak Cryptographic Hash)

coube-backend/src/main/resources/db/migration/factoring/._V20250814101600__alter_payout_request_add_financing_amount.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250814101600__alter_payout_request_add_financing_amount_sql()
File: coube-backend/src/main/resources/db/migration/factoring/._V20250814101600__alter_payout_request_add_financing_amount.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@ATTR^@^@^@^@^@^@^@
^@^@^@^@^@^@^@^@K^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@A^@^@^@
^@^@^@^@K^@^@^Ucom.apple.provenance^@^A^B^@,^R<4S
2
3 undefined
4 undefined
5 undefined
6 undefined
7 undefined
```

coube-backend/src/main/resources/db/migration/factoring/._V20250819021838__alter_factor_add_beneficiary_payment_codes.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250819021838__alter_factor_add_beneficiary_payment_codes_sql()
File: coube-backend/src/main/resources/db/migration/factoring/._V20250819021838__alter_factor_add_beneficiary_payment_codes.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@ATTR^@^@^@^@^@^@^@
^@^@^@^@^@^@^@^@K^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@A^@^@^@
^@^@^@^@K^@^@^Ucom.apple.provenance^@^A^B^@,^R<4S
2
```


© Copyright 2008-2026 Open Text.

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.factoring

coube-backend/src/main/resources/db/migration/factoring/._V20250819021838__alter_factor_add_beneficiary_payment_codes.sql, line 1 (Weak Cryptographic Hash)

```
3 undefined
4 undefined
5 undefined
6 undefined
7 undefined
```

coube-backend/src/main/resources/db/migration/factoring/._V20260114144100__backfill_avr_email_sent_at_for_existing_payouts.s line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20260114144100__backfill_avr_email_sent_at_for_existing_payouts_sql()
File: coube-backend/src/main/resources/db/migration/factoring/._V20260114144100__backfill_avr_email_sent_at_for_existing_payouts.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.factoring

coube-backend/src/main/resources/db/migration/factoring/._V20251215131600__add_payment_reminder_fields_to_payout_request line 1 (Weak Cryptographic Hash)

Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.factoring

coube-backend/src/main/resources/db/migration/factoring/._V20250824195900__alter_payout_request_add_factor_tariff.sql, line 1 (Weak Cryptographic Hash)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250824195900__alter_payout_request_add_factor_tariff_sql()
File: coube-backend/src/main/resources/db/migration/factoring/._V20250824195900__alter_payout_request_add_factor_tariff.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.factoring

coube-backend/src/main/resources/db/migration/factoring/._V20250818200400__alter_payout_request_add_otp_log.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250818200400__alter_payout_request_add_otp_log_sql()
File: coube-backend/src/main/resources/db/migration/factoring/._V20250818200400__alter_payout_request_add_otp_log.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.file

coube-backend/src/main/resources/db/migration/file/._V20250331210228__static_file.sql, line 1 (Weak Cryptographic Hash)

coube-backend/src/main/resources/db/migration/file/._V20250308123201__file_id_change.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250308123201__file_id_change_sql()
File: coube-backend/src/main/resources/db/migration/file/._V20250308123201__file_id_change.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.file

coube-backend/src/main/resources/db/migration/file/._V20250729191745__alter_signature_table.sql, line 1 (Weak Cryptographic Hash)

```
7 undefined
```

coube-backend/src/main/resources/db/migration/file/._V20250205184709__create_file_meta_info_and_signature.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250205184709__create_file_meta_info_and_signature_sql()
File: coube-backend/src/main/resources/db/migration/file/._V20250205184709__create_file_meta_info_and_signature.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.file

coube-backend/src/main/resources/db/migration/file/._V20250308131905__user_driver_lisence.sql, line 1 (Weak Cryptographic Hash)

```
3 undefined
4 undefined
5 undefined
6 undefined
7 undefined
```

Package: .src.main.resources.db.migration.gis

coube-backend/src/main/resources/db/migration/gis/._V20251119173510__add_weight_volume_to_cargo_loading.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20251119173510__add_weight_volume_to_cargo_loading_sql()
File: coube-backend/src/main/resources/db/migration/gis/._V20251119173510__add_weight_volume_to_cargo_loading.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.gis

coube-backend/src/main/resources/db/migration/gis/._V20250627115300__alter_veh_latest_loc.sql, line 1 (Weak Cryptographic Hash)

Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.gis

coube-backend/src/main/resources/db/migration/gis/._V20250728174900__add_waybill_number_to_cargo_loading_history.sql, line 1 (Weak Cryptographic Hash)

Sink: mac()
Enclosing Method: _plsql_block1__v20250728174900__add_waybill_number_to_cargo_loading_history_sql()
File: coube-backend/src/main/resources/db/migration/gis/._V20250728174900__add_waybill_number_to_cargo_loading_history.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.gis

coube-backend/src/main/resources/db/migration/gis/._V20250728175500__add_waybill_number_to_cargo_loading.sql, line 1 (Weak Cryptographic Hash)

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250728175500__add_waybill_number_to_cargo_loading_sql()
File: coube-backend/src/main/resources/db/migration/gis/._V20250728175500__add_waybill_number_to_cargo_loading.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.gis

coube-backend/src/main/resources/db/migration/gis/._V20250625085750__add_veh_latest_loc.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250625085750__add_veh_latest_loc_sql()
File: coube-backend/src/main/resources/db/migration/gis/._V20250625085750__add_veh_latest_loc.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.gis

coube-backend/src/main/resources/db/migration/gis/._V20251223161400__add_apartment_to_cargo_loading.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20251223161400__add_apartment_to_cargo_loading_sql()
File: coube-backend/src/main/resources/db/migration/gis/._V20251223161400__add_apartment_to_cargo_loading.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.gis

coube-backend/src/main/resources/db/migration/gis/._V20251214170000__add_last_sms_code_to_cargo_loading.sql, line 1 (Weak Cryptographic Hash)

coube-backend/src/main/resources/db/migration/gis/._V20250811133200__add_route_distance_to_transportation_route_history.sq line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250811133200__add_route_distance_to_transportation_route_history_sql()
File: coube-backend/src/main/resources/db/migration/gis/._V20250811133200__add_route_distance_to_transportation_route_history.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@ATTR^@^@^@^@^@^@^@
@^@^@^@@^@^@^@^K^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^A^@^@^@@
^@^@^@^K^@^@^Ucom.apple.provenance^@^A^B^@,^R<4S@@]
2
3 undefined
4 undefined
5 undefined
6 undefined
7 undefined
```

coube-backend/src/main/resources/db/migration/gis/._V20250723010000__add_document_and_signature_to_route_history.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250723010000__add_document_and_signature_to_route_history_sql()
File: coube-backend/src/main/resources/db/migration/gis/._V20250723010000__add_document_and_signature_to_route_history.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@ATTR^@^@^@^@^@^@^@
@^@^@^@@^@^@^@^K^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^A^@^@^@@
^@^@^@^K^@^@^Ucom.apple.provenance^@^A^B^@,^R<4S@@]
```


© Copyright 2008-2026 Open Text.

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.gis

coube-backend/src/main/resources/db/migration/gis/._V20250723010000__add_document_and_signature_to_route_history.sql, line 1 (Weak Cryptographic Hash)

```
2
3 undefined
4 undefined
5 undefined
6 undefined
7 undefined
```

coube-backend/src/main/resources/db/migration/gis/._V20260211170200__employee_latest_loc.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20260211170200__employee_latest_loc_sql()
File: coube-backend/src/main/resources/db/migration/gis/._V20260211170200__employee_latest_loc.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.gis

coube-backend/src/main/resources/db/migration/gis/._V20251022133510__add_courier_fields_to_cargo_loading.sql, line 1 (Weak Cryptographic Hash)

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.insurance

coube-backend/src/main/resources/db/migration/insurance/._V20251115224900__extend_insurance_documents_to_match_entity.s line 1 (Weak Cryptographic Hash)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20251115224900__extend_insurance_documents_to_match_entity_sql()
File: coube-backend/src/main/resources/db/migration/insurance/._V20251115224900__extend_insurance_documents_to_match_entity.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.notifications

coube-backend/src/main/resources/db/migration/notifications/._V20251009151400__channel_type_case_insensitive.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20251009151400__channel_type_case_insensitive_sql()
File: coube-backend/src/main/resources/db/migration/notifications/._V20251009151400__channel_type_case_insensitive.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.notifications

coube-backend/src/main/resources/db/migration/notifications/._V20251023150000__create_notification_logs_tables.sql, line 1 (Weak Cryptographic Hash)

coube-backend/src/main/resources/db/migration/notifications/._V20251009145900__notifications_baseline.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20251009145900__notifications_baseline_sql()
File: coube-backend/src/main/resources/db/migration/notifications/._V20251009145900__notifications_baseline.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@ATTR^@^@^@^@^@^@^@
^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.notifications

coube-backend/src/main/resources/db/migration/notifications/._V20251022113310__notification_filters_body_types_to_integer_arr
line 1 (Weak Cryptographic Hash)

```
3 undefined
4 undefined
5 undefined
6 undefined
7 undefined
```

coube-backend/src/main/resources/db/migration/notifications/._V20260128174600__create_notification_blacklist.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20260128174600__create_notification_blacklist_sql()
File: coube-backend/src/main/resources/db/migration/notifications/._V20260128174600__create_notification_blacklist.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^@B^@^@^@
^@^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.notifications

coube-backend/src/main/resources/db/migration/notifications/._V20251023150100__add_created_at_to_notification_tables.sql, line 1 (Weak Cryptographic Hash)

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.reviews

coube-backend/src/main/resources/db/migration/reviews/._V20260107145200__create_reviews_indexes.sql, line 1 (Weak Cryptographic Hash)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20260107145200__create_reviews_indexes_sql()
File: coube-backend/src/main/resources/db/migration/reviews/._V20260107145200__create_reviews_indexes.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.signature

coube-backend/src/main/resources/db/migration/signature/._V20251023000000__create_signature_logs_schema.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20251023000000__create_signature_logs_schema_sql()
File: coube-backend/src/main/resources/db/migration/signature/._V20251023000000__create_signature_logs_schema.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.signature

coube-backend/src/main/resources/db/migration/signature/._V20251023010000__add_column_to_certificate_revocation.sql, line 1 (Weak Cryptographic Hash)

Package: .src.main.resources.db.migration.user

coube-backend/src/main/resources/db/migration/user/._V20251206114600__add_country_id_to_employees.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20251206114600__add_country_id_to_employees_sql()
File: coube-backend/src/main/resources/db/migration/user/._V20251206114600__add_country_id_to_employees.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.user

coube-backend/src/main/resources/db/migration/user/._V20250310221354__org_details.sql, line 1 (Weak Cryptographic Hash)

```
3 undefined
4 undefined
5 undefined
6 undefined
7 undefined
```

coube-backend/src/main/resources/db/migration/user/._V20250902160115__create_kyc_score_table.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250902160115__create_kyc_score_table_sql()
File: coube-backend/src/main/resources/db/migration/user/._V20250902160115__create_kyc_score_table.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@ATTR^@^@^@^@^@^@^@
@^@^@^@@^@^@^@^@K^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@A^@^@^@@
^@^@^@K^@^@^Ucom.apple.provenance^@^A^B^@,^R<4S@@]
2
3 undefined
4 undefined
5 undefined
6 undefined
7 undefined
```

coube-backend/src/main/resources/db/migration/user/._V20250904193300__alter_kyc.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250904193300__alter_kyc_sql()
File: coube-backend/src/main/resources/db/migration/user/._V20250904193300__alter_kyc.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@ATTR^@^@^@^@^@^@^@
@^@^@^@@^@^@^@^@K^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@^@A^@^@^@@
```


© Copyright 2008-2026 Open Text.

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.user

coube-backend/src/main/resources/db/migration/user/._V20250904193300__alter_kyc.sql, line 1 (Weak Cryptographic Hash)

```
1 ^@^@^@^K^@^@^Ucom.apple.provenance^@^A^B^@,^R<4S►►]
2
3 undefined
4 undefined
5 undefined
6 undefined
7 undefined
```

coube-backend/src/main/resources/db/migration/user/._V20250902161500__alter_kyc_score.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250902161500__alter_kyc_score_sql()
File: coube-backend/src/main/resources/db/migration/user/._V20250902161500__alter_kyc_score.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@►
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.user

coube-backend/src/main/resources/db/migration/user/._V20251127184200__make_employee_email_nullable.sql, line 1 (Weak Cryptographic Hash)

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.user

coube-backend/src/main/resources/db/migration/user/._V20251205155000__set_default_kz_country_for_existing_organizations.sql line 1 (Weak Cryptographic Hash)

Enclosing Method: _plsql_block1__v20251205155000__set_default_kz_country_for_existing_organizations_sql()
File: coube-backend/src/main/resources/db/migration/user/._V20251205155000__set_default_kz_country_for_existing_organizations.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.user

coube-backend/src/main/resources/db/migration/user/._V20250625004150__alter_employee_add_transport.sql, line 1 (Weak Cryptographic Hash)

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250625004150__alter_employee_add_transport_sql()
File: coube-backend/src/main/resources/db/migration/user/._V20250625004150__alter_employee_add_transport.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.user

coube-backend/src/main/resources/db/migration/user/._V20251205142800__add_iso_alpha2_to_countries.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20251205142800__add_iso_alpha2_to_countries_sql()
File: coube-backend/src/main/resources/db/migration/user/._V20251205142800__add_iso_alpha2_to_countries.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.user

coube-backend/src/main/resources/db/migration/user/._V20251205145400__add_country_id_to_users_organization.sql, line 1 (Weak Cryptographic Hash)

coube-backend/src/main/resources/db/migration/user/._V20250825043600__add_payment_fields_to_organization.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250825043600__add_payment_fields_to_organization_sql()
File: coube-backend/src/main/resources/db/migration/user/._V20250825043600__add_payment_fields_to_organization.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.user

coube-backend/src/main/resources/db/migration/user/._V20250126143552__create_users.sql, line 1 (Weak Cryptographic Hash)

```
5 undefined
6 undefined
7 undefined
```

coube-backend/src/main/resources/db/migration/user/._V20250815133200__create_kyc_tables.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250815133200__create_kyc_tables_sql()
File: coube-backend/src/main/resources/db/migration/user/._V20250815133200__create_kyc_tables.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
^@^@^@
```

Weak Cryptographic Hash | Low

Package: .src.main.resources.db.migration.user

coube-backend/src/main/resources/db/migration/user/._V20250805193000__add_organization_employees_roles_and_view.sql, line 1 (Weak Cryptographic Hash)

```
2
3 undefined
4 undefined
5 undefined
6 undefined
7 undefined
```

coube-backend/src/main/resources/db/migration/user/._V20250416211538__employee_fields.sql, line 1 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: mac()
Enclosing Method: _plsql_block1__v20250416211538__employee_fields_sql()
File: coube-backend/src/main/resources/db/migration/user/._V20250416211538__employee_fields.sql:1
Taint Flags:

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^@B^@^@^@
^@^@^@^@
```

Weak Cryptographic Hash — Low

Package: .src.main.resources.db.migration.user

coube-backend/src/main/resources/db/migration/user/._V20251022113300__add_column_driver_license_status.sql, line 1 (Weak Cryptographic Hash)

```
1 ^@^E^V^G^@^B^@^@Mac OS X ^@^B^@^@^@ ^@^@^@2^@^@^@q^@^@^@^B^@^@^@
2
3 undefined
4 undefined
5 undefined
6 undefined
7 undefined
```

Package: kz.coube.backend.cmsverify.util

coube-backend/src/main/java/kz/coube/backend/cmsverify/util/SignUtils.java, line 33 (Weak Cryptographic Hash)

Issue Details

Kingdom: Security Features
Scan Engine: SCA (Semantic)

Sink Details

Sink: getInstance()
Enclosing Method: sha1()
File: coube-backend/src/main/java/kz/coube/backend/cmsverify/util/SignUtils.java:33
Taint Flags:

```
30 public static String sha1(String data) {
31 String sha1 = "";
32 try {
33 MessageDigest crypt = MessageDigest.getInstance("SHA-1");
34 crypt.reset();
35 crypt.update(data.getBytes(StandardCharsets.UTF_8));
36 sha1 = bytesToHex(crypt.digest());
```


© Copyright 2008-2026 Open Text.

XML Entity Expansion Injection (1 issue)

Abstract

Using XML parsers that are not configured to prevent or limit Document Type Definition (DTD) entity resolution can expose the parser to an XML Entity Expansion injection

Explanation

XML Entity Expansion injection also known as XML Bombs are Denial Of Service (DoS) attacks that benefit from valid and well-formed XML blocks that expand exponentially until they exhaust the server allocated resources. XML allows to define custom entities which act as string substitution macros. By nesting recurrent entity resolutions, an attacker may easily crash the server resources. The following XML document shows an example of an XML Bomb.

```
<?xml version="1.0"?>
<!DOCTYPE lolz [
<!ENTITY lol "lol">
<!ENTITY lol2 "&lol;&lol;&lol;&lol;&lol;&lol;&lol;&lol;&lol;&lol;">
<!ENTITY lol3 "&lol2;&lol2;&lol2;&lol2;&lol2;&lol2;&lol2;&lol2;&lol2;&lol2;">
<!ENTITY lol4 "&lol3;&lol3;&lol3;&lol3;&lol3;&lol3;&lol3;&lol3;&lol3;&lol3;">
<!ENTITY lol5 "&lol4;&lol4;&lol4;&lol4;&lol4;&lol4;&lol4;&lol4;&lol4;&lol4;">
<!ENTITY lol6 "&lol5;&lol5;&lol5;&lol5;&lol5;&lol5;&lol5;&lol5;&lol5;&lol5;">
<!ENTITY lol7 "&lol6;&lol6;&lol6;&lol6;&lol6;&lol6;&lol6;&lol6;&lol6;&lol6;">
<!ENTITY lol8 "&lol7;&lol7;&lol7;&lol7;&lol7;&lol7;&lol7;&lol7;&lol7;&lol7;">
<!ENTITY lol9 "&lol8;&lol8;&lol8;&lol8;&lol8;&lol8;&lol8;&lol8;&lol8;&lol8;">
]>
<lolz>&lol9;</lolz>
```

This test could crash the server by expanding the small XML document into more than 3GB in memory.

Recommendation

Always configure an XML parser securely so that it does not allow document type definition (DTD) custom entities as part of an incoming XML document. To avoid XML Entity Expansion injection the "secure-processing" property should be set for an XML factory, parser or reader:

```
factory.setFeature("http://javax.xml.XMLConstants/feature/secure-processing",
true);
```

In JAXP 1.3 and earlier versions, when the secure processing feature is on, default limitations are set for DOM and SAX parsers. These limits are:

```
entityExpansionLimit = 64,000
elementAttributeLimit = 10,000
```

Since JAXP 1.4, the secure processing feature is turned on by default. In addition to the preceding limits, a new maxOccur limit is added to the validating parser. The limit is:

```
maxOccur = 5,000
```

If inline DOCTYPE declaration is not needed, it can be completely disabled with the following property:

```
factory.setFeature("http://apache.org/xml/features/disallow-doctype-decl",
true);
```

Issue Summary

© Copyright 2008-2026 Open Text.



Engine Breakdown

	SCA	WebInspect	SecurityScope	Total
XML Entity Expansion Injection	1	0	0	1
Total	**1**	**0**	**0**	**1**

XML Entity Expansion Injection — Low

Package: kz.coube.backend.insurance.service

coube-backend/src/main/java/kz/coube/backend/insurance/service/InsuranceApiClient.java, line 221 (XML Entity Expansion Injection)

Issue Details

Kingdom: Input Validation and Representation
Scan Engine: SCA (Control Flow)

Sink Details

Sink: db.parse(...) : XML document parsed allowing external entity resolution
Enclosing Method: xpathText()
File: coube-backend/src/main/java/kz/coube/backend/insurance/service/InsuranceApiClient.java:221
Taint Flags:

```
218  dbf.setNamespaceAware(true);
219  var db = dbf.newDocumentBuilder();
220  var is = new java.io.ByteArrayInputStream(xml.getBytes(StandardCharsets.UTF_8));
221  org.w3c.dom.Document doc = db.parse(is);
222
223  javax.xml.xpath.XPath xp = javax.xml.xpath.XPathFactory.newInstance().newXPath();
224  String v = xp.evaluate(expr, doc);
```


© Copyright 2008-2026 Open Text.

XML External Entity Injection (1 issue)

Abstract

Using XML parsers that are not configured to prevent or limit external entities resolution can expose the parser to an XML External Entities attack

Explanation

XML External Entities attacks benefit from an XML feature to build documents dynamically at the time of processing. An XML entity allows inclusion of data dynamically from a given resource. External entities allow an XML document to include data from an external URI. Unless configured to do otherwise, external entities force the XML parser to access the resource specified by the URI, e.g., a file on the local machine or on a remote system. This behavior exposes the application to XML External Entity (XXE) attacks, which can be used to perform denial of service of the local system, gain unauthorized access to files on the local machine, scan remote machines, and perform denial of service of remote systems. The following XML document shows an example of an XXE attack.

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<!DOCTYPE foo [
<!ELEMENT foo ANY >
<!ENTITY xxe SYSTEM "file:///dev/random" >]><foo>&xxe;</foo>
```

This example could crash the server (on a UNIX system), if the XML parser attempts to substitute the entity with the contents of the /dev/random file.

Recommendation

Always configure an XML parser securely so that it does not allow external entities as part of an incoming XML document. To avoid XXE injections the following properties should be set for an XML factory, parser or reader:

```
factory.setFeature("http://xml.org/sax/features/external-general-entities",
false);
factory.setFeature("http://xml.org/sax/features/external-parameter-entities",
false);
```

If inline DOCTYPE declaration is not needed, it can be completely disabled with the following property:

```
factory.setFeature("http://apache.org/xml/features/disallow-doctype-decl",
true);
```

Issue Summary



© Copyright 2008-2026 Open Text.

Engine Breakdown

	SCA	WebInspect	SecurityScope	Total
XML External Entity Injection	1	0	0	1
Total	**1**	**0**	**0**	**1**

XML External Entity Injection — High

Package: kz.coube.backend.insurance.service

coube-backend/src/main/java/kz/coube/backend/insurance/service/InsuranceApiClient.java, line 221 (XML External Entity Injection)

Issue Details

Kingdom: Input Validation and Representation
Scan Engine: SCA (Control Flow)

Sink Details

Sink: db.parse(...) : XML document parsed allowing external entity resolution
Enclosing Method: xpathText()
File: coube-backend/src/main/java/kz/coube/backend/insurance/service/InsuranceApiClient.java:221
Taint Flags:

```
218  dbf.setNamespaceAware(true);
219  var db = dbf.newDocumentBuilder();
220  var is = new java.io.ByteArrayInputStream(xml.getBytes(StandardCharsets.UTF_8));
221  org.w3c.dom.Document doc = db.parse(is);
222
223  javax.xml.xpath.XPath xp = javax.xml.xpath.XPathFactory.newInstance().newXPath();
224  String v = xp.evaluate(expr, doc);
```


© Copyright 2008-2026 Open Text.

© Copyright 2008-2026 Open Text.