

# Assignment 02: 01 - Multiple Regression Gradient - Vectorized

In this lab, you will extend the data structures and previously developed routines to support multiple features. Several routines are updated making the lab appear lengthy, but it makes minor adjustments to previous routines making it quick to review.

## Outline

- 1.1 Goals
- 1.2 Tools
- 1.3 Notation
- 2 Problem Statement
  - 2.1 Matrix X containing our examples
  - 2.2 Parameter vector  $w, b$
- 3 Model Prediction With Multiple Variables
  - 3.1 Single Prediction element by element
  - 3.2 Single Prediction, vector
- 4 Compute Cost With Multiple Variables
- 5 Gradient Descent With Multiple Variables
  - 5.1 Compute Gradient with Multiple Variables
  - 5.2 Gradient Descent With Multiple Variables

## 1.1 Goals

- Extend our regression model routines to support multiple features
  - Extend data structures to support multiple features
  - Rewrite prediction, cost and gradient routines to support multiple features
  - Utilize NumPy `np.dot` to vectorize their implementations for speed and simplicity

## 1.2 Tools

In this lab, we will make use of:

- NumPy, a popular library for scientific computing
- Matplotlib, a popular library for plotting data

```
import copy, math
import numpy as np
import matplotlib.pyplot as plt
plt.style.use('./deeplearning.mplstyle')
np.set_printoptions(precision=2) # reduced display precision on numpy arrays
```

## 1.3 Notation

Here is a summary of some of the notation you will encounter, updated for multiple features.

[General Notation | Description| Python (if applicable) |]: -----|:

-----||  $a$  | scalar, non bold ||  $\mathbf{a}$  | vector, bold ||  $A$  | matrix, bold capital || **Regression** ||  $X$  | training example matrix | `X_train` |  $y$  | training example targets | `y_train` |  $x^{(i)}$ ,  $y^{(i)}$  |  $i_{th}$  Training Example | `X[i]`, `y[i]` |  $m$  | number of training examples | `m` |  $n$  | number of features in each example | `n` |  $w$  | parameter: weight, | `w` |  $b$  | parameter: bias | `b` |  $f_{w,b}(x^{(i)})$  | The result of the model evaluation at  $x^{(i)}$  parameterized by  $w, b$ :  $f_{w,b}(x^{(i)}) = w \cdot x^{(i)} + b$  | `f_wb` |

## 2 Problem Statement

You will use the motivating example of housing price prediction. The training dataset contains three examples with four features (size, bedrooms, floors and, age) shown in the table below. Note that, unlike the earlier labs, size is in sqft rather than 1000 sqft. This causes an issue, which you will solve in the next lab!

Size (sqft)	Number of Bedrooms	Number of floors	Age of Home	Price (1000s dollars)
2104	5	1	45	460
1416	3	2	40	232
852	2	1	35	178

You will build a linear regression model using these values so you can then predict the price for other houses. For example, a house with 1200 sqft, 3 bedrooms, 1 floor, 40 years old.

Run the following code cell to create your `X_train` and `y_train` variables.

```
X_train = np.array([[2104, 5, 1, 45], [1416, 3, 2, 40], [852, 2, 1, 35]])
y_train = np.array([460, 232, 178])
```

## 2.1 Matrix X containing our examples

Similar to the table above, examples are stored in a NumPy matrix `X_train`. Each row of the matrix represents one example. When you have  $m$  training examples ( $m$  is three in our example), and there are  $n$  features (four in our example),  $X$  is a matrix with dimensions  $(m, n)$  ( $m$  rows,  $n$  columns).

$$X = \begin{pmatrix} x_0^{(0)} & x_1^{(0)} & \cdots & x_{n-1}^{(0)} \\ x_0^{(1)} & x_1^{(1)} & \cdots & x_{n-1}^{(1)} \\ \vdots & x_0^{(m-1)} & x_1^{(m-1)} & \vdots \end{pmatrix}$$

notation:

- $x^{(i)}$  is vector containing example  $i$ .  $x^{(i)} = (x^{(i)}_0, x^{(i)}_1, \dots, x^{(i)}_{n-1})$
- $x^{(i)}_j$  is element  $j$  in example  $i$ . The superscript in parenthesis indicates the example number while the subscript represents an element.

Display the input data.

```
# data is stored in numpy array/matrix
print(f"X Shape: {X_train.shape}, X Type:{type(X_train)}")
print(X_train)
print(f"y Shape: {y_train.shape}, y Type:{type(y_train)}")
print(y_train)
```

```
X Shape: (3, 4), X Type:<class 'numpy.ndarray'>
[[2104    5    1    45]
 [1416    3    2    40]
 [ 852    2    1    35]]
y Shape: (3,), y Type:<class 'numpy.ndarray'>
[460 232 178]
```

## 2.2 Parameter vector $w, b$

- $w$  is a vector with  $n$  elements.
  - Each element contains the parameter associated with one feature.
  - in our dataset,  $n$  is 4.
  - notionally, we draw this as a column vector

$$w = \begin{pmatrix} w_0 \\ w_1 \\ \vdots \\ w_{n-1} \end{pmatrix}$$

- $b$  is a scalar parameter.

For demonstration,  $w$  and  $b$  will be loaded with some initial selected values that are near the optimal.  $w$  is a 1-D NumPy vector.

```
b_init = 785.1811367994083
w_init = np.array([ 0.39133535, 18.75376741, -53.36032453, -
26.42131618])
print(f"w_init shape: {w_init.shape}, b_init type: {type(b_init)}")
w_init shape: (4,), b_init type: <class 'float'>
```

## 3 Model Prediction With Multiple Variables

The model's prediction with multiple variables is given by the linear model:

$$f_{w,b}(x) = w_0x_0 + w_1x_1 + \dots + w_{n-1}x_{n-1} + b$$

or in vector notation:

$$f_{w,b}(x) = w \cdot x + b$$

where  $\cdot$  is a vector **dot product**

To demonstrate the dot product, we will implement prediction using (1) and (2).

### 3.1 Single Prediction element by element

Our previous prediction multiplied one feature value by one parameter and added a bias parameter. A direct extension of our previous implementation of prediction to multiple features would be to implement (1) above using loop over each element, performing the multiply with its parameter and then adding the bias parameter at the end.

```
def predict_single_loop(x, w, b):
    """
    single predict using linear regression

    Args:
        x (ndarray): Shape (n,) example with multiple features
        w (ndarray): Shape (n,) model parameters
        b (scalar): model parameter

    Returns:
        p (scalar): prediction
    """
```

```

n = x.shape[0]
p = 0
for i in range(n):
    p_i = x[i] * w[i]
    p = p + p_i
p = p + b
return p

# get a row from our training data
x_vec = X_train[0,:]
print(f"x_vec shape {x_vec.shape}, x_vec value: {x_vec}")

# make a prediction
f_wb = predict_single_loop(x_vec, w_init, b_init)
print(f"f_wb shape {f_wb.shape}, prediction: {f_wb}")

x_vec shape (4,), x_vec value: [2104    5    1   45]
f_wb shape (), prediction: 459.9999976194083

```

Note the shape of `x_vec`. It is a 1-D NumPy vector with 4 elements, (4,). The result, `f_wb` is a scalar.

## 3.2 Single Prediction, vector

Noting that equation (1) above can be implemented using the dot product as in (2) above. We can make use of vector operations to speed up predictions.

Recall from the Python/NumPy lab that NumPy `np.dot()` [\[link\]](#) can be used to perform a vector dot product.

```

def predict(x, w, b):
    """
    single predict using linear regression
    Args:
        x (ndarray): Shape (n,) example with multiple features
        w (ndarray): Shape (n,) model parameters
        b (scalar):      model parameter

    Returns:
        p (scalar): prediction
    """
    p = np.dot(x, w) + b
    return p

# get a row from our training data
x_vec = X_train[0,:]
print(f"x_vec shape {x_vec.shape}, x_vec value: {x_vec}")

```

```
# make a prediction
f_wb = predict(x_vec, w_init, b_init)
print(f"f_wb shape {f_wb.shape}, prediction: {f_wb}")

x_vec shape (4,), x_vec value: [2104    5    1   45]
f_wb shape (), prediction: 459.9999976194083
```

The results and shapes are the same as the previous version which used looping. Going forward, `np.dot` will be used for these operations. The prediction is now a single statement. Most routines will implement it directly rather than calling a separate predict routine.

## 4 Compute Cost With Multiple Variables

The equation for the cost function with multiple variables  $J(w, b)$  is:

$$J(w, b) = \frac{1}{2m} \sum_{i=0}^{m-1} \left( f_{w,b}(x^{(i)}) - y^{(i)} \right)^2$$

where:

$$f_{w,b}(x^{(i)}) = w \cdot x^{(i)} + b$$

In contrast to previous labs,  $w$  and  $x^{(i)}$  are vectors rather than scalars supporting multiple features.

Below is an implementation of equations (3) and (4). Note that this uses a *standard pattern for this course* where a for loop over all  $m$  examples is used.

### Exercise 1 - Compute Cost - Non-vectorized

Implement the `compute_cost_nonvectorized()` function, below, according to the specifications below, including the input parameters and return value (cost). This function should *not* make use of any vectorization.

```
def compute_cost_nonvectorized(X, y, w, b):
    """
    compute cost
    Args:
        X (ndarray (m,n)): Data, m examples with n features
        y (ndarray (m,)) : target values
        w (ndarray (n,)) : model parameters
        b (scalar)       : model parameter

    Returns:
        cost (scalar): cost
    """
```

```

# WRITE CODE HERE
m = len(y)
total_cost = 0

for i in range(m):
    total_cost += (np.dot(X[i], w) + b - y[i]) ** 2

cost = total_cost / (2 * m)
return cost

# Compute and display cost using our pre-chosen optimal parameters.
cost = compute_cost_nonvectorized(X_train, y_train, w_init, b_init)
print(f'Cost at optimal w : {cost}')

Cost at optimal w : 1.5578904428966628e-12

```

**Expected Result:** Cost at optimal w : 1.5578904045996674e-12

## Exercise 2 - Compute Cost - Vectorized

Implement the `compute_cost_vectorized()` function, below, according to the specifications below, including the input parameters and return value (cost). This function should have a vectorization-based implementation.

```

def compute_cost_vectorized(X, y, w, b):
    """
    compute cost
    Args:
        X (ndarray (m,n)): Data, m examples with n features
        y (ndarray (m,)) : target values
        w (ndarray (n,)) : model parameters
        b (scalar)       : model parameter

    Returns:
        cost (scalar): cost
    """
    # WRITE CODE HERE
    m = len(y)

    differences = np.dot(X, w) + b - y

    squared_differences = differences ** 2

    total_cost = np.sum(squared_differences)

    cost = total_cost / (2 * m)
    return cost

```

```
# Compute and display cost using our pre-chosen optimal parameters.
cost = compute_cost_vectorized(X_train, y_train, w_init, b_init)
print(f'Cost at optimal w : {cost}')
```

Cost at optimal w : 1.5578904045996674e-12

**Expected Result:** Cost at optimal w : 1.5578904045996674e-12

## 5 Gradient Descent With Multiple Variables

Gradient descent for multiple variables:

$$\begin{aligned} & \text{repeat} \& \text{until convergence:} \quad \{ \\ & \quad w_j = w_j - \alpha \frac{\partial J(\mathbf{w}, b)}{\partial w_j} \quad \text{for } j = 0..n-1 \\ & \quad b = b - \alpha \frac{\partial J(\mathbf{w}, b)}{\partial b} \end{aligned}$$

where,  $n$  is the number of features, parameters  $w_j, b$ , are updated simultaneously and where

$$\frac{\partial J(\mathbf{w}, b)}{\partial w_j} = \frac{1}{m} \sum_{i=0}^{m-1} (f_{\mathbf{w}, b}(x^{(i)}) - y^{(i)}) x_j^{(i)}$$

$$\frac{\partial J(\mathbf{w}, b)}{\partial b} = \frac{1}{m} \sum_{i=0}^{m-1} (f_{\mathbf{w}, b}(x^{(i)}) - y^{(i)})$$

- $m$  is the number of training examples in the data set
- $f_{\mathbf{w}, b}(x^{(i)})$  is the model's prediction, while  $y^{(i)}$  is the target value

### 5.1 Compute Gradient with Multiple Variables

An implementation for calculating the equations (6) and (7) is below. There are many ways to implement this. In this version, there is an

- outer loop over all  $m$  examples.
  - $\frac{\partial J(\mathbf{w}, b)}{\partial b}$  for the example can be computed directly and accumulated
  - in a second loop over all  $n$  features:
    - $\frac{\partial J(\mathbf{w}, b)}{\partial w_j}$  is computed for each  $w_j$ .



## Exercise 3 - Compute Gradient - Non-vectorized

Implement the `compute_gradient_nonvectorized()` function, below, according to the specifications below, including the input parameters and return value (cost). This function should *not* make use of any vectorization.

```
def compute_gradient_nonvectorized(X, y, w, b):  
    """  
    Computes the gradient for linear regression  
    Args:  
        X (ndarray (m,n)): Data, m examples with n features  
        y (ndarray (m,)) : target values  
        w (ndarray (n,)) : model parameters  
        b (scalar)       : model parameter  
  
    Returns:  
        dj_db (scalar): The gradient of the cost w.r.t. the  
        parameter b.  
        dj_dw (ndarray (n,)): The gradient of the cost w.r.t. the  
        parameters w.  
    """  
    # WRITE CODE HERE  
    m = len(y)  
    dj_dw = np.zeros(w.shape)  
    dj_db = 0  
  
    for i in range(m):  
        prediction = np.dot(X[i], w) + b  
        error = prediction - y[i]  
  
        dj_db += error  
        for j in range(len(w)):  
            dj_dw[j] += error * X[i][j]  
  
    dj_dw /= m  
    dj_db /= m  
  
    return dj_db, dj_dw  
  
#Compute and display gradient  
tmp_dj_db, tmp_dj_dw = compute_gradient_nonvectorized(X_train,  
y_train, w_init, b_init)  
print(f'dj_dw at initial w,b: {tmp_dj_dw}')  
print(f'dj_db at initial w,b: {tmp_dj_db}')  
  
dj_dw at initial w,b: [-2.73e-03 -6.27e-06 -2.22e-06 -6.92e-05]  
dj_db at initial w,b: -1.6739251501955248e-06
```

**Expected Result:** `dj_dw at initial w,b: [-2.73e-03 -6.27e-06 -2.22e-06 -6.92e-05]`  
`dj_db at initial w,b: -1.6739251122999121e-06`

## Exercise 4 - Compute Gradient - Vectorized

Implement the `compute_cost_vectorized()` function, below, according to the specifications below, including the input parameters and return value (cost). This function should have a vectorization-based implementation.

```
def compute_gradient_vectorized(X, y, w, b):  
    """  
    Computes the gradient for linear regression  
    Args:  
        X (ndarray (m,n)): Data, m examples with n features  
        y (ndarray (m,)) : target values  
        w (ndarray (n,)) : model parameters  
        b (scalar)       : model parameter  
  
    Returns:  
        dj_db (scalar): The gradient of the cost w.r.t. the  
        parameter b.  
        dj_dw (ndarray (n,)): The gradient of the cost w.r.t. the  
        parameters w.  
    """  
  
    # WRITE CODE HERE  
    m = X.shape[0]  
  
    f = np.dot(X, w) + b  
  
    residuals = f - y  
  
    dj_dw = np.dot(X.T, residuals) / m  
  
    dj_db = np.sum(residuals) / m  
  
    return dj_dw, dj_db  
  
#Compute and display gradient  
tmp_dj_dw, tmp_dj_db = compute_gradient_vectorized(X_train, y_train,  
w_init, b_init)  
print(f'dj_dw at initial w,b: {tmp_dj_dw}')  
print(f'dj_db at initial w,b: {tmp_dj_db}')  
  
dj_dw at initial w,b: [-2.73e-03 -6.27e-06 -2.22e-06 -6.92e-05]  
dj_db at initial w,b: -1.6739251122999121e-06
```

**Expected Result:** `dj_dw at initial w,b: [-2.73e-03 -6.27e-06 -2.22e-06 -6.92e-05]`  
`dj_db at initial w,b: -1.6739251122999121e-06`

## 5.2 Gradient Descent With Multiple Variables

The routine below implements equation (5) above.

```
def gradient_descent(X, y, w_in, b_in, cost_function,
                    gradient_function, alpha, num_iters):
    """
    Performs batch gradient descent to learn w and b. Updates w and b
    by taking
    num_iters gradient steps with learning rate alpha

    Args:
        X (ndarray (m,n)) : Data, m examples with n features
        y (ndarray (m,)) : target values
        w_in (ndarray (n,)) : initial model parameters
        b_in (scalar) : initial model parameter
        cost_function : function to compute cost
        gradient_function : function to compute the gradient
        alpha (float) : Learning rate
        num_iters (int) : number of iterations to run gradient
    descent

    Returns:
        w (ndarray (n,)) : Updated values of parameters
        b (scalar) : Updated value of parameter
    """

    # An array to store cost J and w's at each iteration primarily for
    graphing later
    J_history = []
    w = copy.deepcopy(w_in) #avoid modifying global w within function
    b = b_in

    for i in range(num_iters):

        # Calculate the gradient and update the parameters
        dj_db, dj_dw = gradient_function(X, y, w, b) ##None

        # Update Parameters using w, b, alpha and gradient
        w = w - alpha * dj_dw ##None
        b = b - alpha * dj_db ##None

        # Save cost J at each iteration
        if i < 100000: # prevent resource exhaustion
            J_history.append( cost_function(X, y, w, b))

        # Print cost every at intervals 10 times or as many iterations
    if i < 10:
        if i % math.ceil(num_iters / 10) == 0:
```

```

        print(f"Iteration {i:4d}: Cost {J_history[-1]:8.2f} ")

    return w, b, J_history #return final w,b and J history for
graphing

print("Shape of X_train:", X_train.shape)
print("Shape of y_train:", y_train.shape)

Shape of X_train: (3, 4)
Shape of y_train: (3,)

```

In the next cell you will test the implementation.

```

# initialize parameters
initial_w = np.zeros_like(w_init)
initial_b = 0.
# some gradient descent settings
iterations = 1000
alpha = 5.0e-7
# run gradient descent
w_final, b_final, J_hist = gradient_descent(X_train, y_train,
initial_w, initial_b,

compute_cost_vectorized, compute_gradient_vectorized,
                                alpha, iterations)
print(f"b,w found by gradient descent: {b_final:0.2f},{w_final} ")
m,_ = X_train.shape
for i in range(m):
    print(f"prediction: {np.dot(X_train[i], w_final) + b_final:0.2f},
target value: {y_train[i]}")

```

```

-----
-----
ValueError                                Traceback (most recent call
last)

```

```

Cell In[65], line 8
      6 alpha = 5.0e-7
      7 # run gradient descent
----> 8 w_final, b_final, J_hist = gradient_descent(X_train, y_train,
      9 initial_w, initial_b,
      10 compute_cost_vectorized, compute_gradient_vectorized,
      11 iterations, alpha,
      12 iterations)
      13 print(f"b,w found by gradient descent: {b_final:0.2f},
      14 {w_final} ")
      15 m,_ = X_train.shape

```

```

Cell In[63], line 37, in gradient_descent(X, y, w_in, b_in,
cost_function, gradient_function, alpha, num_iters)

```

```

35 # Save cost J at each iteration
36 if i<100000:      # prevent resource exhaustion
--> 37     J_history.append( cost_function(X, y, w, b))
39 # Print cost every at intervals 10 times or as many iterations
if < 10
40 if i% math.ceil(num_iters / 10) == 0:

Cell In[57], line 16, in compute_cost_vectorized(X, y, w, b)
13 # WRITE CODE HERE
14 m = len(y)
--> 16 differences = np.dot(X, w) + b - y
18 squared_differences = differences ** 2
20 total_cost = np.sum(squared_differences)

ValueError: operands could not be broadcast together with shapes (3,)
(4,)

```

### Expected Result:

b,w found by gradient descent: -0.00,[ 0.2 0. -0.01 -0.07]  
prediction: 426.19, target value: 460  
prediction: 286.17, target value: 232  
prediction: 171.47, target value: 178

```

# plot cost versus iteration
fig, (ax1, ax2) = plt.subplots(1, 2, constrained_layout=True,
figsize=(12, 4))
ax1.plot(J_hist)
ax2.plot(100 + np.arange(len(J_hist[100:])), J_hist[100:])
ax1.set_title("Cost vs. iteration"); ax2.set_title("Cost vs.
iteration (tail)")
ax1.set_ylabel('Cost')           ; ax2.set_ylabel('Cost')
ax1.set_xlabel('iteration step') ; ax2.set_xlabel('iteration step')

plt.show()

```


-----  
-----  
NameError Traceback (most recent call  
last)

```

Cell In[66], line 3
1 # plot cost versus iteration
2 fig, (ax1, ax2) = plt.subplots(1, 2, constrained_layout=True,
figsize=(12, 4))
--> 3 ax1.plot(J_hist)
4 ax2.plot(100 + np.arange(len(J_hist[100:])), J_hist[100:])
5 ax1.set_title("Cost vs. iteration"); ax2.set_title("Cost vs.
iteration (tail)")

```

NameError: name 'J\_hist' is not defined



*These results are not inspiring!* Cost is still declining and our predictions are not very accurate. The next lab will explore how to improve on this.