

Introduction

Namespace ASE

Classes

[Array](#)

The class for storing arrays of numbers

[BOOSEException](#)

Generic BOOSE Language exception Extends Exception

[Canvas](#)

The drawing canvas to be used with this implementation of BOOSE

[CanvasCommand](#)

Abstract class to be extended by CommandXParameter

[Circle](#)

Command for drawing circles around current cursor position

[Command](#)

Base class for all drawing commands

[CommandException](#)

Exception thrown by Command class, message depends on the type of Command that throws the exception

[CommandFactory](#)

Factory class for creating commands

[CommandOneParameter](#)

Abstract class for Commands with one parameter

[CommandThreeParameters](#)

Abstract class for Commands with three parameters

[CommandTwoParameters](#)

Abstract class for Commands with two parameters

[Else](#)

This class doesn't handle what happens when an if condition is false, rather it skips ahead to "end if" when the else keyword is encountered after completing the contents of an "if"

[End](#)

handles the end of "if", "while" and "for"

[Evaluation](#)

An evaluation encompasses all things that can have a value, such as variables, expressions and conditions used in loops and ifs.

[FactoryException](#)

Exception thrown by CommandFactory

[For](#)

A for loop, implemented as an if, while and reassign

[If](#)

The If statement

[Int](#)

Stores an integer

[MoveTo](#)

Command for moving pen to specified position on canvas

[Parser](#)

The class used for reading a BOOSE program

[ParserException](#)

Exception thrown by Parser class

[Peek](#)

Used to access values stored in an array

[PenColour](#)

Command for altering the pen colour using rgb values

[Poke](#)

Used to input data into an array

[Program](#)

Default blazor template code

[Real](#)

Stores a floating point number

[Reassign](#)

Assigns a new value to a variable

[Rect](#)

Command for drawing rectangles at current cursor position

[StoredProgram](#)

Class for storing command objects

[StoredProgramException](#)

Exception thrown by StoredProgram class

[While](#)

The while loop

[Write](#)

Command for writing to the canvas

Interfaces

[ICanvas](#)

The interface to be implemented by the Canvas class

[ICommand](#)

The interface to be implemented by the Command class

[ICommandFactory](#)

The interface to be implemented by the CommandFactory class

[IParser](#)

The interface to be implemented by the Parser class

[IStoredProgram](#)