

UNIVERSITY OF LONDON

BSc EXAMINATION 2017

For Internal Students of
Royal Holloway

DO NOT TURN OVER UNTIL TOLD TO BEGIN

CS2850: Operating Systems

Time Allowed: **TWO hours**

Answer ALL questions
Calculators are not permitted

Important Copyright Notice

This exam paper has been made available in electronic form
strictly for the educational benefit of current Royal Holloway students
on the course of study in question.

No further copying, distribution or publication of this exam paper is permitted.
By printing or downloading this exam paper, you are consenting to these restrictions.

©Royal Holloway, University of London 2017

CS2850

1. (a) The interaction between an operating system and I/O devices can take place via busy waiting or using interrupts. Briefly describe the latter approach. [3 marks]
- (b) Briefly describe the Best Fit memory management algorithm, and point out one of its disadvantages when compared to First Fit. [4 marks]
- (c) Processes and threads are amongst the key concepts of operating systems.
- i. Briefly describe what a process is. [3 marks]
 - ii. How does a thread differ from a process? Give two advantages of threads over processes. [3 marks]
- (d) Give a brief description of the algorithm for First Come, First Served scheduling in batch systems, and present one advantage and one disadvantage of using it. [6 marks]
- (e) Consider the concurrent program that consists of the following two processes that share the variable x :

P1:	$x = 10;$	P2:	$x = 4;$
	$\text{if}(x == 4)$		$x = x - 7;$
	$x = x * 6;$		

How many different values may the variable x have when the program terminates? Give a possible execution sequence for each case. [6 marks]

2. (a) Briefly describe what is a critical region in the context of concurrent programming. [5 marks]
- (b) There are four properties that are required for any correct algorithm to solve the mutual exclusion problem. List these whilst providing a brief description for each. [6 marks]
- (c) Consider the following proposed solution to the mutual exclusion problem for processes P1 and P2, where variables C1 and C2 are both initially set to 1:
- ```
P1: LOOP
 LOOP UNTIL C2 = 1 END_LOOP;
 C1 := 0;
 Critical Region
 C1 := 1;
 Non-Critical Region
 END

P2: LOOP
 LOOP UNTIL C1 = 1 END_LOOP;
 C2 := 0;
 Critical Region
 C2 := 1;
 Non-Critical Region
 END
```
- i. Briefly describe the operation of the algorithm, giving particular emphasis to any dependencies between the two processes. State whether this algorithm enforces strict alternation or not and justify your answer. [4 marks]
- ii. Give one example of execution order that shows the above algorithm does not fully comply with the conditions required for solving the mutual exclusion problem. [5 marks]
- (d) Briefly describe Peterson's algorithm for solving the mutual exclusion problem for two processes. [5 marks]

3. (a) Briefly describe two purposes of semaphores. [6 marks]
- (b) Explain how a semaphore's *up* and *down* operations can be implemented in a multiple CPU scenario whilst guaranteeing they are atomic. [4 marks]
- (c) Revisit the program shown in question 2, copied below:

```
P1: LOOP
 LOOP UNTIL C2 = 1 END_LOOP;
 C1 := 0;
 Critical Region
 C1 := 1;
 Non-Critical Region
END
```

```
P2: LOOP
 LOOP UNTIL C1 = 1 END_LOOP;
 C2 := 0;
 Critical Region
 C2 := 1;
 Non-Critical Region
END
```

- i. Write a revised version of that program using a semaphore. [5 marks]
- ii. What is gained by using a semaphore in that scenario? [4 marks]
- (d) Describe the goal of the message passing synchronisation mechanism, giving emphasis to when this is needed even in systems that support semaphores. Briefly describe how message passing works. [4 marks]

4. (a) Give a short definition of livelock in the context of concurrent programs. Describe an example where livelock can take place. You can use pseudocode for the example. [5 marks]
- (b) What is deadlock? Give an example to explain your definition. [5 marks]
- (c) In the context of deadlock avoidance algorithms:
- Describe what is meant by an unsafe state. [5 marks]
  - Consider the following states, assuming there is only one type of resource.

| State X | Has | Max |
|---------|-----|-----|
| A       | 2   | 4   |
| B       | 1   | 3   |
| C       | 1   | 3   |
| D       | 0   | 1   |

| State Y | Has | Max |
|---------|-----|-----|
| A       | 2   | 3   |
| B       | 0   | 5   |
| C       | 1   | 4   |
| D       | 1   | 5   |

Each row shows the information for a process. The columns show the number of resources held, and the maximum number of resources simultaneously required by each process. In both cases, there are a total of 5 resources in the system (some of which are being held as shown in the tables).

For each of the states (X and Y), indicate if it is a safe or unsafe state, and justify your classification. [4 marks]

- (d) State and briefly describe the four conditions that must all hold for a deadlock to exist. [8 marks]

**END**