

UNIVERSITY OF LONDON

BSc EXAMINATION 2023

For Internal Students of
Royal Holloway

DO NOT TURN OVER UNTIL TOLD TO BEGIN

CS2850: Operating Systems
CS2850R: Operating Systems – for FIRSTSIT/RESIT CANDIDATES

Time Allowed: **TWO hours**

Please answer **ALL** questions

Important Copyright Notice

This exam paper has been made available in electronic form
strictly for the educational benefit of current Royal Holloway students
on the course of study in question.

No further copying, distribution or publication of this exam paper is permitted.
By printing or downloading this exam paper, you are consenting to these restrictions.

©Royal Holloway, University of London 2023

1. Theory Questions (25 marks).

- (a) In the context of memory management, what is the difference between “static” and “dynamic” relocation? [3 marks]
- (b) Briefly describe the linked-list allocation method for storing files. Give one advantage of this method over the contiguous allocation one. [4 marks]
- (c) In a mainframe system without multiprogramming (i.e., programs cannot be run concurrently), consider four jobs A,B, C, and D. Suppose that their estimated running times are:

	running time (minutes)
A	4
B	20
C	3
D	18

Give the **turnaround times** for each of these jobs and the **average turnaround time** in the context of the following two batch system scheduling strategies, making sure to show all your working.

- First-Come First-Served (FCFS), assuming the order A, B, C, D. [5 marks]
 - Shortest Job First (SJF). [5 marks]
- (d) Consider the program that consists of the following two concurrent processes that share the variable x :

```
P1:  x = 4;
      x = x + 2;

P2:  x = 1;
      if (x == 4) {
          x = x * 5;
      }
      else {
          x = x - 1;
      }
```

How many different values may the variable x have when the program terminates? Give a possible execution sequence for each case. [8 marks]

2. Theory Questions (25 marks).

- (a) Consider the following proposed solution to the mutual exclusion problem for two processes. Suppose that the two processes share a variable v , initially set to 0.

```
P1:                                P2:
while(1) {                          while(1) {
    if (v % 2 == 0) {                if (v % 2 == 1) {
        critical_region1();          critical_region2();
        v++;                         v++;
        non_critical_region1();      non_critical_region2();
    }                                }
}
```

- i. Briefly describe the operations of the algorithm, giving particular emphasis to any dependencies between the two processes. Explain why the algorithm does enforce strict alternation. [6 marks]
 - ii. This algorithm does not comply with one of the conditions required for solving the mutual exclusion problem. Indicate which one, and give one example of execution order violating that condition. [5 marks]
- (b) Briefly describe the Banker's algorithm with a single resource type, and indicate how it can be used by the Operating System to determine whether a resource request made by a process should be granted. [6 marks]
- (c) A virtual memory system has 32-bit virtual addresses and page size 4K. To optimise memory usage, it uses a two-level page table, where the left-most 12 bits of the virtual address are used to index the top-level table.
- i. How many second-level page tables are there in total? [4 marks]
 - ii. How many entries does each second-level page table have? [4 marks]

Justify your answers.

3. Pointers (20 marks).

```
#include <stdio.h>

struct point {
    int x;
    int y;
    char label;
};

int main() {
    int i = 1.234;
    printf("1. (float i) = %f\n", (float) i);
    printf("2. (void *) &i = %p\n", (void *) &i);
    int j = 12.345;
    printf("3. j = %o\n", j);
    int *ip = &i;
    int *jp = &j;
    printf("4. (void *) (&i - jp) = %p\n", (void *) (&i - jp));
    printf("5. *(&i + 100) = %d\n", *(&i + 100));
    ip = &j;
    *ip = i;
    printf("6. i - j = %d\n", i - j);
    printf("7. sizeof(struct point) = %lu\n", sizeof(struct
        point));
    struct point z;
    printf("8. sizeof(&z) = %lu\n", sizeof(&z));
    (&z)->x = i;
    z.y = j;
    (&z)->label = '1';
    printf("9. (&z)->label = %d\n", (&z)->label);
    printf("10. z.label = %c\n", z.label);
}
```

A possible `stdout` output of the program above is

```
1. (float i) = 1.000000
2. (void *) &i = 0x7ffe7c124520
3. j = 14
4. (void *) (&i - jp) = 0xffffffffffffffff
5. *(&i + 100) = 2081580231
6. i - j = 0
7. sizeof(struct point) = 12
8. sizeof(&z) = 8
9. (&z)->label = 49
10. z.label = 1
```

For each line of the output, explain what is printed on the terminal and why you obtain those specific values. [20 marks]

4. Swapping functions (10 marks).

The output of the program in Listing 1 when the user enters the character `q` to relabel the point called '1' is

```
point 1: (x = 1, y = 2)
point 2: (x = 3, y = 4)
swapping x coordinates ...
point 1: (x = 3, y = 2)
point 2: (x = 1, y = 4)
enter a new label for point 1:
q
the new label for point 1 is q
point q: (x = 3, y = 2)
point 2: (x = 1, y = 4)
```

Write the definition of

- (a) `swapx`, a function that swaps the `x` coordinate of the points, and [5 marks]
- (b) `changeLabel`, a function that renames one point by asking the user to enter a character in the terminal, [5 marks]

so that the program in Listing 1 behaves exactly as in the output shown above.

Hint: In `changeLabel`, use `char c = getchar();` to read the user input from the terminal and store it in a character variable.

Listing 1: C code of the program

```
#include <stdio.h>
struct point {
    int x;
    int y;
    char label;
};
void swapx(int *p1, int *p2);
void changeLabel(struct point *pz);
void printPoints(struct point *p, struct point *q);
int main() {
    struct point z1, z2;
    (&z1)->x = 1;
    (&z1)->y = 2;
    (&z2)->x = 3;
    (&z2)->y = 4;
    (&z1)->label = '1';
    (&z2)->label = '2';
    printPoints(&z1, &z2);
    swapx(&(z1.x), &(z2.x));
    printPoints(&z1, &z2);
    changeLabel(&z1);
    printPoints(&z1, &z2);
}
void printPoints(struct point *p, struct point *q) {
    printf("point %c: (x = %d, y = %d)\n", p->label, p
        ->x, p->y);
    printf("point %c: (x = %d, y = %d)\n", q->label, q
        ->x, q->y);
}
```

5. String merger (20 marks).

```
#include <stdio.h>
#include <stdlib.h>
#define MAX 10
int stringLen(char *string);
char *merge(char *string, char *s);
int main() {
    char c = '\0';
    char *string = NULL;
    while (c != EOF) {
        char s[MAX];
        int i = 0;
        while (((c = getchar()) != '\n') && (i < (MAX - 1)) && (c != EOF))
            *(s + i++) = c;
        *(s + i) = '\0';
        string = merge(string, s);
        printf("%s\n", string);
    }
    free(string);
}
```

The program above uses dynamic memory allocation to for handle a string of variable length. Read the definition of `stringLen` and `merge` in Listing 2 and answer the following questions.

(a) In `main`:

- i. What does the program do and why do you need to allocate the memory dynamically? [4 marks]
- ii. Why would `char c`; instead of `char c='\0'` produce an execution error? [2 marks]
- iii. Why do you need `i < (MAX - 1)` instead of `i < MAX`? [2 marks]
- iv. What happens if the user enters more than `MAX-1` characters? [2 marks]
- v. Why do you need to null-terminate `s` before passing it to `merge`? [2 marks]
- vi. Why do you need `free(string)` at the end? [2 marks]

(b) In `merge`:

- i. What is the purpose of the first and the second `while` loops? [4 marks]
- ii. Why do you need to check if `string` is a valid pointer before freeing it? [2 marks]

Listing 2: Definition of stringLen and merge

```
int stringLen(char *string) {
    if (!string) return 0;
    int i = 0;
    while (*(string + i) != '\0') i++;
    return i;
}

char *merge(char *string, char *s) {
    int n = stringLen(string);
    int m = stringLen(s);
    int i = 0;
    char *new = malloc(n + m + 1);
    while (i < n) {
        *(new + i) = *(string + i);
        i++;
    }
    while (i < (n + m)) {
        *(new + i) = *(s + i - n);
        i++;
    }
    *(new + i) = '\0';
    if (string) free(string);
    return new;
}
```

END