

# Quiz Practice Problems (Transactions and Locks)

**Instructions:** For each problem, you must perform all of the following tasks correctly in order to get credit.

1. Circle all SQL commands that block.
2. Write an X through all commands that error.
3. If a command causes a deadlock, write DEADLOCK and stop the problem.
4. Write the output of each SELECT statement.

You will be allowed to use a computer and access the internet, but you will not be allowed to connect to postgres and run postgres commands.

## 1 Basic Transactions

**Problem 1:**

Session 1

```
1 CREATE TABLE t ( a INT );
2
3 INSERT INTO t VALUES (5);
4 INSERT INTO t VALUES (6);
5
6 INSERT INTO t VALUES (2);
```

Session 2

```
1
2 SELECT count(*) FROM t;
3
4
5 SELECT count(*) FROM t;
6
7 SELECT count(*) FROM t;
```

**Problem 2:**

Session 1

```
1 CREATE TABLE t ( a INT );
2
3 BEGIN;
4 INSERT INTO t VALUES (5);
5 INSERT INTO t VALUES (6);
6
7 INSERT INTO t VALUES (2);
8 COMMIT;
```

Session 2

```
1
2 SELECT count(*) FROM t;
3
4
5
6 SELECT count(*) FROM t;
7
8
9 SELECT count(*) FROM t;
```

### Problem 3:

Session 1

```
1 CREATE TABLE t ( a INT );
2
3 BEGIN;
4 INSERT INTO t VALUES (5);
5 INSERT INTO t VALUES (6);
6
7 INSERT INTO t VALUES (2);
8 ROLLBACK;
```

Session 2

```
1
2 SELECT count(*) FROM t;
3
4
5
6 SELECT count(*) FROM t;
7
8
9 SELECT count(*) FROM t;
```

### Problem 4:

Session 1

```
1 CREATE TABLE t ( a INT );
2
3 BEGIN;
4 INSERT INTO t VALUES (5);
5 INSERT INTO t VALUES (6);
6
7 INSERT INTO t VALUES (2);
8 ABORT;
```

Session 2

```
1
2 SELECT count(*) FROM t;
3
4
5
6 SELECT count(*) FROM t;
7
8
9 SELECT count(*) FROM t;
```

## 2 Isolation Levels

### Problem 5:

#### Session 1

```
1 CREATE TABLE t ( a INT );
2
3
4 BEGIN;
5 INSERT INTO t VALUES (5);
6 INSERT INTO t VALUES (6);
7
8 INSERT INTO t VALUES (2);
9 COMMIT;
```

#### Session 2

```
1
2 BEGIN;
3 SELECT count(*) FROM t;
4
5
6
7 SELECT count(*) FROM t;
8
9
10 SELECT count(*) FROM t;
11 COMMIT;
12 SELECT count(*) FROM t;
```

### Problem 6:

#### Session 1

```
1 CREATE TABLE t ( a INT );
2
3
4
5 BEGIN;
6 INSERT INTO t VALUES (5);
7 INSERT INTO t VALUES (6);
8
9 INSERT INTO t VALUES (2);
10 COMMIT;
```

#### Session 2

```
1
2 BEGIN ISOLATION LEVEL
3 REPEATABLE READ;
4 SELECT count(*) FROM t;
5
6
7
8 SELECT count(*) FROM t;
9
10
11 SELECT count(*) FROM t;
12 COMMIT;
13 SELECT count(*) FROM t;
```

### Problem 7:

#### Session 1

```
1 CREATE TABLE t ( a INT );
2
3
4 BEGIN;
5 INSERT INTO t VALUES (5);
6 INSERT INTO t VALUES (6);
7
8 INSERT INTO t VALUES (2);
9 COMMIT;
```

#### Session 2

```
1
2 BEGIN ISOLATION LEVEL
3 READ COMMITTED;
4
5
6
7 SELECT count(*) FROM t;
8
9
10 SELECT count(*) FROM t;
11 COMMIT;
12 SELECT count(*) FROM t;
```

**Note 1.** From here on out, you should understand all of the examples as if any transaction was in any isolation level.

### Problem 8:

#### Session 1

```
1 CREATE TABLE t ( a INT );
2
3
4 BEGIN;
5 INSERT INTO t VALUES (5);
6 INSERT INTO t VALUES (6);
7 INSERT INTO t VALUES (2);
8 COMMIT;
```

#### Session 2

```
1
2 BEGIN ISOLATION LEVEL
3 REPEATABLE READ;
4
5
6
7
8
9 SELECT count(*) FROM t;
10 COMMIT;
11 SELECT count(*) FROM t;
```

### Problem 9:

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2	2 BEGIN ISOLATION LEVEL
3	3 REPEATABLE READ;
4	4 SELECT count(*) FROM t;
5 BEGIN ISOLATION LEVEL	5
6 REPEATABLE READ;	6
7 INSERT INTO t VALUES (5);	7
8 SELECT count(*) FROM t;	8
9 INSERT INTO t VALUES (6);	9
10 SELECT count(*) FROM t;	10
11 INSERT INTO t VALUES (2);	11
12 SELECT count(*) FROM t;	12
13 COMMIT;	13
	14 SELECT count(*) FROM t;
	15 COMMIT;
	16 SELECT count(*) FROM t;

## 3 Explicit Locks

### Problem 10:

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 BEGIN;	2
3 LOCK TABLE t IN EXCLUSIVE MODE;	3
4	4 BEGIN;
5	5 LOCK TABLE t IN SHARE MODE;
6 COMMIT;	6
	7 COMMIT;

**Problem 11:**

Session 1

```
1 CREATE TABLE t ( a INT );
2 BEGIN;
3 LOCK TABLE t IN SHARE MODE;
4
5
6 COMMIT;
```

Session 2

```
1
2
3
4 BEGIN;
5 LOCK TABLE t IN EXCLUSIVE MODE;
6
7 COMMIT;
```

**Problem 12:**

Session 1

```
1 CREATE TABLE t ( a INT );
2 BEGIN;
3 LOCK TABLE t IN SHARE MODE;
4
5
6 COMMIT;
```

Session 2

```
1
2
3
4 BEGIN;
5 LOCK TABLE t IN ROW SHARE MODE;
6
7 COMMIT;
```

**Problem 13:**

Session 1

```
1 CREATE TABLE t ( a INT );
2 BEGIN;
3 LOCK TABLE t IN EXCLUSIVE MODE;
4 COMMIT;
```

Session 2

```
1
2
3
4
5 BEGIN;
6 LOCK TABLE t IN EXCLUSIVE MODE;
7 COMMIT;
```

#### Problem 14:

Session 1

```
1 CREATE TABLE t ( a INT );
2 BEGIN;
3 LOCK TABLE t IN ROW EXCLUSIVE MODE;
4
5
6
7 COMMIT;
```

Session 2

```
1
2
3
4 BEGIN;
5 LOCK TABLE t IN ROW SHARE MODE;
6 COMMIT;
```

## 4 Deadlocks

#### Problem 15:

Session 1

```
1 CREATE TABLE t ( a INT );
2
3 BEGIN;
4 LOCK TABLE t IN EXCLUSIVE MODE;
5
6
7 LOCK TABLE u IN EXCLUSIVE MODE;
8
9 COMMIT;
```

Session 2

```
1
2 CREATE TABLE u ( a INT );
3
4
5 BEGIN;
6 LOCK TABLE u IN EXCLUSIVE MODE;
7
8 LOCK TABLE t IN EXCLUSIVE MODE;
9
10 COMMIT;
```

#### Problem 16:

Session 1

```
1 CREATE TABLE t ( a INT );
2
3 BEGIN;
4 LOCK TABLE t IN SHARE MODE;
5
6
7 LOCK TABLE u IN SHARE MODE;
8
9 COMMIT;
```

Session 2

```
1
2 CREATE TABLE u ( a INT );
3
4
5 BEGIN;
6 LOCK TABLE u IN SHARE MODE;
7
8 LOCK TABLE t IN SHARE MODE;
9
10 COMMIT;
```

**Problem 17:**

Session 1

```
1 CREATE TABLE t ( a INT );
2
3 BEGIN;
4 LOCK TABLE t IN SHARE MODE;
5
6
7 LOCK TABLE u IN ROW EXCLUSIVE MODE;
8
9 COMMIT;
```

Session 2

```
1
2 CREATE TABLE u ( a INT );
3
4
5 BEGIN;
6 LOCK TABLE u IN EXCLUSIVE MODE;
7
8 LOCK TABLE t IN ROW SHARE MODE;
9
10 COMMIT;
```

**Problem 18:**

Session 1

```
1 CREATE TABLE t ( a INT );
2
3 BEGIN;
4 LOCK TABLE t IN SHARE MODE;
5 LOCK TABLE u IN ROW EXCLUSIVE MODE;
6 COMMIT;
```

Session 2

```
1
2 CREATE TABLE u ( a INT );
3
4
5
6
7 BEGIN;
8 LOCK TABLE u IN EXCLUSIVE MODE;
9 LOCK TABLE t IN ROW SHARE MODE;
10 COMMIT;
```



### Problem 19:

Session 1

```
1 CREATE TABLE t ( a INT );
2
3 BEGIN;
4 LOCK TABLE t IN SHARE MODE;
5 LOCK TABLE u IN ROW EXCLUSIVE MODE;
6
7
8
9 COMMIT;
```

Session 2

```
1
2 CREATE TABLE u ( a INT );
3
4
5
6 BEGIN;
7 LOCK TABLE u IN EXCLUSIVE MODE;
8 LOCK TABLE t IN ROW SHARE MODE;
9
10 COMMIT;
```

### Problem 20:

Session 1

```
1 CREATE TABLE t ( a INT );
2
3 BEGIN;
4
5 LOCK TABLE t IN ACCESS SHARE MODE;
6
7
8 LOCK TABLE u IN ROW EXCLUSIVE MODE;
9 COMMIT;
```

Session 2

```
1
2 CREATE TABLE u ( a INT );
3
4 BEGIN;
5
6 LOCK TABLE u IN EXCLUSIVE MODE;
7 LOCK TABLE t IN SHARE MODE;
8
9
10 COMMIT;
```

## 5 Implicit Locks I

### Problem 21:

Session 1

```
1 CREATE TABLE t ( a INT );
2 BEGIN;
3 LOCK TABLE t IN ACCESS EXCLUSIVE MODE;
4
5 COMMIT;
```

Session 2

```
1
2
3
4 INSERT INTO t VALUES (5);
```

**Problem 22:**

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 BEGIN;	2
3 LOCK TABLE t IN ACCESS EXCLUSIVE MODE;	3
4	4 SELECT count(*) FROM t;
5 COMMIT;	

**Problem 23:**

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 BEGIN;	2
3 LOCK TABLE t IN SHARE MODE;	3
4	4 INSERT INTO t VALUES (1);
5 COMMIT;	

**Problem 24:**

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 BEGIN;	2
3 LOCK TABLE t IN SHARE MODE;	3
4	4 SELECT count(*) FROM t;
5 COMMIT;	

**Problem 25:**

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 BEGIN;	2
3 LOCK TABLE t IN ROW SHARE MODE;	3
4	4 INSERT INTO t VALUES (1);
5 COMMIT;	

## 6 Implicit Locks II: More interesting commands

**Problem 26:**

Session 1

```
1 CREATE TABLE t ( a INT );
2 BEGIN;
3 LOCK TABLE t IN ROW EXCLUSIVE MODE;
4
5 COMMIT;
```

Session 2

```
1
2
3
4 CREATE INDEX ON t(a);
```

**Problem 27:**

Session 1

```
1 CREATE TABLE t ( a INT );
2 BEGIN;
3 LOCK TABLE t IN ROW EXCLUSIVE MODE;
4
5 COMMIT;
```

Session 2

```
1
2
3
4 CREATE INDEX CONCURRENTLY ON t(a);
```

**Problem 28:**

Session 1

```
1 CREATE TABLE t ( a INT );
2 BEGIN;
3 LOCK TABLE t IN SHARE MODE;
4
5 COMMIT;
```

Session 2

```
1
2
3
4 VACUUM t;
```

**Problem 29:**

Session 1

```
1 CREATE TABLE t ( a INT );
2 BEGIN;
3 LOCK TABLE t IN ROW SHARE MODE;
4
5 COMMIT;
```

Session 2

```
1
2
3
4 VACUUM FULL t;
```

**Problem 30:**

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 BEGIN;	2
3 LOCK TABLE t IN ROW EXCLUSIVE MODE;	3
4	4 ANALYZE t;
5 COMMIT;	

**Problem 31:**

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 BEGIN;	2
3 LOCK TABLE t IN ROW EXCLUSIVE MODE;	3
4	4 CLUSTER t;
5 COMMIT;	

**Problem 32:**

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 BEGIN;	2
3 INSERT INTO t VALUES (5);	3
4	4 BEGIN;
5	5 INSERT INTO t VALUES (6);
6 COMMIT;	6
	7 COMMIT;

## 7 Implicit Locks III: Row Level Locks

**Problem 33:**

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 INSERT INTO t VALUES (1);	2
3 INSERT INTO t VALUES (2);	3
4 INSERT INTO t VALUES (3);	4
5	5 BEGIN;
6 BEGIN;	6
7 UPDATE t SET a=6 WHERE a=1;	7
8	8 UPDATE t SET a=7 WHERE a=1;
9	9 COMMIT;
10 COMMIT;	

**Problem 34:**

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 INSERT INTO t VALUES (1);	2
3 INSERT INTO t VALUES (2);	3
4 INSERT INTO t VALUES (3);	4
5	5 BEGIN;
6 BEGIN;	6
7 UPDATE t SET a=6 WHERE a=1;	7
8	8 DELETE FROM t WHERE a=2;
9	9 COMMIT;
10 COMMIT;	

**Problem 35:**

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 INSERT INTO t VALUES (1);	2
3 INSERT INTO t VALUES (2);	3
4 INSERT INTO t VALUES (3);	4
5	5 BEGIN;
6 BEGIN;	6
7 UPDATE t SET a=6 WHERE a=1;	7
8	8 DELETE FROM t WHERE a=1;
9	9 COMMIT;
10 COMMIT;	

**Problem 36:**

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 INSERT INTO t VALUES (1);	2
3 INSERT INTO t VALUES (2);	3
4 INSERT INTO t VALUES (3);	4
5	5 BEGIN;
6 BEGIN;	6
7 UPDATE t SET a=6 WHERE a=1;	7
8	8 DELETE FROM t;
9	9 COMMIT;
10 COMMIT;	

**Problem 37:**

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 INSERT INTO t VALUES (1);	2
3 INSERT INTO t VALUES (2);	3
4 INSERT INTO t VALUES (3);	4
5	5 BEGIN;
6 BEGIN;	6
7 DELETE FROM t WHERE a=3;	7
8	8 UPDATE t SET a=5;
9	9 COMMIT;
10 COMMIT;	

**Problem 38:**

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 INSERT INTO t VALUES (1);	2
3 INSERT INTO t VALUES (2);	3
4 INSERT INTO t VALUES (3);	4
5	5 BEGIN;
6 BEGIN;	6
7 DELETE FROM t WHERE a=4;	7
8	8 UPDATE t SET a=5;
9	9 COMMIT;
10 COMMIT;	

**Problem 39:**

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 INSERT INTO t VALUES (1);	2
3 INSERT INTO t VALUES (2);	3
4 INSERT INTO t VALUES (3);	4
5	5 BEGIN;
6 BEGIN;	6
7 UPDATE t SET a=6 WHERE a=1;	7
8	8 UPDATE t SET a=7 WHERE a=2;
9	9 COMMIT;
10 COMMIT;	

**Problem 40:**

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 INSERT INTO t VALUES (1);	2
3 INSERT INTO t VALUES (2);	3
4 INSERT INTO t VALUES (3);	4
5	5 BEGIN;
6 BEGIN;	6
7 SELECT * FROM t WHERE a=2 FOR UPDATE;	7
8	8 UPDATE t SET a=7 WHERE a=2;
9	9 COMMIT;
10 COMMIT;	

**Problem 41:**

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 INSERT INTO t VALUES (1);	2
3 INSERT INTO t VALUES (2);	3
4 INSERT INTO t VALUES (3);	4
5	5 BEGIN;
6 BEGIN;	6
7 SELECT * FROM t WHERE a=2 FOR UPDATE;	7
8	8 UPDATE t SET a=7 WHERE a=3;
9	9 COMMIT;
10 COMMIT;	

#### Problem 42:

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 INSERT INTO t VALUES (1);	2
3 INSERT INTO t VALUES (2);	3
4 INSERT INTO t VALUES (3);	4
5	5 BEGIN;
6 BEGIN;	6
7 SELECT * FROM t FOR UPDATE;	7
8	8 UPDATE t SET a=7 WHERE a=3;
9	9 COMMIT;
10 COMMIT;	

## 8 Implicit Locks IV: Unique constraints

#### Problem 43:

Session 1	Session 2
1 CREATE TABLE t ( a INT UNIQUE );	1
2 BEGIN;	2
3 INSERT INTO t VALUES (5);	3
4	4 BEGIN;
5	5 INSERT INTO t VALUES (6);
6 COMMIT;	6
	7 COMMIT;

#### Problem 44:

Session 1	Session 2
1 CREATE TABLE t ( a INT UNIQUE );	1
2 BEGIN;	2
3 INSERT INTO t VALUES (NULL);	3
4	4 BEGIN;
5	5 INSERT INTO t VALUES (6);
6 COMMIT;	6
	7 COMMIT;



**Problem 45:**

Session 1

```
1 CREATE TABLE t ( a INT UNIQUE );
2 BEGIN;
3 INSERT INTO t VALUES (5);
4
5
6 COMMIT;
```

Session 2

```
1
2
3
4 BEGIN;
5 INSERT INTO t VALUES (NULL);
6
7 COMMIT;
```

**Problem 46:**

Session 1

```
1 CREATE TABLE t ( a INT UNIQUE );
2
3 BEGIN;
4 INSERT INTO t VALUES (NULL);
5
6
7 INSERT INTO u VALUES (6);
8
9
10 COMMIT;
```

Session 2

```
1
2 CREATE TABLE u ( a INT UNIQUE );
3
4
5 BEGIN;
6 INSERT INTO u VALUES (NULL);
7
8 INSERT INTO t VALUES (8);
9 COMMIT;
```

**Problem 47:**

Session 1

```
1 CREATE TABLE t ( a INT UNIQUE );
2
3 BEGIN;
4 INSERT INTO t VALUES (5);
5
6
7 INSERT INTO u VALUES (NULL);
8
9
10 COMMIT;
```

Session 2

```
1
2 CREATE TABLE u ( a INT UNIQUE );
3
4
5 BEGIN;
6 INSERT INTO u VALUES (7);
7
8 INSERT INTO t VALUES (8);
9 COMMIT;
```

**Problem 48:**

Session 1	Session 2
1 CREATE TABLE t ( a INT UNIQUE );	1
2	2 CREATE TABLE u ( a INT UNIQUE );
3 BEGIN;	3
4 INSERT INTO t VALUES (5);	4
5	5 BEGIN;
6	6 INSERT INTO u VALUES (7);
7 INSERT INTO u VALUES (6);	7
8	8 INSERT INTO t VALUES (NULL);
9	9 COMMIT;
10 COMMIT;	

## 9 Isolation Levels II: Row Level

**Problem 49:**

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 INSERT INTO t VALUES (9);	2
3 INSERT INTO t VALUES (10);	3
4 BEGIN;	4
5	5 BEGIN;
6 UPDATE t SET a = a+1;	6
7	7 DELETE FROM t WHERE a=10;
8	8 COMMIT;
9 COMMIT;	9 SELECT count(*) FROM t;

**Problem 50:**

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 INSERT INTO t VALUES (9);	2
3 INSERT INTO t VALUES (10);	3
4 BEGIN;	4
5	5 BEGIN;
6 UPDATE t SET a = a+1;	6
7	7 DELETE FROM t WHERE a=10;
8	8 COMMIT;
9 ABORT;	9 SELECT count(*) FROM t;

### Problem 51:

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 INSERT INTO t VALUES (9);	2
3 INSERT INTO t VALUES (10);	3
4 BEGIN;	4
5	5 BEGIN ISOLATION LEVEL
6	6 REPEATABLE READ;
7 UPDATE t SET a = a+1;	7
8	8 DELETE FROM t WHERE a=10;
9	9 COMMIT;
10 COMMIT;	

### Problem 52:

Session 1	Session 2
1 CREATE TABLE t ( a INT );	1
2 INSERT INTO t VALUES (9);	2
3 INSERT INTO t VALUES (10);	3
4 BEGIN;	4
5	5 BEGIN ISOLATION LEVEL
6	6 REPEATABLE READ;
7 UPDATE t SET a = a+1;	7
8	8 DELETE FROM t WHERE a=10;
9	9 COMMIT;
10 ABORT;	

## 10 Foreign Keys

### Problem 53:

Session 1	Session 2
1 CREATE TABLE t(a INT UNIQUE);	1
2 CREATE TABLE u(b INT REFERENCES t(a));	2
3 BEGIN;	3
4	4 BEGIN;
5 INSERT INTO t VALUES (9);	5
6	6 INSERT INTO u VALUES (9);
7 COMMIT;	7
	8 COMMIT;

**Problem 54:**

Session 1

```
1 CREATE TABLE t(a INT UNIQUE);
2 CREATE TABLE u(b INT REFERENCES t(a));
3
4 INSERT INTO t VALUES (9);
```

Session 2

```
1
2
3 BEGIN;
4
5 INSERT INTO u VALUES (9);
6 COMMIT;
```

**Problem 55:**

Session 1

```
1 CREATE TABLE t(a INT UNIQUE);
2 CREATE TABLE u(b INT REFERENCES t(a));
3 INSERT INTO t VALUES (8);
4 INSERT INTO t VALUES (9);
5 BEGIN;
6
7 INSERT INTO u VALUES (9);
8
9 COMMIT;
```

Session 2

```
1
2
3
4
5
6 BEGIN;
7
8 DELETE FROM t WHERE a=9;
9
10 COMMIT;
```

**Problem 56:**

Session 1

```
1 CREATE TABLE t(a INT UNIQUE);
2 CREATE TABLE u(b INT REFERENCES t(a));
3 INSERT INTO t VALUES (8);
4 INSERT INTO t VALUES (9);
5 BEGIN;
6
7 INSERT INTO u VALUES (9);
8
9 COMMIT;
```

Session 2

```
1
2
3
4
5
6 BEGIN;
7
8 DELETE FROM t WHERE a=8;
9
10 COMMIT;
```

**Problem 57:**

Session 1

```
1 CREATE TABLE t(a INT UNIQUE);
2 CREATE TABLE u(b INT REFERENCES t(a));
3 INSERT INTO t VALUES (8);
4 INSERT INTO t VALUES (9);
5 BEGIN;
6
7 INSERT INTO u VALUES (9);
8
9 ABORT;
```

Session 2

```
1
2
3
4
5
6 BEGIN;
7
8 DELETE FROM t WHERE a=9;
9
10 COMMIT;
```

**Problem 58:**

Session 1

```
1 CREATE TABLE t(a INT UNIQUE);
2 CREATE TABLE u(b INT REFERENCES t(a));
3 INSERT INTO t VALUES (8);
4 INSERT INTO t VALUES (9);
5 BEGIN;
6
7 INSERT INTO u VALUES (9);
8
9 ABORT;
```

Session 2

```
1
2
3
4
5
6 BEGIN;
7
8 DELETE FROM t WHERE a=8;
9
10 COMMIT;
```

**Problem 59:**

Session 1

```
1 CREATE TABLE t(a INT UNIQUE);
2 CREATE TABLE u(b INT REFERENCES t(a));
3 INSERT INTO t VALUES (8);
4 INSERT INTO t VALUES (9);
5 BEGIN;
6
7
8 INSERT INTO u VALUES (9);
9
10 COMMIT;
```

Session 2

```
1
2
3
4
5
6 BEGIN;
7 DELETE FROM t WHERE a=9;
8
9 COMMIT;
```

### Problem 60:

Session 1	Session 2
1 CREATE TABLE t(a INT UNIQUE);	1
2 CREATE TABLE u(b INT REFERENCES t(a));	2
3 INSERT INTO t VALUES (8);	3
4 INSERT INTO t VALUES (9);	4
5 BEGIN;	5
6	6 BEGIN;
7	7 DELETE FROM t WHERE a=8;
8 INSERT INTO u VALUES (9);	8
9	9 COMMIT;
10 COMMIT;	

## 11 Deferring Constraints

**Note:** For each problem, you should consider what would happen both with and without the DEFERRABLE INITIALLY DEFERRED line.

### Problem 61:

Session 1	Session 2
1 CREATE TABLE t (	
2     a INT UNIQUE	
3     DEFERRABLE INITIALLY DEFERRED	
4   );	
5 BEGIN;	
6 INSERT INTO t VALUES (8);	
7 INSERT INTO t VALUES (8);	
8 COMMIT;	

**Problem 62:**

Session 1	Session 2
1 CREATE TABLE t (a INT UNIQUE);	1
2 CREATE TABLE u (	2
3     b INT REFERENCES t(a)	3
4     DEFERRABLE INITIALLY DEFERRED	4
5     );	5
6 BEGIN;	6
7	7 BEGIN;
8	8 INSERT INTO u VALUES (8);
9 INSERT INTO t VALUES (8);	9
10 COMMIT;	10
	11 COMMIT;

**Problem 63:**

Session 1	Session 2
1 CREATE TABLE t (a INT UNIQUE);	1
2 CREATE TABLE u (	2
3     b INT REFERENCES t(a)	3
4     DEFERRABLE INITIALLY DEFERRED	4
5     );	5
6 BEGIN;	6
7	7 BEGIN;
8	8 INSERT INTO u VALUES (8);
9 INSERT INTO t VALUES (8);	9
10 ABORT;	10
	11 COMMIT;

#### Problem 64:

Session 1	Session 2
1 CREATE TABLE t (a INT UNIQUE);	1
2 CREATE TABLE u (	2
3     b INT REFERENCES t(a)	3
4     DEFERRABLE INITIALLY DEFERRED	4
5     );	5
6 BEGIN;	6
7	7 BEGIN;
8	8 INSERT INTO u VALUES (8);
9 LOCK TABLE t IN EXCLUSIVE MODE;	9
10	10 COMMIT;
11 INSERT INTO t VALUES (8);	
12 COMMIT;	

#### Problem 65:

Session 1	Session 2
1 CREATE TABLE t (a INT UNIQUE);	1
2 CREATE TABLE u (	2
3     b INT REFERENCES t(a)	3
4     DEFERRABLE INITIALLY DEFERRED	4
5     );	5
6 BEGIN;	6
7	7 BEGIN;
8	8 INSERT INTO u VALUES (8);
9 LOCK TABLE t IN EXCLUSIVE MODE;	9
10	10 COMMIT;
11 COMMIT;	

## 12 Everything at Once



**Problem 66:**

Session 1	Session 2
1 CREATE TABLE t (a INT PRIMARY KEY);	1
2	2 CREATE TABLE u (
3	3 b INT REFERENCES t(a)
4	4 );
5 BEGIN;	5
6 INSERT INTO t VALUES (1);	6
7 INSERT INTO t VALUES (2);	7
8 INSERT INTO u VALUES (2);	8
9	9 BEGIN ISOLATION LEVEL
10	10 REPEATABLE READ;
11	11 SELECT count(*) FROM u;
12 LOCK TABLE t IN EXCLUSIVE MODE;	12
13 SELECT count(*) FROM t;	13
14	14 INSERT INTO u VALUES (1);
15	15 SELECT count(*) FROM u;
16 INSERT INTO t VALUES (NULL);	16
17 COMMIT;	17
18	18 INSERT INTO u VALUES (NULL);
19	19 COMMIT;
20	20 SELECT count(*) FROM t;
21 SELECT count(*) FROM u;	

**Problem 67:**

Session 1	Session 2
1 CREATE TABLE t (a INT PRIMARY KEY);	1
2	2 CREATE TABLE u (b INT NOT NULL);
3 BEGIN;	3
4 INSERT INTO t VALUES (1);	4
5 INSERT INTO t VALUES (2);	5
6 INSERT INTO u VALUES (2);	6
7	7 BEGIN ISOLATION LEVEL
8	8 REPEATABLE READ;
9	9 INSERT INTO t VALUES (2);
10 LOCK TABLE u IN ROWEXCLUSIVE MODE;	10
11 SELECT count(*) FROM t;	11
12	12 INSERT INTO u VALUES (1);
13	13 SELECT count(*) FROM u;
14 INSERT INTO t VALUES (3);	14
15 COMMIT;	15
16	16 UPDATE u SET b=5;
17	17 COMMIT;
18	18 SELECT count(*) FROM t;
19 SELECT count(*) FROM t;	