

# Measuring Students' Performance on Programming Tasks

Tomáš Effenberger

Radek Pelánek

Masaryk University Brno, Czech Republic

## Motivation


Binary success provides too little information for student and tutor modeling.

Using detailed observations hinders reuse, and complicates the development of learning systems.

**Proposal:** Use discrete performance measures with just a few distinct values.


Performance levels and interpretation:

- weak performance ... too difficult task
- good performance ... appropriate task
- excellent performance ... too easy task



## Case study: Design of a performance measure

- adaptive learning system for introductory programming
- 85 tasks, 9 levels x 3 sublevels
- performance measures based on
  - (A) executions count
  - (B) solving time, thresholds per sublevel
  - (C) solving time, thresholds per problem



**Result:** The choice of performance measure matters. Different reasonable choices lead to very different measurements.


## Interaction with domain modeling

**Issue:** Flaws in the domain model impact the accuracy of a performance measure.

**Consequence:** Unconstrained optimization leads to a wild performance measure.

**Solution:** Impose a constraint on the threshold progression (e.g., a constant increase between sublevels).

**Side effect:** The flaws in the domain model are detected.



## Summary

Instead of using binary success, the currently prevalent choice of performance measure, we propose to use a few discrete performance levels with universal interpretation, such as failed, weak, good, and excellent.

Design of a performance should take into account possible interaction with domain modeling.