

- 🛁 Scene Distribution
- 🚢 Scene Utility
- 🍌 Train/Val/Test Splits

```
kitchens = ["FloorPlan%i" for i in range(1, 31)]
living_rooms = ["FloorPlan{200 + i}" for i in range(1, 31)]
bedrooms = ["FloorPlan{300 + i}" for i in range(1, 31)]
bathrooms = ["FloorPlan{400 + i}" for i in range(1, 31)]

scenes = kitchens + living_rooms + bedrooms + bathrooms
```

```
["FloorPlan1", "FloorPlan2", "FloorPlan3", {...}, "FloorPlan430"]
```

Explore the scenes in the [demo](#)!

```
controller.ithor_scenes(
    include_kitchens=True,
    include_living_rooms=True,
    include_bedrooms=True,
    include_bathrooms=True
)
```

```
[
    "FloorPlan1",
    "FloorPlan2",
    {...},
    "FloorPlan201",
    {...},
    "FloorPlan301",
    {...},
    "FloorPlan430",
]
```

```
include_kitchens: bool = True
```

Includes the 30 kitchens (i.e., `FloorPlan[1:30]`) in the returned list when `True`.

include_living_rooms: bool = True

Includes the 30 living rooms (i.e., FloorPlan[201:230]) in the returned list when **True**.

include_bedrooms: bool = True

Includes the 30 bedrooms (i.e., FloorPlan[301:330]) in list when **True**

include_bathrooms: bool = True

Includes the 30 bathrooms (i.e., FloorPlan[401:430]) in list when **True**.

It is common to train agents on a subset of scenes, in order to validate and test how well they generalize to new scenes and environments. For each room type, it is standard practice to treat the first 20 scenes as training scenes, the next 5 scenes as validation scenes, and the last 5 scenes as testing scenes.