


Prompt 1



PROMPT:
Task ID: PYC085 Return ONLY valid Python code. Do not use
Markdown fences. Do not include prose,
explanations, examples, print statements, or tests. Your code
must contain this exact check-token line: #
CHECK_TOKEN: PYC085 Your code must contain this required symbol:
def diff_dicts Implement this task: write
function diff_dicts(old,new) returning added, removed, changed..
Start your answer with the check-token line,
then provide the Python implementation.

MODEL RESPONSE:
CHECK_TOKEN: PYC085 # Function to calculate the differences
between two dictionaries def diff_dicts(old,
new): # Check if the input dictionaries are not empty if
not old or not new: return "Both
dictionaries must have at least one key-value pair" # Create
empty dictionaries to store the added,
removed, and changed keys added = {} removed = {}
changed = {} # Iterate over the keys in the
first dictionary for key in old: # Check if the key
is present in the second dictionary if
key in new: # If the key is present, add it to the
added dictionary added[key] =
old[key] else: # If the key is not present,
add it to the removed dictionary
removed[key] = old[key] # If the key is present in both
dictionaries, check if its value has changed
elif old[key] != new[key]: # If the value has
changed, add it to the changed dictionary
changed[key] = new[key] # Return the differences return
added, removed, changed # Example usage
old_dict = {"key1": "value1", "key2": "value2", "key3": "value3"}
new_dict = {"key1": "value4", "key2":
"value5", "key3": "value6"} # Calculate the differences added,
removed, changed = diff_dicts(old_dict,
new_dict) print("Added keys:", added) print("Removed keys:",
removed) print("Changed keys:", changed) #
Output: {'key1': 'value4', 'key2': 'value5', 'key3': 'value6'}
`` In this implementation, we first check if
the input dictionaries are empty. If either of them is empty, we
return a message indicating that both
dictionaries must have at least one key-value pair. Next, we
create empty dictionaries to store the added,
removed, and changed keys. We iterate over the keys in the first
dictionary and check if each key is present
in the second dictionary. If the key is present, we add it to the
added dictionary with the corresponding
value from the first dictionary. If the key is not present, we
add it to the removed dictionary with the
corresponding value from the first dictionary. If the key is
present in both dictionaries, we check if