adapty | Docs

MIGRATION GUIDE

Migrate Adapty iOS SDK to v. 4.0

Migrate to Adapty iOS SDK v4.0 (beta) by replacing paywall APIs with flow APIs, compatible with both Flow Builder and Paywall Builder.

iOS SDK | v3 → v4 | Flow Builder + Paywall Builder

PLATFORM	SDK VERSION	DOCUMENT
iOS	v4.0 (beta)	Migration Guide

Adapty iOS SDK 4.0 (beta) introduces flows and renames the paywall APIs accordingly. The new APIs work with both the new Flow Builder and the existing Paywall Builder — no setup changes are required on the Adapty Dashboard side.

Quick reference

v3	v4
`Adapty.getPaywall(placementId:locale:)`	`Adapty.getFlow(placementId:)`
`AdaptyUI.getPaywallConfiguration(forPaywall:)`	`AdaptyUI.getFlowConfiguration(forFlow:locale:)`
`Adapty.getPaywallProducts(paywall:)`	`Adapty.getPaywallProducts(flow:)`
`AdaptyPaywallController`	`AdaptyFlowController`
`AdaptyPaywallControllerDelegate`	`AdaptyFlowControllerDelegate`
`AdaptyUI.paywallController(with:delegate:)`	`AdaptyUI.flowController(with:delegate:)`
`.paywall()` (SwiftUI modifier)	`.flow()`
`AdaptyPaywallView`	`AdaptyFlowView`

Removed APIs

- **`Adapty.getPaywallProductsWithoutDeterminingOffer(paywall:)`** — removed. All products now include offer information, so the separate eligibility pass is no longer needed.
- **`AdaptyPaywallProductWithoutDeterminingOffer`** — removed. Callbacks that previously passed this type (such as `didSelectProduct`) now pass `AdaptyPaywallProduct`.

Fetching paywalls

getPaywall + getPaywallConfiguration → getFlow + getFlowConfiguration

The returned types change from `AdaptyPaywall` / `AdaptyUI.PaywallConfiguration` to `AdaptyFlow` / `AdaptyUI.FlowConfiguration`. The `locale` parameter moves out of the fetch call

and onto `getFlowConfiguration`:

```diff
- let paywall = try await Adapty.getPaywall(placementId: "YOUR_PLACEMENT_ID", locale: "en")
- let paywallConfiguration = try await AdaptyUI.getPaywallConfiguration(forPaywall: paywall)
+ let flow = try await Adapty.getFlow(placementId: "YOUR_PLACEMENT_ID")
+ let flowConfiguration = try await AdaptyUI.getFlowConfiguration(forFlow: flow, locale: "en")
```

getPaywallProducts(paywall:) → getPaywallProducts(flow:)

`getPaywallProducts` now takes an `AdaptyFlow` returned by `Adapty.getFlow`:

```diff
- let products = try await Adapty.getPaywallProducts(paywall: paywall)
+ let products = try await Adapty.getPaywallProducts(flow: flow)
```

UIKit

AdaptyPaywallController → AdaptyFlowController

Rename the controller type and the factory method:

```diff
- let controller = try AdaptyUI.paywallController(
-     with: paywallConfiguration,
-     delegate: self
- )
+ let controller = try AdaptyUI.flowController(
+     with: flowConfiguration,
+     delegate: self
+ )
```

AdaptyPaywallControllerDelegate → AdaptyFlowControllerDelegate

Rename the protocol and update every method signature. Note that `didSelectProduct` now receives `AdaptyPaywallProduct` instead of the removed `AdaptyPaywallProductWithoutDeterminingOffer`.

```diff
- class YourClass: AdaptyPaywallControllerDelegate {
+ class YourClass: AdaptyFlowControllerDelegate {

-     func paywallControllerDidAppear(_ controller: AdaptyPaywallController) { }
```

```
+       func flowControllerDidAppear(_ controller: AdaptyFlowController) { }

-       func paywallControllerDidDisappear(_ controller: AdaptyPaywallController) { }
+       func flowControllerDidDisappear(_ controller: AdaptyFlowController) { }

-       func paywallController(_ controller: AdaptyPaywallController,
-                              didPerform action: AdaptyUI.Action) { }
+       func flowController(_ controller: AdaptyFlowController,
+                           didPerform action: AdaptyUI.Action) { }

-       func paywallController(_ controller: AdaptyPaywallController,
-                              didSelectProduct product:
  AdaptyPaywallProductWithoutDeterminingOffer) { }
+       func flowController(_ controller: AdaptyFlowController,
+                           didSelectProduct product: AdaptyPaywallProduct) { }

-       func paywallController(_ controller: AdaptyPaywallController,
-                              didStartPurchase product: AdaptyPaywallProduct) { }
+       func flowController(_ controller: AdaptyFlowController,
+                           didStartPurchase product: AdaptyPaywallProduct) { }

-       func paywallController(_ controller: AdaptyPaywallController,
-                              didFinishPurchase product: AdaptyPaywallProduct,
-                              purchaseResult: AdaptyPurchaseResult) { }
+       func flowController(_ controller: AdaptyFlowController,
+                           didFinishPurchase product: AdaptyPaywallProduct,
+                           purchaseResult: AdaptyPurchaseResult) { }

-       func paywallController(_ controller: AdaptyPaywallController,
-                              didFailPurchase product: AdaptyPaywallProduct,
-                              error: AdaptyError) { }
+       func flowController(_ controller: AdaptyFlowController,
+                           didFailPurchase product: AdaptyPaywallProduct,
+                           error: AdaptyError) { }

-       func paywallControllerDidStartRestore(_ controller: AdaptyPaywallController) { }
+       func flowControllerDidStartRestore(_ controller: AdaptyFlowController) { }

-       func paywallController(_ controller: AdaptyPaywallController,
-                              didFinishRestoreWith profile: AdaptyProfile) { }
+       func flowController(_ controller: AdaptyFlowController,
+                           didFinishRestoreWith profile: AdaptyProfile) { }

-       func paywallController(_ controller: AdaptyPaywallController,
-                              didFailRestoreWith error: AdaptyError) { }
+       func flowController(_ controller: AdaptyFlowController,
+                           didFailRestoreWith error: AdaptyError) { }

-       func paywallController(_ controller: AdaptyPaywallController,
-                              didFailRenderingWith error: AdaptyUIError) { }
+       func flowController(_ controller: AdaptyFlowController,
```

```diff
+                           didFailRenderingWith error: AdaptyUIError) { }

-       func paywallController(_ controller: AdaptyPaywallController,
-                              didFailLoadingProductsWith error: AdaptyError) -> Bool { }
+       func flowController(_ controller: AdaptyFlowController,
+                           didFailLoadingProductsWith error: AdaptyError) -> Bool { }

-       func paywallController(_ controller: AdaptyPaywallController,
-                              didPartiallyLoadProducts failedIds: [String]) { }
+       func flowController(_ controller: AdaptyFlowController,
+                           didPartiallyLoadProducts failedIds: [String]) { }

-       func paywallController(_ controller: AdaptyPaywallController,
-                              didFinishWebPaymentNavigation product: AdaptyPaywallProduct?,
-                              error: AdaptyError?) { }
+       func flowController(_ controller: AdaptyFlowController,
+                           didFinishWebPaymentNavigation product: AdaptyPaywallProduct?,
+                           error: AdaptyError?) { }
  }
```

SwiftUI

.paywall() modifier → .flow()

Rename the modifier and update the configuration parameter name:

DIFF

```diff
  @State var flowPresented = false // rename freely — the variable name is your choice

  var body: some View {
      Text("Hello, AdaptyUI!")
-         .paywall(
+         .flow(
              isPresented: $flowPresented,
-             paywallConfiguration: paywallConfiguration,
+             flowConfiguration: flowConfiguration,
              didFailPurchase: { product, error in /* handle the error */ },
              didFinishRestore: { profile in /* check access level and dismiss */ },
              didFailRestore: { error in /* handle the error */ },
              didFailRendering: { error in flowPresented = false }
          )
  }
```

AdaptyPaywallView → AdaptyFlowView

Rename the view, update the configuration parameter, and update any `didSelectProduct` closure — it now receives `AdaptyPaywallProduct` instead of the removed `AdaptyPaywallProductWithoutDeterminingOffer`:

```diff
- AdaptyPaywallView(
-     paywallConfiguration: paywallConfiguration,
-     didSelectProduct: { product: AdaptyPaywallProductWithoutDeterminingOffer in /* handle */ },
+ AdaptyFlowView(
+     flowConfiguration: flowConfiguration,
+     didSelectProduct: { product: AdaptyPaywallProduct in /* handle */ },
      didFailPurchase: { product, error in /* handle the error */ },
      didFinishRestore: { profile in /* check access level and dismiss */ },
      didFailRestore: { error in /* handle the error */ },
      didFailRendering: { error in /* handle the error */ }
  )
```

AdaptyUI custom assets

AdaptyUICustomVideoAsset

Two changes affect every existing call site:

- `.player` now takes `AVPlayer` instead of `AVQueuePlayer`.
- Every case gained a trailing `resolution: CGSize?` parameter. Pass `nil` to keep the current behavior, or pass the actual pixel size so the player can reserve layout space (aspect ratio = `width / height`) before the video loads.

```diff
- case file(url: URL, preview: AdaptyUICustomImageAsset?)
- case remote(url: URL, preview: AdaptyUICustomImageAsset?)
- case player(item: AVPlayerItem, player: AVQueuePlayer, preview: AdaptyUICustomImageAsset?)
+ case file(url: URL, preview: AdaptyUICustomImageAsset?, resolution: CGSize?)
+ case remote(url: URL, preview: AdaptyUICustomImageAsset?, resolution: CGSize?)
+ case player(item: AVPlayerItem, player: AVPlayer, preview: AdaptyUICustomImageAsset?, resolution: CGSize?)
```