

# Variables and Data Access

*Work Like Tomorrow.™*

**KOFAX**


# Variables - Data



- Data is stored in variables (process/server)
- Variables have a type e.g. String, date, complex (array) etc
- Must decide how much data is required in the process and how much should be held outside the process
- Guidelines
  - Primary keys/Lookup fields
  - Decision points
  - Work queue definition fields
  - Document Creation activity
  - Email activity
  - Document/Folder

# Loan Application Data

- Customer Id
- Customer Name
- Address
- Postcode
- Email
- Tel
- Occupation
- Loan Amount
- Application Date
- Creditscore
- Approved (true/false)



# Variables



- Process Initialisation Variables
  - Initialise job with data
- Input/Outputs
  - Assign variables to activities in the process
  - Inputs are read only data
  - Outputs are editable data
- Data Activity
  - Get, Update, Add, Delete data from SQL/Oracle database
  - Can also run views and stored procedures (including procedures with parameters)
  - Can return a single row (multiple fields) or multiple records (array – complex variable)

# What is a Variable?

- A variable is used to store data in Kofax TotalAgility
- A variable display name can have upper and lower case letters and spaces, e.g. Loan Amount
- The variable ID however must start with a letter and cannot contain spaces, e.g. LOAN\_AMOUNT
- The variable type describes the type of data that the variable will store, e.g. String, Date.

| <u>Name</u>      | <u>Type</u> | <u>Value</u>   | <u>ID</u>   |
|------------------|-------------|----------------|-------------|
| Customer Name    | String      | Robert De Nero | Name        |
| Customer Address | String      | Hollywood      | Address     |
| Loan Amount      | Currency    | 1000.00        | Loan_Amount |

# How are Variables Used?

- Data may be collected at the beginning of the process or during the process:
  - Process Initialization Variables
    - Data collected at the beginning of the process
    - For example, to process a loan application, customer details and the loan amount are required
  - Process Initialization Variables will also be displayed on a Create new job form if one is generated for a process. The form control type is determined by the Data Type

# How are Variables Used?

## Process Initialization Variables

| Variables                                    |                           |          |                                      |                |
|--|---------------------------|----------|--------------------------------------|----------------|
| New  | Initialization order      |          |                                      |                |
| Name   | ID                        | Type     | Value                                | Initialization |
| <a href="#">Approval Body</a>                | APPROVAL_BODY             | String   | Use the following link to appro...   |                |
| <a href="#">Approval Email Subject</a>       | APPROVAL_EMAIL_SUBJECT    | String   | A Loan Requires Approval             |                |
| <a href="#">Approval URL</a>                 | APPROVAL_URL              | String   | http://localhost/TotalAgility/for... |                |
| <a href="#">Approved</a>                     | APPROVED                  | Bool     | false                                |                |
| <a href="#">CASE_REFERENCE</a>               | SPP_CASE_REFERENCE        | System   | SPP_CASE_REFERENCE                   |                |
| <a href="#">Creditscore</a>                  | CREDITSCORE               | Short    | 0                                    |                |
| <a href="#">Customer Id</a>                  | CUSTOMER_ID               | Long     | 1                                    | ✓              |
| <a href="#">Email Body</a>                   | EMAIL_BODY                | String   | Your loan application has been ...   |                |
| <a href="#">Email From</a>                   | EMAIL_FROM                | String   | admin@kofax.com                      |                |
| <a href="#">Email Subject</a>                | EMAIL_SUBJECT             | String   | XYZ Bank Personal Loan Confir...     |                |
| <a href="#">Email To</a>                     | EMAIL_TO                  | String   | ssmyth@kofax.com                     |                |
| <a href="#">First Name</a>                   | FIRST_NAME                | String   | Robert                               | ✓              |
| <a href="#">ID</a>                           | SPP_ID                    | System   | SPP_ID                               |                |
| <a href="#">Last Name</a>                    | LAST_NAME                 | String   | De Niro                              | ✓              |
| <a href="#">Loan Amount</a>                  | LOAN_AMOUNT               | Currency | 5000                                 | ✓              |
| <a href="#">Loan Application Document Id</a> | LOAN_APPLICATION_DOCUMENT | String   |                                      | ✓              |

## Loan Application Create New Job Form

Loan ApplicationBuildCNJForm v1 Released

**LoanApplication**

Customer Id

First Name

Last Name

Loan Amount

Loan Application Document Id

Case Reference

Create Case

Cancel

# How are Variables Used? (cont.)

- Input Variables
  - Data that needs to be visible to an activity for it to be performed, e.g. to complete the 'Loan Approval' activity we could add Customer Name, Loan Amount and Credit Score variables as inputs to the activity
- Output Variables
  - Data that is output from a specific activity within the process, e.g. an Approved variable is set to TRUE
- Input/Output Variables will also be displayed on Activity forms if they are generated for a process
  - Inputs will appear as **read only** controls on an Activity form
  - Outputs will appear as **editable** controls on an Activity form



# How are Variables Used? (cont.)

## Loan Approval Activity in Process

**Activity - loan approval**

Name: Loan Approval

Type: Ordinary activity

**Configuration**

Input variables [Add](#)

- Creditscore (Process variable) ×
- Customer Id (Process variable) ×
- First Name (Process variable) ×
- Last Name (Process variable) ×
- Loan Amount (Process variable) ×
- Loan Application ... (Process variable)

Output variables [Add](#)

- Approved (Process variable) ×

Input/Output Variables

## Loan Approval Activity Form

Loan Application Loan Approval v5 Released

**Loan Approval** Due Date:

help text

**Information**

Customer Id

First Name

Last Name

Creditscore

Loan Amount

Requested

Loan Decision

Loan Application Document Id

Approved ☐

# What is a Variable?

- There are multiple types of variables:
  1. Process Variables
  2. Server Variables
  3. Case Variables
  4. SYSTEM Variables
  5. Document Variables
  6. Folder Variables
- Process and Server variables can be further broken down into:
  - Simple variables (1 value)
  - Complex variables (multiple values / types, e.g. an array)

# Process, Case, and Server Variables

## ■ Process Variables


- Process variables are local (private) to the process they are created for

## ■ Case Variables

- Case variables are specific to 'Case definition' processes
- Case fragments can read and update case definition variable


## ■ Server Variables

- Are global variables, i.e. visible to all business processes



Embedded processes can read and update the main process variables. Process and Server variables can be of *complex* or *dynamic* type.

# Create a Process Variable




# Process Variables



- A variable is a storage location for values that are retrieved at runtime
- Use Process Variables to store data for a specific process
- Process Variables hold values for items that change during the execution of a process

# Creating a Process Variable

- Open the process
- Click the **Variables** tab and click **New**



Case variables are created in the same way as process variables, except you create them within a case definition process

# Server Variables

- Server variables are global variables that can be accessed and modified by any process
- Once the value of a server variable is changed, this becomes the value of that variable in all jobs that utilize it (so it only has to be modified once)
- **Example**
  - Database connection string
  - Template path
  - Company name
  - VAT rate

# Creating a Server Variable

- From the **Main** menu navigate to **System data > Server variables** and click **New**

New server variable \*

\* indicates a required field

Category\* Applications x

Name\* Template Path

ID\* TEMPLATE\_PATH

Type String

Value C:\LoanCases\

Secure ☐

Cancel Save




Server variables are created in the same way as process/case variables, except you don't need to open a process.



# System Variables

- **SYSTEM** variables are inherent to TotalAgility and give you access to system data which you typically do not know at design time
  - For example, who created the job, the job ID, the job state, etc.
- **Examples**
  - AWF\_RES\_JOB\_CREATOR holds the User ID of the creator of a job
  - AWF\_JOBID holds the ID of the job



New variable \*

\* indicates a required field

Name\* RES\_JOB\_CREATOR

ID AWF\_RES\_JOB\_CREATOR

Type System

Value\* AWF\_RES\_JOB\_CREATOR

Cancel OK



System variables are simple non-editable process variables that can be reused whenever required. The Help for Kofax TotalAgility contains a list of the System variables.

# Document Variables



- A document variable is used to store a reference to a document in the TotalAgility database
- Use a Document Variable as a process initialization variable or as an activity input or output variable
- You can also use document fields directly as input or output parameters to an activity
- When you create a job on a process that uses a document variable, the runtime instance ID of the document is stored in the document variable

# Folder Variables

- A folder variable is used to store a reference to a folder in the TotalAgility database
- When you create a job on a process that uses a folder variable, the runtime instance ID of the folder is stored in the folder variable



For a scan enabled process, you can set the variable for process initialization only when it has the root folder as its value. However, for a normal process, the variable value can be a root folder or sub-folder


# Where to use Document or Folder Variables

- Use a document or folder variable in activities such as Ordinary, Email, Business Rule, .NET and in Decision activities
- Use fields or the System properties of a field from a document or folder variable:
  - Any place within a process or rule where a variable can be used
  - In an activity of any type in a process where a variable can be used



You must initialize a document or folder variable before using it in a process or activity; otherwise the job is suspended

# Data Access Activity



# Data Access Activity

- Activity that can be used to **Get/Add/Update/Delete** record(s) in an SQL/Oracle database
- Can also run **Views** and **Stored Procedures**
- Require a **Connection String** to a database
- Requires that the **Service Account** has appropriate permissions on the SQL/Oracle database

Data access configuration - Credit Check

Database connection\*  
CUSTOMER DATAB... (Server variable) x Refresh

Type\*  
Tables

Tables\*  
CreditScores

Record\*  
Get

Return\*  
Single row

Available columns

| Name       |
|------------|
| CustomerId |


Selected columns

| Name        | Output value to                  | Sort |
|-------------|----------------------------------|------|
| CreditScore | Creditscore (Process variable) x | none |

Search criteria

| Column     | Operator | Criteria    | Logic |
|------------|----------|-------------|-------|
| CustomerId | equals   | Customer Id | AND   |

# Work Types



# Work Types – Not covered in Essentials

- Work queues are a primary method of managing workflow in a business process
- They are personalised 'To Do' lists - used by operational staff to control, manage and execute their work tasks
- Work queues are usually rendered on a web page
- TotalAgility enables the Business Analyst/Developer to quickly and easily define 'customised' work queues known as Work Types



# Creating a Work Type

- From the **Main** menu navigate to **System data > Work types** and click **New**
- Enter a work type name
- Enter any fields you wish to see in the queue
- Enter any metadata (optional)

New work type \*

**General** \* indicates a required field

**Associations**

Name\*

Category\*


Metadata

Fields

| Position | Display name  | Type       | Value | ID            | Scope                    |
|----------|---------------|------------|-------|---------------|--------------------------|
| 1        | Customer Name | String     |       | CUSTOMER_NAME | <input type="checkbox"/> |
| 2        | Loan Amount   | Currency 0 |       | LOAN_AMOUNT   | <input type="checkbox"/> |

# Associating a Work Type with a Process

- Once you have created a Work Type you can then associate the Work Type with a specific process. This creates process variables for each field found in the Work Type
- Open the process
- In the **Properties** panel select the **Work type** from the dropdown list



The screenshot shows a configuration window for a process named 'Loan Application'. The window has a sidebar with icons for information, description, type, category, support variants, priority, and work type. The main area contains fields for each of these properties. The 'Work type' field at the bottom is highlighted with a blue border and shows a dropdown menu with 'Loans' selected and a close button (x).

| Property         | Value                    |
|------------------|--------------------------|
| Name             | Loan Application         |
| Description      |                          |
| Type             | Case definition          |
| Category         | Applications             |
| Support variants | <input type="checkbox"/> |
| Priority         | 1                        |
| Work type        | Loans x                  |

# What if I Change the Work Type?

- If you change a Work Type that has a process associated with it, the next time you open that process the Work Type definition variables are refreshed (close processes before altering the work queue definition)
- A message box is displayed to inform you of this (a similar message box is displayed when you modify the Work Type)

# Why Use Work Types?

- Benefits and Considerations:

- The ability to define the required fields within a work queue at design time reduces overall development time, as the designer can now more easily render the work queue on a web page or form
- Allows you to define up to 30 user definable fields in addition to the 12 standard work queue fields
- Process variables (existing or new) are used for these user defined fields
- Field data may come from within Kofax TotalAgility or from calls to 3rd party / internal applications
- Work Types are stored at the server level and can be associated with any process. Types can be copied, modified or deleted