

## TECHNICAL TRAINING LAB INSTRUCTIONS

In this lab you will learn how to create and use variables. Variables are containers for data. Data can be passed into a job when it is first created (Initialization data), retrieved from an external source while the job is running, and can be assigned as inputs (read only), and outputs (updateable), to an activity. As an example, your process may require customer type data e.g. name, address, etc. if you wish to generate a letter and send it to the customer as part of the process.

## Lab 11-1

### Variables

#### *Create Process Variables*

In this part, you will create process variables in the loan application process.

Process variables are used to store data or to reference documents/folders, for example when a loan is applied for, the **Loan Amount** variable holds the amount of the loan being applied for, e.g. 5000. When a loan decision is required the **Approved** variable is set to True or False.

When a variable is assigned as a **Process Initialization** variable its value is provided at the beginning of the process.

1. With the **Loan Application** case definition already open, from the **Ribbon**, select **Variables**.
2. Add the following new process variables and default **Values** as shown below.

File Design <b>Variables</b> Fragments States Milestones Roles Notes Process events Document set Debug Close and unlock Release Save							
Variables							
New	Initialization order						
Name	ID	Type		Value		Initialization	
<a href="#">Approved</a>	APPROVED	Bool		false			...
<a href="#">Credit Score</a>	CREDIT_SCORE	Short		0			...
<a href="#">Customer Id</a>	CUSTOMER_ID	Long		1		✓	...
<a href="#">First Name</a>	FIRST_NAME	String		Robert		✓	...
<a href="#">Last Name</a>	LAST_NAME	String		De Niro		✓	...
<a href="#">Loan Amount</a>	LOAN_AMOUNT	Currency		5000		✓	...
<a href="#">Loan Application Document Id</a>	LOAN_APPLICATION_DOCUMENT_ID	String				✓	...

**Notes:** (i) Loan Amount, Customer Id, First Name, Last Name, and Loan Application Document Id have been set as process initialization variables i.e. the process expects to be initialized with this data.

(ii) The variable name and Id are different for Credit Score, Loan Amount, First Name, Last Name, Loan Application Document Id, and Customer Id (underscores between words in the ID field).

3. With the **Variables** list page still open, click **Initialization order** and set the Initialization order to **Customer Id, First Name, Last Name, Loan Amount, and Loan Application Document Id**.


**Note:** TotalAgility uses the initialization order when you build a Create new job form later in the course. The fields will be created on the form in the order you specify.

**KOFAX** | Education  
**TECHNICAL TRAINING LAB INSTRUCTIONS**

Initialization variables \*

		↑ ↓
Name	ID	
Customer Id	CUSTOMER_ID	
First Name	FIRST_NAME	
Last Name	LAST_NAME	
Loan Amount	LOAN_AMOUNT	
Loan Application Document Id	LOAN_APPLICATION_DOCUMENT_ID	

- Click **OK** to return to the **Variables** list page.
- From the **Ribbon**, select the **Design** tab.




**Note:** Once you create a process variable, you cannot modify its ID or type. You must delete the process variable and re-create it.

#### *Add Input and Output Variables to Activities*

In this part, you will add variables to activities in the **Loan Application** process. For the **Loan Approval** activity an approver will need to know the customer's details and credit score (inputs), before they can approve or reject the loan (outputs).

Also notice the use of the **Credit Score** variable, a variable specific to this activity, which cannot be provided by the loan applicant when the loan application is first applied for. We will retrieve the customer's credit score from a **Customer** database later on in the labs.

- Select the **Loan Approval** activity.
- From the **Properties** panel, from the **Input variables** area, click **Add**.



- Click **Add all** to add all the variables to the **Selected items** list (you can also click each variable individually to add to the Selected items list).

## TECHNICAL TRAINING LAB INSTRUCTIONS

Add input variables

Process variable

Filter

Add all

Server variable

Showing All types

Approved	Bool
Credit Score	Short
Customer Id	Long
First Name	String
Last Name	String
Loan Amount	Currency
Loan Application Document Id	String

Selected items

Remove all

Approved (Process variable) ×

Credit Score (Process variable) ×

Customer Id (Process variable) ×

First Name (Process variable) ×

Last Name (Process variable) ×

Loan Amount (Process variable) ×

Loan Application ... (Process variable) ×

**Note:** The Loan Application Document Id will be used in a later lab to display a customer's Loan Application document in a Web Capture Control on the Loan Approval form.

9. **Delete** the **Approved** variable from the **Selected items** area.
10. Click **Done**.
11. From the **Properties** panel, from the **Output variables** area, click **Add**, click **Approved**, and click **Done**.

Output variables

Add

Approved (Process variable) ×


12. **Save** the process.

### Test a Variable Value in a Decision

In this part, you will test the value of a variable in a Decision.


13. Select the **Approved** decision activity.
14. In the **Condition text** rule editor, delete the word **True**. Right click and from the **Process variable** list select **Approved**.

## TECHNICAL TRAINING LAB INSTRUCTIONS



**Notes:** (i) [Approved] and [Approved]=True are equivalent.

(ii) You can also use the following logical operators/keywords: <, >, =, <>, >=, <=, ! (not), And, Or etc.



15. **Save** the process (leave the process open for the next part).

## TECHNICAL TRAINING LAB INSTRUCTIONS

In this lab, you will add a data access activity to the Loan Application Case Definition. In this example we will use the data access activity to retrieve the applicant's credit score from an external database.

## Lab 11-2

### Data Access Activity


#### *Add a Data Access Activity*

In this part, you will retrieve a credit score from an external SQL database called Customer. To connect to an external database, a connecting string is required. A server variable holding the connection string already exists on your environment. Note that the KTAService account will execute the data activity. The service account must be granted read access to the external database in SQL Server Management Studio.

The connection string is: `Server=(local);Trusted_Connection=Yes;Database=Customer;`


**Note:** This server variable can be found by going to the **Main** menu and clicking **System data > Server variables** and filtering by the **XYZ Bank** category.

1. Skip to step 7 if you are using a Kofax training machine:
2. From the Taskbar open **SQL Server Management Studio** and click **Connect**.
3. Expand the **Security** folder and expand the **Logins** folder.
4. **Double click** the **KTAService** account and select the **User Mapping** page.
5. Select the **Customer** database and grant the **db\_datareader** role to the service account.




## TECHNICAL TRAINING LAB INSTRUCTIONS

6. Click **OK** and **close** SQL Server Management Studio.
7. Select the **Credit Check** activity in the **Loan Application** process.
8. From the **Type** dropdown, select **Data access**.
9. Click **Configure**.
10. Click the **Database connection** dropdown, select the **Server variable** tab, and change the **Category** to **XYZ Bank**. Select the **CUSTOMER DATABASE** server variable.  
**Note:** You can learn about server variable encryption and whitelisting in the Lab Notes.



11. From the **Type** dropdown, select **Tables**, for **Tables** select **CreditScores**, for **Record** select **Get** and for **Return** select **Single Row**.



12. In the **Available columns** list, check the **CreditScore** checkbox, and click the **Add >>** button to move the column to the **Selected columns** list.

## TECHNICAL TRAINING LAB INSTRUCTIONS

13. From the **Output value to** dropdown, select **Credit Score** (process variable).

14. In **Search criteria** click **Add** (+ icon) and configure the following:

15. Click **Add** to add the criteria.

16. Click **Test** (top right).

17. Enter **1** as the **Customer Id** and click **Test**. The Results for the test should return **10**.

**Hint:** To verify results, you can open Microsoft SQL Server Management Studio (from Start menu), login and open the **CreditScores** table in the **Customer** database.

18. Click **Close** on the Test window and **OK** to close the data access configuration. The Query is now listed in the **Query** field in the **Properties** panel.

## TECHNICAL TRAINING LAB INSTRUCTIONS

> Activity - credit check

Name: Credit Check

Type: Data access


Configuration

[Configure](#)

Query

```
SELECT TOP 1 [CreditScore] FROM
[CreditScores] WHERE (( [CustomerId] =
[@Customer ID] ))
```

19. Release the **Loan Application** process. The process looks like this:



### Important Note

You will test the credit check activity at run-time in a later lab. In the next lab, to save time, you will delete the process you have created and import an identical process which has some extra variables and some additional configuration. You can learn how to export a process as part of package in the Export Solution as a Package self-learning lab.



## Lab 11-3


### Import New Version of Loan Application

#### *Import Process*

In this part, you will delete the existing **Loan Application** process. You will then import a new version of the **Loan Application** process that has pre-configured activity notification in the **Loan Approval** activity as well as pre-defined variables for sending emails.

#### *Delete Loan Application Process*

1. **Close and unlock** the **Loan Application** case process.
2. From the **Main** menu navigate to **Workflow > Case definitions**.
3. Locate the **Loan Application** case definition in the list page.
4. Click the **:** and from the context menu, select **Delete**.



5. Click **Yes** to delete all versions of the process and any associated fragments.  
**Note:** You cannot delete a process if there are live jobs in the system based on that process. Run job clear down first to remove live jobs before deleting the process.


#### *Import New Version of Loan Application and Configure*

In this part, you will import a new version of the Loan Application process. Because the version is assigned to the Default category you will reassign the process to the Applications category you created in an earlier lab.

6. From the **Main** menu navigate to **Import...**
7. **Browse** to and open **C:\KTAEssentials\LabFiles\Processes\Loan Application V2.zip**
8. Click **Import**.
9. From the **Main** menu navigate to **Workflow > Case definitions** and from the **Category** dropdown, select **Default Category**.
10. Open the **Loan Application** process.

## TECHNICAL TRAINING LAB INSTRUCTIONS

11. In the **Properties** panel, from the **Category** dropdown, select **Applications**.



The screenshot shows a software interface for configuring a 'Loan Application'. On the left is a vertical sidebar with icons for information, description, type, and category. The main area on the right contains four fields: 'Name' (text input with 'Loan Application'), 'Description' (text area), 'Type' (dropdown menu with 'Case definition'), and 'Category' (dropdown menu with 'Applications'). A red rectangular box highlights the 'Category' dropdown field.

12. **Release** and **Close and unlock** the case definition.

## **Lab Notes**

### *Sever Variables*

1. It is possible to encrypt Server String variable types by setting the **Secure** property of the server variable to checked.
2. You can whitelist connection strings. From the **Main** menu navigate to **System > System settings**, and from the **System** card, click **Whitelist**.

### *Data Access Activity*

3. The **Data Access** activity also supports aggregate functions (Max, Min, and Count) and calling Views and Stored Procedures.
4. You can also connect to Oracle databases using an Oracle connection string. KTA supports the **OLEDDB** driver. An example connection string is shown below:  
Provider=OraOLEDB.Oracle;Data Source=SecureOracle;User  
Id=KTA\_USER;Password=W0rkstation;

**Revision Questions**

1. What is a process variable used for?  
\_\_\_\_\_  
\_\_\_\_\_
2. What is a process initialization variable?  
\_\_\_\_\_
3. A process variable can only be used within the process that it has been created in?  
\_\_\_\_\_
4. A server variable can be accessed by?  
\_\_\_\_\_
5. What is an Input variable?  
\_\_\_\_\_  
\_\_\_\_\_
6. What is an Output variable?  
\_\_\_\_\_  
\_\_\_\_\_
7. You can change the ID of a variable after it has been created?  
\_\_\_\_\_
8. The initialization order of variables in a process determines the order of fields that are displayed on a create new job form?  
\_\_\_\_\_
9. Which account must be given database access when using the data access activity to interact with a non TotalAgility database?  
\_\_\_\_\_
10. What type of variable would be required if you are returning multiple rows from a data access query?  
\_\_\_\_\_
11. TotalAgility allows you to run queries against which object types in SQL Server?  
\_\_\_\_\_
12. Can you add multiple conditions to a query?  
\_\_\_\_\_
13. To connect to an external database, you will need to define a?  
\_\_\_\_\_