Status	Finished
Started	Tuesday, 29 September 2026, 3:22 PM
Completed	Tuesday, 29 September 2026, 3:26 PM
Duration	4 mins 2 secs
Grade	**14.00** out of 15.00 (**93.33**%)

Question **1**

Correct

Mark 1.00 out of 1.00

To obtain the number of entries in dictionary which command is used?

a. d.size()

b. size(d)

c. d.len()

d. len(d) ✓

Question **2**

Correct

Mark 1.00 out of 1.00

What will be the Output of the following code?
dl={1:10, 2:20, 3:30, 4:40}
d2={5:50, 6:60, 7:70}
dl.update (d2)
print (dl)

a. [1: 10, 2: 20, 3: 30, 4: 40, 5: 50, 6: 60, 7: 70]

b. {1: 10, 2: 20, 3: 30, 4: 40, 5: 50, 6: 60, 7: 70} ✓

c. [(1, 10), (2, 20), (3, 30), (4, 40), (5, 50)]

d. {1:10, 2: 20, 4: 40, 5: 50, 6: 60, 7: 70}

Question **3**

Incorrect

Mark 0.00 out of 1.00

Only values (without keys) can be printed in dictionary?

a. False ✗

b. True

Question **4**

Correct

Mark 1.00 out of 1.00

Which of the following is feature of Dictionary?

- a. All of the mentioned ✓
- b. Keys are unique within a dictionary.
- c. Keys must be of an immutable data type.
- d. Dictionary is mutable.

Question **5**

Correct

Mark 1.00 out of 1.00

Write a statement to retrieve the value corresponding to the key 7 in dictionary 'D1'.

- a. D1.get(7) ✓
- b. D1.values(7)
- c. D1.disp(7)
- d. D1.pop(7)

Question **6**

Correct

Mark 1.00 out of 1.00

Write the output of the following codes.
>>>dl={1:10,2:20,3:30,4:40, 5:50}
>>>dl.items ()

- a. [1, 2, 3, 4, 5]
- b. [(1, 10), (2, 20), (3, 30), (4, 40), (5, 50)] ✓
- c. [10, 20, 30, 40, 50]
- d. Error

Question **7**

Correct

Mark 1.00 out of 1.00

The key-value pair in dictionary is called ____.

- a. paired value
- b. item ✓
- c. pair item
- d. value

Question **8**

Correct

Mark 1.00 out of 1.00

What is the value of counter after the code is run?

```
phrase = "Cheese!!!! Cheese!!!! Python is a programming Language.Python!!"
counter = 0
letters = {}
for word in phrase.split():
    for letter in word:
        letter = letter.lower()
        if letter not in letters.keys():
            letters[letter] = 0
        letters[letter] += 1
for key in letters.keys():
    if letters[key] > 2:
        counter += 1
print(counter)
```

Answer: 9 ✓

Question **9**

Correct

Mark 1.00 out of 1.00

Dictionaries are flexible in nature, means elements can be added or removed from it.

- a. False
- b. True ✓

Question **10**

Correct

Mark 1.00 out of 1.00

Choose the correct statement, in reference to the following code: D1.update(D2) #D1 and D2 are dictionaries

- a. It will merge all the elements of dictionary 'D2' in dictionary 'D1'. ✓
- b. None of the mentioned
- c. It will merge all the elements of dictionary 'D1' in dictionary 'D2'.
- d. It will create a new dictionary.

Question **11**

Correct

Mark 1.00 out of 1.00

Dictionary is a ____ data type.

- a. Mapping ✓
- b. None of the mentioned
- c. Ordered
- d. Sequence

Question **12**

Correct

Mark 1.00 out of 1.00

A = {"A" : "Apple", "B" : "Ball", "C" : "Cat"} Which of the following statement will return : dict_items([('A', 'Apple'), ('B', 'Ball'), ('C', 'Cat')])

- a. print(A.values)
- b. print(A.Items) ✓
- c. print(A.get)
- d. print(A.keys)

Question **13**

Correct

Mark 1.00 out of 1.00

Which function helps to merge dictionary 'D1' and 'D2'?

- a. append
- b. merge
- c. update ✓
- d. get

Question **14**

Correct

Mark 1.00 out of 1.00

What does the following code print?

```
names = {'Janice': 5, 'Emily': 3, 'John': 7, 'Eleanor': 2}
list_o_names = []
names['Emily'] += 10
names['Erik'] = 22

for name in names:
    if names[name] > 5:
        list_o_names.append(name)
print(list_o_names)
```

a. ['Janice', 'Emily', 'John']

b. ['Emily', 'John', 'Erik'] ✓

c. ['Janice', 'Emily', 'John', 'Eleanor']

d. ['Janice', 'John', 'Erik']

Question **15**

Correct

Mark 1.00 out of 1.00

Following statement return values in the form of: D1.keys() # D1 is a dictionary

a. string

b. list ✓

c. tuple

d. dictionary