

OUTDOOR EQUIPMENT CABINET WITH COOLING



DESCRIPTION

DATACOM outdoor cabinet which can protect customer's equipments from damage and extreme weather conditions, vandalism, dust, rain, snow and dripping water. The cabinet is an ideal solution for physical connections of outdoor telecommunication equipment, transmission equipment, power equipment, monitoring equipment, lithium batteries and other supporting equipment. Both active telecom equipment and passive telecom equipment can be accommodated inside the cabinet. Cabinets are available with integrated thermal management using air conditioner to control internal temperatures to protect sensitive equipment.

DATACOM offers IP55/IP66 rated floor standing equipment Cabinets. Cabinet sizes are Customizable ranging from 15U internal space to 47U special height sizes. External size is 650x650mm with a base of 200mm. The cabinet is made with Galvanized steel with 20mm thermal insulation. The cabinet has a 200mm base + side panel, a hinged door with a lock. The rear door is fitted with air conditioning.

DATACOM outdoor cabinets are made of Galvanized steel thickness of 1.5mm- 2.0mm single wall /Double wall Construction. Cabinet is equipped with 2 sets of 19" profiles for equipment mounting.

Air condition units can be configured depends on the size of cabinet and heat load requirement, cooling capacity range from 300Watts to 3000Watts. All Cabinets are constructed of Strong anti-theft ability, embedded door, inner hinge three-point lock, supporting additional pad lock.

APPLICATION

- Outdoor cabinet is widely used in telecom operators' mobile Telecommunications sites.
- Outdoor Small Shelters.
- Railway Electrical Control Cabinets.
- Electronic Police.
- Communication Base Stations.
- Outdoor Air Detection Stations.
- Solar Control Cabinets, etc

FEATURES

- High protection grade: IP55, IP65, IP67
- Strong anti-theft ability, embedded door, inner hinge three-point lock, supporting additional pad lock.
- Cooling system is installed on cabinet, convenient for maintenance, cleaning and replacement.
- Comprehensive protection: door sensor, smoke sensor, water sensor, temperature and humidity sensor, etc.
- Support remote management, improve security and minimize customer's operation cost.
- Compact structure and easy maintenance AC Unit
- CE Certified
- Surface treatment outdoor powder painting to anti-corrosion
- Support Modbus RS485 communication

OUTDOOR EQUIPMENT CABINET WITH COOLING

CONSTRUCTION	
Protection Grade	IP54,IP55,IP65,IP67,IP68
Depth	600mm - 800mm
Height	15U - 47U
Cabinet Configuration	Cabinet body + cabinet door + base + top cover + rack + cabinet lock Cabinet type: 1 unit, 1 cabin, front door
Material	Steel plate + 20mm thick insulation layer
Thermal insulation performance	Thermal conductivity <0.472W/(m2.k)
Equipment shelf	19 inches, 3 pairs rack
Cabinet base	200mm high, 2.0mm thick
Line entry method	Bottom in and bottom out $\Phi 50 \times 8$
Anti-theft design	Built-in door, built-in hinge, 3-point anti-theft lock
Color Appearance	RAL7035, professional outdoor powder coating
Accessories	LED light*1, open the door light on, close the door light off, AC fan*1 with automatic opening and closing function according to the temperature, grounding copper

AC-SPECIFICATION	
Cooling capacity	300W - 3000W
Energy efficiency ratio	2.2
Input voltage	AC220V
Temperature control method	Intelligent temperature control, which can be automatically adjusted according to the temperature in the cabin
Protection level	IP55
Communication method	RS485
System certification	ISO9001, ISO14001, ISO45001
Product certification	3C
Weight range	15Kg - 100Kg

DC FAN - SPECIFICATION	
Operating Voltage & Rated current	DC 36~54V 0.64A (Max:1.0A)
Power consumption	30.72W (Max:48W)
Speed	5000 $\pm$ 10%RPM
Airflow @ Zero Static	242.2CFM
Noise Level	65.5dB-A(Max:68.7dB-A)
Life expectancy	70000 hrs at
Operating temperature range	-40°C ~ 60°C

OUTDOOR EQUIPMENT CABINET WITH COOLING

CABINET PART NUMBER CONFIGURATOR

CONSTANT			VARIABLES													
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	15.1	16
			IP Rating	Mount option		Height (U)	Width (mm)		Depth (mm)	Material	Skin Type	COO		Cooling Type	AC Power *Only for AC Cabinet	Colour
DC	"_"	O	4 = IP54	F=Fres standing	"_"	12U to 47U	600=60	"X"	550=55	G=GI	SW=Single Wall	U=U.A.E	"_"	A = AC	03 = 300W	B=RAL9005 (BLACK)
			5 = IP55	W=Wall Mount			650=65		600=60	S=SS	DW=Dual Wall	C=China		F = FAN	05 = 500W	G=RAL7035 (GREY)
			6 = IP65	P=Pole Mount			700=70		650=65			T=Turkey		NF=No Fan	08 = 800W	
			7 = IP67				750=75		700=70						10 = 1000W	
			8 = IP66				800=80		750=75						16 = 1600W	
							850=85		800=80							

** Examples

Description	Part No.
Datcom Outdoor Cabinet IP55 27U 700x700 Galvanized Steel Body with Intelligent Temperature Control,800W AC Powered Cooling-RAL7035	DC-O5F-27U70X70GSWU-A08G
Datcom Outdoor Cabinet IP55 24U 800x800 Galvanized Steel Body with 4 Fans,Canopy, Plinth,Led Light,Castors and Single Skin Design-RAL7035	DC-O5F-24U80X80GSWU-FG
Datcom Outdoor Cabinet IP55 27U 600x600 Galvanized Steel Body with Intelligent Temperature Control,500W AC Powered Cooling-RAL7035	DC-O5F-27U60X60GSWU-A05G
Datcom Outdoor Cabinet IP55 27U 600x800 Galvanized Steel Body with Intelligent Temperature Control,800W AC Powered Cooling-RAL7035	DC-O5F-27U60X80GSWU-A08G
Datcom Outdoor Cabinet IP55 15U 650x650 Galvanized Steel Body with Intelligent Temperature Control,500W AC Powered Cooling-RAL7035	DC-O5F-15U65X65GSWU-A05G
Datcom Outdoor Cabinet IP55 12U 600x450 Galvanized Steel Body with Intelligent Temperature Control,300W AC Powered Cooling-RAL7035	DC-O5F-12U60X45GSWU-A03G