

MODULAR PLUGS



STANDARDS COMPLIANCE

- ANSI/TIA - 568-C.2
- TIA-968-A
- CE, FCC, UL, RoHS

FEATURES

- Meet the requirement in the cat6A T568C.2
- Featuring gold plated contacts for the best possible connection
- Conductor: Solid and stranded cable.
- Available for RoHS parts.
- Exclusive stagger conductors guide design reduces near end cross talk
- Can make your network function to its maximum potential.
- Number of Positions 8P8C.

SPECIFICATION

Contact Base Material	Phosphor Bronze
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Thickness	3-50"
Storage Temperature	-40°C~+70°C
Dielectric Withstanding Voltage	AC 500V Per Minute
Contact Resistance	20mΩ Max.(Initial)
Operating Temperature	-20°C~+60°C
Housing Color	Thermoplastic(UL 94V-0) or Customized
Housing Material	PC or ABS

ORDERING INFORMATION

Description
Datacom Cat6 RJ45 8p8c, Modular Plugs & Transparent Boot
Datacom Cat6A Shielded, 8-Position Modular Plug

Part No.
DC-MPC6-8P8CU
DC-MPC6A-8P8CU-SH