

RACK MOUNT UHR1 SERIES UPS

DATAKOM UHRC series, range from 1kVA to 10kVA, is double conversion online rack UPS with fully digital control technology. This new generation of UPS is compatible with lithium batteries, and charging current can be increased up to 12A. With its compact design of high density (Output PF =1) in 2U height, UHRC series makes it ideal choice for computers, telecommunication equipment and other sensitive device.

	MODEL		DC-UHR1101CS/CL*	DC-UHR1102CS/CL*	DC-UHR1102CS/CL*
System Capacity	Phase	Single Phase in, Single Phase out (all models)			
Input	Input Voltage Range				
	Input Power Factor	176VAC~276VAC for 100% load; 276VAC~300VAC for 50% load			
	Input Frequency	0.99 (all models)			
	Input Frequency Range	50/60 Hz			
	Frequency Adaptable	40Hz~70Hz (all models)			
Output	Output Voltage	200/208/220/230/240VAC (all models)			
	Voltage Regulation	±1% (all models)			
	Rate Frequency	50/60Hz (all models)			
	Frequency Range	±0.1% (all models)			
	Output PF	1 (0.9 for 200VAC/208VAC) (all models)			
	Crest Factor	3:1 (all models)			
	Overload Capability				
	Inverter	102%~110% for 30mins; 110%~125% for 10mins; 125%~150% for 30s (all models)			
	Battery	102%~110% for 1min; 110%~125% for 10s; 125%~150% for 5s (all models)			
	Bypass	<130% long term operation; <150% for 10mins; <180% for 5s (all models)			
Battery	DC Voltage	36V/48Vdc	36Vdc	72Vdc	72Vdc/96V
	Number/Type	External	12V, 7Ah*3	12V, 7Ah*6	12V, 9Ah*6
	Charging Voltage	Settable (all models)			
	Max Charging Current	1-12A	1A	1A	1A
	Battery Cold Start	Standard (all models)			
System	Normal Mode	94.5%@100% load (all models)			
	Efficiency- ECO	98%	95.5%@100% load		
	Battery Mode	89.5%@100% load	91.5%@100% load		
	Noise (1m away)	<43dB@60%load	<50dB@60%load		
	Display	LED+LCD (all models)			
	Interface	RS232, input socket (IEC C14 for 1K, C20 for 2-3K) output socket (4 National standard sockets) (all models)			
	Optional	RS485, USB SNMP Card, EPO External Battery Temperature, RJ45 Surge Protection, Dust net (all models)			
**Last two letters of the PN (CS/CL) denotes battery internal Or external. CS-Internal and CL- external					



Applications

- IDC (Internet Data Center)
- Network, servers and workstations
- Servers and workstations
- Control system
- Communication system
- office ,PC etc.

Feature

- High Efficiency: Reaches up to 95.5% efficiency in Normal Mode and 97% in ECO Mode.
- Unity Power Factor: Output PF of 1 ensures maximum power delivery for sensitive devices.
- Flexible Charging: Includes a 1-12A adjustable charger making it a perfect choice for PCs and devices requiring longer backup times
- Advanced Support: Fully compatible with Lithium battery setups.
- Full Protection: Comprehensive safeguards against over-voltage and short-circuits.
- Smart Monitoring: Features an LCD/LED display and auto fan speed adjustment based on load

