

DATACOM UHT SERIES 1-2KVA TOWER ONLINE UPS



DESCRIPTION

The DATACOM UHT Series represents a new generation of online double-conversion UPS systems. Featuring fully digital control technology, this series offers ultra-high input and output power factors with a significant efficiency increase of 5% over previous generations.

CORE FEATURES

- **High Efficiency:** Reaches up to 95.5% efficiency in Normal Mode and 97% in ECO Mode.
- **Unity Power Factor:** Output PF of 1 ensures maximum power delivery for sensitive devices.
- **Flexible Charging:** Includes a 1-12A adjustable charger, making it a perfect choice for PCs and devices requiring longer backup times.
- **Advanced Support:** Fully compatible with Lithium battery setups.
- **Full Protection:** Comprehensive safeguards against over-voltage and short-circuits
- **Smart Monitoring:** Features an LCD/LED display and auto fan speed adjustment based on load

TECHNICAL SPECIFICATIONS

Specification	Details
System Capacity	1kVA / 2kVA / 3kVA
Input Voltage Range	110VAC - 300VAC
Output Voltage	200/208/220/230/240VAC (Settable)
Voltage Regulation	±1%
Transfer Time	0ms (Online Mode)
Battery Voltage	36VDC (1k), 72VDC (2k), 96VDC (3k)
Communication	RS232 (Standard); Optional: RS485, USB, SNMP,EPO.

DATACOM UHT SERIES 1-2KVA TOWER ONLINE UPS

SPECIFICATION

Category	Parameter	DC-UHT1101CL	DC-UHT1101CS	DC-UHT1102CL	DC-UHT1102CS
System	Capacity	1kVA	1kVA	2kVA	2kVA
	Phase	1 Phase In / 1 Phase Out			
Input	Voltage Range	110–300VAC			
	Frequency Range	40–70Hz			
	Power Factor	≥0.99			
Output	Rated Voltage	200/208/220/230/240VAC			
	Output PF	1.0			
	Voltage Regulation	±1%			
	THD	≤2% linear / ≤5% non-linear			
	Frequency	50/60Hz			
Battery	DC Voltage	36VDC	36VDC	72VDC	72VDC
	Battery Type	External 12V 7Ah ×3		Extn. 12V 7Ah ×6	
	Charging Current	1–12A	1A	1–12A	1A
	Cold Start	Supported			
Efficiency	Normal Mode @100% Load	89.5%	94.5%	91.5%	95.5%
	ECO Mode	97%			
Physical	Dimensions (W×D×H mm)	144×354×224	144×354×224	144×410×223	190×405×330
	Net Weight (kg)	4.3	10.3	5.8	21.1
Environment	Noise <60% Load	<50dB	<43dB	<50dB	<47dB
	Noise >60% Load	<55dB	<47dB	<55dB	<55dB
Interface	Communication Ports	RS232, RS485, USB, SNMP, Dry Contact, EPO.			