

MODULAR RACK MOUNTABLE PLC SPLITTER



DESCRIPTION

Datacom provides a series of 2XN PLC Splitter Cassette suitable to fix in modular Rack mount splitter Panel. Modular panel is 1U height made up of steel and has 4 slots for accepting Splitter cassettes. Splitter capacity can be tailored by filling cassettes according to the application.

APPLICATION

- FTTX Applications
- Passive Optical Network
- CATV Links
- Test equipment

STANDARDS COMPLIANCE

- Telcordia GR-1221 and GR-1209
- TIA-568.3-D
- TIA-604-3, FOCIS-3
- RoHS

FEATURES

- Low Insertion Loss
- Low Polarization Dependent Loss
- The enclosure can serve as a transition from backbone cabling to distribution switching in telecommunication rooms or an interconnect to active equipment in server cabinets or switch racks or can be specified for interconnect use in a main distribution area or horizontal distribution area.

MODULAR RACK MOUNTABLE PLC SPLITTER

MECHANICAL CHARACTERISTICS

PERFORMANCE SPECIFICATIONS	2 x 02	2 x 08	2 x 16
Operating Wavelength (nm)	1260~1650	1260~1650	1260~1650
Fiber Type	G657A2 /G652D	G657A2 /G652D	G657A2 /G652D
Connector/Adaptor Type	SC/APC , LC/APC	SC/APC , LC/APC	SC/APC , LC/APC
Insertion Loss (dB) (P/S Grade)	3.9/4/2	10.5/11	14.4/14.6
Loss Uniformity (dB)	≤0.6	≤1.2	≤1.5
PDL(dB)	≤0.2	≤0.2	≤1.5
Return Loss (dB)	≥55	≥55	≥55
Directivity (dB) Min	55	55	55
Wavelength Dependent Loss (dB)	≤0.3	≤0.5	≤0.5
Maximum Power Handling (mW)	500	500	500

ENVIRONMENTAL CONDITIONS

Operating Temperature	-40~80
Storage Temperature	-40~85

ORDERING INFORMATION

Description

Datacom 1U 19" Unloaded Panel for Splitter Module Cassettes

Datacom PLC Splitter Module Cassette

Part No.

DC-PPU-19-FMC

DC-FMC-2'NN' 'XX'7

** NN - Number of Ports (02,08,16).

XX - Connector/Adaptor Type(SA=SC/APC,LA=LC/APC).