

HORIZONTAL POWER DISTRIBUTION UNIT



DESCRIPTION

Datacom PDUs are used for distribution of power to equipment within a cabinet or rack. Horizontal orientated PDU fit into a 19" frame and can have 4-6 sockets. PDUs can come with a master on/off switch or without switch. Selection is optional. Our high quality PDUs have passed all relevant international standards can come with all international plug/socket types, such as: UK, IEC, etc.

APPLICATION

- LAN & WAN Networking.
- Telecommunications
- Audio / Video System
- Security System

STANDARDS COMPLIANCE

- ROHS

FEATURES

- Horizontal 19" rack mountable
CE Approved & RoHS compliant.
- 250V AC 50/60Mhz rating.
- Outlet socket types available, including UK & IEC 4-8 sockets horizontal.
- Master on/off switch optional
- LED indicated Unit Power
- High quality, lightweight aluminum housing

TECHNICAL SPECIFICATIONS

Voltage Rating	Input Voltage	250V AC
	Frequency	50 / 60 Hz
Power Rating	Regulatory Verated Input Current	13 Amps
	Max Power (Watt)	3250
Input Plug Style		BS1363
Outlet Plug Style		BS1363
Power Cord	Length (Mtr.)	1.8
	Guage	3X2.5sq.,mm
Visual Indicator	Led	Yes
Outer Body	Type	19" Rack mount
	Material	Extruded Aluminium

ORDERING INFORMATION

Description

Datacom 6 Way 1U 19" Horizontal Mounted 13AMP UK Type Switched PDU

Datacom 6 Way 1U 19" Horizontal Mounted 13AMP UK Type Un Switched PDU

Part No.

DC-PDI-SHBLK-06

DC-PDI-NHBLK-06