

NAME

rm – remove files or directories

SYNOPSIS

rm [*OPTION*]... [*FILE*]...

DESCRIPTION

This manual page documents the GNU version of **rm**. **rm** removes each specified file. By default, it does not remove directories.

If the **-I** or **--interactive=once** option is given, and there are more than three files or the **-r**, **-R**, or **--recursive** are given, then **rm** prompts the user for whether to proceed with the entire operation. If the response is not affirmative, the entire command is aborted.

Otherwise, if a file is unwritable, standard input is a terminal, and the **-f** or **--force** option is not given, or the **-i** or **--interactive=always** option is given, **rm** prompts the user for whether to remove the file. If the response is not affirmative, the file is skipped.

OPTIONS

Remove (unlink) the *FILE*(s).

-f, --force

ignore nonexistent files and arguments, never prompt

-i

prompt before every removal

-I

prompt once before removing more than three files, or when removing recursively; less intrusive than **-i**, while still giving protection against most mistakes

--interactive[=WHEN]

prompt according to *WHEN*: never, once (**-I**), or always (**-i**); without *WHEN*, prompt always

--one-file-system

when removing a hierarchy recursively, skip any directory that is on a file system different from that of the corresponding command line argument

--no-preserve-root

do not treat **'/'** specially

--preserve-root[=all]

do not remove **'/'** (default); with **'all'**, reject any command line argument on a separate device from its parent

-r, -R, --recursive

remove directories and their contents recursively

-d, --dir

remove empty directories

-v, --verbose

explain what is being done

--help display this help and exit

--version

output version information and exit

By default, **rm** does not remove directories. Use the **--recursive** (**-r** or **-R**) option to remove each listed directory, too, along with all of its contents.

To remove a file whose name starts with a **'-'**, for example **'-foo'**, use one of these commands:

```
rm -- -foo
```

```
rm ./-foo
```

Note that if you use **rm** to remove a file, it might be possible to recover some of its contents, given sufficient expertise and/or time. For greater assurance that the contents are truly unrecoverable, consider using **shred**.

AUTHOR

Written by Paul Rubin, David MacKenzie, Richard M. Stallman, and Jim Meyering.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report any translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright © 2020 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

unlink(1), unlink(2), chattr(1), shred(1)

Full documentation <<https://www.gnu.org/software/coreutils/rm>>
or available locally via: info '(coreutils) rm invocation'