

NAME

`rmdir` – remove empty directories

SYNOPSIS

`rmdir` [*OPTION*]... *DIRECTORY*...

DESCRIPTION

Remove the *DIRECTORY*(ies), if they are empty.

`--ignore-fail-on-non-empty`

ignore each failure that is solely because a directory
is non-empty

`-p, --parents`

remove *DIRECTORY* and its ancestors; e.g., '`rmdir -p a/b/c`' is similar to '`rmdir a/b/c a/b a`'

`-v, --verbose`

output a diagnostic for every directory processed

`--help` display this help and exit

`--version`

output version information and exit

AUTHOR

Written by David MacKenzie.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report any translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright © 2020 Free Software Foundation, Inc. License GPLv3+: GNU GPL version 3 or later
<<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

`rmdir`(2)

Full documentation <<https://www.gnu.org/software/coreutils/rmdir>>
or available locally via: `info '(coreutils) rmdir invocation'`